

## **Recurrent Neural Networks**


TOTAL POINTS 10

1. Suppose your training examples are sentences (sequences of words). Which of the following refers to the  $j^{th}$  word in the  $i^{th}$  training example?

1 point

1 point


- $\bigcirc \ x^{(i) < j >}$
- $\bigcirc x^{< i > (j)}$
- $\bigcirc \ x^{(j) < i >}$
- $\bigcirc \ x^{< j > (i)}$
- 2. Consider this RNN:




This specific type of architecture is appropriate when:

- $\bigcap T_x = T_y$
- $\bigcap T_x < T_y$
- $\bigcap T_x > T_y$
- $\bigcap T_x = 1$
- 3. To which of these tasks would you apply a many-to-one RNN architecture? (Check all that apply).

1 point




- Speech recognition (input an audio clip and output a transcript)
- Sentiment classification (input a piece of text and output a 0/1 to denote positive or negative sentiment)
- Image classification (input an image and output a label)
- Gender recognition from speech (input an audio clip and output a label indicating the speaker's gender)
- 4. You are training this RNN language model.



At the  $t^{th}$  time step, what is the RNN doing? Choose the best answer.

- $\bigcirc \ \ \operatorname{Estimating} P(y^{<1>},y^{<2>},\ldots,y^{< t-1>})$
- igcup Estimating  $P(y^{< t>})$
- $\bigcirc \ \ \mathsf{Estimating} \ P(y^{< t>} \mid y^{< 1>}, y^{< 2>}, \dots, y^{< t-1>})$
- $\bigcirc$  Estimating  $P(y^{< t>} \mid y^{< 1>}, y^{< 2>}, \ldots, y^{< t>})$
- 5. You have finished training a language model RNN and are using it to sample random sentences, as follows:

1 point



What are you doing at each time step t?

- (i) Use the probabilities output by the RNN to pick the highest probability word for that time-step as  $\hat{y}^{< t>}$ . (ii) Then pass the ground-truth word from the training set to the next time-step.
- (i) Use the probabilities output by the RNN to randomly sample a chosen word for that time-step as  $\hat{y}^{< t>}$ . (ii) Then pass the ground-truth word from the training set to the next time-step.
- (i) Use the probabilities output by the RNN to pick the highest probability word for that time-step as  $\hat{y}^{< t>}$ . (ii) Then pass this selected word to the next time-step.
- (i) Use the probabilities output by the RNN to randomly sample a chosen word for that time-step as  $\hat{y}^{< t>}$ . (ii) Then pass this selected word to the next time-step.
- 6. You are training an RNN, and find that your weights and activations are all taking on the value of NaN ("Not a Number"). Which of these is the most likely cause of this problem?


1 point

- O Vanishing gradient problem.
- Exploding gradient problem.
- ReLU activation function g(.) used to compute g(z), where z is too large.
- Sigmoid activation function g(.) used to compute g(z), where z is too large.
- 7. Suppose you are training a LSTM. You have a 10000 word vocabulary, and are using an LSTM with 100-dimensional activations  $a^{< t>}$ . What is the dimension of  $\Gamma_u$  at each time step?

1 point

- O 1
- 0 100
- 300
- 0 10000
- 8. Here're the update equations for the GRU.

1 point



Learn more about Coursera's Honor Code