

Windows GDID and the Reverse-Engineered Global Device Identifier

Architecture, telemetry flows, forensic attribution, privacy exposure, and cybersecurity controls

Field	Value
Author	OxAllow
Publication date	07.07.2026
Version	2.0 - evidence-aware technical edition
Scope	Public Microsoft documentation, court-record evidence, and clearly labeled reverse-engineering inferences.
Source policy	No third-party writeup is cited or promoted; the source base is public Microsoft documentation, public court records, and clearly labeled inference.

Important boundary statement

This white paper does not claim access to private Microsoft source code, private Microsoft telemetry stores, or non-public law-enforcement returns. Where the public record is silent, the document uses explicit labels: official documentation, court record, inference, or unknown.

Abstract

The Microsoft Global Device Identifier, usually surfaced as GlobalDeviceId or GDID, is a persistent device-level identifier in the Windows ecosystem. Public Microsoft documentation names it directly in Azure Monitor / Windows Update for Business Delivery Optimization reporting, while a 2026 federal criminal complaint describes a broader use of GDID-linked Microsoft records for forensic attribution. This paper models GDID as a correlation key rather than a standalone surveillance mechanism: its forensic and privacy significance appears when the identifier is joined with event timestamps, source IPs, visited or reputation-checked URLs, account records, and third-party provider logs.^{[1][2]}

The primary conclusion is narrow but important: GDID is not publicly documented enough for independent reviewers to audit its complete lifecycle. However, the combination of a persistent install-level ID, telemetry events, cloud-side IP observation, and service-specific records creates a high-value attribution surface. The same surface is operationally useful for security and reliability, but it creates privacy exposure if retention, access control, and purpose limitation are weak.

1. Evidence model and scope

This document uses four evidence grades throughout. The grade is attached to each major claim, not to the entire paper.

Grade	Meaning	Example in this paper
Official documentation	Published Microsoft documentation or Microsoft Support material.	UCDOStatus contains GlobalDeviceId; Diagnostic Data Viewer exposes diagnostic events; diagnostic data uses unique identifiers.
Court record	Allegations or representations in a sworn complaint or affidavit. Court-record facts may still be contested in litigation.	The complaint describes GDID g:6755467234350028 and Microsoft records linked to ngrok, URLs, IPs, and account activity.
Inference	A technical conclusion derived from documented flows, schemas, and normal telemetry architecture, but not directly disclosed by Microsoft.	GDID likely acts as a join key in selected Microsoft analytic systems.
Unknown	Not publicly documented or not reproducible from available sources.	Exact generation algorithm, all local storage paths, complete Microsoft service fan-out, and internal retention rules.

No third-party writeup is used as authority in this version. When local discovery methods are discussed, they are described as experimental and must be validated on the reader's own device or tenant.

2. Executive findings

Finding	Technical meaning
GDID is real and publicly named.	Microsoft documents GlobalDeviceId as a Microsoft global device identifier in UCDOStatus, a Windows Update for Business / Azure Monitor table. The schema states that this identifier is used internally by Microsoft.
The public schema is narrow.	UCDOStatus is Delivery Optimization reporting. It includes fields such as GlobalDeviceId, DeviceName, city/country based on IP, ISP, OSVersion, and download/peering metrics. It is not a general browsing-history table.
The court record shows broader correlation.	The complaint states that Microsoft records associated a GDID with an ngrok account setup event, a specific signup URL, proxy IP activity, and overlapping account/IP activity. The complaint does not reveal the exact internal Microsoft tables behind those records.
The privacy risk is joinability.	A durable install-level identifier becomes sensitive when it is joined with time, URL, IP, account identity, device name, location, game/service logins, or third-party provider returns.
The cybersecurity value is also real.	The same joinability helps identify abuse infrastructure, link malicious tooling to devices, deduplicate telemetry, detect campaigns, and support incident response. The security value does not remove the need for transparency and access controls.
Independent audit is incomplete today.	Microsoft has not published a complete GDID lifecycle: local generation, local storage, reset conditions, service fan-out,

3. Terminology: GDID versus adjacent Windows identifiers

Identifier	Role and distinction
GDID / GlobalDeviceId	Persistent Windows ecosystem identifier described in court records as tied to a Windows OS installation and documented by Microsoft in UCDOStatus. Not equivalent to a MAC address or advertising ID.
MachineGuid / SQMClient MachineId	Local Windows identifiers used by different Windows components. Microsoft diagnostic schemas mention local device IDs and SQM identifiers, but those are not automatically the same as GDID.
Advertising ID	Per-user advertising identifier exposed to apps for interest-based advertising. It can be reset/disabled through Windows privacy settings and is distinct from GDID.
Azure AD / Entra device ID	Tenant-managed cloud identity for a device. UCDOStatus also includes AzureADDeviceId/AzureADTenantId fields, but the public documentation's wording appears internally inconsistent; treat it as a separate tenant/device join surface.
Correlation Vector / ETW ActivityId	Event-correlation fields for tracing activity flow. Useful operationally, but not a durable device identity by itself.
IP address	Network-layer source observed by Microsoft or third-party services. IP alone is weak identity; IP plus GDID plus account records is much stronger.


4. Technical architecture

The defensible architecture is a layered identity and telemetry model. Windows components generate operational events. Some events include local or cloud identifiers, component fields, timestamps, and diagnostic metadata. At Microsoft ingress, the network source IP is naturally observable even when the client payload does not explicitly include it. Selected services persist events in product-specific stores, Azure Monitor tables, security analytics systems, or account systems. GDID becomes powerful when these stores can be joined on device identity, timestamp, account identity, or network source.^[3]

Microsoft publicly documents diagnostic endpoints such as `v10.events.data.microsoft.com` for Connected User Experiences and Telemetry, and states that diagnostic data is collected to keep Windows secure, up to date, reliable, and operating properly. Microsoft also states that diagnostic data is stored with one or more unique identifiers that help recognize a user on an individual device and understand service issues and use patterns.^{[4] [5]}

Figure 1 - GDID data-flow model (evidence-aware)

Legend: O=official Microsoft documentation, C=court record, I=inference, U=unknown/not public



Reading rule: a GDID is not a packet sniffer. It is a durable correlation key. Exposure comes from joining it with telemetry, IP, URL, account, and provider re

- The only public Microsoft schema that names GlobalDeviceId directly is currently Windows Update for Business / Azure Monitor UCDOStatus.
- Court records show a broader Microsoft-record use case, but do not disclose the exact internal tables or service owners.
- Every defensive or forensic claim should separate confirmed fields from inferred pipeline behavior.

Figure 1. GDID model. The boxes are deliberately short and evidence-labeled to avoid implying undocumented certainty.

4.1 Components that matter

Component	Relevance to GDID or attribution
Connected User Experiences and Telemetry / DiagTrack	Primary Windows diagnostic-data pipeline. Public docs describe event categories, common data extensions, and management controls, but do not disclose a complete GDID map.
Windows Error Reporting	Crash/error reports can include diagnostic context; organizations can limit dump and diagnostic log collection.
Windows Update / Delivery Optimization	Publicly confirmed GDID surface through UCDOStatus. Delivery Optimization is cloud-managed and supports peer/cache download optimization.
Microsoft Defender SmartScreen / reputation services	Reputation protection evaluates URLs, downloads, apps, and certificates. Microsoft Support states SmartScreen sends data about websites visited and downloaded files to Microsoft for protection.
Microsoft Edge and browser diagnostics	Can produce browser/service telemetry. Edge diagnostic data collection has separate treatment in some regions and versions.
Microsoft Account / identity services	Account sign-ins and device/account binding are a likely correlation surface, but public documents do not prove all GDID uses in account systems.
Xbox / gaming-related services	Microsoft diagnostic schemas expose Xbox-related device and IP fields. Court records used a game login URL plus Ubisoft records; this is not proof that GDID alone reports all games played.

5. Where GDID surfaces publicly

The cleanest public Microsoft surface is UCDOStatus. Microsoft describes UCDOStatus as providing single-device Delivery Optimization bandwidth and download information. Its columns include GlobalDeviceId, City, Country, DeviceName, DownloadMode, ISP, LastCensusSeenTime, OSVersion, and transfer/peer metrics. The GlobalDeviceId column is described as a Microsoft global device identifier used internally. ^{[2] [6]}

UCDOStatus field	Why it matters
GlobalDeviceId	The public proof that Microsoft uses this identifier in at least one customer-visible telemetry table.
DeviceName	Allows tenant administrators to associate a GDID with an organization-provided device name, if configured.
City / Country / ISP	Approximate network-location metadata based on IP while downloading content.
LastCensusSeenTime	Freshness marker for the device's last successful census scan.
DownloadMode / ContentType / Bytes fields	Delivery Optimization behavior, not general web browsing.
AzureADDeviceId / AzureADTenantId	Tenant/device join fields that can help enterprise administrators map a GDID to managed-device identity.

A recurring error in public discussion is to treat UCDOStatus as evidence that Windows exposes full browsing history to Azure Monitor. That is not supported by Microsoft's UCDOStatus schema. The table is about Delivery Optimization. The separate court-record claim that Microsoft records contained URL activity should be treated as a broader Microsoft internal-record issue, not as a UCDOStatus-only issue.

6. Reverse-engineered model: what is defensible and what is not

A professional reverse-engineering paper must not confuse three different things: a local cached value, a cloud-issued identifier, and a derived identifier calculated by a researcher. These may be related, but they are not interchangeable unless proven by live service correlation.

Claim type	Defensible treatment
Local registry or cache contains a value that looks like g:<digits>.	Treat as a candidate GDID-like artifact. Validate against Azure Monitor UCDOStatus or Microsoft-produced records when possible.
A value is named GLOBALDEVICEID inside a Microsoft cache blob.	Stronger than a blind string match, but still not a full lifecycle proof. It may be stale, service-specific, or one of multiple identifiers.
A reverse-engineered algorithm computes a number.	Do not call it GDID unless it matches cloud-observed GlobalDeviceId for the same install.
The identifier survives feature updates.	Supported by the court record, which states GDID remains consistent across Windows OS updates.
The identifier changes on Windows reinstall.	Supported by the court record. Exact behavior under reset, sysprep, cloning, and VM snapshots needs independent testing.
All Microsoft services receive the same GDID.	Not proven publicly. State as unknown unless service-specific records or schemas show it.

6.1 Practical validation criteria

A value should be called “your GDID” only if at least one of the following is true:

- It appears in your organization's UCDOStatus records for your device in Azure Monitor / Windows Update for Business reports.
- It appears in a Microsoft-produced record for your device under a lawful support, enterprise, privacy, or legal process response.
- It appears in multiple first-party Microsoft local or cloud artifacts and matches the format used in public Microsoft documentation, while being marked as unverified if no cloud-side confirmation exists.

7. How to find your own GDID

There is no consumer-facing Microsoft settings page that simply displays “your GDID.” The two most defensible discovery paths are enterprise-side Log Analytics and local diagnostic/cached-artifact review. The local path is useful for research, but it is not an official Microsoft support procedure and may not work on all builds.

7.1 Method A - Enterprise / Azure Monitor / Windows Update for Business reports

If the device is enrolled in Windows Update for Business reports and the tenant ingests UCDOStatus into Log Analytics, query the UCDOStatus table. Microsoft explicitly documents GlobalDeviceId in that table.^[2]

```
// Azure Monitor / Log Analytics KQL
```

```
UCDOSStatus
| where TimeGenerated > ago(30d)
| where DeviceName =~ "<YOUR-WINDOWS-DEVICE-NAME>"
| summarize arg_max(TimeGenerated, *) by GlobalDeviceId
| project TimeGenerated, DeviceName, GlobalDeviceId, AzureADDeviceId,
    AzureADTenantId, OSVersion, ISP, City, Country, LastCensusSeenTime
```

If DeviceName is “#” or missing, query by AzureADDeviceId, TenantId, known OSVersion, city/country, or recent LastCensusSeenTime. DeviceName visibility may require configuration to send the device name.

7.2 Method B - Diagnostic Data Viewer and PowerShell

Microsoft provides Diagnostic Data Viewer and a PowerShell module that can show historical Windows diagnostic data uploaded by the machine. This may show related identifiers and event fields. It does not guarantee that GlobalDeviceId will be visible.^[7]

```
# Run in elevated PowerShell
Install-Module -Name Microsoft.DiagnosticDataViewer -Scope CurrentUser
Enable-DiagnosticDataViewing
Start-Sleep -Seconds 300
Get-DiagnosticData | ConvertTo-Json -Depth 12 |
    Out-File "$env:USERPROFILE\Desktop\diagnostic-data.json" -Encoding utf8

# Search the exported JSON for identity-related fields
Select-String -Path "$env:USERPROFILE\Desktop\diagnostic-data.json" `
    -Pattern "GlobalDeviceId|GLOBALDEVICEID|sqmId|MachineId|localId|installId|device" `
    -CaseSensitive:$false
```

Interpretation rule: Diagnostic Data Viewer is strong evidence for what the local diagnostic store exposes, not a complete statement of all data Microsoft may receive or retain in backend systems.

7.3 Method C - Local cached first-party content, experimental

Some Windows builds may cache first-party service responses that contain a field named GLOBALDEVICEID or a g:<digits> value. This is an experimental research method. It is not an official Microsoft-documented path and should be cross-checked against Method A when possible.

```
# Experimental. Read-only. Does not modify the registry.
$paths = @(
    "HKCU:\Software\Microsoft\Windows\CurrentVersion\IrisService\IrisActionCreatives",
    "HKCU:\Software\Microsoft\Windows\CurrentVersion\IrisService"
)
foreach ($p in $paths) {
    if (Test-Path $p) {
        Get-ItemProperty -Path $p -ErrorAction SilentlyContinue |
            Out-String -Width 4096 |
            Select-String -Pattern 'GLOBALDEVICEID|GlobalDeviceId|g:\d{8,}' -AllMatches
    }
}
```

Do not delete or edit these keys as a privacy tactic. Deleting cache values may break shell/service behavior and does not prove that Microsoft backend identity has been reset. For enterprise testing, use disposable VMs and compare before/after UCDOStatus values.

8. Telemetry flows: what can feed a GDID-centric graph

The most accurate model is not “GDID reports everything.” The accurate model is “multiple Microsoft components can emit events, and at least some Microsoft systems can join selected events to a persistent Windows install-level identifier.”

Flow	Typical data	GDID confidence
Diagnostic data / DiagTrack	Required and optional diagnostic events, common data extensions, local IDs, component names, event time, OS/app context.	Officially documented as diagnostic telemetry; relationship to GDID is not fully documented.
Delivery Optimization / Windows Update	Content type, download mode,	Publicly confirmed GDID surface.

	bandwidth/peer metrics, approximate location by IP, ISP, DeviceName, GlobalDeviceId.	
SmartScreen / Defender reputation	Visited webpages and downloaded-file data for protection; URL/file/app/certificate reputation decisions.	Officially documented data flow; exact GDID linkage not public.
Microsoft Account / cloud identity	Sign-in, device registration, service access, account tokens, tenant/account join surfaces.	Likely correlation surface; GDID-specific use not fully public.
Edge / browser services	Browser diagnostics and reputation/sync/service interactions depending on settings, account state, and region.	Official data categories exist; GDID-specific join not fully public.
Gaming/Xbox/Store	Service-specific device/user identifiers, title IDs, IP fields, app/service activity.	Some diagnostic fields are public; court record used a game login URL plus Ubisoft records.


Microsoft's required diagnostic-events documentation describes common data extensions, including device-related fields, local IDs, SQM identifiers, OS boot IDs, app identifiers, user-auth fields, and Xbox-related fields. These are not proof that every event includes GDID, but they show that Windows diagnostic architecture is explicitly designed for event correlation and device-context analysis.^[8]

9. The complete chain: GDID-assisted forensic attribution

The following chain is the cleanest way to explain the public court-record example without overstating it. GDID is one link. The conclusion depends on the combination of Microsoft records, provider records, IP overlap, timestamps, account metadata, and location corroboration.

Figure 2 - The complete chain: GDID-assisted forensic attribution

This is an evidence chain, not a claim that GDID alone identifies a person.



Forensic standard: strong attribution requires independent corroboration. GDID provides continuity; provider records and timing provide corroboration.

Figure 2. Evidence-aware chain. Each step should be independently tested in a real investigation; GDID continuity is not personal identity by itself.

9.1 What the court record says

The complaint states that the ngrok account was set up through Global Device Identifier g:6755467234350028. A Microsoft representative described GDID as a persistent device-level identifier designed to uniquely identify an installation of Windows on a physical device or virtual machine across certain Microsoft services and scenarios. The complaint further states that a GDID remains consistent across Windows OS updates, while a reinstall of Windows produces a new unique GDID.^[1]

The same record states that at the ngrok-account creation time, the device with the GDID accessed the ngrok signup page, and that Microsoft records showed the device using proxy-provider IPs and visiting a victim-related web property. It also describes overlapping IP activity between the GDID and subject accounts at Facebook, Snapchat, Apple, Ubisoft, and other provider records.^[2]

9.2 What the court record does not say

- It does not identify the exact Microsoft internal tables used to produce the GDID-associated web and IP records.
- It does not prove that UCDOStatus is the source of the web-activity evidence.
- It does not prove that GDID logs every website, every game, or all application activity.
- It does not disclose Microsoft internal retention, access-review, or approval workflow for GDID searches.
- It does not disclose whether URL data came from SmartScreen, Edge, account services, Defender, diagnostic telemetry, or another Microsoft pipeline.

10. Complete lifecycle model: from generation to investigative query

Stage	Data handled	Evidence status	Retention/search condition
1. Install / OOBE	Windows installation receives or later obtains durable device-level identifiers. GDID is tied to the OS installation according to court record.	Court record; exact algorithm unknown.	GDID persists across OS updates; reinstall creates a new GDID according to court record.
2. Local event generation	Windows and Microsoft components emit diagnostic, update, security, identity, reputation, and service events.	Official for event categories; GDID inclusion varies/unknown.	Local Diagnostic Data Viewer default shows up to 1 GB or 30 days unless configured.
3. Upload / ingress	Events are sent over Microsoft endpoints; source IP is observed at ingress; settings endpoint can configure diagnostics behavior.	Official endpoint documentation.	Backend retention varies; not fully public by GDID.
4. Service storage	Events land in diagnostic, update, security, account, and product-service stores.	Official in general; exact GDID fan-out unknown.	Microsoft states retention varies by purpose, data type, legal obligations, and service.
5. Customer-visible reporting	UCDOStatus exposes GlobalDeviceId with DO metrics, approximate city/country, ISP, and device freshness.	Official.	Log Analytics default retention is generally 30 days for most tables and can be extended, depending on table/workspace settings.
6. Security analytics	Microsoft security analysts may identify machine IDs, IPs, malware samples, and related group activity.	Court record.	Internal retention/search workflow not public.
7. Investigation/legal production	Records may be disclosed under valid legal process or for safety/security/legal obligations.	Microsoft privacy statement + court record.	Search likely requires authorized internal workflow or legal/compliance process; exact controls not public.

11. Privacy exposure analysis

The privacy exposure is not only collection volume. It is the ability to bind events together over time. A stable per-install identifier can make a VPN, account rotation, browser reset, or IP change less effective if the same Windows installation continues to emit identifiable events to Microsoft services.

Exposure	Risk mechanism	Risk level
GDID + IP history	Links one Windows installation across residential, travel, corporate, VPN, proxy, and cloud networks.	High
GDID + URL/reputation events	Can reveal selected browsing or tool-use events depending on the component that emitted the data.	High if full URL is stored; medium if reputation-limited.

GDID + Microsoft account	Can bind local device continuity to a real account identity or tenant account.	High
GDID + third-party provider records	A provider timestamp/IP/account can corroborate Microsoft device records.	High for investigations.
GDID + DeviceName / tenant IDs	Enterprise admins can map GDID to managed assets and users.	Medium to high depending on RBAC.
GDID + long retention	Old activity remains joinable after context changes.	High if retention is long and access broad.


Microsoft's privacy statement says personal data may be retained for purposes such as providing services, legal obligations, security, product improvement, and dispute resolution, and that actual retention periods vary by data type and context. This supports a key limitation: no public source gives a single universal GDID retention period.^[9]

12. Cybersecurity controls

Controls should be designed for legitimate administration, DFIR, privacy minimization, and compliance. Do not disable core security protections blindly. A privacy-motivated control that creates malware exposure is usually a bad trade.

Figure 3 - Cybersecurity and privacy control map

Objective: preserve security value while reducing unnecessary correlation exposure.



Important trade-off: disabling security reputation checks can reduce some URL/file submissions, but it also removes anti-phishing and anti-malware protection. Good engineering control is not blind blocking. It is documented data minimization, retention discipline, RBAC, and transparent auditability.

Figure 3. Control map. The practical goal is governed visibility, not blind telemetry destruction.

12.1 Enterprise control checklist

Control area	Recommended action
Diagnostic data policy	Set required/optional diagnostic-data posture through Group Policy or MDM. Disable optional diagnostic data where business need is absent.
Limit dumps/logs	Use policies to limit dump collection and diagnostic log collection where appropriate.
Diagnostic Data Viewer	Use it for transparency and local validation. Turn off data viewing when finished to clear local diagnostic-data history.
Delivery Optimization	Decide whether LAN/group peering, HTTP-only, or Connected Cache is appropriate. Avoid Internet peers if policy requires tight privacy boundaries.
SmartScreen / Defender	Prefer keeping protection enabled. If exceptions are required, manage them with documented policy, risk acceptance, and compensating controls.
Azure Monitor retention	Set Log Analytics retention by table/workspace. Keep only operationally justified history; document legal/compliance needs.

RBAC and audit	Limit who can query UCDOStatus and device telemetry. Review access to Log Analytics, Sentinel, Intune, and Defender portals.
Network transparency	Document Microsoft telemetry/update endpoints allowed through egress controls. Do not rely on VPNs to prevent device-level correlation.
Lab isolation	Use disposable VMs or dedicated hardware for malware analysis and research. Treat cloned OS installs carefully because duplicate identifiers can corrupt telemetry and attribution.
Forensic discipline	Corroborate GDID with independent logs. Preserve timestamps, time zones, provider returns, and chain of custody. Never use GDID alone as identity proof.

13. Conditions under which GDID can be searched or used

The public record supports several contexts where GDID-linked data can be used, but only some are documented in customer-visible systems.

Search/use context	Who can perform it	Confidence	Caveat
Enterprise UCDOStatus query	Tenant admins or analysts with Log Analytics rights.	High / official.	Only Delivery Optimization report data, not general browsing history.
Microsoft support/security investigation	Microsoft internal teams under internal policy.	Medium to high / general official + court.	Exact access rules not public.
Law-enforcement production	Microsoft compliance/legal process response or security referral.	High / privacy statement + court.	Specific scope depends on legal process and available records.
Consumer self-service	Individual user via Diagnostic Data Viewer or Privacy Dashboard.	Medium for diagnostic data; low for GDID visibility.	No official GDID display page.
Reverse-engineering local artifacts	Researcher on own system.	Variable.	Must not be treated as authoritative without cloud-side match.

14. Top 10 questions for Microsoft engineers - with defensible answers

These are the questions that should be put to senior Windows, Azure Monitor, Defender, identity, and privacy engineers. The answers below are not Microsoft statements; they are the most defensible public-evidence answers as of 07.07.2026.

Question	Defensible public-evidence answer
1. Where is GDID generated and by which component?	Unknown publicly. Court records say GDID is tied to a Windows installation and survives OS updates but changes on reinstall. Microsoft has not published the generating component or algorithm.
2. Where is GDID stored locally?	No official Microsoft path is documented. Researchers can look for candidate g:<digits> or GLOBALDEVICEID values in first-party caches, but only Azure Monitor or Microsoft-produced records can confirm the cloud-observed value.
3. Which Windows services can read or attach GDID to events?	Publicly confirmed only for UCDOStatus. Court records show broader Microsoft records linked to GDID, but exact service owners are undisclosed.
4. Is GDID the same as MachineGuid, SQM MachineId, Advertising ID, Entra device ID, or Xbox device ID?	No public evidence shows equivalence. Treat them as adjacent identifiers with possible backend joins, not synonyms.
5. Which events can be queried by GDID?	Customer-visible: UCDOStatus. Internal: court records suggest web/IP/tool/account-related records could be associated with GDID. The exact internal queryable event list is not public.
6. Does GDID log all browsing?	No public evidence supports "all browsing." SmartScreen and browser/security services can send website/download data, and court records show specific URL access records; the collection path remains undisclosed.
7. What resets GDID?	Court record says Windows reinstall creates a new unique GDID and OS updates do not. Behavior for Reset this PC, sysprep, clone, VM snapshot, motherboard replacement, and account sign-out is not fully documented.
8. What is the retention period for GDID-indexed data?	No universal public retention exists. Azure Monitor customer logs follow workspace/table retention; Microsoft backend retention varies by service, purpose, data type, legal obligations, and security needs.
9. Who inside Microsoft can search GDID-linked data?	Not publicly disclosed. The court record describes Microsoft cybersecurity researchers having access to machine IDs, IPs, and malware samples for sophisticated cybergroup analysis. Exact RBAC, audit, and approval rules

	are unknown.
10. Why is GDID not documented as a first-class privacy identifier?	Unknown. A credible answer would be that GDID is an internal operational identifier. That answer is insufficient for audit: Microsoft should publish lifecycle, reset, service-scope, access, and retention details.

15. Limitations and unresolved research

- The exact GDID generation algorithm is not public.
- The exact local storage path, if any single authoritative path exists, is not public.
- The exact service fan-out across Windows, Edge, Defender, Microsoft Account, Store, Xbox, and Azure services is not public.
- The exact internal Microsoft retention period for GDID-indexed data is not public.
- The exact authorization workflow for internal GDID search is not public.
- The relationship between GDID and common schema fields such as localId, sqmId, installId, and service-specific device IDs is not fully documented.
- The court record is powerful but not a schema. It proves what was represented in that investigation, not the full design of Windows telemetry.

16. Recommendations

Audience	Recommendation
Microsoft	Publish a GDID lifecycle note: generation, reset, local visibility, service scope, retention categories, and access controls. Add GDID to privacy dashboards where legally and technically feasible.
Enterprise admins	Inventory where GlobalDeviceId appears in Log Analytics. Apply least privilege to telemetry tables and set retention to a documented operational need.
DFIR teams	Use GDID as a continuity signal, never as identity proof. Corroborate with provider logs, endpoint artifacts, account records, and time-zone-normalized timelines.
Privacy engineers	Model GDID as a pseudonymous persistent identifier with high re-identification risk when joined with IP/account/URL data.
Researchers	Publish reproducible tests that compare local candidate values with cloud-observed UCDOStatus values. Label build numbers, edition, account state, VM/physical status, and reset/reinstall conditions.
Users	Review Windows diagnostic settings, SmartScreen trade-offs, Edge sync/diagnostics, and Microsoft account use. Do not assume VPN use prevents device-level correlation.

References

- [1] United States v. Peter Stokes, superseding criminal complaint / affidavit, U.S. Department of Justice, Northern District of Illinois, 2026. <https://www.justice.gov/usao-ndil/media/1450651/dl?inline=>
- [2] Microsoft Learn, Azure Monitor Logs reference - UCDOStatus. <https://learn.microsoft.com/en-us/azure/azure-monitor/reference/tables/ucdostatus>
- [3] Microsoft Learn, Delivery Optimization data in Windows Update for Business reports. <https://learn.microsoft.com/en-us/windows/deployment/update/wufb-reports-do>
- [4] Microsoft Learn, Configure Windows diagnostic data in your organization. <https://learn.microsoft.com/en-us/windows/privacy/configure-windows-diagnostic-data-in-your-organization>
- [5] Microsoft Support, Diagnostics, feedback, and privacy in Windows. <https://support.microsoft.com/en-us/windows/privacy/diagnostics-feedback-and-privacy-in-windows>
- [6] Microsoft Learn, UCDOStatus data schema - Windows Update for Business reports. <https://learn.microsoft.com/en-us/windows/deployment/update/wufb-reports-schema-ucdostatus>
- [7] Microsoft Learn, Diagnostic Data Viewer and Diagnostic Data Viewer for PowerShell. <https://learn.microsoft.com/en-us/windows/privacy/diagnostic-data-viewer-overview>

[8] Microsoft Learn, Required diagnostic events and fields for Windows 11 25H2/24H2.

<https://learn.microsoft.com/en-us/windows/privacy/required-diagnostic-events-fields-windows-11-24h2>

[9] Microsoft Privacy Statement - retention, legal process, and disclosure language.

<https://www.microsoft.com/en-us/privacy/privacystatement>

[10] Microsoft Learn, Microsoft Defender SmartScreen overview.

<https://learn.microsoft.com/en-us/windows/security/operating-system-security/virus-and-threat-protection/microsoft-defender-smartscreen/>

[11] Microsoft Support, General privacy settings in Windows - SmartScreen and Advertising ID.

<https://support.microsoft.com/en-us/windows/privacy/general-privacy-settings-in-windows>

[12] Microsoft Learn, Manage Data Retention in a Log Analytics Workspace. <https://learn.microsoft.com/en-us/azure/azure-monitor/logs/data-retention-configure>

[13] Microsoft Learn, Optional diagnostic data for Windows 11 and Windows 10.

<https://learn.microsoft.com/en-us/windows/privacy/optional-diagnostic-data>

[14] Han, Park, Chung, Lee, Forensic analysis of Windows telemetry for diagnostics, arXiv, 2020.

<https://arxiv.org/abs/2002.12506>

Closing note

The best technical position is neither panic nor denial. GDID appears to be a durable Windows-install correlation key. Public Microsoft documentation proves a narrow Azure Monitor surface; the court record proves that Microsoft can associate a GDID with broader investigative records in at least some circumstances. The missing piece is transparency: a complete Microsoft-published lifecycle, service-scope, access-control, and retention specification.

Date: 07.07.2026

Author: 0xAllow