

lockdownMode

domain

WBS Lockdown Mode Preferences Manager set Lockdown Mode Enabled for Domain 🤔

How to disable LDM

In Safari

Where is this per site data stored?

Grepping around the symbols for `lockdownMode` and `domain` I found:



–`[WBSLockdownModePreferenceManager setLockdownModeEnabled:forDomain:]` sounds like what I need 🤔

How to disable LDM In Safari

class-dumping the dylib in the DSC with `ipsw`

```
› ipsw dyld macho dyld_shared_cache_arm64e SafariShared --objc -V
```

```
@interface WBSLockdownModePreferenceManager : WBSPerSitePreferenceManager<WBSPerSitePreferenceManagerDefaultsDelegate, WBSPerSitePreferenceManagerStorageDelegate, WBSPerSitePreferenceBinaryToggleItemManager> { // 0x1de0dd828
    /* instance variables */
    WBSPerSitePreferencesSQLiteStore *_perSitePreferenceStore; // +size offset // +0x8 0x20
    WBSPerSitePreference *_lockdownPreference; // +0x8 0x28
}

@property (readonly, nonatomic) WBSPerSitePreference *lockdownPreference;
@property (readonly, nonatomic) WBSPerSitePreferencesSQLiteStore *perSitePreferencesStore;
@property (readonly) unsigned long long hash;
@property (readonly) Class superclass;
@property (readonly, copy) NSString *description;
@property (readonly, copy) NSString *debugDescription;

/* instance methods */

// 0x1a3f0fbcc
- (id)preferences;
// 0x1a3f0fca4
- (id)onValueForPreference:(id)arg1;
// 0x1a3f0fc7c
- (id)preferenceNameForPreference:(id)arg1;
// 0x1a3f0fc8c
- (id)defaultPreferenceValueForPreferenceIfNotCustomized:(id)arg1;
// 0x1a3f0fcc0
- (void).cxx_destruct;
// 0x1a3f0fc58
- (id)localizedStringForValue:(id)arg1 inPreference:(id)arg2;
// 0x1a3f0fc98
- (id)offValueForPreference:(id)arg1;
// 0x1a3f0fc6c
- (id)perSitePreferencesStore;
// 0x1a3f0fb00
- (void)didUpdatePreference:(id)arg1 toValue:(id)arg2 forDomain:(id)arg3;
// 0x1a3f0fc4c
- (id)valuesForPreference:(id)arg1;
// 0x1a3f0f978
- (void)getLockdownModeEnabledForDomain:(id)arg1 withTimeout:(double)arg2 fallbackEnabledState:(BOOL)arg3 usingBlock:(id /* block */)arg4;
// 0x1a3f0f81c
- (id)initWithPerSitePreferenceStore:(id)arg1;
// 0x1a3f0fcb0
- (id)lockdownPreference;
// 0x1a3f0fc64
- (BOOL)preferenceDoesNotHaveForOtherWebsitesDefault:(id)arg1;
// 0x1a3f0f8e8
- (void)setLockdownModeEnabled:(BOOL)arg1 forDomain:(id)arg2;
@end
```