

SoftwareUpdateServices

The `isLockdownModeEnabled` is also called from the following binaries in the Filesystem DMG:

- `/usr/libexec/mc_mobile_tunnel`
- `/System/Library/PrivateFrameworks/SoftwareUpdateServices.framework/Support/softwareupdateservicesd`

SoftwareUpdateServices

mc_mobile_tunnel

isLockdownModeEnabled is called in the function:

```
-[MTIPCUTunnelParser _commandInstallProfile:]
```

Here is a snippet from IDA:

```
if ( [MTIPCUTunnelParser _isLockdownModeEnabled] )
{
    v16 = DMCErrorsArray(CFSTR("ERROR_PROFILE_INSTALL_PREVENTED_BY_LOCKDOWN"));
    v17 = (id)objc_claimAutoreleasedReturnValue(v16);
    v18 = DMCErrorsTypeFatal;
    v19 = DMCErrorsInstallationErrorDomain;
    v20 = 4021LL;
}
else
{
    v27 = DMCErrorsArray(CFSTR("ERROR_PROFILE_NO_INTERACTIVE_INSTALLATION"));
    v17 = (id)objc_claimAutoreleasedReturnValue(v27);
    v18 = DMCErrorsTypeFatal;
    v19 = DMCErrorsInstallationErrorDomain;
    v20 = 4020LL;
}
```

This is where it's preventing the [installation of profiles](#) when [Lockdown Mode](#) is enabled as mentioned by Apple.