



B1- Unix and C Lab Seminar

B-CPE-100

Day 05

Recursivity

v2.0





Day 05

Recursivity


repository name: CPool_DayO5_\$ACADEMICYEAR


repository rights: ramassage-tek

language: C group size: 1

• Your repository must contain the totality of your source files, but no useless files (binary, temp files, obj files,...).









Create your repository at the beginning of the day and submit your work on a regular basis! The delivery directory is specified within the instructions for each task. In order to keep your repository clean, pay attention to gitignore.



All of the day's functions must produce an answer in under 2 seconds. Overflows must be handled (as errors).






my_compute_factorial_it

Write an iterative function that returns the factorial of the number given as a parameter. It must be prototyped the following way:

int my_compute_factorial_it(int nb);

In case of error, the function should return O.

Delivery: CPool_DayO5_\$ACADEMICYEAR/my_compute_factorial_it.c



Task 02

my_compute_factorial_rec

Write a recursive function that returns the factorial of the number given as a parameter. It must be prototyped the following way:

int my_compute_factorial_rec(int nb)

In case of error, the function should return O.

Delivery: CPool_DayO5_\$ACADEMICYEAR/my_compute_factorial_rec.c




my_compute_power_it

Write an iterative function that returns the first argument raised to the power p, where p is the second argument. It must be prototyped the following way:

```
int my_compute_power_it(int nb, int p);
```

Delivery: CPool_DayO5_\$ACADEMICYEAR/my_compute_power_it.c



Task 04

my_compute_power_rec

Write an recursive function that returns the first argument raised to the power p, where p is the second argument. It must be prototyped the following way:

```
int my_compute_power_rec(int nb, int p);
```

Delivery: CPool_DayO5_\$ACADEMICYEAR/my_compute_power_rec.c

Task 05

my_compute_square_root

Write a function that returns the square root (if it is a whole number) of the number given as argument. If the square root is not a whole number, the function should return 0. It must be prototyped the following way:

int my_compute_square_root(int nb);

Delivery: CPool_DayO5_\$ACADEMICYEAR/my_compute_square_root.c





my_is_prime

Write a function that returns 1 if the number is prime and 0 if not. It must be prototyped the following way:

int my_is_prime(int nb);

Delivery: CPool_DayO5_\$ACADEMICYEAR/my_is_prime.c



As you know, 0 and 1 are not prime numbers.

Task 07

my_find_prime_sup

Write a function that returns the smallest prime number that is greater than, or equal to, the number given as a parameter.

It must be prototyped the following way:

int my_find_prime_sup(int nb);

Delivery: CPool_DayO5_\$ACADEMICYEAR/my_find_prime_sup.c





The n queens

Write a function that returns the number of possible ways to place n queens on a nxn chessboard without them being able to run into each other in a single move.

It must be prototyped the following way:

```
int count_valid_queens_placements(int n);
```

The output must be as follows:

Delivery: CPool_DayO5_\$ACADEMICYEAR/count_valid_queens_placements.c

