

Exam of Informatics - R Programming

We have a data frame `points` with two columns x and y representing points in a two dimensional space. For each point p_i we want to find the point $p_{nn(i)}$ such that his distance $d(p_i, p_{nn(i)})$ is the minimum with respect to the distances $d(p_i, p_j), \forall j \notin \{i, nn(i)\}$ of the other points

	x	y	nn	nn_dist
1	1	1	7	0.58309518948453
2	2	1.5	7	0.53851648071345
3	4	4	4	1.4142135623731
4	3	3	3	1.4142135623731
5	1.5	3	4	1.5
6	4	1.5	4	1.80277563773199
7	1.5	1.3	2	0.53851648071345

The solution must not assume that the x values are sorted. Write a function which takes as parameters a numeric vector x and a positive integer n and returns the vector of discretised values xd.

Translate in R the pseudo-code algorithm(s) provided in next page.

Continue

Algorithm

Given a dataframe whose columns represent the coordinates of points in a d-dimensional space, for each point find the index and the distance of the nearest neighbour

Method:

for each point scan the entire dataset to find the other point with minimal distance

Parameters:

- df: a dataframe where each row represent a point in a d-dimensional space

Uses:

- i: index for the main loop on points
- j: index for the secondary loop on the neighbours of a point i
- dist_nn_i: distance of the nearest neighbour of i
- nn_i: nearest neighbour of i
- dist_ij: distance of the current pair i,j

Algorithm:

- prepare an empty dataframe with two columns: the index of the nearest neighbour and its distance from the corresponding point
- repeat for each row i of the dataframe
 - initialize the minimum distance dist_nn from i to the maximum double
 - for each row j in the dataframe different from i
 - compute the distance dist_ij between the point in i and the point in j
 - if dist_ij is smaller than the current minimum dist_nn_i
 - set dist_nn_i to dist_ij
 - set nn_i to j
 - store the pair nn_i,dist_nn_i to the i row of the output
- return the output dataframe

#Test program

- read the file into a dataframe df
- store in a dataframe df_nn the result of the call of the function with parameter df
- print df_nn