The
Oaklisp Language Manual

November 5, 2026

Barak A. Pearlmutter
Dept. of Computer Science
Maynooth University
Co. Kildare
Ireland
barak+oaklisp@pearlmutter.net

Kevin J. Lang
Yahoo! Research
1961–2019

Copyright ©1985, 1986, 1987, 1988, 1989, 1991. by Barak A. Pearlmutter and Kevin J. Lang.

Contents

1 Introduction **1**

2 Types and Objects **4**
2.1 Fundamental Types . . . 4
2.2 Operations on Objects . . . 5
2.3 Operations on Types . . . 5
2.4 Defining New Types . . . 6
2.5 Type Predicates . . . 6
2.6 Constants . . . 6
2.7 Standard Truth Values . . . 7
2.8 Coercion . . . 7
2.9 Mixing Types . . . 8

3 Methods and Scoping **9**
3.1 Methods . . . 9
3.2 Scoping . . . 9
3.3 Functional Syntax . . . 10
3.4 Dispatching to Supertypes . . . 11
3.5 Rest Args . . . 11

4 Side Effects **13**
4.1 Assignment . . . 13
4.2 Locatives . . . 13
4.3 Operation Types . . . 14
4.4 Modification Forms . . . 14

5 Evaluation and Locales **15**
5.1 Evaluation . . . 15
5.2 Installing Names in a Locale . . . 16
5.3 Structuring the Namespace . . . 17
5.4 Variables . . . 17
5.5 Macros . . . 18
5.6 Compilation . . . 18

6 Dynamic State **19**
6.1 Fluid Variables . . . 19
6.2 Non-local Exits . . . 19
6.3 Error Resolution . . . 21
6.3.1 Signaling Errors . . . 21
6.3.2 Restart Handlers . . . 21
6.3.3 Error Handlers . . . 22
6.3.4 Operations on Errors . . . 22
6.3.5 Error Types . . . 23

7 Threads **25**
7.1 Threads . . . 25
7.2 Mutexes . . . 26
7.3 Condition Variables . . . 26
7.4 Atomic Operations . . . 27
7.5 Examples . . . 27

8 Control **28**
8.1 Simple Constructs . . . 28
8.2 Mapping Constructs . . . 29

9 Sequences **30**
9.1 Type Predicates . . . 30
9.2 Sequence Operations . . . 31
9.3 Vector Constructors . . . 31
9.4 List Constructors . . . 32
9.5 List Accessors . . . 32
9.6 Lists as Sets . . . 33
9.7 Lists as Associations . . . 33
9.8 Lists as Stacks . . . 34

10 Numbers **35**
10.1 Arithmetic . . . 35
10.2 Comparison . . . 36
10.3 Conversion . . . 37
10.4 Predicates . . . 37
10.5 Rounding . . . 37
10.6 Bitwise Logical Operations . . . 38
10.7 Accessing Components . . . 38

11 Input and Output **39**
11.1 Streams and Files . . . 39
11.2 Reading . . . 41

11.3 Printing 43

12 Miscellaneous **45**
12.1 Tables 45
12.2 Delays 45

13 User Interface **47**
13.1 Invoking Oaklisp 47
13.1.1 Architectures 48
13.2 The Top Level Environment 49
13.3 Miscellaneous Functions 50
13.4 Debugging 50

Chapter 1

Introduction

This is the introduction to the original Oaklisp proposal which we wrote in January 1985. Although the core language hasn't changed since then, some of the peripheral ideas in the proposal have been modified or abandoned.

One of the most interesting language ideas to emerge from the 1970's was the object-oriented programming model. Although this model has been incorporated to some extent in a number of recent Lisps, these implementations have not had the generality and power that characterize a true object-based system like Smalltalk. The most significant trend in the contemporary Lisp world is the move toward lexical scoping, which was initiated by Steele and Sussman with their Scheme papers and continued most faithfully by the designers of T.

The major goal of Oaklisp was to combine the ideas of Smalltalk and Scheme in a simple but expressive language that inherits their exemplary properties of modularity and consistency. Unlike T, which adds an object-based capability to Scheme by constructing objects out of closures, Oaklisp builds a lexically scoped Lisp system on top of a general message-passing system that allows for full inheritance of methods from multiple superclasses.

The first design choice for Oaklisp was the extent to which we should push the object-based model. We agreed with the designers of ADA that the packaging of state and procedures into new types can be a significant modularity tool for users of the language. We also agreed with the designers of the Lisp Machine that single-user Lisp systems should be open, with no clear line between system and user code. Therefore, both to allow the system implementors to use powerful user-level tools and to allow users to easily manipulate the system, we decided that absolutely everything should be a full-fledged object in Oaklisp. There is no reason why user-defined types should be any different from the types used to build the system. Oaklisp stands in marked contrast to other object-oriented Lisp systems which have magic data types that are not part of the user-level type hierarchy.[1] Our current Oaklisp implementation takes this idea to such an extreme that there are no magic objects anywhere in the system, no matter how deep you go. This meant not only that the vast majority of the system could be written in Lisp, but that the construction of the debugger and garbage collector was greatly simplified.

[1] For example, ZetaLisp flavors are not themselves instances of flavors.

As a corollary to the previous decision, we decided that all computation should be performed by methods that are invoked after a search up the type hierarchy. Functions can be thought of as methods attached to the top of the hierarchy, since they are methods that can perform an operation on any type. This leads to the interesting result that after a function has been defined, a new method can be added to take over that operation for a special case.

The power of the method-invocation model of computation is derived from the generality of the inheritance mechanism.[2] A simple type-tree would have provided Oaklisp with the ability to define shadowable system-wide defaults for `print` and so forth. However, we felt that the mixin concept of flavors was such a valuable tool for factoring object functionality that inheritance from multiple supertypes was essential. This idea of inheriting from several mixins, each of which knows how to do something and encapsulates its own state, led to the following inheritance rule: a new type inherits all of the methods of its supertypes, but methods for the new type cannot refer to instance variables from the supertypes (even though those variables do exist in the new composite object.) This does not cause problems, because when operations for the supertypes are passed to the object, the methods which handle them *can* reference the appropriate instance variables. Since the names of instance variables are never inherited, conflicts cannot occur between names in the various supertypes.

This treatment of instance variable names was also motivated by our decision to follow Scheme and make Oaklisp lexically scoped. Oaklisp not only benefits from the conceptual correctness which results from being able to close methods at compile time, but takes full advantage of tail-recursion and the lack of search associated with variable references. Once again, we decided to carry a principle to its extreme, and say that *all* variable references must be resolved at compile time, which results in both a simpler compiler and faster execution of code. Although this decision sounds intolerable for users, it actually represents a shift of functionality from the compiler to the error-handling system and user-interface, both of which we decided to make unusually powerful in our Oaklisp implementation.

Another principle which we borrowed from Scheme is anonymity. The lack of coupling between names and objects gives the system a degree of modularity and flexibility that would otherwise be difficult to achieve. For example, if a type is redefined, old instances of that type will still have pointers to the old type descriptor. Operations on both kinds of object will be handled by the correct methods, and when the last instance of the old type goes away, the old type descriptor will also be garbage collected.

The portion of Oaklisp that has been described so far can be considered its kernel. The portion that follows can mostly be implemented as methods at the user level. It is interesting to note that the dynamic variables and mutable binding contours which are described below can be built on top of a bare lexical Lisp kernel. However, the Oaklisp kernel is not a usable system, since we intentionally stripped it down knowing that the lost facilities would be replaced at a higher level.

The first addition is a mutable binding contour facility based the locale structures of T.[3] Oaklisp locales are objects that accept messages which install and look up names. Locales

[2] It is primarily the lack of inheritance that weakens the T object facility.

[3] In place of locales we could have implemented a simple top-level binding environment.

can have multiple superiors which are recursively searched if a name can't be found. Unlike T locales, Oaklisp locales are not associated with textual binding contours that can interact with `let`'s and generate ambiguities. Moreover, a reference to an undefined name creates an error, which means that forward references to uninstalled names are impossible.

The second addition is a dynamic scoping facility that knows how to deal with `catch` and `throw`. The new dynamic variables are entirely separate from the static variables, and are always textually distinguishible from static variables to avoid confusion. Dynamic variables use deep-binding in our implementation so that they will behave correctly when there is more than one process. The implementation of dynamic variables is an issue since we decided to follow the Lisp Machine and implement light-weight processes that share the same address space to expedite data sharing and fast context switching.

Our final design decision was also influenced by the Lisp Machine. Error handling in Oaklisp is designed to take maximum advantage of the type inheritance mechanism that is built into the language. A complete hierarchy exists of all the types of system errors. When an error occurs, an instance of that error type is created, and a message is sent to the error object asking for a handler to take control. The default message causes the debugger to be invoked. However, each process has some dynamic state which can be modified with the `bind-error-handler` construct to cause a different handler to be invoked when a particular error occurs at a particular time. This mechanism brings the full power of the language to bear on the problem of resolving errors, and is the reason that we felt we could make the language itself so strict with respect to variable references. Since our implementation of Oaklisp runs on the Lisp Machine and the Macintosh, it was no problem to delegate authority for reporting and resolving unbound variable references to the user-interface, which uses menus and dialog boxes to determine the user's intentions. If the user sets a switch that indicates that he wants unbound names to be automatically installed in the innermost locale, then the interface merely creates an error-handler to perform that function, and the user is not bothered again.

Chapter 2

Types and Objects

Oaklisp is an object-oriented language which is organized around the concept of *type*. The type of an object determines its behavior when operations are performed on it. To permit the modular specification of types with complex behaviors, a type is allowed to have multiple supertypes. There is no distinction in Oaklisp between predefined system types and user-defined types.

A type specifies the behavior of an object by providing methods that are used to perform operations on that object. Because methods are inherited from supertypes, a subtype only needs to supply those methods which are required to distinguish itself from the more general types. A method defined for a given type pre-empts any inherited methods for the same operation.

Instance variables are the mechanism for keeping state in objects. Every object possesses a data structure where the values of its instance variables are stored. Although each object contains storage for all of the instance variables required by its type and supertypes, methods for a given type can only refer to instance variables defined in that type. In particular, methods cannot refer to instance variables that are defined in supertypes.

It is possible to think of Oaklisp in terms of messages that are being passed to objects, rather than in terms of operations that are being performed on objects. The latter view was chosen because it is more consistent with Lisp syntax and semantics.

2.1 Fundamental Types

There are two important relations in the Oaklisp type system: *is-a* and *subtype*. An object is related to its type by the relation *is-a*, and a type is related to its supertypes by the relation *subtype*. Each of these relations defines a tree structure which includes all of the objects in the system.

The most fundamental types in the system are `type` and `object`. They are distinguished by their position at the top of the *is-a* and *subtype* hierarchies, and by their circular definitions.

`type` *Type*

This type is the top of the *is-a* hierarchy. It is the type of types, so new types are created by instantiating it.

`object` *Type*

This type is the top of the *subtype* hierarchy, and has no supertype. Every other type is a subtype of `object`, so default methods for operations such as `print` are defined for `object`.

2.2 Operations on Objects

The following operations are defined for all objects. Because they determine the semantics of the language, they cannot be redefined or shadowed.

`(get-type` *`object`*`)` *Operation*

Returns the type of `object`.

`(eq?` *`object object`*`)` *Predicate*

Determines object identity. Two objects may look and act the same, but still fail the `eq?` test. In particular, numbers are not guaranteed to be unique. Symbols *are* interned, though.

2.3 Operations on Types

Types are distinguished from other objects by the fact that they can perform the `make` operation, which is the mechanism for generating new objects.

`(make` *`type`*`)` *Operation*

Returns a new instance of `type`.

The instance variables of an object returned by `make` are all bound to some unspecified value. Usually new objects need to be initialized in some other way, which can be accomplished by performing an operation on them immediately after they are made. By convention, this operation is `initialize`.

`(initialize` *`object`*`)` *Operation*

Returns `object`.

This method for `initialize` is clearly a no-op. When a type requires special initialization, it should shadow this default.

2.4 Defining New Types

Since types are objects, new ones are created by sending a `make` message to the appropriate type object, which in this case is `type`.

`(make type` *ivars supertypes*`)` *Operation*

Returns a new type-object with the supertypes and instance variables specified by the argument lists.

At run-time, methods are chosen by performing a left-to-right depth-first search on the supertype list.[1] Instances of the new type will contain a block of instance variables for each of the ancestor types, although duplicate types in the ancestor tree are eliminated.[2]

2.5 Type Predicates

The implicit type checking performed by the method invocation mechanism of Oaklisp reduces the need to call explicit type predicates. Furthermore, the two predicates defined in this section are sufficiently general to replace all of the ordinary Lisp type predicates such as `null?` and `number?`. A few of these have been retained to make the environment more familiar.

`(is-a?` *object type*`)` *Predicate*

Determines whether `object` is an instance of *type* or one of its subtypes. `(is-a?` *object* `object)` is always true.

`(subtype?` *type1 type2*`)` *Predicate*

Determines whether *type1* is a subtype of *type2*. As you would expect, `subtype?` is transitive. Since each type is a subtype of itself, `subtype?` defines a partial ordering of all the types in the system.

2.6 Constants

Some objects have external representations that are not self-evaluating expressions. `quote` allows the inclusion of such objects as constants in code.

`(quote` *object*`)` *Special Form*

Returns *object* without evaluating it.

[1] Of course, Oaklisp implementations are free to use more efficient mechanisms that have the same effect.

[2] This aspect of the language is in flux, and should not be relied upon by users.

2.7 Standard Truth Values

The standard truth values of Oaklisp are represented by the objects bound to the following variables.

`t` *Global Variable*

The value of this is `#t`. Any non-false value will do just as well for the purpose of logical tests.

`#f` *Global Variable*

This is the false value, the only object recognized by logical tests as denoting falsehood.

`nil` *Global Variable*

The value of this is the empty list, written `()`. Notice that `nil` itself is just a variable, so `(eq? nil 'nil)` is false.

Note: currently `()` is the same as `#f`, the object used to represent falsehood. In the future it is possible that these two notions, emptiness and falsehood, will be disconfabulated. Programs should be written in such a way that if `#f` and `()` were not the same object, they would still work.

2.8 Coercion

Some types are *coercable*, meaning that there is an operation associated with that type that allows objects to be coerced to that type. To create a coercable type, one instantiates `coercable-type` rather than `type`.

`(coercer` *`coercable-type`*`)` *Locatable Operation*

This returns the coercer of a type. For example, to coerce a list into a string one uses `(coercer string)`, as in `((coercer string) '(#\f #\o #\o))` ⇒ `"foo"`. The reader will read `frog` preceded by a control-y character as `(coercer frog)`; this was motivated by the fact that control-y prints as → on both Macintosh™ and Symbolics computers, giving coercion a pleasant syntax, `(→string '(#\f #\o #\o))` ⇒ `"foo"`.

`coercable-type` *Type*

This is a subtype of `type` with has the added functionality of responding to the `coercer` message by returning its coercion operation. By default, `(is-a?` *`foo bar`*`)` implies that `((coercer` *`bar`*`)` *`foo`*`)` ⇒ *`foo`*

2.9 Mixing Types

Frequently, type hierarchies become so rich that they threaten to overwhelm users with a plethora of possible combinations of mixins. The combinatorial explosion of the number of possible concocted types seems intrinsic to the style of programming involving multiple functionally orthogonal mixins. Above a certain level of complexity, finding a type with certain known characteristics can become difficult. Programmers are left wondering "Has a type based on *foo* with *bar, baz* and *zonk* mixed in been created, if so what's its name, and if not what should I name it and where should I define it?"

Oaklisp's *mixin managers* take care of this problem. When one needs "the type based on *foo* with *bar, baz* and *zonk* mixed in," one asks a mixin manager for it. If such a type has already been created, it is returned; if not, the mixin manager creates an appropriate new type, caches it, and returns it. This eliminates the burden of remembering which types have been concocted and what they are named.

`(mix-types` ***mixin-manager type-list***`)` *Operation*

This returns a composite type whose supertypes are *type-list*. *Mixin-manager* checks its cache, and if the requested type is not found it creates a type with `(make type '()` ***type-list***`)`, caches it, and returns it.

`mixin-manager` *Type*

Instances of this cache composite types, acting as a sort of composite type library.

The Oaklisp operation type hierarchy is quite elaborite, containing a large number of functionally orthogonal mixins, and therefore the Oaklisp internals make heavy use of the mxin manager facility when dealing with operations. For example, the following definition of `eqv?` is drawn from deep within the bowels of Oaklisp.

```
(define-constant eqv?
  (add-method ((make (mix-types oc-mixer (list foldable-mixin operation)))
               (object) x y)
    (eq? x y)))
```

Chapter 3

Methods and Scoping

In Chapter 2, the concept of *type* was discussed. The assertion was made that operation methods lie at the heart of the typing system, because they determine the behavior of objects. This chapter describes the mechanism for defining methods.

3.1 Methods

A table of methods is maintained in the descriptor of every type. At run-time, these tables are searched to find the methods which are used to handle operations on objects. The only mechanism for manipulating method tables is the following side-effecting special form.

`(add-method (`*`operation`* [`(`*`type . ivar-list`*`)`] `.` *`arg-list`*`). `*`body`*`)` *Special Form*

> Adds a method for *operation* to the method table of *type*. If a method for *operation* already exists, it is replaced. The value returned by `add-method` is *operation*.

The body of the form is surrounded by an implicit `block`. The arguments to the method are specified by *arg-list*. Since the first argument is always the object handling the message, a useful convention is to call it `self`. Instance variables of *type* can be referenced in the body if they are declared in *ivar-list*. Instance variables of supertypes may not be referenced in any case. Naming conflicts between instance variables and arguments are resolved by the rule that the variables in *arg-list* shadow instance variables that have the same names. Oaklisp closes methods over free variable references at compile-time, thereby solving the upward funarg problem and allowing procedures to share state in a controlled manner.

3.2 Scoping

Oaklisp is a lexically scoped language in which all variable references are resolved at compile-time. When a variable reference is encountered, the compiler searches outwards from that

point through the nested lexical binding contours until it finds a declaration for the variable.[1] We have already seen one mechanism for introducing new lexical contours: the argument list of the `add-method` special form. Oaklisp provides several other forms which can be used to define local variables and procedures.

`(let ((`var_1 val_1`)...`var_n val_n`). body)` *Special Form*

Evaluates *body* in an environment where the n variables are bound to the n values. The value returned is that of *body*.

`(let* ((`var_1 val_1`)...`var_n val_n`). body)` *Special Form*

This form is similar to `let`. The difference is that `let` performs the bindings simultaneously whereas `let*` performs the bindings sequentially so that each value expression can refer to the preceding variables.

`(labels ((`var_1 val_1`)...(`var_n val_n`)). body)` *Special Form*

`labels` differs from `let` in that the value expressions are evaluated in a binding environment in which all of the variables are already defined. This facilitates the definition of mutually recursive procedures.

3.3 Functional Syntax

Sometimes it is convenient to adopt a more conventional Lisp viewpoint while designing programs. This viewpoint considers functions to be the primary programming abstraction, with objects downgraded to the status of data which is passed around between functions. The key to this programming style is the ability to write functions which can accept arguments of any type.

Oaklisp readily accommodates the functional programming style, since methods can be defined for the type `object`, which is the supertype of all other types. In fact, if the type specifier is omitted in an `add-method` form, the type `object` is assumed. Thus, `(add-method (cons-1 x) (cons x 1))` defines a method that is valid for any type. To give the language a more familiar appearance when this programming style is used, the following macros are also provided.

`(lambda arg-list . body)` *Macro*

≡ `(add-method ((make operation) .` *arg-list*`) .` *body*`)`

`(define (`*variable* `.` *arg-list*`). body)` *Macro*

≡ `(define` *variable* `(lambda` *arg-list* `.` *body*`))`

[1] If a declaration isn't found, the compiler proceeds to look for the variable in the appropriate locale. See Chapter 5.

When *arg-list* is dotted, the rest name is bound the native way, as described in the section on rest args below, only if the body uses it as a rest name: at the end of a call in tail position, or in a `rest-length` form. A body that uses the name any other way—as an ordinary variable, at the end of a call that is not in tail position, or inside an inner `lambda`—gets it bound to a list of the extra arguments, collected with `listify-args`; in such a body `(f a . rest)` means `(apply f a rest)` and `(rest-length rest)` means `(length rest)`. This holds for every method, whether written with `lambda`, `define` or `add-method`. A `lambda` or `define` body that never passes its rest args on gets the list as well, since it could not otherwise return. A rest name that begins with `%` is always bound the native way, for code that plays tricks with the stack.

3.4 Dispatching to Supertypes

Sometimes a method doesn't want to override the inherited method completely, but rather wishes only to modify or extend its behaviour. For instance, imagine that the type `dog` has a method so that the `notice-stranger` operation causes it to run around, jump up and down, bark, and return the amount of time wasted. Say that `stupid-dog` is a subtype of `dog` defined by `(define-instance stupid-dog type '() (list dog))`, and that we want stupid dogs to behave just like regular dogs in response to a `see-stranger` message, except that they do it twice. This could be accomplished without the duplication of code by dispatching to the supertype twice, as in the following code fragment.

```
(add-method (see-stranger (stupid-dog) self stranger)
  (+ (↑super dog see-stranger self stranger)
     (↑super dog see-stranger self stranger)))
```

`(↑super` *type operation self . args*`)` *Operation*

This is just like (*operation self . args*) except that the method search begins at *type* rather than at the type of *self*. It is required that *type* be an immediate supertype of the type that the method this call appears in is added to, although our current implementation does not yet enforce this restriction. `↑super` is analogous to the Smalltalk-80 mechanism of the same name, except that due to Oaklisp's multiple inheritance it is necessary for the programmer to explicitly state which supertype is to be dispatched to.

3.5 Rest Args

When a method is defined with a parameter list that is improper (*i.e.* dotted) the method is permitted to receive extra values in addition to its regular parameters at run time. These values are associated with the pseudo variable name that appears after the dot, which will henceforth be called the rest name. Unlike a real variable name, a rest name can't be evaluated and can only be referred to in two places: at the end of a function call that uses

dotted syntax (which signifies that the extra values should be passed on to the function being called), and in a `rest-length` form, which is the mechanism for finding out how many rest args a method has been passed. (A method whose body uses its rest name in any other way receives the rest args as a list instead; see `lambda` above.)

`(rest-length` *`rest-name`*`)` *Special Form*

Yields the number of extra values that were received by the method in which `rest-name` is declared.

Used the native way, rest args can never be accessed directly, but must be passed tail recursively to other functions. In fact, a function is not permitted to return without disposing of its rest args. Usually a function that takes a variable number of arguments will recurse on itself or on a helper function, consuming its arguments one by one until they are all gone, at which point the function is free to return.

The following functions have been provided to make it easier to write a function definition that satisfies all of the rules for rest args.

`(consume-args` *`val . args`*`)` *Operation*

Returns *val* after consuming *args*.

`(listify-args` *`op . args`*`)` *Operation*

Calls *op* on a list consisting of the values of *args*.

A call to `listify-args` can be used as the body of a method definition as a means of trivially satisfying the rest arg rules. When using this technique, *op* is a lambda that performs all of the computation for the method. The rest args of the method are wrapped up in a list that is passed in as the lambda's one parameter, and the regular parameters and instance variables of the method are available inside the lambda because of lexical scoping.

Chapter 4

Side Effects

The treatment of side effects in Oaklisp is modelled on that of T. The salient feature of this approach is the use of reversible access procedures to perform side effects on composite data structures and anonymous storage cells.

4.1 Assignment

Side effects on variables and objects are performed with the `set!` special form, which combines the functionality of the `setq` and `setf` forms found in other Lisps.

`(set!` *`location new-value`*`)` *Special Form*

Changes the value of *location* to *new-value*, which is then returned as the value of the expression.

If *location* is a symbol, then it is interpreted as a variable name. The variable must have been previously defined in some lexical binding contour or locale.

If *location* is a list, then it is interpreted as a reference to a settable access operation. For example, `(set! (car foo) 'bar)` means the same thing as `(rplaca foo 'bar)` in Common Lisp.

`(setter` *`operation`*`)` *Locatable Operation*

Takes a settable access operation and returns the corresponding alteration operation.

4.2 Locatives

`locative` is an Oaklisp type that is similar to the pointer types found in procedural languages such as C or Pascal. Locatives are created and dereferenced by the following constructs.

`(make-locative` *`location`*`)` *Special Form*

Returns a locative that points to *location*, which must be a variable or a list with the form of a call on a locatable access operation.

`(locater operation)` *Locatable Operation*

Takes a locatable access operation and returns the corresponding locative-making operation.

`(contents locative)` *Locatable Operation*

Returns the contents of the location which is referenced by *locative*. Since `contents` is a settable operation, side effects can be performed on locations through locatives. For example, `(set! (contents (make-locative (car foo))) 'bar)` has the same effect as `(set! (car foo) 'bar)`.

4.3 Operation Types

Since operations are objects, they are classified into types according to the operations which can be performed on them. The types discussed here can generate side-effecting operations from access operations.

`operation` *Type*

This is the generic operation type that is a component of all other operation types.

`settable-operation` *Type*

An access operation is settable if side effects can be performed through it. Settable operations respond to `setter`.

`locatable-operation` *Type*

An access operation is locatable if it retrieves information from a single physical location. Locatable operations respond to `setter` and `locater`.

4.4 Modification Forms

See Chapter 6 of *The T Manual* for a description of the following forms.

`(swap location`$_1$ `location`$_2$`)` *Special Form*

Exchanges the contents of the two locations.

`(modify-location location procedure)` *Special Form*

Stores the result of calling *procedure* on the contents of *location* back into *location*.

Chapter 5

Evaluation and Locales

Locales are the namespace structuring mechanism of Oaklisp. Whenever an Oaklisp expression is evaluated, a locale must be provided in order to specify a particular mapping from symbols to macro-expanders and from symbols to storage cells.

5.1 Evaluation

`(eval` *`form locale`*`)` *Operation*

Evaluates *form* relative to *locale*.

Although programmers don't often need to call `eval` directly, every expression typed at the top level is passed in to `eval` to be evaluated relative to the locale specified by the fluid variable `current-locale`. Files may be evaluated using the `load` function.

`(load` *`file-name`* [*`locale`*]`)` *Operation*

Reads all of the forms in the file *file-name* and evaluates them relative to *locale*, which defaults to the value of `(fluid current-locale)` if not specified.

The file compiler can be used to create an assembly language file that has the same effect as an Oaklisp source file.

`(compile-file` *`locale file-name`* [*`output-name`*]`)` *Operation*

Compiles the file *file-name* relative to *locale*, which defaults to the value of `(fluid current-locale)`. A file must be compiled and loaded relative to the same locale in order to guarantee that the program's semantics are preserved. The object is written to *output-name* if given, otherwise into the directory `(fluid compiler-output-directory)` if that is set, otherwise beside the source.

Oaklisp source files have a default extension of `.oak` while compiled files are given the extension `.oa`. `compile-file` first tries to read the file *file-name*`.oak`, and then looks for *file-name*, while `load` looks for *file-name*`.oa`, then for *file-name*`.oak`, and finally for *file-name*. When both *file-name*`.oa` and *file-name*`.oak` exist, `load` uses whichever was modified more recently, so a source file edited after it was last compiled is not shadowed by a stale object; if their modification times are equal the compiled file wins.

5.2 Installing Names in a Locale

Oaklisp has several forms that can be used to insert global variables and macro definitions into a locale. The target locale isn't explicitly specified by any of these forms, but is implicitly understood to be the locale with respect to which the form is being evaluated. Thus, when a form is typed at the top level, the effect is on `(fluid current-locale)`, and when a file is loaded, the effect is on the locale specified in the call to `load`.

`(define` *var val*`)` *Special Form*

Installs the global variable *var* in the current locale with value *val*.

`(define-constant` *var val*`)` *Special Form*

This form is like `define` except that *var* is marked as frozen in the current locale so that the compiler can be free to substitute the value for references to *var*.

`(define-instance` *var typ . make-args*`)` *Special Form*

If the contents of *var* isn't of type *typ*, this is the same as `(set!` *var* `(make` *typ . make-args*`))`. If *var* is already bound to an object of the right type, this form has no effect. *Note:* this language feature is in flux. Currently, it sends an `initialize` message to the object with the new *make-args*.

`(define-syntax` *macro-name expander*`)` *Special Form*

Installs *macro-name* in the current locale. *expander* should be a lambda that is able to translate an example of the macro into a form that has simpler syntax.

As with all Oaklisp forms, the effect of a `define-syntax` form in a file is not felt until run-time when the file is loaded. Since it is often convenient to be able to use a macro in the file in which it is defined, a special mechanism has been provided for defining file-local macros that are in effect at compile time. The following magic forms should be used with care, since they violate the usually absolute dichotomy between compile time and load time.

`(local-syntax` *macro-name expander*`)` *Special Form*

During the compilation of a file in which a `local-syntax` form is contained, the form augments the name space with the macro specified by *macro-name* and *expander*. This form can only appear at top level in a file; and essentially disappears before load time.

`(define-local-syntax` *macro-name expander*`)` *Special Form*

Temporarily augments the compile-time name space with the specified macro, and also installs the macro in the current locale when the file is loaded. This form can only appear at top level in a file.

5.3 Structuring the Namespace

Oaklisp locales are not associated with textual binding contours, nor are they particularly user-friendly objects. They were designed to be a powerful implementation tool, leaving the task of providing a convenient interactive interface to higher-level code.

`(make locale` *`superior-list`*`)` *Operation*

Returns a new locale which inherits names from the locales in *superior-list*. During recursive name lookups, the superiors are searched deapth first in left-to-right order.

5.4 Variables

Locales are essentially mappings from symbols to storage cells. Although locales can be created on-the-fly, their main use is in building the structured top-level environment for global variables. Variable names must be installed in a locale before they can be referenced. Precise control over shadowing and cross-referencing can be achieved using the following settable operations.

`(variable?` *`locale symbol`*`)` *Settable Operation*

Returns a locative to the appropriate storage cell if *symbol* is installed as a variable name, or `#f` otherwise. The search is allowed to proceed to superior locales if necessary.

`(set! (variable?` *`locale symbol`*`)` *`locative`*`)` *Operation*

If *symbol* is not currently defined at any level, then it is installed in *locale*, with the location named by *locative* serving as its value cell. If *symbol* is defined at some level, then its value cell at the highest level[1] is changed to be the location referenced by *locative*.

`(set! (variable?` *`locale symbol`*`)` *`#f`*`)` *Operation*

If *symbol* is defined at some level, then its definition is removed from the highest level. Otherwise an error is generated.

`(variable-here?` *`locale symbol`*`)` *Settable Operation*

Returns a locative to the appropriate storage cell if *symbol* is installed as a variable name, or `#f` otherwise. The search is constrained to *locale* itself.

`(set! (variable-here?` *`locale symbol`*`)` *`locative`*`)` *Operation*

[1] *i.e.* in the nearest locale to the one handling the operation.

If *symbol* is not currently defined in *locale*, then it is installed, with the location named by *locative* serving as its value cell. If *symbol* is defined in *locale*, then its value cell is changed to be the location referenced by *locative*.

`(set! (variable-here? locale symbol) #f)` *Operation*

If *symbol* is defined in *locale* then its definition is removed. Otherwise an error is generated.

5.5 Macros

Macro definitions are also stored in locales. These definitions are stored as a mapping from names to macro expanders. A macro expander is simply a one-argument function that takes an S-expression as its input and returns a transformed S-expression. Macro definitions are installed with the following settable operations, which are entirely analogous to the ones described in Section 5.4.

`(macro? locale symbol)` *Settable Operation*

Returns the appropriate macro expander if *symbol* is installed as a macro name and `#f` otherwise. The search is allowed to proceed to superior locales if necessary.

`(macro-here? locale symbol)` *Settable Operation*

Returns the appropriate macro expander if *symbol* is installed as a macro name, or `#f` otherwise. The search is constrained to *locale* itself.

5.6 Compilation

All evaluation in Oaklisp is performed with respect to some locale. The syntax of the language is determined by the macro tables visible from that locale, and free variable references are likewise resolved using the global variables defined in its name space.

`(frozen? locale symbol)` *Settable Predicate*

Returns `#t` if *symbol* is a frozen variable, otherwise `#f`. The search is allowed to proceed to superior locales if necessary. If *symbol* is not found anywhere, an error occurs.

`(frozen-here? locale symbol)` *Settable Predicate*

Returns `#t` if *symbol* is a frozen variable, otherwise `#f`. The search is constrained to *locale* itself. If *symbol* is not installed as a variable in *locale*, an error occurs.

Chapter 6

Dynamic State

As Steele and Sussman pointed out in *The Art of the Interpreter*, dynamic scoping provides the most natural decomposition of state in certain situations. This chapter describes the Oaklisp facilities for creating and manipulating state that has dynamic extent.

6.1 Fluid Variables

To avoid the problems that arise when fluid variables are integrated with the lexical environment, Oaklisp fluid variables have been placed in a completely separate dynamic environment. Fluid variables don't even look like lexical variables, since they can only be referenced using the `fluid` special form. The mechanism for creating fluid variables is `bind`, which syntactically resembles `let`.

`(bind ((`*fluid* *var*$_1$`)`*val*$_1$`)...((`*fluid* *var*$_n$ *val*$_n$`). `*body*`)` *Special Form*

Evaluates *body* in a dynamic environment where the n symbols are bound to the n values.

`(fluid `*symbol*`)` *Special Form*

Returns the value of the fluid variable *symbol*. Even though `fluid` is a special form, it is settable, so `(set! (fluid `*symbol*`) `*value*`)` changes the value of the fluid variable *symbol* to *value*. The reader will read `foo` preceded by a control-v character as `(fluid foo)`; this was motivated by the fact that control-v prints as • on both Macintosh^{tm} and Symbolics computers.

6.2 Non-local Exits

Most Lisp dialects include some sort of `catch` facility for performing non-local exits. Oaklisp provides two facilities at varying points on the generality vs. cost spectrum.

`(call-with-current-continuation` *`operation`*`)` *Operation*

Calls *operation* with one argument, the current continuation. The synonym `call/cc` is provided for those who feel that `call-with-current-continuation` is excessively verbose.

`(catch` *`variable . body`*`)` *Special Form*

variable is lexically bound to an escape operation that may be called from anywhere within *body*'s dynamic extent. If *variable* is not called, `catch` yields the value of *body*. This is implemented in such a way that *body* is called tail recursively.

`(native-catch` *`variable . body`*`)` *Special Form*

variable is lexically bound to an escape tag that may be thrown from anywhere within *body*'s dynamic extent. If *variable* is not thrown to, `native-catch` yields the value of *body*. This is implemented in such a way that *body* is called tail recursively.

`(throw` *`tag value`*`)` *Operation*

Causes execution to resume at the point specified by *tag*. This point is always a `native-catch` expression, which immediately yields *value*. Cleanup actions specified with `wind-protect` are performed while the stack is being unwound.

`(wind-protect` *`before form after`*`)` *Special Form*

≡ `(dynamic-wind (lambda () ` *`before`*`) (lambda () ` *`form`*`) (lambda () ` *`after`*`))`

`(funny-wind-protect` *`before abnormal-before form after abnormal-after`*`)` *Special Form*

A `wind-protect` evaluates *before*, *form*, and *after*, returning the value of *form*. If *form* is entered or exited abnormally (due to `call/cc` or `catch`) the *before* and *after* forms, respectively, are automatically executed. `funny-wind-protect` is the same except that different guard forms are evaluated depending on whether the dynamic context is entered or exited normally or abnormally.

`(dynamic-wind` *`before-op main-op after-op`*`)` *Operation*

Calls the operation *before-op*, calls the operation *main-op*, calls the operation *after-op*, and returns the value returned by *main-op*. If *main-op* is exited abnormally, *after-op* is called automatically on the way out. Similarly, if *main-op* is entered abnormally, *before-op* is called automatically on the way in.

6.3 Error Resolution

Note: the error system is not stable, and will probably evolve towards the Common Lisp error system, which has a number of good ideas.

Programs interact with the error system in three ways: they signal various sorts of errors (typically throwing the user into the debugger), they provide restart handlers that the user can invoke (using `ret`) to escape from the debugger, and they provide handlers to be invoked when various types of errors occur.

6.3.1 Signaling Errors

Errors are signalled using the following operations.

`(warning` *`format-string . format-args`*`)` *Operation*
Prints out the message specified by *format-string* and *format-args* and continues execution.

`(error` *`format-string . format-args`*`)` *Operation*
This signals `generic-fatal-error`, which normally has the effect of printing out the error message specified by *format-string* and *format-args* and dumping the user into a subordinate read-eval-print loop.

`(cerror` *`continue-string format-string . format-args`*`)` *Operation*
This signals `generic-proceedable-error`, which normally has the effect of printing the error message specified by *format-string* and *format-args* and dumping the user into a subordinate read-eval-print loop in which there is a restart handler that continues the computation by returning a user specified value from `cerror`. *Continue-string* is the text associated with this handler when it is listed as an option by the subordinate evaluator.

6.3.2 Restart Handlers

There are two special forms that programs can use to define more complex restart handlers than just returning from the call to `cerror`. The simpler of the two is `error-return`, which is similar to `catch` in that it can be forced to return a value before its body has been fully evaluated. This form is used in the definition of `cerror`.

`(error-return` *`string . body`*`)` *Macro*
Evaluates *body* in a dynamic context in which a restart handler is available that can force the form to return. The handler is identified by *string* in the list of choices the debugger presents to the user. If the handler is invoked by calling `ret` with an argument in addition to the handler number, the `error-return` form returns this value; otherwise it returns `#f`. If no error occurs, `error-return` yields the value of *body*.

The second special form acts just like a `let` unless an error occurs, in which case an error handler is available that re-executes the body of the form after (possibly) rebinding the lexical variables specified at the top of the form.

`(error-restart` *string* `((`var_0 val_0`)...)` . *body*`)` *Macro*

Evaluates *body* in a dynamic context in which a restart handler is available that can force the re-evaluation of the body with new values for var_0 .... These new values are specified as additional arguments to `ret`. If there are not enough arguments to `ret`, the remaining variables are left at their previous values. The handler is identified by *string* in the list of choices printed by the debugger. If no error occurs, `error-restart` yields the value of *body*.

6.3.3 Error Handlers

Oaklisp uses its type system to govern the resolution of errors. The top-level environment contains a hierarchy of types which characterizes every error that can occur. When an error condition arises, the appropriate type is instantiated, and an error resolution operation is performed on the new object. This operation is performed by a method that deals with the error in a manner consistent with its type.

There are clearly better ways of dealing with some errors than invoking the debugger. A variety of methods have been written to deal with the most common errors. For example, there are `proceed` methods for simple arithmetic traps which substitute a program specified value for that of the failed computation. The use of `proceed` and other error resolution operations is prescribed by the following special form.

`(bind-error-handler (`*err op*`).` *body*`)` *Macro*

Evaluates *body* in a dynamic environment where the error type *err* has been associated with the error resolution operation *op*; nest the forms to handle several types. When an error occurs, the current list of condition bindings is searched to find an operation to perform. An operation associated with a supertype of the actual error type will be selected if it is encountered on the list. If a suitable operation cannot be found, the default operation `invoke-debugger` is performed.

6.3.4 Operations on Errors

There are a number of operations that can be invoked on error objects in error handlers.

`(report` *error stream*`)` *Operation*

Instructs *error* to print a descriptive message to *stream*.

`(invoke-debugger` *error*`)` *Operation*

This is the default error resolution operation. It is performed on all errors unless it is explicitly overridden.

`(proceed` *error* . *values*`)` *Operation*

Attempts to continue from the error, eg. a file system error would retry the failed operation. The *values* have semantics determined by the precise type of error. For instance, continuing a failed attempt to open a file with a value might instruct the system to try a new filename.

`(remember-context` *`error after-operation`*`)` *Operation*

Instructs *error* to salt away the current continuation and then call *after-operation*, which should never return.

`(invoke-in-error-context` *`error operation`*`)` *Operation*

Invokes *operation* on *error* after moving back to the context of the error if its been salted away.

6.3.5 Error Types

There are a plethora of error types defined in Oaklisp.

`general-error` *Type*

This is the top of the error type hierarchy. An operation defined for `general-error` can be used to resolve any error.

`generic-fatal-error` *Type*

Signaled by `error`.

`(make proceedable-error` *`message`*`)` *Operation*

Uses *message* in composing its report.

`generic-proceedable-error` *Type*

Signaled by `cerror`.

`error-opening` *Type*

Various subtypes of this are signaled when various types of error while opening files occur.

`read-error` *Type*

Subtypes of this are signaled when `read` sees malformed or truncated input.

`unexpected-eof` *Type*

This subtype of `read-error` is signaled when the reader comes to the end of a file unexpectedly.

Work for idle hands: Many types of errors have yet to be implemented. For example, domain errors in arithmetic functions generally call `error` rather than signaling some special variety of error, template mismatch in the `destructure*` macro should signal some special type of error rather than calling `cerror`, etc. Basically, most calls to `error` and `cerror` in system level code should be replaced with `signal`, and appropriate ideosyncratic types of errors should be defined, thereby giving users more precise control over what types of system level errors to handle.

Chapter 7

Threads

Oaklisp has two kinds of concurrency. *Processes* are lightweight: any number of them share one or more operating-system threads under a scheduler of Oaklisp's own, switching at `pause` and when preempted, and they are what `future`, `delay` and the semaphores of this chapter are built on. *Threads* are operating-system threads: with an emulator built with thread support (`configure -enable-threads`) Oaklisp code runs on several of them at once, and a program may make one of its own with `make-thread`.

Each thread runs one process from a thunk to its end. That process starts with a copy of its creator's fluid bindings and its creator's winding stack, so `bind` and `wind-protect` nest as they would in a call; global variables and all other objects are shared. The runtime's own tables (the symbol table, the locales, the streams) are safe to use from several threads at once, and `format` writes a call's whole output to a stream at once; a hash table of the program's own is safe to read while another thread writes it, but two writers need a mutex.

7.1 Threads

`(make-thread` *`thunk`* [*`name`*]`)` *Operation*

Starts an operating-system thread running *thunk* and returns its `thread` object at once. *Name* is for messages and `thread-name`; by default the threads are numbered. An error if the emulator has no thread support.

`(thread-join` *`thread`* [*`milliseconds`*]`)` *Operation*

Waits for *thread* to finish and returns the value of its thunk; joined again, returns it again. If the thunk signaled an error that nothing in the thread handled, `thread-join` signals an error in the joiner, carrying the thread's. With *milliseconds*, waits at most that long and returns `#f` if the thread is still running. While it waits, the joiner's own operating-system thread is parked: no other process runs on it meanwhile.

`(thread-alive?` *`thread`*`)` *Operation*

Whether *thread* has not finished yet.

`(thread-name` *thread*`)` *Operation*

The name *thread* was made with.

`(current-thread )` *Operation*

The `thread` object of the thread this is called on; the main thread's is named `main`, a scheduler thread's `scheduler`.

`(thread-count )` *Operation*

The number of operating-system threads running Oaklisp code.

`(thread-sleep` *milliseconds*`)` *Operation*

Suspends the calling thread for *milliseconds*.

7.2 Mutexes

A mutex may be held by one process at a time. It is held by a *process*: a process that is preempted inside a critical section and resumed on another thread still holds it, and only the holder may release it. A mutex is reentrant: the holder may acquire it again, and must release it as many times.

`(make-named-mutex` *name*`)` *Operation*

A new mutex, named for messages; `(make mutex)` makes an anonymous one.

`(acquire-mutex` *mutex*`)` *Operation*

Waits until *mutex* is free and takes it. While it waits the thread runs other processes or sleeps; it does not spin. A wait that goes on for seconds is reported on standard error, naming the mutex and its holder.

`(release-mutex` *mutex*`)` *Operation*

Releases *mutex*; an error if the caller does not hold it.

`(with-mutex` *mutex . body*`)` *Macro*

Evaluates *body* holding *mutex*, releasing it however the body is left, including by a throw.

7.3 Condition Variables

`(condition-variable )` *Operation*

The type; `(make condition-variable)` makes one. Used with a mutex that protects the state being waited for.

`(condition-wait` *condition-variable mutex* [*milliseconds*]`)` *Operation*

The caller must hold *mutex*. Releases it, waits until the condition variable is notified (or for at most *milliseconds*), takes *mutex* again and returns `#t`, or `#f` after a timeout. Wake-ups can be spurious: test the condition in a loop around the wait.

`(condition-notify` *`condition-variable`*`)` *Operation*

Wakes one waiter, if any; whether there was one.

`(condition-notify-all` *`condition-variable`*`)` *Operation*

Wakes every waiter; how many.

7.4 Atomic Operations

These act on a cell given as a locative, as `(make-locative (car x))` or `(make-locative variable)`, and compare with `eq?`, so they are for fixnums and objects, not bignums.

`(compare-and-swap` *`locative old new`*`)` *Operation*

If the cell holds *old* (by `eq?`), stores *new* and returns *old*; otherwise returns what the cell holds, unchanged. Atomic with respect to every other thread.

`(fetch-and-add` *`locative n`*`)` *Operation*

Adds n to the fixnum in the cell and returns the value it had.

7.5 Examples

Two programs in `doc/examples`: `parallel-map.oak`, a `map` that runs each application on a thread of its own, and `producer-consumer.oak`, a bounded queue with a mutex and two condition variables between a producer thread and a consumer.

Chapter 8

Control

Nonlocal control constructs like `call/cc` are described in section 6.2.

Since control structures are not a very interesting issue, we followed existing Lisp dialects closely when designing this aspect of Oaklisp. Every control structure in this chapter does just what you would expect.

8.1 Simple Constructs

These forms are compatible with both T (Rees et al., 1984, chapter 5) and the Scheme standard (Rees et al., 1986).

`(cond . clauses)` *Special Form*

The *clauses* are run through sequentially until one is selected. Each clause can be of four possible forms. (*test* . *body*) evaluates *body* if *test* is true. `(else` . *body*) always evaluates *body*, and if present must be the last clause. (*test* `=>` *operation*) calls *operation* on the result of *test* if the result of evaluating *test* was not *false*. (*test*) is equivalent to (*test* `=>` *identity*).

`(if test consequent` [*alternate*]) *Special Form*

`(not object)` *Predicate*

`(and . tests)` *Special Form*

`(or . tests)` *Special Form*

`(iterate variable specs . body)` *Special Form*

`(block . body)` *Special Form*

Evaluates the forms of *body* sequentially, returning (tail recursively) the value of the last one.

`(block0` *`form . body`*`)` *Special Form*
≡(let ((x *form*)) (block . *body*) x)

`(dotimes (`*`variable number`* [*`rform`*]`). body)` *Special Form*
≡(let ((x (lambda (*variable*) . *body*))) (map x (iota *number*)) *rform*)

`(dolist (`*`variable list`* [*`rform`*]`). body)` *Special Form*
≡(let ((x (lambda (*variable*) . *body*))) (map x *list*) *rform*)

`(dolist-count (`*`variable list count-var`*`). body)` *Special Form*
Just like `dolist` except that *count-var* gives the count of the current element in the list, starting at zero.

`(while` *`condition . body`*`)` *Special Form*
≡(let ((q (lambda () *test*))(x (lambda () . *body*))) (iterate aux () (cond ((*q*) (*x*) (aux)))))

`(unless` *`test . body`*`)` *Special Form*
≡(cond ((not *test*) . *body*))

`(do ((`*`var initial step`*` )...)(`*`termination-test . termination-body`*` ). body)` *Special Form*
≡(iterate aux ((*var initial*) ...) (cond (*termination-test* . *termination-body*) (else (block . *body*) (aux *step* ...))))

8.2 Mapping Constructs

Although these can be used as control constructs, they can also be thought of as ways to manipulate data structures. `map` maps an operation over some sequences generating a sequence of results. `for-each`, which doesn't save the results, is used when the operation is called for effect only. For all of these, the order of evaluation is undefined; the system may apply the operation to the various elements of the sequence in any order it desires.

`(map` *`operation . sequences`*`)` *Operation*

`(mapcdr` *`operation . lists`*`)` *Operation*
Applies *operation* to successive "cdrs" rather than to elements, and returns a list of the returned values.

`(for-each` *`operation . sequences`*`)` *Operation*

`(for-each-cdr` *`operation . lists`*`)` *Operation*
Like `mapcdr` but for effect only.

`(map!` *`operation . sequences`*`)` *Operation*
Like `map`, except that the retuned values are destructively placed into the successive storage locations of the first *sequence*.

Chapter 9

Sequences

Sequences are manipulated using the `nth` operation, which is settable (and locatable). The sequence heirarchy is shown in figure 9.1.




Figure 9.1: The sequence type hierarchy. Abstract types are in plain face and instantiable ones in bold.

9.1 Type Predicates

`(sequence?` *object*`)` *Predicate*

`(vector?` *object*`)` *Predicate*

`(string?` *object*`)` *Predicate*

`(list?` *object*`)` *Predicate*

`(pair?` *object*`)` *Predicate*

`(null?` *object*`)` *Predicate*

(atom? *object*) *Predicate*

9.2 Sequence Operations

These operations work on all sequences.

(length *list*) *Operation*

(nth *list n*) *Locatable Operation*

(last *list*) *Locatable Operation*

(tail *list n*) *Locatable Operation*

(copy *sequence*) *Operation*

(append *sequence1 sequence2*) *Operation*
Returns a sequence of the type of *sequence1*. The arguments must all be of the same type, except that when the first is a list the last one may be anything at all: as in Scheme, it becomes the tail of the result, so `(append '(1 2) 3)` is `(1 2 . 3)`. A mismatch between any of the others is an error.

(append! *sequence1 sequence2*) *Operation*
Most sequences have immutable lengths, and hence are not appropriate arguments to `append!`. The major exception is lists. The same rule about the last argument applies here as in `append`.

(reverse *sequence*) *Operation*

(reverse! *sequence*) *Operation*

Some mapping operations are also applicable to sequences, and are documented in Section 8.2.

9.3 Vector Constructors

(vector . *objects*) *Operation*
Returns a `simple-vector` containings *objects*.

(make simple-vector *length*) *Operation*

((coercer simple-vector) *sequence*) *Coarcable Type*

9.4 List Constructors

(list . *objects*) *Operation*

(make list-type *length fill-value*) *Operation*

((coercer list-type) *sequence*) *Coarcable Type*

(cons *object1 object2*) *Operation*

(make lazy-cons-pair *car-thunk cdr-thunk*) *Operation*

(lazy-cons *car-form cdr-form*) *Macro*
≡ (make lazy-cons-pair (lambda () *car-form*) (lambda () *cdr-form*))

(lazy-map *operation list . lists*) *Operation*
Like map on lists, but the result is a lazy list, each element computed when first accessed; the *lists* may themselves be lazy and unbounded.

9.5 List Accessors

(car *pair*) *Locatable Operation*

(cdr *pair*) *Locatable Operation*

(c[ad]*r *pair*) *Locatable Operation*
Actually these are only provided for up to four a's and d's. If you think you need more, you should probably be defining accessor functions or using nth or perhaps destructure.

(last-pair *pair*) *Locatable Operation*
Takes successive cdr's of *pair* until it finds a pair whose cdr is not a pair, which it returns. (last-pair '(a b c)) ⇒ (c). (last-pair '(a b c . d)) ⇒ (c . d).

(destructure *template structure . body*) *Macro*
This is for destructuring lists, and is sort of the inverse of backquote. *Template* is a possibly nested list of variables. These variables are bound to the corresponding values of *structure* while *body* is evaluated. For instance, (destructure (a (b) . c) x (foo a b c)) ≡ (let ((a (car x))(b (caadr x))(c (cddr x))) (foo a b c))

. It is guaranteed that *structure* will be evaluated only once. We note that `destructure` typically generates more efficient code than the corresponding code one might typically write.

If there is a position in *template* that should be ignored, one can place a `#t` there. For convenience and compatiblity with `destructure*`, positions in *template* containing `()`, `#f` and `(quote x)` are also ignored.

`(destructure*` *`template structure . body`*`)` *Macro*

This is just like `destructure` except that an error is signaled if *structure* doesn't precisely match *template*. Positions containing `#f` and `()` are required to match literally. Positions containing `(quote x)` are required to match x literally, where x is not evaluated. As with `destructure`, positions containing `#t` are ignored.

`destructure*` is particularly useful in macro expanders where it can do much of the syntax checking automatically.

`(destructure**` *`structure (template . body)... [(otherwise . nomatch-body)]`*`)` *Macro*

This is just like `destructure*` except that, when one template does not match, the next in line is considered. If none match than the OTHERWISE one does; if no otherwise clause is present, an error is signaled.

9.6 Lists as Sets

`(mem` *`predicate object list`*`)` *Operation*

Returns the first tail of *list* whose `car` equals *object* according to *predicate*.

`(memq` *`object list`*`)` *Operation*

`(del` *`predicate object list`*`)` *Operation*

`(delq` *`object list`*`)` *Operation*

`(del!` *`predicate object list`*`)` *Operation*

`(delq!` *`object list`*`)` *Operation*

9.7 Lists as Associations

`(ass` *`predicate object list`*`)` *Operation*

(assq *object list*) *Operation*

(cdr-ass *predicate object list*) *Settable Operation*

(cdr-assq *object list*) *Settable Operation*

9.8 Lists as Stacks

(push *location object*) *Macro*

(pop *location*) *Macro*

Chapter 10

Numbers




Figure 10.1: The numeric type hierarchy. Abstract types are in plain face and instantiable ones in bold. Floating point numbers are not implemented.

10.1 Arithmetic

`(+ . numbers)` *Operation*

`(1+ n)` *Operation*

`(- n1 n2 . numbers)` *Operation*

`(- n)` *Operation*

`(* . numbers)` *Operation*

(/ *n1 n2*) *Operation*

(quotient *n1 n2*) *Operation*

(modulo *n1 n2*) *Operation*

(abs *n1*) *Operation*

(max *n . ns*) *Operation*

(min *n . ns*) *Operation*

(expt *n1 n2*) *Operation*

(gcd . *ns*) *Operation*

The non-negative greatest common divisor of *ns*, or zero when there are none.

(lcm . *ns*) *Operation*

The non-negative least common multiple of *ns*, or one when there are none.

10.2 Comparison

(= *n1 n2 . ns*) *Operation*

(< *n1 n2 . ns*) *Operation*

(> *n1 n2 . ns*) *Operation*

(<= *n1 n2 . ns*) *Operation*

(>= *n1 n2 . ns*) *Operation*

These take two or more arguments and are true when each adjacent pair is in the given relation, so `(< a b c)` means `(and (< a b) (< b c))`. A call with two arguments is open coded; a longer direct call is open coded as a chain of two-argument comparisons, and the operations can also be called as values, for instance through `apply`, with any number of arguments from two up. Methods added to `=` or `<` for new types take exactly two arguments.

(!= *n1 n2*) *Operation*

True when *n1* and *n2* are not equal. Takes exactly two arguments.

10.3 Conversion

`(string->number` *string* [*radix*]`)` *Operation*

Parses *string* as a number in *radix*, which defaults to 10, and returns it, or `#f` if *string* is not a number in that radix. The syntax accepted is an optional radix prefix (`#b`, `#o`, `#d`, `#x`), an optional exactness prefix (`#e` or `#i`, which is ignored since all numbers are exact), an optional sign, and an integer, a ratio such as `-3/4`, or a decimal such as `1.5`, read exactly as `3/2`, as the reader reads it.

10.4 Predicates

`(zero?` *n*`)` *Predicate*

`(negative?` *n*`)` *Predicate*

`(positive?` *n*`)` *Predicate*

`(even?` *n*`)` *Predicate*

`(odd?` *n*`)` *Predicate*

10.5 Rounding

These operations should work on any subtype of `real`.

`(floor` *x*`)` *Operation*

Returns the largest integer less than or equal to x.

`(ceiling` *x*`)` *Operation*

Returns the smallest integer greater than or equal to x.

`(truncate` *x*`)` *Operation*

Could be defined `(if (negative? x) (ceiling x) (floor x))`.

`(round` *x*`)` *Operation*

Returns nearest integer to x. Ties are broken by rounding to an even number.

10.6 Bitwise Logical Operations

These operations are only defined for integers.

(ash-left *i amount*) *Operation*

(ash-right *i amount*) *Operation*

(rot-left *i amount*) *Operation*

(rot-right *i amount*) *Operation*

(bit-not *i*) *Operation*

(bit-and *i1 i2*) *Operation*

(bit-or *i1 i2*) *Operation*

(bit-nor *i1 i2*) *Operation*

(bit-xor *i1 i2*) *Operation*

(bit-nand *i1 i2*) *Operation*

(bit-andca *i1 i2*) *Operation*

(bit-equiv *i1 i2*) *Operation*

10.7 Accessing Components

(numerator *rational*) *Operation*

(denominator *rational*) *Operation*

(real-part *number*) *Operation*

(imag-part *number*) *Operation*

Chapter 11

Input and Output

11.1 Streams and Files

Streams are the tokens through which interaction with the outside world occurs. Although streams are primarily used for reading and writing to files, they have found a number of internal uses.

`stream` *Type*

The supertype of all streams.

`input-stream` *Type*

This is an abstract type. Instantiable subtypes must define methods for the `really-read-char` operation.

`(read-char` *`input-stream`*`)` *Operation*

Return a character, or `the-eof-token` if we've already read the last character in the stream.

`(unread-char` *`input-stream character`*`)` *Operation*

Puts *character* back into *input-stream*. One can only put one character back, and it must be the last character read.

`(peek-char` *`input-stream`*`)` *Operation*

Equivalent to `(let ((c (read-char` *`input-stream`*`))) (unread-char` *`input-stream`* `c) c)`.

`the-eof-token` *Object*

This distinguished object is returned to indicate that one has read past the end of the file.

`output-stream` *Type*

This is an abstract type. Instantiable subtypes must define methods for the `write-char` operation.

`(write-char` *`output-stream character`*`)` *Operation*

`(newline` *`output-stream`*`)` *Operation*

Outputs a carriage return to *output-stream*.

`(freshline` *`output-stream`*`)` *Operation*

Ensures that *output-stream* is at the beginning of a line.

`(flush` *`output-stream`*`)` *Operation*

Flushes any buffered output.

`(interactive?` *`stream`*`)` *Operation*

Returns true if and only if *stream* is connected to the user. This is used to check if an end of file condition on the control stream is really an end of file or if the user just typed control-D.

`(position` *`stream`*`)` *Settable Operation*

Returns the position we are at within *stream*. By setting this, one can get back to a previous position.

`(write-string` *`string output-stream`*`)` *Operation*

Writes the characters of *string* to *stream*.

`(with-open-file (`*`variable filename . options`*`). body)` *Macro*

Binds *variable* to a stream which is connected to the file with the name *filename*. *Options* is not evaluated, and describes how *filename* should be opened. Possible symbols include `in` for input, `out` for output, and `append` for output with position set to the end of the file. The `ugly` option can be added to either `out` or `append` if the user doesn't mind poor formating, as in files meant to be read only by other programs. The opened stream will be closed when the `with-open-file` is exited, even upon abnormal exit. **Note:** the stream is not reopened upon abnormal entry, but this may be changed in future versions of the system.

`(with-input-from-string (`*`variable sequence`*`). body)` *Macro*

Binds *variable* to an input stream whose contents are the characters of *sequence*. Although *sequence* is usually a string, this will work correctly for any sequence type.

`(make string-output-stream )` *Operation*

These save all their output and return it as a string in response to the `(coercer string)` operation.

11.2 Reading

Oaklisp has an industrial strength reader, replete with nonterminating macro characters and descriptive error messages. List syntax is not described below; read some other lisp manual. Our reader is modeled after the Common Lisp reader, so we emphasize differences with the Common Lisp reader below.

`(read` ***input-stream***`)` *Operation*

Returns a lisp object read from *stream*. This is sensitive to a large number of factors detailed below.

`standard-read-table` *Object*

This holds the read table for usual lisp syntax. The `nth` operation can be used to get and set elements of read tables, which are indexed by characters. Potential entries are `whitespace`, `constituent`, `single-escape`, `illegal`, `(terminating-macro .` *operation*`)`, and `(nonterminating-macro .` *operation*`)`.

`(skip-whitespace` ***input-stream***`)` *Operation*

Reads characters from *input-stream* until the next character is not whitespace.

The reader is not sensitive to the case of macro characters.

`(define-macro-char` ***character operation***`)` *Operation*

Defines *character* to be a reader macro in `standard-read-table`. When *character* is encountered by the reader, *operation* is called with two arguments, the stream and the character that was read.

`(define-nonterminating-macro-char` ***character operation***`)` *Operation*

Just like `define-macro-char` except that the macro is not triggered if *character* is read inside a token.

There are a number of "quotelike" macro characters present for the convenience of the user.

macro character	symbol
'	quote
`	quasiquote
control-v	fluid
control-y	coercer
,@	unquote-splicing
,	unquote

`(define-quotelike-macro-char` ***character object print?***`)` *Operation*

Makes *character* a terminating macro which returns a list of *object* and the next thing read. This also arranges for the printer to print using analogous syntax when *print?* is true. For instance, the quote syntax is defined with the line `(define-quotelike-macro-char #\' 'quote #t)` in the system internals.

`the-unread-object` *Object*

When a reader macro returns this, the reader takes it to mean that nothing at all was read. For instance, the reader macro for `;` reads the remainder of the line and returns this.

The character `[` is used to read lists in the same way that `(` is, except that `[` must be matched by a `]`. This is mostly for compatiblity with code written at the University of Indiana.

Since there are no packages in Oaklisp, the `:` character is treated like any other constituent.

Most of the Common Lisp hash reader macros are supported. For instance, the character object representing `a` is read `#\a`. Many special characters have long names, such as `#\space`.

`(define-hash-macro-char` ***character operation***`)` *Operation*

Defines *character* to be a hash reader macro character. *Operation* should take three arguments: a stream, the character, and the numeric argument that was between the hash and the character, `#f` if none was passed.

There are many hash reader macro characters, including `#o`, `#x`, `#d`, `#b` and `#c` for octal, hexidecimal, decimal, binary and complex numbers, respectively. The syntax `#`***nrxxx*** is used to read *xxx* in base *n*. `#(...)` is used for reading vectors. The `#|` macro comments out text until a matching `|#`, with proper nesting. `#;`***e*** comments out the s-expression *e*. As described in Section 2.7, `#t` and `#f` are read as the canonical true and false values, respectively.

The `#[symbol "..."]` syntax can be used to read arbitrary characters, although the `|...|` construction is prefered. Analogous constructors can be added with the settable operation `hash-bracket-option`.

`(fluid input-base)` *Fluid Variable*

The radix in which numbers will be read. A token is read as a number when it is an optional sign, `-` or `+`, and digits in this radix, a ratio such as `-3/4`, or digits with a decimal point, read exactly (`1.5` is `3/2`). So `+5` is the number 5, and a symbol of that name prints as `|+5|`.

`(fluid features)` *Fluid Variable*

A list of "features" present in the current implementation, used by the `#+` and `#-` reader macros. Testable and settable with the `feature?` settable operation. The `oaklisp` feature is always present.

`(fluid current-locale)` *Fluid Variable*

The `#.` macro evaluates its argument in this locale.

`(fluid read-suppress)` *Fluid Variable*

This is true when what is being read will just be ignored, and indicates to the reader that it shouldn't go to the trouble of interpreting the meaning of complex tokens or anything like that.

11.3 Printing

The printer is pretty heavy duty, but has no facilities for printing circular objects.

`(format` *`stream control-string . args`*`)` *Operation*

This is very similar to the Common Lisp `format` function, and is the usual way for users to print things.

Stream is permitted to be `#t` to indicate that output should be sent to the standard output, and `#f` to indicate that the output should be bundled up into a string and returned.

Characters in control-string are printed directly, except for the `~` character which indicates that some action should be taken. The `~` may be followed by a number or by a `:` or `@`, which vary the action that would normally be taken in some way.

Currently defined `~` characters and their associated actions are:

`A` Print and argument with `(fluid print-escape)` bound to `#f`.

`~` Print a `~`.

`%` Do a `newline`.

`&` Do a `freshline`.

`S` Print an argument with `(fluid print-escape)` bount to `#t`.

`B` Print an argument in binary.

`D` Print an argument in decimal.

`O` Print an argument in octal.

`X` Print an argument in hex.

`n``R` Print an argument in base *n*.

`C` Print an argument which is a character.

`P` Print an `s` if the argument is not 1.

`!` Print a weak pointer to the argument, preceded by an expression which evaluates to the argument if `(fluid fancy-references)` is on. This is used to print unique id's for objects without nice printed representations, like operations.

The numbers before a directive are the Common Lisp *mincol* and *padchar* parameters. With a *mincol* the output of `A`, `S` and `C` is padded on the right to that width, and the output of `B`, `D`, `O` and `X` is padded on the left. A second parameter gives the character to pad with, so `~5,'0D` prints 42 as `00042`. Since `~`*`n`*`R` already takes the base as its first parameter, its *mincol* and *padchar* are its second and third.

A tilde followed by a newline is ignored; this construct is used for making *control-string* more readable by breaking it across lines.

`(print` *`object stream`*`)` *Operation*

Writes a representation of *object* to *stream*. Users are encouraged to add informative print methods for types they define.

`(define-simple-print-method` *`type string`*`)` *Operation*

Instructs the printer to include *string* in the printed representation of instances of *type*.

`(fluid print-radix)` *Fluid Variable*

The radix in which numbers will be printed. The default is ten.

`(fluid print-level)` *Fluid Variable*

The number of levels of list structure to be printed before the printer abbreviates. The default is `#f`, meaning never abbreviate.

`(fluid print-length)` *Fluid Variable*

The number of elements of a list to be printed before the printer abbreviates. The default is `#f`, meaning never abbreviate.

`(fluid print-escape)` *Fluid Variable*

This controls whether the printer tries to print things that are easy for people to read, or ones that can be read back in to Oaklisp. The default is `#t`, meaning to maintain print/read consistency at the expense of readability.

`(fluid symbol-slashification-style)` *Fluid Variable*

This controls the style of printing of symbols when they are escaped. See the implementation manual for details.

`(fluid fraction-display-style)` *Fluid Variable*

This can be either `normal`, `fancy` or `float`. In these cases, `(/ -5 3)` would print as either `-5/3`, `-1 2/3` or `-1.6666666666`, respectively.

Chapter 12

Miscellaneous

12.1 Tables

The types are `generic-hash-table` and `eq-hash-table`. The access interface is `present?`, which returns a `pair` whose `car` is the key and whose `cdr` is the associated value. A different interface to hash tables is provided by the T-style `table-entry` operation which returns the associated value or `#f` if the key isn't in the table. The setter of either operation can be used to add, modify, and remove associations.

`(make generic-hash-table` ***key-hash-op equal-op*** `)` *Operation*

`(make eq-hash-table )` *Operation*

`(present?` ***table key*** `)` *Settable Operation*
Returns `(`***key . val***`)` pair, or `#f` if not present.

`(table-entry` ***table key*** `)` *Settable Operation*
Returns value indexed by *key* or `#f` if not present.

12.2 Delays

Oaklisp's delays provide Scheme's `delay` and `force`, and extend those primitive facilities in two ways. First, the system will automatically force promises when appropriate. For instance, `(+ 2 (delay 3))` does not signal an error; it returns `5`. Similarly, delays are printed transparently, slightly violating read/print consistency. Secondly, the delay facility is user extensible. Users can create new kinds of delays that have special protocols, for instance numeric delays that do not force themselves upon arithmetic operations, but instead make more and more complicated delays.

`(delay` ***expression*** `)` *Special Form*
This immediately returns a *promise* for *expression*, without actually computing *expression*. This promise does not compute *expression* until it is forced, at which point it returns the value of *expression*, computing it if it hasn't already done so.

`(force x)` *Operation*

If x is a promise, it is forced to compute its value, which is returned. If x is not a promise, it itself is returned.

`promise` *Type*

This is the type of the objects returned by `delay`.

`forcible` *Type*

This is an abstract type, of which `promise` is a concrete subtype. Subtypes of `forcible` are expected to respond to the `force` operation in a sensible fashion. Oaklisp's system internals sometimes force instances of `forcible` automatically, for instance when sending them messages for which no appropriate method can otherwise be found.

`(fluid forcible-print-magic)` *Fluid Variable*

Controls how delays are printed. This is how `(delay 'foo)` would print under various settings of `forcible-print-magic`.

value	**print style**
`#f`	`#<DELAY 3462>`
`indicate`	`#[DELAY FOO 3462]`
`transparent`	`FOO`

The default is `transparent`. A setting of `indicate` is more instructive if you encounter odd behavior that might be due to delays.

Chapter 13

User Interface

The Oaklisp user interface currently consists of a read-eval-print loop and a simple debugging facility.

Errors land the user into a recursive evaluation loop in which special restart handlers are available. Our implementation includes mechanisms for inspecting objects and tracing function calls.

13.1 Invoking Oaklisp

Oaklisp is run as

```
oaklisp [emulator options] -- [Oaklisp options]
```

The options before the `--` are for the bytecode emulator and the ones after it are processed by the Oaklisp world itself, in order, when it boots; without any it enters the read-eval-print loop. The emulator options include

`--world` ***file*** the world image to boot (the installed `oakworld.bin` by default, or the file named by the environment variable `OAKWORLD`);

`--dump` ***file*** dump the world to *file* on exit;

`--size-heap` ***n*** the size of the heap, in units of 1024 references;

`--batch` do not trap interrupts, for use from scripts and makefiles;

`--no-line-editing` read the terminal a character at a time, without GNU readline (when built with it, a line typed at the terminal can be edited, and earlier lines recalled, before it is read);

`--version` print the version and architecture (section 13.1.1) and exit.

The Oaklisp options are

`--eval` ***expression*** evaluate *expression*, given as one argument;

`--load` ***file*** load *file*, as `load` would;

`--compile` ***file*** compile *file*`.oak` to *file*`.oa`, as `compile-file` would;

`--outdir` ***directory*** write the objects of the following `--compile` switches to *directory* rather than beside their sources (it sets `(fluid compiler-output-directory)`);

`--target` ***architecture*** compile the following files for *architecture* rather than for the running system (it sets `(fluid target-architecture)`);

`--locale` ***locale*** evaluate, load and compile the following in *locale*, e.g. `system-locale` or `compiler-locale`, rather than the current locale (initially `user-locale`);

`--exit` exit, with a nonzero status if any earlier switch failed.

For example, to compile a file in the system locale and leave:

```
oaklisp -- --locale system-locale --compile myfile --exit
```

`(exit` *`[status]`*`)` *Operation*
Leaves Oaklisp, giving the shell the status *status*, an integer from 0 to 255, or 0. (After an error, the status is the debugger's nesting level, so that a script that errored does not report success.)

`(dump-world` *`file-name`*`)` *Operation*
Saves the running world to *file-name*, a binary world image, and keeps running. The image can be booted with `--world`.

`(load-world` *`file-name`*`)` *Operation*
Replaces the running world with the image in *file-name*. It never returns.

`system-version` *Global Variable*
A string naming the version of Oaklisp, e.g. `"Oaklisp 2.0.1"`.

13.1.1 Architectures

An Oaklisp system is built for an *architecture*: the size of a reference in bits (32 or 64, which fixes the range of fixnums at 30 or 62 bits), the number of 16-bit instructions packed into each reference in a code vector (2, or 4 with 64-bit references), and the byte order of the machine. Architectures are named `bc2-32`, `bc2-64` and `bc4-64` for compiled code, which does not depend on byte order, and `bc2-el32`, `bc2-eb32`, `bc2-el64`, `bc2-eb64`, `bc4-el64` and `bc4-eb64` for running systems and world images, `el` and `eb` being little and big endian. Compiled code can be loaded by any system with the same instruction packing; a file compiled for 32-bit references can be loaded by a 64-bit system, since the difference is only the range its integer constants are assumed to fit. Compiled files and world images carry a header line naming their architecture, and a mismatch is an error.

`host-architecture` *Global Variable*

Describes the running system: an association list with the keys `word-size` (32 or 64), `instructions-per-ref` (2 or 4) and `endian` (`little` or `big`).

`(fluid target-architecture)` *Fluid Variable*
The architecture the compiler generates code for, in the same form; by default the host's. It is set by the `--target` switch, and the compiler may be given any architecture, which is how Oaklisp is bootstrapped onto a new one.

`(parse-architecture-name` *`string`*`)` *Operation*
Returns the architecture named by *string*, e.g. `"bc2-64"`, as an association list; an error if the name is not one of those above.

`(architecture-name` *`architecture`*`)` *Operation*
The name of *architecture*, the inverse of the above.

`most-positive-fixnum` *Global Variable*

`most-negative-fixnum` *Global Variable*
The largest and smallest fixnums of the running system: $2^{29} - 1$ and -2^{29} with 32-bit references, $2^{61} - 1$ and -2^{61} with 64-bit ones.

13.2 The Top Level Environment

All expressions must be evaluated with respect to a particular naming environment. The read-eval-print loop uses the locale specified by the fluid variable `current-locale`. The Oaklisp system boots up with this variable bound to `user-locale`. Other useful name spaces are `system-locale` and `compiler-locale`.

Several fluid variables are used to keep a short history of the dialogue conducted by the top level evaluator. The most useful of these is `(fluid *)`, which contains the value produced by the most recent user expression. The value of this variable is rolled back into `(fluid **)` and then into `(fluid ***)` to provide access to the three most recent values. Similarly, there are three copies of `(fluid +)` and `(fluid ?)` that provide access to recent expressions that were read in and to their form after macro expansion.

The switch `(fluid fancy-references)` controls the printing of anonymous objects. When this switch is turned off, an object usually prints out something like this: `#<op 806>`. This format indicates the type of the object, and provides a weak pointer that can be derefenced with `object-unhash` to get the object. When the `(fluid fancy-references)` switch is turned on, the printer attempts to generate an expression that will evaluate to the object in the current locale. For example, the above operation might print out as `#<op (setter car) 806>`. The default value for this switch is `#f`, but it is briefly switched on by `describe`.

Two more fluid variables that are frequently used at the top level are `(fluid print-length)` and `(fluid print-level)`, which are normally set to small integer values in order to abbreviate the printing of long lists, but which can be set to `#f` in order to enable exhaustive printing.

13.3 Miscellaneous Functions

There are some other very useful functions that are part of the user interface.

`(apropos` *word [place]*`)` *Operation*

Returns either variables or symbols containing *word*, depending on *place*, which can be a locale or `symbol-table`. *place* defaults to `(fluid current-locale)`.

`(%gc)` *Operation*

Collect garbage. This does not collect garbage in "static space," but it is exceedingly unlikely that there is any there.

`(%full-gc)` *Operation*

Collect more garbage. This does collect garbage from "static space," but more importantly, it put everything not freed into static space, so it need not be transported in future normal garbage collections.

13.4 Debugging

The following special forms can be used to trace the execution of an operation.

`(trace-variable-in` *global-var*`)` *Special Form*

Puts a trace on the operation stored in *global-var*, causing a message to be printed every time the operation is called.

`(trace-variable-out` *global-var*`)` *Special Form*

Puts a trace on the operation stored in *global-var*, causing a message to be printed every time a call to the operation returns.

`(trace-variable-in-out` *global-var*`)` *Special Form*

`(untrace-variable` *global-var*`)` *Special Form*

Objects can be examined in detail with the `describe` function, which prints the object and its type with `(fluid fancy-references)` turned on, followed by the object's internal state. The internal state is organized as instance-variable blocks from the object's various component types. An object's internal state usually contains anonymous objects whose printed representation includes weak pointers which can be dereferenced using `object-unhash`. Together, `describe` and `object-unhash` constitute a simple but effective inspector.

To simplify this process `describe` applied to an integer which is the `object-hash` of some object will describe that object. In other words, `describe` can be applied to the numeric ID in an object's printed representation.

`(describe` *object*`)` *Operation*

Prints out lots of stuff about *object*.

`(object-unhash` *i*`)` *Operation*

Dereferences the weak pointer *i*.

When an error occurs in our implementation of Oaklisp, the user is thrown into a recursive evaluation loop whose dynamic context is nested inside that of the error. Several restart handlers are typically available in a recursive evaluation loop, and the `ret` function is the mechanism for invoking one of these handlers. `call/cc` can be used to preserve an error context when it might be useful to restart the computation at a later time.

`(ret` *n* `.` *args*`)` *Operation*

Invokes restart handler *n*, as specified by the list of handlers printed out by a subordinate evaluation loop. `(ret 0)`, which returns control to the top level evaluation loop, is always in effect.

The following dialogue with Oaklisp illustrates some of these points.

```
Welcome to Oaklisp 2.1.2
Oaklisp evaluation loop.
  Active handlers:
  0: Return to top level.
> (with-open-file (inf "fone.nums" in) (car (read inf)))

Error: Unable to open "fone.nums" for READ access.
Oaklisp evaluation loop.
  Active handlers:
  0: Return to top level.
  1: Supply a file to READ instead (none to retry "fone.nums").
  2: Return to debugger level 1.
>> (call/cc identity)                ;get error context.
#<Op 1363>
>> (set foo (fluid *))               ;stash it away.

Warning: Installing FOO in #<Locale USER-LOCALE 1365>.
#<Op FOO 1363>
>> (ret 0)                           ;back to top level.

Invoking handler "Return to top level."
  Active handlers:
  0: Return to top level.
> (describe foo)                    ;inspect continuation.

#<Op FOO 1363> is of type #<Type OPERATION 1366>.
 from #<Type OPERATION 1366>:
    LAMBDA? : #<Object 1367>        ;what's this thing?
```

```
    CACHE-TYPE : #<Undefined IVAR IVAR-UNDEFINED-VALUE 1368>
    CACHE-METHOD : #<Undefined IVAR IVAR-UNDEFINED-VALUE 1368>
    CACHE-TYPE-OFFSET : #<Undefined IVAR IVAR-UNDEFINED-VALUE 1368>
#<Op FOO 1363>
> (describe (object-unhash 1367))

#<Object 1367> is of type #<Type 1369>.
 from #<Type 1369>:
    THE-CODE : #<VLmixin 1370>
    THE-ENVIRONMENT : #<VLmixin 1371>
#<Object 1367>
> (foo 0)                           ;re-enter error context.
0
>> (ret 1 "phone.nums")             ;resume computation.

Invoking handler "Supply a file to READ instead (none to retry "fone.nums")."
268-7598                            ;got that phone number!
> (exit)

Oaklisp stopped itself.
```

Using the error system effectively is an important part of providing the user with a helpful interface. Details on the error system can be found in Section 6.3.

Bibliography

Software helps city plan trash pickup. *Government Computer News*, 6(18), September 1987.

Henry G. Baker, Jr. Actor systems for real-time computation. Technical Report TR-197, MIT Laboratory for Computer Science, March 1978.

Danny Bobrow et al. Commonloops: Merging common lisp and object-oriented programming. In OOPSLA-86, pages 17–29. Special issue of *ACM SIGPLAN Notices* 21(11).

Adele J. Goldberg and David Robson. *Smalltalk-80: The Language and its Implementation*. Addison-Wesley, 1983.

Robert H. Halstead. Multilisp: A language for concurrent symbolic computation. *Transactions of Programming Languages and Systems*, 7(4):501–38, October 1985.

Kevin J. Lang and Barak A. Pearlmutter. Oaklisp: an object-oriented Scheme with first class types. In OOPSLA-86, pages 30–7. doi: 10.1145/960112.28701. Special issue of *ACM SIGPLAN Notices* 21(11).

Kevin J. Lang and Barak A. Pearlmutter. Oaklisp: an object-oriented dialect of Scheme. *Lisp and Symbolic Computation*, 1(1):39–51, May 1988.

David A. Moon. Object-oriented programming with flavors. In OOPSLA-86, pages 1–8. Special issue of *ACM SIGPLAN Notices* 21(11).

OOPSLA-86. *ACM Conference on Object-Oriented Systems, Programming, Languages and Applications*, September 1986. Special issue of *ACM SIGPLAN Notices* 21(11).

Barak A. Pearlmutter. Garbage collection with pointers to individual cells. *Communications of the ACM*, 39(12):202–6, December 1996. doi: 10.1145/272682.272712.

Barak A. Pearlmutter and Kevin J. Lang. The implementation of Oaklisp. In Peter Lee, editor, *Topics in Advanced Language Implementation*, pages 189–215. MIT Press, 1991. ISBN 0262121514.

Jonathan A. Rees and Norman I. Adams, IV. T: A dialect of lisp or, lambda: the ultimate software tool. In *ACM Symposium on Lisp and Functional Programming*, August 1982.

Jonathan A. Rees, William Clinger, et al. The revised[3] report on the algorithmic language Scheme. *SIGPLAN Notices*, 21(12):37–79, December 1986.

Jonathan A. Rees et al. *The T Manual*. Yale University Computer Science Department, fourth edition, 1984.

Brian Cantwell Smith. Reflection and semantics in lisp. Technical Report CSLI-84-8, Center for the Study of Language and Information, 1984.

Alan Snyder. Encapsulation and inheritance in object-oriented programming languages. In OOPSLA-86, pages 38–45. Special issue of *ACM SIGPLAN Notices* 21(11).

Guy Lewis Steele, Jr. Lambda: the ultimate declarative. Technical Report AI Memo 379, MIT AI Lab, 1976. URL ftp://publications.ai.mit.edu/ai-publications/pdf/AIM-379.pdf.

Guy Lewis Steele, Jr. and Gerald J. Sussman. The art of the interpreter. Technical Report AI Memo 453, MIT AI Lab, 1978.

Guy L. Steele Jr. *Common Lisp: The Language*. Digital Press, 1984.

SYMBOLICS. *Symbolics Release 7 Documentation, Volume 2A*. Symbolics, Inc., August 1986.

Index

bignum, 35
call/cc, *see* 20
complex, 35
cons-pair, 30
fixnum, 35
float, 35
fraction, 35
integer, 35
lazy-cons-pair, 30
list-type, 30
null-type, 30
number, 35
pair, 30
rational, 35
real, 35
sequence, 30
simple-vector, 30
string, 30
vector-type, 30
(), 7, 33
.oa, 15, 48
.oak, 15, 48
<, 36
=, 36
OAKWORLD, 47
Oaklisp 2.0.1|hyperpage, 48
#+, 42
#-, 42
#., 42
#b, 42
#c, 42
#d, 42
#f, 7, 17, 18, 21, 33, 37, 42-45, 49
#o, 42
#t, 7, 18, 33, 42-44
#x, 42
add-method, 9-11
append, 31, 40
append!, 31
apply, 36
bc2-32, 48
bc2-64, 48
bc2-64|hyperpage, 49
bc2-eb32, 48
bc2-eb64, 48
bc2-el32, 48
bc2-el64, 48
bc4-64, 48
bc4-eb64, 48
bc4-el64, 48
big, 49
bind, 19, 25
bind-error-handler, 3
block, 9
call-with-current-continuation, 20
call/cc, 20, 28, 51
car, 33, 45
catch, 3, 20, 21
cdr, 32, 45
cerror, 21, 23, 24
coercable-type, 7
coercer, 7, 41
compile-file, 15, 48
compiler-locale, 48, 49
constituent, 41
contents, 14
current-locale, 15, 49
define, 11, 16
define-macro-char, 41
define-syntax, 16

delay, 25, 45, 46
describe, 49, 50
destructure, 32, 33
destructure*, 24, 33
eb, 48
el, 48
else, 28
endian, 49
eq-hash-table, 45
eq?, 5, 27
eqv?, 8
error, 23, 24
error-restart, 22
error-return, 21
eval, 15
fancy, 44
feature?, 42
float, 44
fluid, 19, 41
for-each, 29
force, 45, 46
forcible, 46
format, 25, 43
freshline, 43
funny-wind-protect, 20
future, 25
general-error, 23
generic-fatal-error, 21
generic-hash-table, 45
generic-proceedable-error, 21
hash-bracket-option, 42
illegal, 41
in, 40
indicate, 46
initialize, 5, 16
instructions-per-ref, 49
invoke-debugger, 22
labels, 10
lambda, 11, 12
let, 3, 10, 19, 22
let*, 10
listify-args, 11, 12
little, 49
load, 15, 16, 48
local-syntax, 16
locale, 17
locater, 14
locative, 13
make, 5, 6
make-thread, 25
map, 27, 29, 32
mapcdr, 29
native-catch, 20
newline, 43
nil, 7
nonterminating-macro, 41
normal, 44
nth, 30, 32, 41
null?, 6
number?, 6
oaklisp, 42
oakworld.bin, 47
object, 4-6, 10
object-unhash, 49, 50
out, 40
pair, 45
pause, 25
present?, 45
print, 2, 5
proceed, 22
promise, 46
quasiquote, 41
quote, 6, 41
read, 23
read-error, 23
real, 37
really-read-char, 39
rest-length, 11, 12
rest-name, 12
ret, 21, 22, 51
self, 9
set!, 13
setf, 13
setq, 13

setter, 14
signal, 24
simple-vector, 31
single-escape, 41
standard-read-table, 41
subtype?, 6
symbol-table, 50
system-locale, 48, 49
table-entry, 45
terminating-macro, 41
the-eof-token, 39
thread, 25, 26
thread-join, 25
thread-name, 25
throw, 3
transparent, 46
type, 4-7
ugly, 40
unquote, 41
unquote-splicing, 41
user-locale, 48, 49
whitespace, 41
wind-protect, 20, 25
with-open-file, 40
word-size, 49
write-char, 39
↑super, 11
***
   fluid, 49
**
   fluid, 49
*
   fluid, 49
   Operation, 35
+
   fluid, 49
   Operation, 35
-
   Operation, 35
/
   Operation, 35
1+
   Operation, 35
<=
   Operation, 36
<
   Operation, 36
=
   Operation, 36
>=
   Operation, 36
>
   Operation, 36
?
   fluid, 49
#f
   Global Variable, 7
%full-gc
   Operation, 50
%gc
   Operation, 50
abs
   Operation, 36
acquire-mutex
   Operation, 26
add-method
   Special Form, 9
and
   Special Form, 28
append!
   Operation, 31
append
   Operation, 31
apropos
   Operation, 50
architecture-name
   Operation, 49
ash-left
   Operation, 38
ash-right
   Operation, 38
assq
   Operation, 33
ass

Operation, 33
atom?
Predicate, 30
bind-error-handler
Macro, 22
bind
Special Form, 19
bit-andca
Operation, 38
bit-and
Operation, 38
bit-equiv
Operation, 38
bit-nand
Operation, 38
bit-nor
Operation, 38
bit-not
Operation, 38
bit-or
Operation, 38
bit-xor
Operation, 38
block0
Special Form, 29
block
Special Form, 28
c[ad]*r
Locatable Operation, 32
call-with-current-continuation
Operation, 20
car
Locatable Operation, 32
catch
Special Form, 20
cdr-assq
Settable Operation, 34
cdr-ass
Settable Operation, 34
cdr
Locatable Operation, 32
ceiling
Operation, 37
cerror
Operation, 21
coercable-type
Type, 7
coercer
Locatable Operation, 7
compare-and-swap
Operation, 27
compile-file
Operation, 15
compiler-output-directory
fluid, 15, 48
condition-notify-all
Operation, 27
condition-notify
Operation, 27
condition-variable
Operation, 26
condition-wait
Operation, 26
cond
Special Form, 28
consume-args
Operation, 12
cons
Operation, 32
contents
Locatable Operation, 14
copy
Operation, 31
current-locale
fluid, 15, 16, 50
Fluid Variable, 42
current-thread
Operation, 26
define-constant
Special Form, 16
define-hash-macro-char
Operation, 42
define-instance
Special Form, 16

define-local-syntax
   Special Form, 16
define-macro-char
   Operation, 41
define-nonterminating-macro-char
   Operation, 41
define-quotelike-macro-char
   Operation, 41
define-simple-print-method
   Operation, 44
define-syntax
   Special Form, 16
define
   Macro, 10
   Special Form, 16
del!
   Operation, 33
delay
   Special Form, 45
delq!
   Operation, 33
delq
   Operation, 33
del
   Operation, 33
denominator
   Operation, 38
describe
   Operation, 50
destructure**
   Macro, 33
destructure*
   Macro, 33
destructure
   Macro, 32
dolist-count
   Special Form, 29
dolist
   Special Form, 29
dotimes
   Special Form, 29
do
   Special Form, 29
dump-world
   Operation, 48
dynamic-wind
   Operation, 20
eq-hash-table
   Making, 45
eq?
   Predicate, 5
error-opening
   Type, 23
error-restart
   Macro, 22
error-return
   Macro, 21
error
   Operation, 21
eval
   Operation, 15
even?
   Predicate, 37
exit
   Operation, 48
expt
   Operation, 36
fancy-references
   fluid, 43, 49, 50
features
   Fluid Variable, 42
fetch-and-add
   Operation, 27
floor
   Operation, 37
fluid
   Special Form, 19
flush
   Operation, 40
for-each-cdr
   Operation, 29
for-each
   Operation, 29
force

Operation, 46
forcible-print-magic
Fluid Variable, 46
forcible
Type, 46
format
Operation, 43
fraction-display-style
Fluid Variable, 44
freshline
Operation, 40
frozen-here?
Settable Predicate, 18
frozen?
Settable Predicate, 18
funny-wind-protect
Special Form, 20
gcd
Operation, 36
general-error
Type, 23
generic-fatal-error
Type, 23
generic-hash-table
Making, 45
generic-proceedable-error
Type, 23
get-type
Operation, 5
host-architecture
Global Variable, 48
if
Special Form, 28
imag-part
Operation, 38
initialize
Operation, 5
input-base
Fluid Variable, 42
input-stream
Type, 39
interactive?
Operation, 40
invoke-debugger
Operation, 22
invoke-in-error-context
Operation, 23
is-a?
Predicate, 6
iterate
Special Form, 28
labels
Special Form, 10
lambda
Macro, 10
last-pair
Locatable Operation, 32
last
Locatable Operation, 31
lazy-cons-pair
Making, 32
lazy-cons
Macro, 32
lazy-map
Operation, 32
lcm
Operation, 36
length
Operation, 31
let*
Special Form, 10
let
Special Form, 10
list-type
Coercer, 32
Making, 32
list?
Predicate, 30
listify-args
Operation, 12
list
Operation, 32
load-world
Operation, 48

load
   Operation, 15
local-syntax
   Special Form, 16
locatable-operation
   Type, 14
locater
   Locatable Operation, 14
macro-here?
   Settable Operation, 18
macro?
   Settable Operation, 18
make-locative
   Special Form, 13
make-named-mutex
   Operation, 26
make-thread
   Operation, 25
make
   Operation, 5, 17
map!
   Operation, 29
mapcdr
   Operation, 29
map
   Operation, 29
max
   Operation, 36
memq
   Operation, 33
mem
   Operation, 33
min
   Operation, 36
mix-types
   Operation, 8
mixin-manager
   Type, 8
modify-location
   Special Form, 14
modulo
   Operation, 36
most-negative-fixnum
   Global Variable, 49
most-positive-fixnum
   Global Variable, 49
native-catch
   Special Form, 20
negative?
   Predicate, 37
newline
   Operation, 40
nil
   Global Variable, 7
not
   Predicate, 28
nth
   Locatable Operation, 31
null?
   Predicate, 30
numerator
   Operation, 38
object-unhash
   Operation, 51
object
   Type, 5
odd?
   Predicate, 37
operation
   Type, 14
or
   Special Form, 28
output-stream
   Type, 39
pair?
   Predicate, 30
parse-architecture-name
   Operation, 49
peek-char
   Operation, 39
pop
   Macro, 34
position
   Settable Operation, 40

positive?
Predicate, 37
present?
Settable Operation, 45
print-escape
fluid, 43
Fluid Variable, 44
print-length
fluid, 49
Fluid Variable, 44
print-level
fluid, 49
Fluid Variable, 44
print-radix
Fluid Variable, 44
print
Operation, 44
proceedable-error
Making, 23
proceed
Operation, 22
promise
Type, 46
push
Macro, 34
quote
Special Form, 6
quotient
Operation, 36
read-char
Operation, 39
read-error
Type, 23
read-suppress
Fluid Variable, 42
read
Operation, 41
real-part
Operation, 38
release-mutex
Operation, 26
remember-context
Operation, 23
report
Operation, 22
rest-length
Special Form, 12
ret
Operation, 51
reverse!
Operation, 31
reverse
Operation, 31
rot-left
Operation, 38
rot-right
Operation, 38
round
Operation, 37
sequence?
Predicate, 30
set!
Special Form, 13
settable-operation
Type, 14
setter
Locatable Operation, 13
simple-vector
Coercer, 31
Making, 31
skip-whitespace
Operation, 41
standard-read-table
Object, 41
stream
Type, 39
string->number
Operation, 37
string-output-stream
Making, 40
string?
Predicate, 30
string
coercer, 7, 40

subtype?
   Predicate, 6
swap
   Special Form, 14
symbol-slashification-style
   Fluid Variable, 44
system-version
   Global Variable, 48
table-entry
   Settable Operation, 45
tail
   Locatable Operation, 31
target-architecture
   fluid, 48
   Fluid Variable, 49
the-eof-token
   Object, 39
the-unread-object
   Object, 42
thread-alive?
   Operation, 25
thread-count
   Operation, 26
thread-join
   Operation, 25
thread-name
   Operation, 26
thread-sleep
   Operation, 26
throw
   Operation, 20
trace-variable-in-out
   Special Form, 50
trace-variable-in
   Special Form, 50
trace-variable-out
   Special Form, 50
truncate
   Operation, 37
type
   Making, 6
   Type, 4
t
   Global Variable, 7
unexpected-eof
   Type, 23
unless
   Special Form, 29
unread-char
   Operation, 39
untrace-variable
   Special Form, 50
variable-here?
   Settable Operation, 17
   Setter, 17, 18
variable?
   Settable Operation, 17
   Setter, 17
vector?
   Predicate, 30
vector
   Operation, 31
warning
   Operation, 21
while
   Special Form, 29
wind-protect
   Special Form, 20
with-input-from-string
   Macro, 40
with-mutex
   Macro, 26
with-open-file
   Macro, 40
write-char
   Operation, 40
write-string
   Operation, 40
zero?
   Predicate, 37
--batch
   switch, 47
--compile
   switch, 48

--dump
   switch, 47
--eval
   switch, 48
--exit
   switch, 48
--load
   switch, 48
--locale
   switch, 48
--no-line-editing
   switch, 47
--outdir
   switch, 48
--size-heap
   switch, 47
--target
   switch, 48, 49
--version
   switch, 47
--world
   switch, 47, 48
--
   switch, 47
!=
   Operation, 36
↑super
   Operation, 11

Smalltalk-80, 11