

This document was generated on 03/14/2019

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0533093070

Status: Active

Overview: SlimStack Board-to-Board Connectors

**Description:** SlimStack Board-to-Board Connector, 0.80mm Pitch, Floating Series, Plug, 5.65 or

6.65mm Mated Height, 30 Circuits, Right-Angle, with Boss

**Documents:** 

3D Model Product Literature (PDF)

Drawing (PDF) Product Specification PS-52465-014-001 (PDF)

Product Specification PS-52588-031-001 (PDF)

Product Specification PS-52588-032-001 (PDF)

Packaging Specification SPK-53309-001-001 (PDF)

Product Literature (PDF)

Product Literature (PDF)

Product Literature (PDF)

Product Literature (PDF)

RoHS Certificate of Compliance (PDF)

General

Product Family PCB Headers
Series 53309

Application Board-to-Board, Signal

Overview SlimStack Board-to-Board Connectors

Product Literature Order No 987651-8814, 987651-8815\_ZH, 987651-8817\_DE,

987651-8818\_JA, 987651-8819\_KO, 987651-8820\_ES

Product Name SlimStack
Series Name 0.80 Floating
UPC 822348124329

**Physical** 

Breakaway No 30 Circuits (Loaded) Circuits (maximum) 30 Color - Resin Natural Durability (mating cycles max) 30 First Mate / Last Break No Glow-Wire Capable No **Guide to Mating Part** No Keying to Mating Part None Lock to Mating Part Yes

Mated Height5.65mm, 6.65mmMated Width4.70mm, 7.20mmMaterial - MetalPhosphor Bronze

Material - Plating Mating Tin Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

Net Weight 574.055/mg

Number of Rows


Orientation Right Angle PC Tail Length 0.40mm, 0.50mm

PCB Locator No PCB Retention None

Packaging Type Embossed Tape on Reel

Pitch - Mating Interface 0.80mm
Plating min - Mating 1.016µm
Plating min - Termination 1.016µm
Polarized to PCB No
Shrouded Fully

Temperature Range - Operating -40° to +105°C
Termination Interface: Style Surface Mount



**EU ELV** 

**Not Relevant** 

EU RoHS China RoHS

Compliant

REACH SVHC
Not Contained Per

-ED/88/2018 (15

January 2019) Halogen-Free

**Status** 

**Not Low-Halogen** 

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

**Search Parts in this Series** 

53309 Series

**Mates With** 

52465, 52588 Board-to-Board Receptacle

**Electrical** 

Current - Maximum per Contact 0.5A Voltage - Maximum 50V

**Material Info** 

**Reference - Drawing Numbers** 

Packaging Specification SPK-53309-001-001

Product Specification PS-52465-014-001, PS-52588-031-001,

PS-52588-032-001

This document was generated on 03/14/2019

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION