

E2E Full Test Dual 18 Bandpass

Dual chamber 6th order bandpass, Sub category

Drivers: 18 IPAL (front chamber), 18iD (rear chamber)

Dimensions (mm): H900 x W650 x D750

Volume: net 280L / gross 320L, loaded weight 85kg

Panel stock: 18mm plywood, 3 sheets 2500x1250mm

Cut list

Panel	Size (mm)	Qty
Baffle (front)	650 x 900	1
Baffle (rear)	650 x 900	1
Top/Bottom	650 x 750	2
Sides	750 x 900	2
Chamber divider	650 x 750	1
Bracing	various	4

Port & tuning

Rear chamber tuned via Hornresp, port area 800cm²

Fb 34Hz, F3 32Hz (low), F3 45Hz (high), F6 28Hz

Max SPL 142dB (excursion-limited 138dB, thermal-limited 142dB)

Power handling: AES 4000W, program 8000W, recommended 4000W

Nominal impedance 4 ohm, minimum 2.6 ohm

Assembly notes

1. Glue and screw chamber divider before attaching baffles.
2. Seal front chamber fully airtight around D1 cutout.
3. Rear chamber port faces down, 18mm roundover on all edges.
4. Brace at 1/3 and 2/3 height on all unsupported panels >600mm.
5. Recommended crossover 120Hz, connect via speakON NL4.