ThrottleIQ for Maya Ride: integration guide

For Fahad Chowdhury, Maya Ride · from Abraar, ThrottleIQ · 25 October 2026

Everything is in the **`mayabi`** branch of `github.com/blankframe-tech/ThrottleIQ`. The Dart package is in the `mayabi/` folder. It is pure Dart with no dependencies, so your app keeps its own GPS and sensor plugins and its own design. Read these three files first:

- `mayabi/README.md`: step-by-step integration with code samples
- `mayabi/API.md`: the HTTP contract (every endpoint, the rules for each field, error codes)
- `mayabi/PRIVACY.md`: exactly what leaves the phone, with consent text in English and Bangla

1. What runs on the phone, and what needs a server

Feature	Package API	Works without a server?
True trip cost (fuel and maintenance, unpaid km)	`CostProfile`, `TripCost`	**Yes, fully on the phone**
Ride recording, hard braking, sudden acceleration, overspeeding, crash detection	`RideRecorder`	**Yes**
Riding score	`report.eventScore` / `uploadRide`	**Basic score: yes. Road-by-road comparison with Dhaka riders: needs the server**
"Are you OK?" after a crash or a long stop	`SafetyCheck`	**The prompt: yes. Alerting your ops team: needs the server**
SOS by SMS to emergency contacts, and a 999 call	`sosSmsUri`, `telUri`	**Yes (works with no internet)**
Rider history for Maya ops	`riderScore`	**Needs the server**
Live share link for family	`startLive` / `updateLive` / `endLive`	**Needs the server**

No raw GPS track leaves the phone. Only trip totals and average speeds per ~150 m road cell are sent, and live position is sent only while a live link is active.

2. The server: two options

> **Option A: use ThrottleIQ's hosted API.** The server code (`functions/src/partner-api/`) is written and tested, but **it is not deployed yet**. Firebase Cloud Functions need the paid **Blaze** plan, and ThrottleIQ is on the free plan today. Blaze is pay-as-you-go: there's a free monthly allowance, and you pay for usage above it. These are my rough estimates (the live-share updates are the biggest cost):
>
> - Small pilot, up to ~100 trips a day: about **US$0–5 a month** (about ৳0–600)
> - Around 1,000 trips a day with live share on: about **US$15–30 a month** (about ৳1,800–3,700), and the cost grows with riders
>
> Until Blaze is turned on, calls to `throttleiqfb.web.app/api/partner/` will fail.

> **Option B: take the code into your own app and server.** You don't have to wait for me. Take whatever parts you like from the `mayabi` branch and have Claude (or Cursor, or your developers) integrate them into the Maya Ride app and your own backend. **I'm completely fine with that.** See the permission note at the end.
>
> - **Phone side:** use the `mayabi/` package as it is, or copy the files you need.
> - **Server side:** either deploy `functions/src/partner-api/` to your own Firebase project (it needs Blaze on your own account), or rebuild the same endpoints on your existing backend, using `API.md` as the specification. The package can talk to your server instead of ours: `ThrottleIqClient(apiKey: ..., baseUrl: Uri.parse('https://your-server/...'))`.
> - If you run your own server, the Dhaka road-speed comparison starts from your own riders' data instead of the shared ThrottleIQ pool.

3. Integration steps (phone side)

1. **Add the package** to `pubspec.yaml`:

   ```
   throttleiq_mayabi:
     git:
       url: https://github.com/blankframe-tech/ThrottleIQ.git
       ref: mayabi
       path: mayabi
   ```

   Also add, if the app doesn't have them yet: `geolocator`, `sensors_plus`, `url_launcher`, and `battery_plus` (optional).
2. **Background location.** Riders lock their phones, so recording needs it. On Android: a foreground service and `ACCESS_BACKGROUND_LOCATION`. On iOS: `UIBackgroundModes: location` and "Always" permission. Ask the first time a rider goes online, using the consent text in `PRIVACY.md`.
3. **Trip cost:** during onboarding, collect the fuel price, mileage and maintenance items into a `CostProfile`. Show the cost before a rider accepts a trip and again after it ends (README §2).
4. **Recording:** create one `RideRecorder` per trip. Feed it GPS at 1 Hz and the motion sensors at 50 Hz, and switch `phase` to pickup, on trip and to home. Call `finish()` at the end to get the report and the score (README §3).
5. **Safety:** wire `onSafetyEvent` to a `SafetyCheck` that shows a full-screen "Are you OK?" prompt with a countdown. Keep an SOS button on screen for the whole trip that opens SMS and 999 (README §5).
6. **Server calls** (once a server exists): `uploadRide`, `riderScore`, live share and `sendAlert`. Keep the API key on your server, not in the app (README §8).
7. **Test:** `cd mayabi && dart pub get && dart test`. Then pilot with a few riders. Sensor rates, background recording on OEM Android builds and battery use haven't been tested on real phones yet.

4. New: a permanent family link

Last night I added this to the ThrottleIQ app: each rider gets **one fixed, password-protected link**. Family members can open it at any time. During a ride it shows her live position, and after the ride it shows the last known location ("Last seen", which opens in Maps). This is **not in the `mayabi/` package yet**. The package's live links still last one ride, up to 12 hours. To take it, look at commit `502dc519` in the repository, mainly: `app/lib/core/services/public_live_link_setting.dart`,

`live_session_coordinator.dart`, `public/live-viewer.html` and the `handleLinks` part of `firestore.rules`. It relies on ThrottleIQ's own sign-in, so in your app it would sit behind your own rider accounts and server.

5. A prompt you can give Claude

```
Integrate ThrottleIQ's Maya Ride kit into this Flutter app.
Source: github.com/blankframe-tech/ThrottleIQ, branch "mayabi".
Read mayabi/README.md, mayabi/API.md and mayabi/PRIVACY.md first.
1. Add the throttleiq_mayabi package and wire up trip cost, RideRecorder,
   SafetyCheck and the SOS button, following the README sections.
2. Add background location for Android and iOS, with the consent text
   from PRIVACY.md.
3. Server: implement the endpoints in API.md on our backend
   (or port functions/src/partner-api/), and point
   ThrottleIqClient(baseUrl: ...) at it. Keep the API key server-side.
4. Optional: port the password-protected permanent family link from
   commit 502dc519 onto our own rider accounts.
Show me a plan first, then implement step by step with tests.
```

> **Permission.** The ThrottleIQ repository is public under a source-available license (TSAL), which normally only allows viewing. As the owner, I give **Maya Ride written permission to copy, modify and use the code in the `mayabi` branch of the ThrottleIQ repository in Maya Ride's own apps and servers**, including with AI tools such as Claude. This permission covers the `mayabi` branch only, not the rest of the repository. Questions or problems: message me any time. — Abraar, ThrottleIQ