Tell us about your PDF experience.

Azure Terraform REST APIs

Article • 12/03/2024

Enables Azure Terraform workflows across various Azure resources. Currently, only an export workflow is supported.

See also

- Overview of the Azure Terraform Resource Provider

Resource Manager

08/26/2025

REST Operation Groups

Expand table

Operation Group
Operations
Terraform

Operations

Service: Terraform

API Version: 2025-09-01-preview

Operations

Expand table

List	List the operations for the provider

Operations - List

Service: Terraform

API Version: 2025-09-01-preview

List the operations for the provider

HTTP

```
GET https://management.azure.com/providers/Microsoft.AzureTerraform/operations?
api-version=2025-09-01-preview
```

URI Parameters

Expand table

Name	In	Required	Type	Description
`api-version`	query	True	string minLength: 1	The API version to use for this operation.

Responses

Expand table

Name	Type	Description
200 OK	OperationList Result	Azure operation completed successfully.
Other Status Codes	Error Response	An unexpected error response.

Security

azure_auth

Azure Active Directory OAuth2 Flow.

Type: oauth2
Flow: implicit
Authorization URL: https://login.microsoftonline.com/common/oauth2/authorize

Scopes

Expand table

Name	Description
user_impersonation	impersonate your user account

Examples

Get a list of operations for a resource provider

Sample request

HTTP

HTTP

```
GET
https://management.azure.com/providers/Microsoft.AzureTerraform/operations?
api-version=2025-09-01-preview
```

Sample response

Status code: 200

JSON


```
{
  "value": [
    {
      "name": "Microsoft.AzureTerraform/operations/read",
      "display": {
        "provider": "Microsoft AzureTerraform",
        "resource": "Azure Terraform Resource Provider",
        "operation": "ListOperations",
        "description": "Lists all of the available RP operations."
      }
    },
    {
      "name": "Microsoft.AzureTerraform/exportTerraform/action",
      "display": {
        "provider": "Microsoft AzureTerraform",
        "resource": "Azure Terraform Resource Provider",
        "operation": "ExportTerraform",
        "description": "Exports the Terraform configuration used for the specified
```

```
scope."
      }
    }
  ]
}
```

Definitions

Expand table

Name	Description
ActionType	Enum. Indicates the action type. "Internal" refers to actions that are for internal only APIs.
Display	Localized display information for this particular operation.
ErrorAdditionalInfo	The resource management error additional info.
ErrorDetail	The error detail.
ErrorResponse	Error response
Operation	REST API Operation
OperationListResult	A list of REST API operations supported by an Azure Resource Provider. It contains an URL link to get the next set of results.
Origin	The intended executor of the operation; as in Resource Based Access Control (RBAC) and audit logs UX. Default value is "user,system"

ActionType

Enumeration

Enum. Indicates the action type. "Internal" refers to actions that are for internal only APIs.

Expand table

Value	Description
Internal	

Display

Object

Localized display information for this particular operation.

Expand table

Name	Type	Description
description	string	The short, localized friendly description of the operation; suitable for tool tips and detailed views.
operation	string	The concise, localized friendly name for the operation; suitable for dropdowns. E.g. "Create or Update Virtual Machine", "Restart Virtual Machine".
provider	string	The localized friendly form of the resource provider name, e.g. "Microsoft Monitoring Insights" or "Microsoft Compute".
resource	string	The localized friendly name of the resource type related to this operation. E.g. "Virtual Machines" or "Job Schedule Collections".

ErrorAdditionalInfo

Object

The resource management error additional info.

Expand table

Name	Type	Description
info	object	The additional info.
type	string	The additional info type.

ErrorDetail

Object

The error detail.

Expand table

Name	Type	Description
additionalInfo	Error Additional Info[]	The error additional info.
code	string	The error code.

details	ErrorDetail[]	The error details.
message	string	The error message.
target	string	The error target.

ErrorResponse

Object

Error response

Expand table

Name	Type	Description
error	ErrorDetail	The error object.

Operation

Object

REST API Operation

Expand table

Name	Type	Description
actionType	ActionType	Enum. Indicates the action type. "Internal" refers to actions that are for internal only APIs.
display	Display	Localized display information for this particular operation.
isDataAction	boolean	Whether the operation applies to data-plane. This is "true" for data-plane operations and "false" for ARM/control-plane operations.
name	string	The name of the operation, as per Resource-Based Access Control (RBAC). Examples: "Microsoft.Compute/virtualMachines/write", "Microsoft.Compute/virtualMachines/capture/action"
origin	Origin	The intended executor of the operation; as in Resource Based Access Control (RBAC) and audit logs UX. Default value is "user,system"

OperationListResult

Object

A list of REST API operations supported by an Azure Resource Provider. It contains an URL link to get the next set of results.

Expand table

Name	Type	Description
nextLink	string (uri)	URL to get the next set of operation list results (if there are any).
value	Operation[]	List of operations supported by the resource provider

Origin

Enumeration

The intended executor of the operation; as in Resource Based Access Control (RBAC) and audit logs UX. Default value is "user,system"

Expand table

Value	Description
user	
system	
user,system	

Terraform

Service: Terraform

API Version: 2025-09-01-preview

Operations

Expand table

Export Terraform	Exports the Terraform configuration of the specified resource(s).

Terraform - Export Terraform

Service: Terraform

API Version: 2025-09-01-preview

Exports the Terraform configuration of the specified resource(s).

HTTP

```
POST
https://management.azure.com/subscriptions/{subscriptionId}/providers/Microsoft.AzureTerraform/exportTerraform?api-version=2025-09-01-preview
```

URI Parameters

Expand table

Name	In	Required	Type	Description
`subscriptionId`	path	True	string (uuid)	The ID of the target subscription. The value must be an UUID.
`api-version`	query	True	string minLength: 1	The API version to use for this operation.

Request Body

The request body can be one of the following:

Expand table

Name	Description
ExportQuery	Uses ARG (Azure Resource Graph) query to choose resources to be exported.
ExportResource	Specified resources to be exported by their ids.
ExportResourceGroup	Export parameter for a resource group

ExportQuery

Uses ARG (Azure Resource Graph) query to choose resources to be exported.

Expand table

Name	Required	Type	Description
query	True	string	The ARG where predicate. Multiple predicates can be combined using `and` operator. Example: `resourceGroup =~ "my-rg" and type =~ "microsoft.network/virtualnetworks"`. The default ARG table is `Resources`, use 'table' property to query a different table.
type	True	string: ExportQuery	The parameter type
authorizationScopeFilter		authorizationScopeFilter	The ARG Scope Filter parameter.
excludeAzureResource		string[]	Excludes specified Azure Resource Ids. Case-insensitive Azure Resource ID regular expression. Example: `["/subscriptions/[0-9a-f-]+/resourceGroups/my-rg.*"]`.
excludeTerraformResource		string[]	Excludes specified Terraform resource types. Example: `["azurerm_virtual_network"]`.
fullProperties		boolean	Whether to output all non-computed properties in the generated Terraform configuration. If set to `false` empty-valued properties will be omitted from the configuration. Defaults to `true`.
includeManagedResource		boolean	Whether to include internal resources managed by Azure in the exported configuration. Defaults to `false`.
includeResourceGroup		boolean	Includes the resource group in the exported Terraform resources. Defaults to `false`.
includeRoleAssignment		boolean	Whether to include RBAC role assignments assigned to the resources exported. Only resource-scoped role assignments are supported. Defaults to `false`.
maskSensitive		boolean	Mask sensitive attributes in the Terraform configuration. Defaults to `true`.
namePattern		string	The id prefix for the exported Terraform resources. Defaults to `res-`.

recursive	boolean	Recursively includes child resources. Defaults to `false`.
table	string	The ARG table name. Defaults to 'Resources'.
targetProvider	target Provider	The target Azure Terraform provider. Defaults to `azurerm`.

ExportResource

Specified resources to be exported by their ids.

Expand table

Name	Required	Type	Description
resourceIds	True	string[] (arm-id)	The id(s) of the resource to be exported. Example: `["/subscriptions/12345678-1234-1234-1234-1234567890ab/resourceGroups/my-rg"].
type	True	string: Export Resource	The parameter type
excludeAzureResource		string[]	Excludes specified Azure Resource Ids. Case-insensitive Azure Resource ID regular expression. Example: `["/subscriptions/[0-9a-f-]+/resourceGroups/my-rg.*"]`.
excludeTerraformResource		string[]	Excludes specified Terraform resource types. Example: `["azurerm_virtual_network"]`.
fullProperties		boolean	Whether to output all non-computed properties in the generated Terraform configuration. If set to `false` empty-valued properties will be omitted from the configuration. Defaults to `true`.
includeManagedResource		boolean	Whether to include internal resources managed by Azure in the exported configuration. Defaults to `false`.
includeResourceGroup		boolean	Includes the resource group in the exported Terraform resources. Defaults to `false`.
includeRoleAssignment		boolean	Whether to include RBAC role assignments assigned to the resources exported. Only resource-scoped role assignments are supported. Defaults to `false`.

maskSensitive	boolean	Mask sensitive attributes in the Terraform configuration. Defaults to `true`.
namePattern	string	The id prefix for the exported Terraform resources. Defaults to `res-`.
recursive	boolean	Recursively includes child resources. Defaults to `false`.
resourceName	string	The Terraform id of the exported resource. Only effective when `resourceIds` contains only one item. Defaults to `res-0`.
resourceType	string	The Terraform resource type to map to. Only effective when `resourceIds` has one item. Example: `azurerm_virtual_network`. Automatic type mapping will be performed if not provided.
targetProvider	target Provider	The target Azure Terraform provider. Defaults to `azurerm`.

ExportResourceGroup

Export parameter for a resource group

Expand table

Name	Required	Type	Description
resourceGroupName	True	string	The name of the resource group to be exported.
type	True	string: Export Resource Group	The parameter type
excludeAzureResource		string[]	Excludes specified Azure Resource Ids. Case-insensitive Azure Resource ID regular expression. Example: `["/subscriptions/[0-9a-f-]+/resourceGroups/my-rg.*"]`.
excludeTerraformResource		string[]	Excludes specified Terraform resource types. Example: `["azurerm_virtual_network"]`.
fullProperties		boolean	Whether to output all non-computed properties in the generated Terraform configuration. If set to

		`false` empty-valued properties will be omitted from the configuration. Defaults to `true`.
includeManagedResource	boolean	Whether to include internal resources managed by Azure in the exported configuration. Defaults to `false`.
includeRoleAssignment	boolean	Whether to include RBAC role assignments assigned to the resources exported. Only resource-scoped role assignments are supported. Defaults to `false`.
maskSensitive	boolean	Mask sensitive attributes in the Terraform configuration. Defaults to `true`.
namePattern	string	The id prefix for the exported Terraform resources. Defaults to `res-`.
targetProvider	target Provider	The target Azure Terraform provider. Defaults to `azurerm`.

Responses

Expand table

Name	Type	Description
200 OK	Terraform Operation Status	Azure operation completed successfully.
202 Accepted		Resource operation accepted. Headers • Azure-AsyncOperation: string • Location: string • Retry-After: integer
Other Status Codes	Error Response	An unexpected error response.

Security

azure_auth

Azure Active Directory OAuth2 Flow.

Type: oauth2
Flow: implicit
Authorization URL: https://login.microsoftonline.com/common/oauth2/authorize

Scopes

Expand table

Name	Description
user_impersonation	impersonate your user account

Examples

ExportTerraform

Sample request

HTTP

HTTP

```
POST https://management.azure.com/subscriptions/00000000-0000-0000-0000-000000000000/providers/Microsoft.AzureTerraform/exportTerraform?api-version=2025-09-01-preview

{
  "type": "ExportResourceGroup",
  "resourceGroupName": "rg1"
}
```

Sample response

Status code: 200

JSON

```
{
  "startTime": "2025-08-06T06:26:16.7243919Z",
  "endTime": "2025-08-06T06:26:32.8297901Z",
  "status": "Succeeded",
```

```
  "id": "/subscriptions/00000000-0000-0000-0000-
000000000000/providers/Microsoft.AzureTerraform/operationStatuses/00000000-0000-
0000-0000-000000000000",
  "name": "00000000-0000-0000-0000-000000000000",
  "properties": {
    "configuration": "terraform {\n  required_providers {\n    azurerm = {\n
source  = \"azurerm\"\n      version = \"4.33.0\"\n    }\n  }\n}\nprovider
\"azurerm\" {\n  features {}\n}\nresource \"azurerm_resource_group\" \"res-0\" {\n
location   = \"australiaeast\"\n  managed_by = \"\"\n  name       = \"rg1\"\n
tags       = {}\n}\n",
    "import": "import {\n  id = \"/subscriptions/00000000-0000-0000-0000-
000000000000/resourceGroups/rg-1\"\n  to = azurerm_resource_group.res-0\n}\n"
  }
}
```


Status code: 202

HTTP

```
Azure-AsyncOperation: https://management.azure.com/subscriptions/00000000-0000-
0000-0000-
000000000000/providers/Microsoft.AzureTerraform/operationStatuses/00000000-0000-
0000-0000-000000000000?api-version=2025-09-01-preview
Location: https://management.azure.com/subscriptions/00000000-0000-0000-0000-
000000000000/providers/Microsoft.AzureTerraform/operationStatuses/00000000-0000-
0000-0000-000000000000?api-version=2025-09-01-preview
```

Definitions

Expand table

Name	Description
authorizationScopeFilter	The Azure Resource Graph Authorization Scope Filter parameter
ErrorAdditionalInfo	The resource management error additional info.
ErrorDetail	The error detail.
ErrorResponse	Error response
ExportQuery	Uses ARG (Azure Resource Graph) query to choose resources to be exported.
ExportResource	Specified resources to be exported by their ids.
ExportResourceGroup	Export parameter for a resource group
ExportResult	The Terraform export result

ResourceProvisioningState	The operation status
targetProvider	The target Azure Terraform provider. Defaults to `azurerm`.
TerraformOperationStatus	The status of the LRO (Long Running Operation) and the export result.
Type	The parameter type

authorizationScopeFilter

Enumeration

The Azure Resource Graph Authorization Scope Filter parameter

Expand table

Value	Description
AtScopeAndBelow	Returns assignments for the given scope and all child scopes.
AtScopeAndAbove	Returns assignments for the given scope and all parent scopes, but not child scopes.
AtScopeAboveAndBelow	Returns assignments for the given scope, all parent scopes, and all child scopes.
AtScopeExact	Returns assignments only for the given scope; no parent or child scopes are included.

ErrorAdditionalInfo

Object

The resource management error additional info.

Expand table

Name	Type	Description
info	object	The additional info.
type	string	The additional info type.

ErrorDetail

Object

The error detail.

Expand table

Name	Type	Description
additionalInfo	Error Additional Info[]	The error additional info.
code	string	The error code.
details	ErrorDetail[]	The error details.
message	string	The error message.
target	string	The error target.

ErrorResponse

Object

Error response

Expand table

Name	Type	Description
error	ErrorDetail	The error object.

ExportQuery

Object

Uses ARG (Azure Resource Graph) query to choose resources to be exported.

Expand table

Name	Type	Default value	Description
authorizationScopeFilter	authorization ScopeFilter		The ARG Scope Filter parameter.
excludeAzureResource	string[]		Excludes specified Azure Resource Ids. Case-insensitive Azure Resource ID regular expression. Example: `["/subscriptions/[0-9a-f-]+/resourceGroups/my-rg.*"]`.
excludeTerraformResource	string[]		Excludes specified Terraform resource types.

			Example: `["azurerm_virtual_network"]`.
fullProperties	boolean	True	Whether to output all non-computed properties in the generated Terraform configuration. If set to `false` empty-valued properties will be omitted from the configuration. Defaults to `true`.
includeManagedResource	boolean	False	Whether to include internal resources managed by Azure in the exported configuration. Defaults to `false`.
includeResourceGroup	boolean	False	Includes the resource group in the exported Terraform resources. Defaults to `false`.
includeRoleAssignment	boolean	False	Whether to include RBAC role assignments assigned to the resources exported. Only resource-scoped role assignments are supported. Defaults to `false`.
maskSensitive	boolean	True	Mask sensitive attributes in the Terraform configuration. Defaults to `true`.
namePattern	string	res-	The id prefix for the exported Terraform resources. Defaults to `res-`.
query	string		The ARG where predicate. Multiple predicates can be combined using `and` operator. Example: `resourceGroup =~ "my-rg" and type =~ "microsoft.network/virtualnetworks"`. The default ARG table is `Resources`, use 'table' property to query a different table.
recursive	boolean	False	Recursively includes child resources. Defaults to `false`.
table	string	Resources	The ARG table name. Defaults to 'Resources'.
targetProvider	target Provider	azurerm	The target Azure Terraform provider. Defaults to `azurerm`.
type	string: ExportQuery		The parameter type

ExportResource

Object

Specified resources to be exported by their ids.

Expand table

Name	Type	Default value	Description
excludeAzureResource	string[]		Excludes specified Azure Resource Ids. Case-insensitive Azure Resource ID regular expression. Example: `["/subscriptions/[0-9a-f-]+/resourceGroups/my-rg.*"]`.
excludeTerraformResource	string[]		Excludes specified Terraform resource types. Example: `["azurerm_virtual_network"]`.
fullProperties	boolean	True	Whether to output all non-computed properties in the generated Terraform configuration. If set to `false` empty-valued properties will be omitted from the configuration. Defaults to `true`.
includeManagedResource	boolean	False	Whether to include internal resources managed by Azure in the exported configuration. Defaults to `false`.
includeResourceGroup	boolean	False	Includes the resource group in the exported Terraform resources. Defaults to `false`.
includeRoleAssignment	boolean	False	Whether to include RBAC role assignments assigned to the resources exported. Only resource-scoped role assignments are supported. Defaults to `false`.
maskSensitive	boolean	True	Mask sensitive attributes in the Terraform configuration. Defaults to `true`.
namePattern	string	res-	The id prefix for the exported Terraform resources. Defaults to `res-`.
recursive	boolean	False	Recursively includes child resources. Defaults to `false`.
resourceIds	string[] (arm-id)		The id(s) of the resource to be exported. Example: `["/subscriptions/12345678-1234-1234-1234-1234567890ab/resourceGroups/my-rg"].
resourceName	string	res-0	The Terraform id of the exported resource. Only effective when `resourceIds` contains only one item. Defaults to `res-0`.

resourceType	string		The Terraform resource type to map to. Only effective when `resourceIds` has one item. Example: `azurerm_virtual_network`. Automatic type mapping will be performed if not provided.
targetProvider	target Provider	azurerm	The target Azure Terraform provider. Defaults to `azurerm`.
type	string: Export Resource		The parameter type

ExportResourceGroup

Object

Export parameter for a resource group

Expand table

Name	Type	Default value	Description
excludeAzureResource	string[]		Excludes specified Azure Resource Ids. Case-insensitive Azure Resource ID regular expression. Example: `["/subscriptions/[0-9a-f-]+/resourceGroups/my-rg.*"]`.
excludeTerraformResource	string[]		Excludes specified Terraform resource types. Example: `["azurerm_virtual_network"]`.
fullProperties	boolean	True	Whether to output all non-computed properties in the generated Terraform configuration. If set to `false` empty-valued properties will be omitted from the configuration. Defaults to `true`.
includeManagedResource	boolean	False	Whether to include internal resources managed by Azure in the exported configuration. Defaults to `false`.
includeRoleAssignment	boolean	False	Whether to include RBAC role assignments assigned to the resources exported. Only resource-scoped role assignments are supported. Defaults to `false`.

maskSensitive	boolean	True	Mask sensitive attributes in the Terraform configuration. Defaults to `true`.
namePattern	string	res-	The id prefix for the exported Terraform resources. Defaults to `res-`.
resourceGroupName	string		The name of the resource group to be exported.
targetProvider	target Provider	azurerm	The target Azure Terraform provider. Defaults to `azurerm`.
type	string: Export Resource Group		The parameter type

ExportResult

Object

The Terraform export result

Expand table

Name	Type	Description
configuration	string	The exported Terraform HCL configuration.
errors	ErrorDetail[]	A list of errors encountered during export operation.
import	string	The Terraform import blocks for the configuration, necessary for managing existing Azure resources in Terraform.
skippedResources	string[] (arm-id)	A list of Azure resources which could not be exported to Terraform. The most common cause is lack of Terraform provider support. Change the provider type to `azapi` for bigger set of supported resources.

ResourceProvisioningState

Enumeration

The operation status

Expand table

Value	Description
Succeeded	Resource has been created.
Failed	Resource creation failed.
Canceled	Resource creation was canceled.

targetProvider

Enumeration

The target Azure Terraform provider. Defaults to `azurerm`.

Expand table

Value	Description
azurerm	https://registry.terraform.io/providers/hashicorp/azurerm/latest
azapi	https://registry.terraform.io/providers/Azure/azapi/latest

TerraformOperationStatus

Object

The status of the LRO (Long Running Operation) and the export result.

Expand table

Name	Type	Description
endTime	string (date-time)	Operation complete time
error	ErrorDetail	Errors that occurred if the operation ended with Canceled or Failed status
id	string	The unique identifier for the operationStatus resource
name	string	The name of the operationStatus resource
percentComplete	number (double)	The progress made toward completing the operation
properties	ExportResult	RP-specific properties for the operationStatus resource, only appears when operation ended with Succeeded status

startTime	string (date-time)	Operation start time
status	Resource Provisioning State	The operation status

Type

Enumeration

The parameter type

Expand table

Value	Description
ExportResource	
ExportResourceGroup	
ExportQuery	