

1 Grammar Rules

Types and Contexts

$$\begin{array}{ll}
\sigma, \tau & ::= \mathbf{unit} \mid \mathbf{num} \mid \sigma \otimes \sigma \mid \alpha \quad (\text{Types}) \\
\alpha & ::= m(\sigma) \quad (\text{Discrete Types}) \\
\Gamma & ::= \emptyset \mid \Gamma, x :_r \sigma \quad (\text{Linear Typing Contexts}) \\
\Phi & ::= \emptyset \mid \Phi, z : \alpha \quad (\text{Discrete Typing Contexts})
\end{array}$$

Expressions

$$\begin{array}{lcl}
e, f & ::= & x \mid z \mid () \mid !e \mid (e, f) \mid \mathbf{inl} e \mid \mathbf{inr} e \\
& | & \mathbf{let} x = e \mathbf{in} f \mid \mathbf{let} (x, y) = e \mathbf{in} f \mid \mathbf{dlet} z = e \mathbf{in} f \mid \mathbf{dlet} (x, y) = e \mathbf{in} f \\
& | & \mathbf{case} e' \mathbf{of} (\mathbf{inl} x.e \mid \mathbf{inr} y.f) \mid \mathbf{add} e f \mid \mathbf{sub} e f \mid \mathbf{mul} e f \mid \mathbf{dmul} e f \mid \mathbf{div} e f
\end{array}$$

2 Typing Rules

Context Variables

$$\frac{}{\Phi \mid \Gamma, x :_r \sigma \vdash x : \sigma} (\text{Var}) \qquad \frac{}{\Phi, z : \alpha \mid \Gamma \vdash z : \alpha} (\text{DVar})$$

Tensor Destructors

$$\frac{\Phi \mid \Gamma \vdash e : \tau_1 \otimes \tau_2 \quad \Phi \mid \Delta, x :_r \tau_1, y :_r \tau_2 \vdash f : \sigma}{\Phi \mid r + \Gamma, \Delta \vdash \mathbf{let} (x, y) = e \mathbf{in} f : \sigma} (\otimes E_\sigma)$$

$$\frac{\Phi \mid \Gamma \vdash e : \alpha_1 \otimes \alpha_2 \quad \Phi, z_1 : \alpha_1, z_2 : \alpha_2 \mid \Delta \vdash f : \sigma}{\Phi \mid \Gamma, \Delta \vdash \mathbf{dlet} (z_1, z_2) = e \mathbf{in} f : \sigma} (\otimes E_\alpha)$$

Let Bindings

$$\frac{\Phi \mid \Gamma \vdash e : \tau \quad \Phi \mid \Delta, x :_r \tau \vdash f : \sigma}{\Phi \mid r + \Gamma, \Delta \vdash \mathbf{let} x = e \mathbf{in} f : \sigma} (\text{Let}) \qquad \frac{\Phi \mid \Gamma \vdash e : \alpha \quad \Phi, z : \alpha \mid \Delta \vdash f : \sigma}{\Phi \mid \Gamma, \Delta \vdash \mathbf{dlet} z = e \mathbf{in} f : \sigma} (\text{DLet})$$

Bang Destructor

$$\frac{\Phi \mid \Gamma \vdash e : \sigma}{\Phi \mid \Gamma \vdash !e : m(\sigma)} (\text{Disc})$$

Operations

$$\frac{}{\Phi \mid \Gamma, x :_{\varepsilon+r_1} \mathbf{num}, y :_{\varepsilon+r_2} \mathbf{num} \vdash \{\mathbf{add}, \mathbf{sub}\} x y : \mathbf{num}} (\text{Add, Sub})$$

$$\frac{}{\Phi \mid \Gamma, x :_{\varepsilon/2+r_1} \mathbf{num}, y :_{\varepsilon/2+r_2} \mathbf{num} \vdash \mathbf{mul} x y : \mathbf{num}} (\text{Mul})$$

$$\frac{}{\Phi \mid \Gamma, x :_{\varepsilon/2+r_1} \mathbf{num}, y :_{\varepsilon/2+r_2} \mathbf{num} \vdash \mathbf{div} x y : \mathbf{num} + \mathbf{unit}} (\text{Div})$$

$$\frac{}{\Phi, z : m(\mathbf{num}) \mid \Gamma, x :_{\varepsilon+r} \mathbf{num} \vdash \mathbf{dmul} z x : \mathbf{num}} (\text{DMul})$$

References

- [1] Ariel E. Kellison, Laura Zielinski, David Bindel, and Justin Hsu. Bean: A language for backward error analysis. *Proceedings of the ACM on Programming Languages*, 9(PLDI):1838–1862, 2025.

This is a part of the hand-out to be given to the participants of the Tutorial on “Implementing an Integrated Development Environment: a Quick Start Guide for PL Researchers” at the 47th ACM (Association for Computing Machinery) SIGPLAN (Special Interest Group on Programming Languages) Conference on Programming Language Design and Implementation (PLDI 2026), held in Boulder, Colorado, United States on June 15, 2026 by Mikhail Barash (Associate Professor, University of Bergen, Norway) and Alberto Tontoni (Ph.D. Candidate, University of Bergen, Norway).

Link to the tutorial page at the PLDI 2026 website: <https://pldi26.sigplan.org/details/pldi-2026-tutorials/3/Implementing-an-Integrated-Development-Environment-a-Quick-Start-Guide-for-PL-Resear>