## 17—LANDSLIDE AND MASS-WASTING FEATURES (continued)

| REF NO | DESCRIPTION | SYMBOL | CARTOGRAPHIC SPECIFICATIONS* | NOTES ON USAGE* |
|---|---|---|---|---|
| 17.20 | Main toe of landslide—Active, sharp, distinct, and accurately located | | *3.0 mm; 60°; 1.0 mm; lineweight .25 mm* | Place line along base of toe; sawteeth on over-riding block. May be shown in red or other colors. |
| 17.21 | Main toe of landslide—Inactive, subdued, indistinct, and (or) approximately located | | *.5 mm; 3.0 mm* | |
| 17.22 | Minor toe, internal thrust fault, or pressure ridge in landslide—Active, sharp, distinct, and accurately located | | *2.5 mm; 60°; .85 mm; lineweight .25 mm* | |
| 17.23 | Minor toe, internal thrust fault, or pressure ridge in landslide—Inactive, subdued, indistinct, and (or) approximately located | | *.5 mm; 2.0 mm* | |
| 17.24 | Minor toe, internal thrust fault, or pressure ridge in landslide, showing transport reversal—Active, sharp, distinct, and accurately located | | *lineweight .25 mm; 60°; .85 mm; .85 mm; 5.0 mm; 60°* | |
| 17.25 | Minor toe, internal thrust fault, or pressure ridge in landslide, showing transport reversal—Inactive, subdued, indistinct, and (or) approximately located | | *.5 mm; 2.0 mm* | |
| 17.26 | Right flank of landslide or right-lateral shear feature —Active, sharp, distinct, and accurately located | | *15°; 2.5 mm; arrow lineweight .175 mm; lineweight .25 mm; 5.0 mm* | Arrow shows sense of lateral movement. Place arrow on side of moving ground or on displaced earth materi-als. In cross section, can also be used to show plane of slope failure. May be shown in red or other colors. |
| 17.27 | Right flank of landslide or right-lateral shear feature —Inactive, subdued, indistinct, and (or) approxi-mately located | | *.5 mm; 3.0 mm* | |
| 17.28 | Right flank of landslide or right-lateral shear feature —Concealed by landslide deposits or debris mate-rials | | *.5 mm; .5 mm* | |
| 17.29 | Right flank of landslide or right-lateral shear feature —Showing amount of offset (in meters) | 2.3 | *2.3; HI-7* | |
| 17.30 | Left flank of landslide or left-lateral shear feature— Active, sharp, distinct, and accurately located | | *2.5 mm; 15°; arrow lineweight .175 mm; lineweight .25 mm; 5.0 mm* | |
| 17.31 | Left flank of landslide or left-lateral shear feature— Inactive, subdued, indistinct, and (or) approxi-mately located | | *.5 mm; 3.0 mm* | |
| 17.32 | Left flank of landslide or left-lateral shear feature— Concealed by landslide deposits or debris materi-als | | *.5 mm; .5 mm* | |
| 17.33 | Left flank of landslide or left-lateral shear feature— Showing amount of offset (in meters) | 2.3 | *2.3; HI-7* | |
| 17.34 | Open tension crack or fracture on landslide | | *hachure height .5 mm; all lineweights .2 mm; 1.5 mm* | Hachures point into crack. |
| 17.35 | Tension crack or fracture on landslide (1st option) | | *all lineweights .2 mm; 1.0 mm* | May be shown in red or other colors. |
| 17.36 | Tension crack or fracture on landslide (2nd option) | | *all lineweights .2 mm; 1.2 mm; dash .375 mm; space .325 mm* | |
| 17.37 | Tension crack or fracture on landslide (3rd option) | | *lineweight .2 mm* | |
| 17.38 | En echelon cracks or fractures on landslide, indicat-ing right-lateral shear | | *15°; 2.5 mm; crack lineweights .2 mm; arrow lineweight .175 mm; 5.0 mm* | Arrow shows sense of lateral movement. May be shown in red or other colors. |
| 17.39 | En echelon cracks or fractures on landslide, indicat-ing left-lateral shear | | *2.5 mm; 15°; crack lineweights .2 mm; arrow lineweight .175 mm; 5.0 mm* | |
| 17.40 | Anticlinal soft-sediment fold, buckle fold, bulge, or linear ridge on landslide | | *line length can vary; 60°; 1.0 mm; 2.0 mm; arrow lineweight .175 mm; lineweight .25 mm* | May be shown in red or other colors. |
| 17.41 | Dome structure or bulge on landslide | | *line length can vary; 60°; 1.0 mm* | |
| 17.42 | Synclinal soft-sediment fold or linear depression on landslide | | *lineweight .25 mm; 60°; 1.0 mm; 1.0 mm; arrow lineweight .175 mm; line length can vary* | |
| 17.43 | Basin structure or depression on landslide | | *1.0 mm; line lengths can vary; 60°; .75 mm* | |

**For more information, see general guidelines on pages A-i to A-v.*