

1—CONTACTS, KEY BEDS, AND DIKES (continued)

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
1.4—Line-symbol decorations and notations for contacts, key beds, and dikes				
1.4.1	Inclined contact, dike, key bed, clay bed, coal bed, or bed of economically important commodity (1st option)—Showing dip value and direction		tick length 1.75 mm; line weight .15 mm 35 ← H-6	Line-symbol decorations may be added to any type or style of contact, as well as to any type or style of key bed or dike (use proper line-weights, etc., to show clay beds, coal beds, dikes, etc.).
1.4.2	Inclined contact, dike, key bed, clay bed, coal bed, or bed of economically important commodity (2nd option)—Showing dip value and direction		tick length 1.375 mm; line weight .15 mm 15 ← H-6 30°	
1.4.3	Vertical or near-vertical contact, dike, key bed, clay bed, coal bed, or bed of economically important commodity (1st option)		tick length 2.5 mm; line weight .15 mm	
1.4.4	Vertical or near-vertical contact, dike, key bed, clay bed, coal bed, or bed of economically important commodity (2nd option)		90 ← H-6	
1.4.5	Overtaken contact, dike, key bed, clay bed, coal bed, or bed of economically important commodity (1st option)—Showing dip value and direction		tick length 1.75 mm; line weight .15 mm 85 ← H-6 .625 mm radius	Place tick, arrow, or other line-symbol decoration where observation was made. Add arrowhead or '90' to ticks showing dip if necessary for clarity.
1.4.6	Overtaken contact, dike, key bed, clay bed, coal bed, or bed of economically important commodity (2nd option)—Showing dip value and direction		tick length 1.375 mm; line weight .15 mm 75 ← H-6 .625 mm radius 30°	
1.4.7	Lineation on surface of contact, dike, key bed, clay bed, coal bed, or bed of economically important commodity—Showing bearing and plunge		6.0 mm 65 ← H-6 line weight .175 mm 25°	
1.4.8	Lineation on surface of inclined contact, dike, key bed, clay bed, coal bed, or bed of economically important commodity—Tick shows contact dip value and direction; arrow shows bearing and plunge of lineation		tick length 1.75 mm; line weight .15 mm H-6 → 25 35	
1.4.9	Contact—Showing relative age of intrusive or extrusive units where known: Y, younger; O, older		H-7 → Y H-7 → O	Use proper line-weights, etc., to show clay beds, coal beds, dikes, etc.
1.4.10	Contact—Showing location where contact is particularly well exposed in field		1/20° 1.75 mm .75 mm	
1.4.11	Key bed, clay bed, coal bed, bed of economically important commodity, or dike—Showing thickness and location where measured		1.5 ← H-6	
1.4.12	Key bed—Showing name		ds ← H-8	
1.4.13	Clay bed—Showing name		sc ← H-8 (100% black)	
1.4.14	Bed of economically important commodity—Showing name		gyp ← H-8	
1.4.15	Coal bed—Showing name		lg ← H-8 (100% black)	
1.4.16	Clinkered coal bed—Showing name		m ← H-8 (100% black)	
1.4.17	Area of clinkered coal bed—Showing name		pg ← H-8 (100% black)	Although only "dike (2nd option)" is shown labeled here, map-unit labels may be added to any type of dike symbol. Use a queried map-unit label if identity of dike is questionable.
1.4.18	Dike—Showing name		Km ← H-8 leader line weight .175 mm	
1.4.19	Dike of variable thickness—Showing name		KJd ← H-8 leader line weight .175 mm	
1.4.20	Dike intruding fault (1st option)—Showing name		Km ← H-8 leader line weight .175 mm	
1.4.21	Dike intruding fault (2nd option)—Showing name		H-8 → Td leader line weight .175 mm	

*For more information, see general guidelines on pages A-i to A-v.