

17—LANDSLIDE AND MASS-WASTING FEATURES

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
17.1	Outline of slip surface of landslide—Identity and existence certain, location accurate		linecolor 60% black lineweight .2 mm	May be used to outline area of slip surface of landslide if desired. Do not use to outline landslide deposits (use a map-unit boundary contact instead).
17.2	Outline of slip surface of landslide—Identity or existence questionable, location accurate		H-8 (60% black) 12.0 mm 7.5 mm	
17.3	Outline of slip surface of landslide—Identity and existence certain, location approximate		3.5 mm	
17.4	Outline of slip surface of landslide—Identity or existence questionable, location approximate		7.5 mm 7.5 mm	
17.5	Outline of slip surface of landslide—Identity and existence certain, location inferred		1.5 mm	
17.6	Outline of slip surface of landslide—Identity or existence questionable, location inferred		7.5 mm 7.5 mm	
17.7	Outline of slip surface of landslide—Identity and existence certain, location concealed		.5 mm	
17.8	Outline of slip surface of landslide—Identity or existence questionable, location concealed		7.5 mm 7.5 mm	
17.9	Area of slip surface of landslide		pattern 431-K in 50% black (rotated so lines parallel slip direction)	Downslope edge of slip surface is usually concealed by landslide deposits or debris materials. Landslide arrows may be shown singly or in pairs.
17.10	Direction of downslope movement of landslide		outline of slip surface [lineweight .2 mm, in 60% black] contact [lineweight .15 mm] 50°/ 2.0 mm	
17.11	Landslide deposits—Arrows show direction of downslope movement		arrow lineweight .175 mm length and curve of arrow may vary	
17.12	Head or main scarp of landslide—Active, sharp, distinct, and accurately located. Hachures point down scarp		all lineweights .25 mm hachure height 1.0 mm; spacing 1.75 mm	Place line along crown of scarp. May be shown in red or other colors.
17.13	Head or main scarp of landslide—Inactive, subdued, indistinct, and (or) approximately located. Hachures point down scarp		.5 mm 3.0 mm	
17.14	Head or main scarp of landslide—Showing height (in meters). Hachures point down scarp		0.8 HI-7	
17.15	Head or main scarp of rotated block in landslide—Arrow shows direction of oblique slip. Hachures point down scarp		5.0 mm 2.5 mm 15° arrow lineweight .175 mm	
17.16	Internal or minor scarp in landslide—Active, sharp, distinct, and accurately located. Hachures point down scarp		all lineweights .25 mm hachure height .75 mm; spacing 1.25 mm	
17.17	Internal or minor scarp in landslide—Inactive, subdued, indistinct, and (or) approximately located. Hachures point down scarp		.5 mm 2.0 mm	
17.18	Internal or minor scarp in landslide—Showing height (in meters). Hachures point down scarp		0.3 HI-6	
17.19	Internal or minor scarp of rotated block in landslide—Arrow shows direction of oblique slip. Hachures point down scarp		4.5 mm 15° 2.0 mm arrow lineweight .175 mm	

*For more information, see general guidelines on pages A-i to A-v.