

17—LANDSLIDE AND MASS-WASTING FEATURES (continued)

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
17.20	Main toe of landslide—Active, sharp, distinct, and accurately located		3.0 mm line weight .25 mm	Place line along base of toe; sawteeth on over-riding block.
17.21	Main toe of landslide—Inactive, subdued, indistinct, and (or) approximately located		.5 mm line weight .25 mm	May be shown in red or other colors.
17.22	Minor toe, internal thrust fault, or pressure ridge in landslide—Active, sharp, distinct, and accurately located		2.5 mm line weight .25 mm	
17.23	Minor toe, internal thrust fault, or pressure ridge in landslide—Inactive, subdued, indistinct, and (or) approximately located		.5 mm line weight .25 mm	
17.24	Minor toe, internal thrust fault, or pressure ridge in landslide, showing transport reversal—Active, sharp, distinct, and accurately located		line weight .25 mm .85 mm	
17.25	Minor toe, internal thrust fault, or pressure ridge in landslide, showing transport reversal—Inactive, subdued, indistinct, and (or) approximately located		.5 mm line weight .25 mm	
17.26	Right flank of landslide or right-lateral shear feature—Active, sharp, distinct, and accurately located		15° line weight .25 mm	Arrow shows sense of lateral movement. Place arrow on side of moving ground or on displaced earth materials.
17.27	Right flank of landslide or right-lateral shear feature—Inactive, subdued, indistinct, and (or) approximately located		.5 mm line weight .25 mm	
17.28	Right flank of landslide or right-lateral shear feature—Concealed by landslide deposits or debris materials		.5 mm line weight .25 mm	In cross section, can also be used to show plane of slope failure.
17.29	Right flank of landslide or right-lateral shear feature—Showing amount of offset (in meters)		2.3 line weight .25 mm	May be shown in red or other colors.
17.30	Left flank of landslide or left-lateral shear feature—Active, sharp, distinct, and accurately located		2.5 mm line weight .25 mm	
17.31	Left flank of landslide or left-lateral shear feature—Inactive, subdued, indistinct, and (or) approximately located		.5 mm line weight .25 mm	
17.32	Left flank of landslide or left-lateral shear feature—Concealed by landslide deposits or debris materials		.5 mm line weight .25 mm	
17.33	Left flank of landslide or left-lateral shear feature—Showing amount of offset (in meters)		2.3 line weight .25 mm	
17.34	Open tension crack or fracture on landslide		hachure height .5 mm all line weights .2 mm	Hachures point into crack.
17.35	Tension crack or fracture on landslide (1st option)		1.0 mm all line weights .2 mm	May be shown in red or other colors.
17.36	Tension crack or fracture on landslide (2nd option)		1.2 mm all line weights .2 mm	
17.37	Tension crack or fracture on landslide (3rd option)		line weight .2 mm	
17.38	En echelon cracks or fractures on landslide, indicating right-lateral shear		15° crack line weights .2 mm	Arrow shows sense of lateral movement. May be shown in red or other colors.
17.39	En echelon cracks or fractures on landslide, indicating left-lateral shear		2.5 mm crack line weights .2 mm	
17.40	Anticlinal soft-sediment fold, buckle fold, bulge, or linear ridge on landslide		line length can vary line weight .25 mm	May be shown in red or other colors.
17.41	Dome structure or bulge on landslide		line length can vary line weight .25 mm	
17.42	Synclinal soft-sediment fold or linear depression on landslide		line weight .25 mm line weight .25 mm	
17.43	Basin structure or depression on landslide		1.0 mm line weight .25 mm	

*For more information, see general guidelines on pages A-i to A-v.