

30—TOPOGRAPHIC AND HYDROGRAPHIC FEATURES (continued)

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
30.2—Drainage features				
30.2.1	Perennial river, stream, or creek (single-line drainage)		 line weight .2 mm line color 100% cyan	Letter size and spacing may be increased along longer features.
30.2.2	Intermittent river, stream, creek, or wash (single-line drainage)		 line weight .2 mm long dash length 4.3 mm; very short dash, .2 mm; spacing .6 mm color 100% cyan	
30.2.3	Perennial river, stream, or creek (double-line drainage)		 TI-8 (100% black) color fill 20% cyan all line weights .2 mm spacing may vary	Letter size and spacing may be increased along wider features.
30.2.4	River mileage marker		 line weight .2 mm H-6	
30.2.5	Intermittent river, stream, creek, or wash (double-line drainage)		 pattern 132-C	
30.2.6	Braided river, stream, or creek		 all line weights .2 mm color 100% cyan	
30.2.7	Canal or ditch (single-line drainage)		 line weight .2 mm HI-6 (100% cyan)	
30.2.8	Canal or ditch (double-line drainage)		 color fill 20% cyan all line weights .2 mm spacing may vary	
30.2.9	Canal lock (single-line drainage) (1st option)		 1.25 mm H-6 (100% black) line weight .35 mm	
30.2.10	Canal lock (single-line drainage) (2nd option)			
30.2.11	Canal lock (double-line drainage)		 line weight .35 mm width may vary	
30.2.12	Floodgate		 line weight .35 mm H-6 (100% black)	
30.2.13	Tidegate		 line weight .35 mm H-6 (100% black)	
30.2.14	Sluice gate		 line weight .35 mm H-6 (100% black)	
30.2.15	Fish ladder		 line weight .5 mm length may vary H-6 (100% black)	
30.2.16	Aqueduct (single-line drainage)		 line weight .2 mm HI-6 (100% cyan)	
30.2.17	Aqueduct (double-line drainage)		 color fill 20% cyan all line weights .2 mm spacing may vary	
30.2.18	Underground or underwater aqueduct		 dash length 1.25 mm; spacing .5 mm	
30.2.19	Aboveground water pipeline		 HI-6 (100% cyan)	
30.2.20	Underground or submerged water pipeline		 dash length 1.25 mm; spacing .5 mm HI-6 (100% cyan)	
30.2.21	Elevated water pipeline		 wing length .575 mm; angle 45° all line weights .2 mm HI-6 (100% cyan)	
30.2.22	Flume		 HI-6 (100% cyan)	
30.2.23	Siphon		 dash length 1.25 mm; spacing .5 mm HI-6 (100% cyan)	
30.2.24	Penstock		 HI-6 (100% cyan)	