
















19—NATURAL RESOURCES (continued)

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
19.3—Mining and mineral exploration (at surface)				
19.3.1	Prospect (pit or small open cut)	X	lineweight .2 mm 	
19.3.2	Sand, gravel, clay, or placer pit		3.125 mm all lineweights .15 mm 60° 1.75 mm 7 mm	
19.3.3	Abandoned sand, gravel, clay, or placer pit		all lineweights .15 mm 1.5 mm	
19.3.4	Open pit, quarry, or glory hole		pick thickness .25 mm; radius 1.625 mm 1.5 mm 3.125 mm lineweight .15 mm hammerhead thickness .3 mm; radius 1.625 mm	
19.3.5	Abandoned open pit, quarry, or glory hole		all lineweights .15 mm 1.5 mm	
19.3.6	Open pit or quarry (mapped to scale)		all lineweights .25 mm hachure height .6 mm; spacing 1.5 mm	
19.3.7	Trench (generalized trace)		1.5 mm all lineweights .25 mm length may vary 90°	
19.3.8	Trench (drawn to scale)		all lineweights .25 mm hachure height .6 mm; spacing 1.5 mm	
19.3.9	Adit or tunnel entrance (1st option)		all lineweights .175 mm 90° 3.5 mm 1.5 mm 2.75 mm	Long line points in direction of adit or tunnel entrance at surface.
19.3.10	Approximately located adit or tunnel entrance (1st option)		3.5 mm 1.0 mm 2.5 mm	Map position of adit or tunnel entrance is at intersection of long line and two short lines.
19.3.11	Destroyed adit or tunnel entrance (1st option)		2.5 mm 2.5 mm	
19.3.12	Abandoned or inaccessible adit or tunnel entrance (1st option)		all lineweights .175 mm 1.75 mm 1.25 mm	
19.3.13	Adit or tunnel entrance (1st option)—Showing angle of inclination (negative value indicates downward slope)		HI-6 -40	Angle of inclination may be added to any adit or tunnel entrance symbol.
19.3.14	Adit or tunnel entrance (2nd option)		all lineweights .175 mm 90° 3.5 mm 1.5 mm 2.75 mm 1.0 mm	Long line points in direction of adit or tunnel entrance at surface.
19.3.15	Approximately located adit or tunnel entrance (2nd option)		3.5 mm 1.0 mm 2.5 mm	Map position of adit or tunnel entrance is at intersection of long line and two short lines.
19.3.16	Destroyed adit or tunnel entrance (2nd option)		2.5 mm 2.5 mm	
19.3.17	Abandoned or inaccessible adit or tunnel entrance (2nd option)		all lineweights .175 mm 1.75 mm 1.25 mm	
19.3.18	Adit or tunnel entrance (2nd option)—Showing angle of inclination (negative value indicates downward slope)		HI-6 -50	Angle of inclination may be added to any adit or tunnel entrance symbol.
19.3.19	Portal		all lineweights .175 mm radius .75 mm 3.5 mm 1.5 mm	Long lines point in direction of portal entry at surface.
19.3.20	Approximately located portal		3.5 mm 1.0 mm 2.5 mm	Map position of portal entry is between the two lines, at the position where the short curved lines intersect the long lines.
19.3.21	Destroyed portal		2.5 mm 2.5 mm	
19.3.22	Abandoned or inaccessible portal		all lineweights .175 mm 1.75 mm	
19.3.23	Portal and open cut		all lineweights .175 mm tick length .5 mm radius .75 mm	Open cut may be added to any portal symbol.
19.3.24	Portal—Showing angle of inclination (negative value indicates downward slope)		HI-6 -30	Angle of inclination may be added to any portal symbol.