

19—NATURAL RESOURCES (continued)

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
19.2—Areas of extensively disturbed ground; surface workings; subsurface workings projected to surface				
19.2.1	Graded area—Extensive amount of mapped geologic unit has been removed		lineweight .2 mm line color 100% red pattern 226-R (at 45°)	Patterns should overlay other mapped units. Generally shown in black or red, but may also be shown in brown or other colors.
19.2.2	Strip mine (1st option)		lineweight .15 mm lineweight .3 mm pattern 226-K (at 45°)	
19.2.3	Strip mine (2nd option)		pattern 419-R in 50% red	
19.2.4	Artificial fill—Earth materials		lineweight .15 mm H-8 20% black	Show as separately mapped units. Generally shown in black or red, but may also be shown in other colors.
19.2.5	Artificial fill—Human-generated refuse (landfill)		lineweight .15 mm H-8 pattern 226-R (at 45°)	
19.2.6	Tailings		lineweights .125 mm draft as shown	Symbols should overlay other mapped units. Generally shown in red or black, but may also be shown in brown or other colors.
19.2.7	Mine dump (1st option)		all lineweights .125 mm dash length and spacing may vary draft as shown	
19.2.8	Mine dump (2nd option)		all lineweights .125 mm dash length and spacing may vary draft as shown	
19.2.9	Mine dump bench		.75 mm 2.5 mm all lineweights .125 mm	Different symbols may be used to show different levels of workings. Symbols should overlay other mapped units. Generally shown in red, but may also be shown in black or other colors.
19.2.10	Subsurface workings, projected to surface (1st option)		color 100% red lineweights .2 mm spacing may vary	
19.2.11	Subsurface workings, projected to surface (2nd option)		dash 3.0 mm; spacing .5 mm	
19.2.12	Subsurface workings, projected to surface (3rd option)		dash 1.5 mm; spacing .5 mm	
19.2.13	Subsurface workings, projected to surface (4th option)		dash .5 mm; spacing .5 mm	
19.2.14	Subsurface workings, projected to surface (5th option)		long dash 2.5 mm; short dashes .5 mm; spacing .5 mm	
19.2.15	Subsurface workings, projected to surface (6th option)		long dash 4.0 mm; short dash .5 mm; spacing .5 mm	

*For more information, see general guidelines on pages A-i to A-v.