

26—GEOHYDROLOGIC FEATURES (continued)

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
26.2—Springs				
26.2.1	Spring, type of use unspecified		all lineweights .15 mm draft "tail" as shown circle diameter 1.75 mm	Rotate "tail" to point in direction of flow. May also be shown in cyan, red, or other colors.
26.2.2	Unused spring		bar lineweight .3 mm circle and "tail" lineweight .2 mm 3.725 mm	
26.2.3	Spring used for collection of water-quality data		circle and "tail" lineweight .2 mm dot diameter .375 mm	
26.2.4	Spring used for domestic-water supply		"tail" lineweight .2 mm draft "tail" as shown dot diameter 1.75 mm	
26.2.5	Thermal spring used for domestic-water supply		H-6 →	
26.2.6	Mineral spring used for domestic-water supply		H-6 →	
26.2.7	Extinct spring, once used for domestic-water supply		3.725 mm bar lineweight .2 mm	
26.2.8	Spring used for stock-water supply		"tail" lineweight .2 mm draft "tail" as shown circle diameter 1.75 mm; lineweight .25 mm	
26.2.9	Thermal spring used for stock-water supply		H-6 →	
26.2.10	Mineral spring used for stock-water supply		H-6 →	
26.2.11	Extinct spring, once used for stock-water supply		3.725 mm bar lineweight .2 mm	
26.2.12	Spring used for irrigation-water supply		inner circle diameter 1.125 mm; lineweight .15 mm draft "tail" as shown "tail" lineweight .2 mm outer circle diameter 1.75 mm; lineweight .2 mm	
26.2.13	Thermal spring used for irrigation-water supply		H-6 →	
26.2.14	Mineral spring used for irrigation-water supply		H-6 →	
26.2.15	Extinct spring, once used for irrigation-water supply		3.725 mm bar lineweight .2 mm	
26.2.16	Spring used for industrial-water supply		inner dot diameter 1.125 mm draft "tail" as shown "tail" lineweight .2 mm outer circle diameter 1.75 mm; lineweight .2 mm	
26.2.17	Thermal spring used for industrial-water supply		H-6 →	
26.2.18	Mineral spring used for industrial-water supply		H-6 →	
26.2.19	Extinct spring, once used for industrial-water supply		3.725 mm bar lineweight .2 mm	
26.2.20	Spring used for public-water supply		"tail" lineweight .2 mm draft "tail" as shown circle diameter 2.0 mm; lineweight .375 mm	
26.2.21	Thermal spring used for public-water supply		H-6 →	
26.2.22	Mineral spring used for public-water supply		H-6 →	
26.2.23	Extinct spring, once used for public-water supply		3.725 mm bar lineweight .2 mm	

*For more information, see general guidelines on pages A-i to A-v.