

13—GLACIAL AND GLACIOFLUVIAL FEATURES

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
13.1	Crevasse on glacier		lineweights .2 mm color 100% cyan lengths may vary	
13.2	Ice-flow direction		lineweight .25 mm color 100% cyan length may vary 60° 1.5 mm	
13.3	Glacial-lake spillway—Arrow shows direction of flow		color 100% cyan 1.25 mm lineweight .2 mm 25° 60° 2.0 mm length may vary	
13.4	Glacial-lake spillway—Showing elevation. Arrow shows direction of flow		785' HI-6 (100% black)	
13.5	Inferred glacial-lake spillway—Arrow shows direction of flow		all lineweights .2 mm	
13.6	Inferred glacial-lake spillway—Showing estimated elevation. Arrow shows direction of flow		785'	
13.7	Glacial meltwater stream—Barbs show direction of flow		all lineweights .2 mm 7.5 mm color 100% cyan 3.0 mm 2.25 mm spacing may vary ≤ 20°	
13.8	Cutbanks of glacial meltwater stream channel (mapped to scale)—Hachures point into channel		spacing may vary all lineweights .25 mm 1.125 mm color 100% cyan 3.0 mm	
13.9	Flow direction of glacial meltwater in stream channel		color 100% cyan all lineweights .2 mm 2.0 mm stem lengths may vary ≤ 25°	
13.10	Crest line of moraine, sense of symmetry unspecified (1st option)		color 100% cyan lineweight .2 mm circle diameter .75 mm; spacing .625 mm	
13.11	Crest line of moraine, sense of symmetry unspecified (2nd option)		color 100% cyan dot diameter .825 mm; spacing .625 mm	
13.12	Crest line of symmetrical moraine		color 100% cyan 3.0 mm .5 mm all lineweights .2 mm circle diameter .675 mm; hachure height 1.5 mm	
13.13	Crest line of asymmetrical moraine—Ticks point down steeper slope		hachure height .75 mm	
13.14	Ridges on moraine		color 100% cyan lineweight .25 mm lengths and spacing may vary	
13.15	Scarp at top of ice-contact slope—Hachures point downscarp		.5 mm 1.375 mm 12° color 100% cyan	
13.16	Ice-contact slope		pattern 521-C in 50% cyan	
13.17	Esker or ice-channel deposit, transport direction unknown		1.25 mm .375 mm .625 mm color 100% cyan lineweight .2 mm 70°	
13.18	Esker or ice-channel deposit, transport direction known (1st option)—Chevrons point in direction of transport		color 100% cyan 70° 1.25 mm 1.0 mm lineweight .2 mm	
13.19	Esker or ice-channel deposit, transport direction known (2nd option)—Chevrons point in direction of transport		color 100% cyan 70° 5.0 mm 1.25 mm lineweight .375 mm lineweight .2 mm	
13.20	Drumlin—Showing bearing and direction of flow		2.25 mm 1.25 mm 25° color 100% cyan 1.875 mm 6.0 mm	Point of observation is at the midpoint of the bearing line.
13.21	Drumlin, flow direction unknown (1st option)—Showing bearing		1.875 mm 6.0 mm	May also be shown in black or other colors.
13.22	Drumlin, flow direction unknown (2nd option)—Showing bearing		1.75 mm 1.0 mm 3.5 mm lineweight .2 mm color 100% cyan	
13.23	Drumlin (length mapped to scale)—Showing bearing and direction of flow		color 100% cyan 1.25 mm draw length to scale 1.25 mm 25° all lineweights .2 mm	Use when map scale is large enough to show actual length of drumlin.
13.24	Drumlin (length mapped to scale), flow direction unknown—Showing bearing		draw length to scale	May also be shown in black or other colors.

*For more information, see general guidelines on pages A-i to A-v.