

**19—NATURAL RESOURCES (continued)**

| REF NO                                    | DESCRIPTION                                                                                                                                                     | SYMBOL | CARTOGRAPHIC SPECIFICATIONS*                                                         | NOTES ON USAGE*        |
|-------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|--------------------------------------------------------------------------------------|------------------------|
| <b>19.4—Mines and subsurface workings</b> |                                                                                                                                                                 |        |                                                                                      |                        |
| 19.4.1                                    | Vertical mine shaft at surface (drawn to scale), as shown on subsurface exploration maps                                                                        |        | size may vary<br>lineweight .175 mm                                                  |                        |
| 19.4.2                                    | Inclined mine shaft at surface (drawn to scale), as shown on subsurface exploration maps—Showing direction of inclination                                       |        | all lineweights .175 mm<br>lengths may vary                                          |                        |
| 19.4.3                                    | Inclined mine shaft at surface (drawn to scale), as shown on subsurface exploration maps—Showing angle of inclination (negative value indicates downward slope) |        | -30<br>HI-6                                                                          |                        |
| 19.4.4                                    | Mine shaft, above and below level (drawn to scale), as shown on subsurface exploration maps                                                                     |        | size may vary<br>all lineweights .175 mm                                             |                        |
| 19.4.5                                    | Bottom of mine shaft (drawn to scale), as shown on subsurface exploration maps                                                                                  |        | size may vary<br>all lineweights .175 mm                                             |                        |
| 19.4.6                                    | Winze or head of raise (drawn to scale), as shown on subsurface exploration maps                                                                                |        | size may vary<br>all lineweights .175 mm                                             |                        |
| 19.4.7                                    | Raise or winze extending through level (drawn to scale), as shown on subsurface exploration maps                                                                |        | size may vary<br>all lineweights .175 mm                                             |                        |
| 19.4.8                                    | Raise or foot of winze (drawn to scale), as shown on subsurface exploration maps                                                                                |        | size may vary<br>all lineweights .175 mm                                             |                        |
| 19.4.9                                    | Crosscut tunnel or intersection of workings (drawn to scale), as shown on subsurface exploration maps                                                           |        | radius 1.25 mm<br>lineweight .175 mm                                                 | size may vary          |
| 19.4.10                                   | Workings (drawn to scale), as shown on subsurface exploration maps                                                                                              |        | spacing may vary<br>lineweights .175 mm                                              |                        |
| 19.4.11                                   | Caved or otherwise inaccessible workings (drawn to scale), as shown on subsurface exploration maps                                                              |        | all lineweights .175 mm<br>length of crossbar may vary<br>dash 1.5 mm; spacing .5 mm | spacing may vary       |
| 19.4.12                                   | Inclined workings, as shown on subsurface exploration maps (drawn to scale)—Chevrons point down-slope (multiple chevrons indicate steeper slope)                |        | all lineweights .175 mm<br>spacing may vary<br>90°                                   |                        |
| 19.4.13                                   | Ore chute (drawn to scale), as shown on subsurface exploration maps                                                                                             |        | 1.5 mm<br>spacing may vary<br>all lineweights .15 mm                                 |                        |
| 19.4.14                                   | Lagging or cribbing along drift (drawn to scale), as shown on subsurface exploration maps                                                                       |        | all lineweights .15 mm<br>spacing may vary<br>circle diameter .75 mm; spacing .75 mm |                        |
| 19.4.15                                   | Elevation of roof or back, as shown on subsurface exploration maps                                                                                              |        | 1.0 mm<br>60°<br>2801'<br>HI-6                                                       | all lineweights .15 mm |
| 19.4.16                                   | Elevation of floor or sill, as shown on subsurface exploration maps                                                                                             |        | HI-6<br>2809'<br>1.0 mm<br>60°                                                       |                        |
| 19.4.17                                   | Stoped area (drawn to scale), as shown on subsurface exploration maps (section view)                                                                            |        | all lineweights .15 mm<br>dash 1.5 mm; spacing .5 mm                                 |                        |
| 19.4.18                                   | Inferred stoped area (drawn to scale), as shown on subsurface exploration maps (section view)                                                                   |        | pattern 226-K (at 45°)<br>dash .3 mm; spacing .3 mm                                  |                        |

\*For more information, see general guidelines on pages A-i to A-v.