

1—CONTACTS, KEY BEDS, AND DIKES (continued)

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
1.3—Dikes				
1.3.1	Dike (1st option)—Identity and existence certain, location accurate		color 100% red lineweight .25 mm	Use when dike is too narrow to show as an area at map scale. Add map-unit labels to dikes if needed (see Section 1.4); use a queried label if identity of dike is questionable. May also be shown in black or other colors.
1.3.2	Dike (1st option)—Identity and existence certain, location approximate		3.5 mm 3.5 mm 3.5 mm lineweight .75 mm	
1.3.3	Dike (2nd option)—Identity and existence certain, location accurate		color 100% red lineweight .25 mm 2.0 mm 1.25 mm	
1.3.4	Dike (2nd option)—Identity and existence certain, location approximate		3.5 mm 3.5 mm 3.5 mm lineweight .75 mm	
1.3.5	Dike (3rd option)—Identity and existence certain, location accurate		color 100% red lineweight .25 mm 90° 4.25 mm 1.0 mm	
1.3.6	Dike (3rd option)—Identity and existence certain, location approximate		3.5 mm 3.5 mm 3.5 mm lineweight .75 mm	
1.3.7	Dike (4th option)—Identity and existence certain, location accurate		color 100% red lineweight .25 mm dot diameter 1.125 mm 4.25 mm	
1.3.8	Dike (4th option)—Identity and existence certain, location approximate		3.5 mm 3.5 mm 3.5 mm lineweight .75 mm	
1.3.9	Dike (5th option)—Identity and existence certain, location accurate		color 100% red lineweight .25 mm circle diameter 1.175 mm 4.25 mm	
1.3.10	Dike (5th option)—Identity and existence certain, location approximate		3.5 mm 3.5 mm 3.5 mm lineweight .75 mm	
1.3.11	Dike (6th option)—Identity and existence certain, location accurate		color 100% red lineweight .25 mm 1.125 mm 4.25 mm	
1.3.12	Dike (6th option)—Identity and existence certain, location approximate		3.5 mm 3.5 mm 3.5 mm lineweight .75 mm	
1.3.13	Dike of variable thickness		50% red contact [lineweight .15 mm]	Although only "dike (2nd option)" is shown here, any type of dike symbol may be used. Add map-unit labels to dikes if needed (see Section 1.4). Thick dikes may also be shown in other colors.
1.3.14	Dike intruding fault (1st option)		fault [lineweight .375 mm]	
1.3.15	Dike intruding fault (2nd option)		contact [lineweight .15 mm]	

*For more information, see general guidelines on pages A-i to A-v.