

19—NATURAL RESOURCES (continued)

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
19.4—Mines and subsurface workings				
19.4.1	Vertical mine shaft at surface (drawn to scale), as shown on subsurface exploration maps		size may vary lineweight .175 mm	
19.4.2	Inclined mine shaft at surface (drawn to scale), as shown on subsurface exploration maps—Showing direction of inclination		all lineweights .175 mm lengths may vary	
19.4.3	Inclined mine shaft at surface (drawn to scale), as shown on subsurface exploration maps—Showing angle of inclination (negative value indicates downward slope)		all lineweights .175 mm lengths may vary	
19.4.4	Mine shaft, above and below level (drawn to scale), as shown on subsurface exploration maps		size may vary all lineweights .175 mm	
19.4.5	Bottom of mine shaft (drawn to scale), as shown on subsurface exploration maps		size may vary all lineweights .175 mm	
19.4.6	Winze or head of raise (drawn to scale), as shown on subsurface exploration maps		size may vary all lineweights .175 mm	
19.4.7	Raise or winze extending through level (drawn to scale), as shown on subsurface exploration maps		size may vary all lineweights .175 mm	
19.4.8	Raise or foot of winze (drawn to scale), as shown on subsurface exploration maps		size may vary all lineweights .175 mm	
19.4.9	Crosscut tunnel or intersection of workings (drawn to scale), as shown on subsurface exploration maps		radius 1.25 mm lineweight .175 mm	size may vary
19.4.10	Workings (drawn to scale), as shown on subsurface exploration maps		spacing may vary lineweights .175 mm	
19.4.11	Caved or otherwise inaccessible workings (drawn to scale), as shown on subsurface exploration maps		all lineweights .175 mm length of crossbar may vary dash 1.5 mm; spacing .5 mm	spacing may vary
19.4.12	Inclined workings, as shown on subsurface exploration maps (drawn to scale)—Chevrons point down-slope (multiple chevrons indicate steeper slope)		all lineweights .175 mm spacing may vary	90°
19.4.13	Ore chute (drawn to scale), as shown on subsurface exploration maps		1.5 mm spacing may vary all lineweights .15 mm	
19.4.14	Lagging or cribbing along drift (drawn to scale), as shown on subsurface exploration maps		all lineweights .15 mm spacing may vary circle diameter .75 mm; spacing .75 mm	.55 mm
19.4.15	Elevation of roof or back, as shown on subsurface exploration maps		1.0 mm all lineweights .15 mm	60° 2801'
19.4.16	Elevation of floor or sill, as shown on subsurface exploration maps		1.0 mm all lineweights .15 mm	60° 2809'
19.4.17	Stoped area (drawn to scale), as shown on subsurface exploration maps (section view)		all lineweights .15 mm dash 1.5 mm; spacing .5 mm	
19.4.18	Inferred stoped area (drawn to scale), as shown on subsurface exploration maps (section view)		pattern 226-K (at 45°) dash .3 mm; spacing .3 mm	

*For more information, see general guidelines on pages A-i to A-v.