

26—GEOHYDROLOGIC FEATURES (continued)

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
26.7—Miscellaneous geohydrologic features				
26.7.1	Watershed basin boundary, drainage divide, or surface-water basin boundary		lineweight .6 mm dash length 7.5 mm dot diameter .625 mm; spacing .5 mm	May also be shown in cyan or other colors.
26.7.2	Watershed subbasin boundary, drainage subdivide, or surface-water subbasin boundary		lineweight .425 mm dash length 5.0 mm dot diameter .45 mm; spacing .5 mm	
26.7.3	Ground-water divide—Accurately located		dot diameter .675 mm; spacing .575 mm	
26.7.4	Ground-water divide—Approximately located		lineweight .15 mm circle diameter .675 mm; spacing .575 mm	
26.7.5	Ground-water barrier (geologic)—Accurately located		lineweight .175 mm dot diameter .675 mm; spacing .575 mm	
26.7.6	Ground-water barrier (geologic)—Approximately located		lineweight .175 mm circle lineweight .15 mm; diameter .675 mm; spacing .575 mm	
26.7.7	Infiltration gallery		all lineweights .15 mm square side 1.125 mm	
26.7.8	Direction of ground-water flow (1st option)—Accurately located		1.125 mm 5.75 mm 30° 2.125 mm	
26.7.9	Direction of ground-water flow (2nd option)—Accurately located		lineweight .15 mm	
26.7.10	Direction of ground-water flow (1st option)—Approximately located		6.75 mm all lineweights .25 mm 2.75 mm 1.5 mm 25°	
26.7.11	Direction of ground-water flow (2nd option)—Approximately located		dash 1.5 mm; space .5 mm	

*For more information, see general guidelines on pages A-i to A-v.