

2—FAULTS (continued)

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS*	NOTES ON USAGE*
2.13—Quaternary faulting				
2.13.1	Fault showing displacement during historic time (includes areas of known fault creep)		 fault [lineweight .375 mm] lineweight 1.25 mm; color 100% red	Although only shown here on "identity and existence certain, location accurate," generic faults, color may be added to any type or style of fault to highlight where geomorphic evidence indicates displacement during Quaternary time.
2.13.2	Fault showing displacement during Holocene time		 fault [lineweight .375 mm] lineweight 1.25 mm; color 100% orange	
2.13.3	Fault showing displacement during late Quaternary time		 fault [lineweight .375 mm] lineweight 1.25 mm; color 100% green	
2.13.4	Fault showing displacement during Quaternary time (undifferentiated)		 fault [lineweight .375 mm] lineweight 1.25 mm; color 100% violet	
2.14—Shear zones; mylonite zones; fault-breccia zones				
2.14.1	Ductile shear zone or mylonite zone—May or may not be associated with mappable faults		 3.75 mm all lineweights .2 mm	Orient S-shaped symbols to indicate linear trend of zone; spacing may be varied to show intensity of shear. Width of zones may vary. Patterns may either overprint other map units or be used as stand-alone map units (if zones have well-defined boundaries).
2.14.2	Zone of sheared rock within fault		 pattern 405-K (at ~45° to fault trend)	
2.14.3	Fault-breccia zone or zone of broken rock within fault		 pattern 401-K	
2.14.4	Fault-breccia zone or zone of broken rock around fault		 pattern 401-K	
2.15—Small, minor faults				
2.15.1	Small, minor inclined fault—Showing strike and dip		 HI-6 35 1.425 m tick lineweight .2 mm lineweight .375 mm	Use to show small, minor faults that are observed in outcrop but that cannot be traced away from that outcrop.
2.15.2	Small, minor vertical or near-vertical fault—Showing strike		 2.5 mm	
2.15.3	Small, minor shear fault—Showing dip. Arrow shows direction of relative horizontal displacement		 85 arrow lineweight .2 mm	

*For more information, see general guidelines on pages A-i to A-v.