

Triad strict-CI beats Lange at 7 of 8 $d \geq 7$ ops points;
loses to PM at $d=9$ $p=0.015$ (above threshold)

d=3, p=0.005	loss -8.59 pp	—	overlap	WIN +0.002 pp
d=3, p=0.007	loss -10.91 pp	—	overlap	WIN +0.08 pp
d=3, p=0.01	loss -13.02 pp	—	loss -0.03 pp	WIN +0.10 pp
d=3, p=0.015	loss -14.07 pp	—	overlap	WIN +0.28 pp
d=5, p=0.005	overlap	—	overlap	WIN +0.35 pp
d=5, p=0.007	overlap	—	overlap	WIN +0.80 pp
d=5, p=0.01	overlap	—	WIN +0.03 pp	WIN +1.48 pp
d=5, p=0.015	WIN +0.22 pp	—	WIN +0.65 pp	WIN +2.30 pp
d=7, p=0.005	overlap	overlap	WIN +0.005 pp	WIN +0.25 pp
d=7, p=0.007	WIN +0.26 pp	WIN +0.05 pp	WIN +0.37 pp	WIN +0.78 pp
d=7, p=0.01	WIN +1.22 pp	WIN +0.55 pp	WIN +1.71 pp	WIN +1.25 pp
d=7, p=0.015	WIN +2.31 pp	WIN +0.27 pp	WIN +3.77 pp	WIN +0.74 pp
d=9, p=0.005	loss -0.12 pp	—	overlap	WIN +0.17 pp
d=9, p=0.007	loss -0.48 pp	—	WIN +0.15 pp	WIN +0.68 pp
d=9, p=0.01	loss -1.55 pp	—	WIN +1.83 pp	WIN +0.98 pp
d=9, p=0.015	loss -1.01 pp	—	WIN +3.36 pp	loss -0.56 pp
	PFWL3S vs Lange-pub	PFWL3S vs Lange-FT	Triad vs Lange-pub	Triad vs PyMatching
	strict-CI WIN (95% non-overlap)	overlap (statistical tie)	strict-CI loss	

Wilson 95% CIs at 100K shots / point. WIN = row-decoder strictly beats column-decoder. Numbers show CI-EDGE separation in percentage points (pp; point-estimate gaps are larger). PFWL3S rows: $d \leq 7$ = the Table-11 re-eval (ensemble_pfwl3s_v2.json); $d=9$ = the PFWL3S-H256-d9 variant (Table 14). The 'loss' cell at $d=9$ $p=0.015$ in the right column reflects that the $d=9$ surface code is above its pseudo-threshold there, where PM's combinatorial structure is provably near-optimal.