


# Watson Studio SPSS Modeler Overview

This lab will introduce the SPSS Modeler capability using the Titanic dataset. The lab will guide the development of an SPSS Modeler stream that will prepare the input data for modeling to run a machine learning algorithm predicting survivability of a passenger on the Titanic.

## Step 1: Adding a Data Asset to the Watson Studio Labs project

1. Download the Titanic data file by clicking on the link [Titanic Data Set](#) and following the instructions below.


Right click on Raw, and click on Save link as ....




The screenshot shows the GitHub interface for the repository 'jpatter / ML-POT'. The file 'titanic\_cleansed.csv' is selected, showing its commit history and contributors. The file size is 75.6 KB and it contains 1045 lines (1044 sloc). The 'Raw' button is highlighted with a yellow arrow, indicating the next step in the process.

1	2	3	4	5	6	7	8	9	10
pclass	survived	name	sex	sibsp	parch	ticket	fare	embarked	
1	1	Allen, Miss. Elisabeth Walton	female	0	0	24160	211.337500	S	
1	1	Allison, Master. Hudson Trevor	male	1	2	113781	151.550000	S	
1	0	Allison, Miss. Helen Loraine	female	1	2	113781	151.550000	S	
1	0	Allison, Mr. Hudson Joshua Creighton	male	1	2	113781	151.550000	S	
1	0	Allison, Mrs. Hudson J.C. (Beatrice Maria) Daniels	female	1	2	113781	151.550000	S	


- Go back to the Watson Studio project. Click on **New data asset**, or if you don't see **New data asset**, click on the  icon.




- Click on the **Load** tab.




- Click on **browse**.



- Go to the folder where the titanic\_csv file is stored. Select the titanic.csv file and then click **Open**.



6. The file is now added as a Data Asset.


Data assets						New data asset
0 assets selected.						
NAME	TYPE	SERVICE	CREATED BY	LAST MODIFIED	ACTIONS	
 titanic.csv	Data Asset	Project	Michael	7 Feb 2018, 5:01:18 pm	⋮	

## Step 2: Create a Model to predict survival


In this section, we will create a Machine Learning flow using SPSS nodes. Documentation describing the nodes is available at <https://dataplatform.ibm.com/docs/content/analyze-data/ml-canvas-spss.html?context=analytics>.

### Step 2.1 Create a New Flow and Load the Data


1. In the Watson Studio project, click on **New flow** in the **Modeler flows** section.




2. Enter a **Name** for the flow, optionally enter a **Description**, click on Modeler Flow for the **flow type** (should be the default), click on IBM SPSS Modeler for the **Runtime** (should be the default), and click on **Create**.




3. This opens the Flow Editor. Click on **Import** and then **Data Asset** and hold the left mouse key on the Data Asset icon and **drag it onto the left side of the canvas**. Release the left mouse key.




4. Double click on the **Data Asset**. In the window pane on the right-hand-side click on **Change data asset**.




5. Select the **titanic.csv** option, and click **OK**.



6. Click on **Annotation**.




7. Click on **Custom name**, and type **titanic.csv**, and click on **Save**.





8. Note, the depiction of the flow nodes in the user interface has slightly changed from what is shown in this document. The text in the UI is now below the icon, instead of to the right.


Old icon --




New icon-




9. Click on the **Outputs** menu item in the Node Palette on the left and then click on the **Table** icon and drag the icon to the right of the titanic.csv icon. The SPSS Table node will display the contents of the csv file. If the Node Palette is not visible, click on the Node Palette icon 




10. Connect the right side of the titanic.csv icon to the left side of the Table icon. This is accomplished by clicking on the little circle at the right side of the titanic.csv icon holding the left mouse key and dragging the mouse to the little circle on the left side of the Table icon, and then releasing the left mouse key.



11. Right click on the **Table** icon, and select **Run**.





12. The “Running Flow” prompt will appear and then when completed a Table output selection will appear on the right side of the screen under the **Outputs** tab. If the Table output selection does not appear, select the  icon.




13. Double click on the Table selection and the contents of the titanic.csv will be displayed. Each row contains information on a passenger on the Titanic. We will use this data to make predictions on survivability.


PCLASS	SURVIVED	NAME	SEX	AGE	SIBSP	PARCH	TICKET	FARE	CABIN	EMBARKED	BOAT
1	1	Allen, Miss. Elisabeth	female	29	0	0	24160	211.3375	B5	S	2
1	1	Allison, Master. Huds	male	0.9167	1	2	113781	151.55	C22 C26	S	11
1	0	Allison, Miss. Helen L	female	2	1	2	113781	151.55	C22 C26	S	
1	0	Allison, Mr. Hudson J	male	30	1	2	113781	151.55	C22 C26	S	
1	0	Allison, Mrs. Hudson	female	25	1	2	113781	151.55	C22 C26	S	
1	1	Anderson, Mr. Harry	male	48	0	0	10952	26.55	E12	S	3
1	1	Andrews, Miss. Korn	female	63	1	0	13502	77.9583	D7	S	10
1	0	Andrews, Mr. Thoma	male	39	0	0	112050	0	A36	S	
1	1	Appleton, Mrs. Edwa	female	53	2	0	11789	51.4792	C101	S	D
1	0	Artagaveytia, Mr. Ra	male	71	0	0	PC 17609	49.5042		C	
1	0	Astor, Col. John Jacc	male	47	1	0	PC 17757	227.525	C62 C64	C	
1	1	Astor, Mrs. John Jac	female	18	1	0	PC 17757	227.525	C62 C64	C	4
1	1	Aubart, Mme. Leonti	female	24	0	0	PC 17477	69.3	B35	C	9
1	1	Barber, Miss. Ellen ?	female	26	0	0	19877	78.85		S	6
1	1	Barkworth, Mr. Alger	male	80	0	0	27042	30	A23	S	B

Page 1 / 7


## Step 2.2 Explore the Data using the Data Audit Node


Perusing through the data in the table, we can see that there are missing values. The SPSS Modeler has a Data Audit node that provides profiling information on the input data that is useful for cleansing the data. It provides a comprehensive first look at the data, including summary statistics, as well as information about outliers, missing values, and extremes.


1. Add a **Data Audit** node to the flow clicking on the **Outputs** menu item in the Node Palette, and then dragging the **Data Audit** node to underneath the titanic.csv node. If the Node Palette is not visible, click on the Node Palette icon . Connect the titanic.csv node to the Data Audit node. The canvas should appear as below.



2. Right click on the **Data Audit** node and click **Run**.



- The “Running Flow” prompt will appear and then when completed a Data Audit output selection will appear on the right side of the screen under the **Outputs** tab. If the **Outputs** tab doesn’t display, click on the  icon.



- Double click on the **Data Audit of [14 fields]** to view the Data Audit output. We can see that several fields have many missing values (cabin, boat, body, home.dest). These fields will be removed using a **Filter** node below. Other fields have only a few missing values (fare, embarked, age). The rows containing the missing values will be removed using a **Select** node below.

IBM Knowledge Center | dataref-support | Issues - dataconnect | Data & Analytics | Creating machine | Mail | Calendar | Homepage - Update

Secure | https://datapatform.ibm.com/canvas/streams/679a6dfc-27a6-4dc0-955a-63b183a355fd/outputs/61f248bb-9f92-4309-99e8-6ec93e70df13?context=analytics

IBM Data Science Experience | Projects | Tools | Data Services | Community | US South | Settings | Notifications | User

My Projects > Titanic-SPSS-Lab > Titanic-Flow > Data Audit of [14 fields] #8

### Data Audit of [14 fields] #8


	Field	Graph	Measurement	Min	Max	Mean	Std. Dev	Skewness	Unique	Valid
1	pclass		Continuous	1	3	2.295	0.838	-0.599	--	1309
2	survived		Continuous	0	1	0.382	0.486	0.486	--	1309
3	name		Categorical	--	--	--	--	--	--	1309
4	sex		Categorical	--	--	--	--	--	2	1309
5	age		Continuous	0.167	80.000	29.881	14.413	0.408	--	1046
6	sibsp		Continuous	0	8	0.499	1.042	3.844	--	1309
7	parch		Continuous	0	9	0.385	0.866	3.669	--	1309
8	ticket		Categorical	--	--	--	--	--	--	1309
9	fare		Continuous	0.000	512.329	33.295	51.759	4.368	--	1308
10	cabin		Categorical	--	--	--	--	--	186	295
11	embarked		Categorical	--	--	--	--	--	3	1307
12	boat		Categorical	--	--	--	--	--	27	486
13	body		Continuous	1	328	160.810	97.697	0.092	--	121
14	home.dest		Categorical	--	--	--	--	--	--	745


	Field	Measurement	Outliers	Extremes	Action	Impute Missing	Method	% Complete	Valid Records	Null Value	Empty String	White Space	Blank Value
1	pclass	Continuous	0	0	None	Never	Fixed	100.000	1309	0	0	0	0
2	survived	Continuous	0	0	None	Never	Fixed	100.000	1309	0	0	0	0
3	name	Categorical	--	--	--	Never	Fixed	100.000	1309	0	0	0	0
4	sex	Categorical	--	--	--	Never	Fixed	100.000	1309	0	0	0	0
5	age	Continuous	3	0	None	Never	Fixed	79.908	1046	263	0	0	0
6	sibsp	Continuous	28	9	None	Never	Fixed	100.000	1309	0	0	0	0
7	parch	Continuous	14	10	None	Never	Fixed	100.000	1309	0	0	0	0
8	ticket	Categorical	--	--	--	Never	Fixed	100.000	1309	0	0	0	0
9	fare	Continuous	34	4	None	Never	Fixed	99.924	1308	1	0	0	0
10	cabin	Categorical	--	--	--	Never	Fixed	22.536	295	1014	0	0	0



## Step 2.3 Explore the Data using Graph Nodes.

Let’s explore the data using Graph Nodes. The Distribution node, and the Histogram node will be used to explore some of the characteristics of the Titanic Data Set. First, we will add a Type node to the canvas. The Type node specifies field metadata and properties. We will change the



measurement property for the “pclass” and “survived fields” that was derived as “Continuous” by scanning the data values to “Ordered Set” and “Flag” respectively.

1. Add a **Type** node to the flow by clicking on the **Field Operations** menu item in the Node Palette and then drag the **Type** node underneath the **Data Audit** node. If the Node Palette is not visible, click on the Node Palette icon . Connect the titanic.csv node to the **Type** node. The canvas should appear as below.







2. Double click on the **Type** node. This will open a **Type** menu pallet on the right side of the screen.



3. Click on the **Settings** dropdown. Select **Configure Types**.



4. Select **Add Columns**.



5. Click on the checkboxes adjacent to the **pclass** and **survived** fields, and then click on the left arrow next to **Select Fields for Type**.

# Select Fields for Type

Search in column

Field name

Filter:

[Reset](#)

<input type="checkbox"/>	Field name ^	Data type ^
<input checked="" type="checkbox"/>	pclass	integer
<input checked="" type="checkbox"/>	survived	integer
<input type="checkbox"/>	name	string
<input type="checkbox"/>	sex	string
<input type="checkbox"/>	age	double
<input type="checkbox"/>	sibsp	integer
<input type="checkbox"/>	parch	integer
<input type="checkbox"/>	ticket	string
<input type="checkbox"/>	fare	double
<input type="checkbox"/>	cabin	string
<input type="checkbox"/>	embarked	string
<input type="checkbox"/>	boat	string
<input type="checkbox"/>	body	integer
<input type="checkbox"/>	home.dest	string


Cancel


OK


- ## Configure Types

- Click on **Save** in the bottom right of the Types pallet.





8. Add a **Distribution** node to the flow by clicking on the **Graph** menu item and then dragging the **Distribution** node to the canvas to the right of the **Type** node. If the Node Palette is not visible, click on the Node Palette icon . Connect the **Type** node to the **Distribution** node. The canvas should appear as below. The ? indicates that the fields to be plotted have not been identified.




9. Double click on the Distribution Node. Click on the **Plot** dropdown. In the Field (discrete) dropdown, select **pclass**. In the Color (discrete) dropdown, select **survived**. Click on the **normalize by color** checkbox, and then click **Save**.

The screenshot shows the Orange3 data mining software interface. A workflow is visible with nodes: 'titanic.csv', 'Table', '14 Fields', 'Type', and a 'Distribution' node (represented by a box with a question mark). A yellow arrow points to the 'Distribution' node. Another yellow arrow points to the 'Plot' dropdown menu in the right-hand configuration panel. The 'Plot' panel is expanded, showing options for 'Specified' and 'All flags (true values)'. Below this, the 'Field (discrete)' dropdown is set to 'pclass', and the 'Color (discrete)' dropdown is set to 'survived'. The 'Sort' section has 'Alphabetic' selected. The 'Normalize by color' checkbox is checked, and the 'Use proportional scale' checkbox is unchecked. At the bottom of the panel, the 'Save' button is highlighted with a yellow arrow.


10. Right click on the Distribution node, and select Run.

The screenshot shows the same Orange3 workflow as before. A right-click context menu is open over the 'Distribution' node, which now displays the name 'pclass'. A yellow arrow points to the 'Run' option at the bottom of the context menu. The context menu includes options: 'Open', 'Disconnect', 'Preview', 'Edit', 'Delete', 'Create supernode', 'Save as a model', and 'Run'.


11. The Distribution of pclass output will appear under the **Outputs** tab.





12. Double click on the **Distribution of pclass** to view the graph. We can see from the graph that the likelihood of surviving is correlated to the passenger class. The first class passengers have the highest rate of survivability. **Note if you see a graph with green bars, instead of the one below, redo Step 10 (this is a defect that has been reported).**




13. You can change the distribution graph to show the survivability by gender by double clicking on the Distribution node and replacing **pclass** with **sex** and clicking Save. Re-run the graph by right clicking on the Distribution node and selecting Run. Double click on the **Distribution of sex** to display the graph.




14. Add a **Histogram** node to the flow by clicking on the **Graphs** menu item and then dragging the **Histogram** node to the canvas underneath the **Distribution** node. If the Node Palette is not visible, click on the Node Palette icon . Connect the **Type** node to the **Histogram** node. The canvas should appear as below. The ? indicates that the fields to be plotted have not been identified.




15. Double click on the **Histogram** node. Click on the **Plot** dropdown. Select **fare** from the Field (continuous) dropdown. Select **survived** from the Color (discrete) dropdown. Click on **Save**.



16. Right click on the **Histogram** node and select **Run**.




17. Double click on the Histogram of fare



under the Outputs

tab at the right of the screen.



18. We can see that the histogram is skewed. Skewness will impact the effectiveness of some machine learning techniques. One way to deal with skewness is to do a logarithmic transformation of the data. We will do this transformation in the preparing the data for modeling section below.


## Step 2.4 Prepare the Data for Modeling


Based on our exploration of the data, there are several transformations that are needed to prepare the data for modeling. This section will introduce, the **Filter** node, the **Select** node, and the **Derive** node that will do the necessary transformations. The **Filter** and **Derive** nodes act on a field level, whereas the **Select** node acts on a record level.

**Filter** node – The **Filter** node performs two functions. It specifies fields that can be dropped. It also allows fields to be renamed. We will drop the fields cabin,boat,body, and home.dest.

**Derive** node – The **Derive** node modifies data values or creates new fields from one or more existing fields. We will use the derive node to do a logarithmic transformation of the fare field. We will also use this node to bin the age and fare fields.

**Select** node – The **Select** node is used to select or discard a subset of records from the data stream based on a specific condition. We will remove the rows where there are missing information in the fare, age, or embarked fields.

1. Add a **Filter** node to drop fields with many missing values. Add the **Filter** node by clicking on the **Field Operations** menu item in the Node palette and dragging the **Filter** node onto the canvas underneath the fare **Histogram** node. If the Node Palette is not visible, click on the Node Palette icon  first. Connect the **Type** node to the **Filter** node. The canvas should appear as below.



2. Double click on the **Filter** node. Click on the **Filter** dropdown. In the Filter panel, click on **Add Columns**.

## Filter

FILTER

Mode

☒ Filter the selected fields

☐ Retain the selected fields (all other fields are filtered)

Select Fields

−

+

Add Columns





RENAME















ANNOTATIONS


3. Click on the checkboxes adjacent to the **cabin**, **boat**, **body**, and **home.dest** fields, and then click on **OK**.



## Select Fields for Filter

Search in column:  Field name  Filter:   [Reset](#) 

<input type="checkbox"/> Field name ^	Data type ^
<input type="checkbox"/> pclass	 integer
<input type="checkbox"/> survived	 integer
<input type="checkbox"/> name	 string
<input type="checkbox"/> sex	 string
<input type="checkbox"/> age	 double
<input type="checkbox"/> sibsp	 integer
<input type="checkbox"/> parch	 integer
<input type="checkbox"/> ticket	 string
<input type="checkbox"/> fare	 double
<input checked="" type="checkbox"/> cabin	 string
<input type="checkbox"/> embarked	 string
<input checked="" type="checkbox"/> boat	 string
<input checked="" type="checkbox"/> body	 integer
<input checked="" type="checkbox"/> home.dest	 string

[Cancel](#) [OK](#) 

4. Click **Save** on the Filter panel.

Filter

FILTER

Mode

☒ Filter the selected fields

☐ Retain the selected fields (all other fields are filtered)

Select Fields

−

+

Add Columns

cabin

boat

body


home.dest


RENAME

ANNOTATIONS

Cancel


Save


5. Add a **Select** node by clicking on the **Record Operations** menu item in the Node palette, and then dragging the **Select** node to the canvas to the right of the **Filter** node. Connect the **Filter** node to the **Select** node. If the Node Palette is not visible, click on the Node Palette icon  first. The canvas should appear as below.




6. Double click on the **Select** node. Click on the **Settings** dropdown. In the **Select** panel, click on the **Discard** radio button, and re-type in the code shown below in the **Condition** text box, and then click **Save**.

@NULL (age) or embarked==" or @NULL(fare)



7. Add a **Derive** node to the canvas by clicking on the **Field Operations** menu item in the Node palette, and then dragging the **Derive node** onto the canvas to the right of the **Select** node. If the Node Palette is not visible, click on the Node Palette icon  first. Connect the **Select** node to the **Derive** node. The canvas should appear as below.



8. Double click on the **Derive** node. Click on the **Settings** Dropdown. Click on the **Single** radio button, enter log\_fare for the **Derive field**, select **Range** for the measurement, enter the following code in the **Expression** text box, and click Save.


```
if (fare /=0) then log(fare)
```


```
else 0
```

```
endif
```

The screenshot shows the 'Derive' node settings dialog in QGIS. The dialog is titled 'Derive' and has a 'SETTINGS' dropdown. The 'Mode' section has 'Single' selected. The 'Derive field' is 'log\_fare'. The 'Derive As' section has 'Formula' selected. The 'Measurement' is 'Range'. The 'Expression' text box contains the code: 'if (fare /=0) then log(fa', 'else 0', 'endif'. The 'Save' button is highlighted with a red box.

9. Binning of continuous fields is a technique sometimes used in preparing data for modeling. We will bin the age field, and the log\_fare field. Add a **Derive** node by clicking on the **Field Operations** menu item in the Node palette and dragging the **Derive** node on the canvas underneath the log\_fare **Derive** node.

If the Node Palette is not visible, click on the Node Palette icon  first. Connect the log\_fare **Derive** node to the newly added **Derive** node. The canvas should appear as below.



10. Double click on the **Derive** node. Click on the **Settings** dropdown. Click on the **Single** radio button, enter age\_bucket for the **Derive** field, select OrderedSet for the **Measurement**, enter the following code in the **Expression** text box, and then click **Save**.

```
if age >=0 and age < 6 then 0
else if age >=6 and age < 12 then 1
else if age>=12 and age< 18 then 2
else if age>=18 and age <40 then 3
else if age>=40 and age <65 then 4
else if age>=65 and age<80 then 5
else 6
endif
endif
endif
endif
endif
endif
```

Derive

SETTINGS

Mode

☒ Single

☐ Multiple

Derive field

age\_bucket

118

Derive As

Formula

Measurement

OrderedSet

Expression

```
if age >=0 and age < 6 th
else if age >=6 and age <
else if age>=12 and age<
else if age>=18 and age <
```

Cancel


Save

?

Select




11. Add a **Derive** node by clicking on the Field Operations menu item in the Node palette and dragging the **Derive** node onto the canvas underneath the age\_bucket **Derive** node. Connect the age\_bucket **Derive** node to the newly created **Derive** Node. The canvas should appear as below.



12. Double click the **Derive** node. In the **Derive** panel, click on the **Single** radio button, enter **fare\_bucket** in the **Derive field**, click on **OrderedSet** for the **Measurement**, enter the following code in the **Expression** text box, and click on **Save**.


```
if log_fare < 0 then 0
else if log_fare > 8 then 9
else to_integer(log_fare)+1
endif
endif
```



## Step 2.5 Modeling and Evaluation

Now that the data is prepared, we can start the modeling effort. First, we will add a **Partition** node to divide the data set into Training and Testing sets. In addition, a **Type** node is needed prior to modeling to type the new data fields that were created. Then we will add a **Logistic Regression** node, and use the Training set to train the model. Finally, we will add an **Analysis** node to evaluate the results.

1. Add a **Partition** node by clicking on the Field Operations menu item in the Node palette and dragging the **Partition** node onto the canvas to the right of the fare\_bucket **Derive** node. Connect the fare\_bucket **Derive** node to the **Partition** node. The canvas should appear as below.



2. Double click on the Partition node. Set the **Training Partition** to 70 and the **Test Partition** to 30. Leave the other defaults, and click on **Save**.

The screenshot shows the 'Partition' configuration window. The 'SETTINGS' tab is active. The 'Derived Field Name' is 'Partition'. The 'Training Partition' is set to 70 and the 'Testing Partition' is set to 30. The 'Create validation partition' checkbox is unchecked, and the 'Repeatable partition assignment' checkbox is checked. The 'Seed' is 1234567. The 'Use unique field to assign partitions' checkbox is unchecked. The 'Annotations' tab is also visible. A 'Select' node is connected to the Partition node. A yellow arrow points to the 'Save' button.

Partition

SETTINGS

Derived Field Name  
Partition

Training Partition  
70

Testing Partition  
30

☐ Create validation partition

☒ Repeatable partition assignment


Seed [Generate](#)  
1234567

☐ Use unique field to assign partitions


Annotations

Cancel Save

3. Add a **Type** node by clicking on the **Field Operations** in the Node palette and dragging the **Type** node onto the canvas above the **Partition** node. Connect the **Partition** node to the **Type** node. The canvas should appear as below.



4. Double click on the **Type** node. Click on **Configure Types**.



5. Click on **Add Columns**.

### Configure Types

Types

⊖ ⊕ **Add Columns**

Field ^	Measure ^	Role ^	Value mode ^	Values ^	Check ^






Cancel




















OK




- Click on checkboxes adjacent to the **log\_fare**, **age\_bucket**, **fare\_bucket**, and **Partition** fields (You may need to scroll down). Click on **OK**.

## Select Fields for Type

 Filter:    [Reset](#) 

<input type="checkbox"/>	Field name ^	Data type ^
<input type="checkbox"/>	sex	 string
<input type="checkbox"/>	age	 double
<input type="checkbox"/>	sibsp	 integer
<input type="checkbox"/>	parch	 integer
<input type="checkbox"/>	ticket	 string
<input type="checkbox"/>	fare	 double
<input type="checkbox"/>	cabin	 string
<input type="checkbox"/>	embarked	 string
<input type="checkbox"/>	boat	 string
<input type="checkbox"/>	body	 integer
<input type="checkbox"/>	home.dest	 string
<input checked="" type="checkbox"/> 	log_fare	 double
<input checked="" type="checkbox"/> 	age_bucket	 integer
<input checked="" type="checkbox"/> 	fare_bucket	 integer
<input checked="" type="checkbox"/> 	Partition	 string

[Cancel](#) [OK](#) 



7. For the **Partition** field, select **Ordinal** for the **Measurement**. For the log\_fare, select **Continuous** for the **Measurement**. For the fare\_bucket field, select **Ordinal** for the **Measurement**, and for the age\_bucket, select **Ordinal** for the **Measurement**, and click **OK**.

## Configure Types

Read Values

Types

+

Add Columns

Field^	Measure^	Role^	Value mode^	Values^	Check^
Partition	Ordinal	Input	Specify	1_Trainin...	None
log_fare	Continuous	Input	Specify	0.0, 6.23...	None
fare_bucket	Ordinal	Input	Specify	1, 2, 3, 4,...	None
age_bucket	Ordinal	Input	Specify	0, 1, 2, 3,...	None

Cancel

OK

## 8. Click on **Save**

**Type**

SETTINGS

**Default mode**

☒ Read metadata

☐ Pass (do not scan)

**Configure Types**

Types

log_fare	Range	Input
age_bucket	OrderedSet	Input
fare_bucket	OrderedSet	Input
Partition	Set	Input


ANNOTATIONS

Cancel Save

?

Select

9. Add a **Logistic Regression** node by clicking on the **Modeling** menu item in the Node palette and dragging the **Logistic** node onto the canvas above the **Type** node. Connect the **Type** node to the **Logistic Regression** node. The canvas should appear as below.



10. Double click on the **Logistic Regression** node. Click on the checkbox next to **Use custom field roles**, select **survived** for the **Target**, select **Partition** for the **Partition**, and click on **Add Columns** to add the input fields.

The screenshot shows the configuration interface for a Logistic Regression node. The window is titled "No Targets" and has a search bar at the top. The main area is divided into two sections: "FIELDS" and "ANNOTATIONS".

In the "FIELDS" section, the following settings are visible:




- ☒ Use custom field roles
- Target**: survived
- Inputs**:  ⊖ ⊕ Add Columns
- Partition**: Partition

On the left side of the interface, a "Select" node is visible, connected to the main configuration area. At the bottom of the configuration window, there are "Cancel" and "Save" buttons, along with a circular icon containing a checkmark.

11. Click on the checkboxes next to pclass, sex, sibsp, parch, embarked, age\_bucket, fare\_bucket fields (you have to scroll down), and then click **OK**.

### Select Fields for No Targets

Search in column Field name


Filter:   

[Reset](#)

<input type="checkbox"/>	Field name ^	Data type ^
<input checked="" type="checkbox"/>	pclass	integer
<input type="checkbox"/>	name	string
<input checked="" type="checkbox"/>	sex	string
<input type="checkbox"/>	age	double
<input checked="" type="checkbox"/>	sibsp	integer
<input checked="" type="checkbox"/>	parch	integer
<input type="checkbox"/>	ticket	string
<input type="checkbox"/>	fare	double
<input type="checkbox"/>	cabin	string
<input checked="" type="checkbox"/>	embarked	string
<input type="checkbox"/>	boat	string
<input type="checkbox"/>	body	integer
<input type="checkbox"/>	home.dest	string
<input type="checkbox"/>	log_fare	double
<input checked="" type="checkbox"/>	age_bucket	integer

Cancel

OK



12. Click **Save**.

The screenshot shows a configuration window titled "No Targets" with a search icon and a list icon in the top left. The window is divided into two main sections: "FIELDS" and "ANNOTATIONS".

**FIELDS**


- ☒ Use custom field roles
- Target**  
survived
- Inputs** (with minus and plus icons, and a link "Add Columns")  
parch  
embarked  
age\_bucket  
fare\_bucket
- Partition**  
Partition

**ANNOTATIONS**


At the bottom of the window, there are two buttons: "Cancel" and "Save". A yellow arrow points to the "Save" button. To the left of the "Save" button is a teal circular icon with a white document symbol.

On the left side of the interface, there is a "Select" button with a question mark icon, connected by a blue line to the "FIELDS" section.


13. Right click on the **Logistic Regression** node and then click **Run**. A **Logistic Regression** “nugget” will be created” connected by a dotted line to the **Logistic Regression** node. Drag the nugget and place it above the **Logistic Regression** node. The canvas should appear as below.




14. Add an **Analysis** node by clicking on the **Outputs** menu item in the Node palette and dragging the **Analysis** node onto the canvas above the nugget icon. Connect the nugget icon to the **Analysis** node. The canvas should appear as below.



15. Double click on the Analysis node. Click on the **Settings** dropdown. Click on the **Evaluation metric** checkbox, uncheck **Separate by partition**, and click on **Save**.



16. Right click on the Analysis node, and select Run. After completion, double click on the  link in the Outputs tab on the right side of the screen. The results should be similar to those shown below.


<b>Results for output field survived</b>		
<b>Individual Models</b>		
<b>Comparing \$L-survived with survived</b>		
Correct	828	79.39%
Wrong	215	20.61%
Total	1,043	
<b>Evaluation Metrics</b>		
Model	AUC	Gini
\$L-survived	0.857	0.714



## Step 2.6 Saving a Model


Now that we have created and evaluated a model, we will save the model as an asset. This saved model can be deployed at a future date, removing the need to recreate the same model from scratch.

1. Right click on the Analysis node and then click on **Save branch as a model**.



**If you receive a “Required Service Missing” page, proceed to step 1.A.** If you do not receive this page, proceed to step 2.

- 1.A. Click on “**Create a new Watson Machine Learning service instance.**”



1.B. Scroll down and click on “**Lite**” to select the Lite plan and then click on **Create**.

IBM Data Science Experience | Projects Tools Community Services US South

easy for developers and data scientists to work together to integrate predictive capabilities with their applications. The Machine Learning service is a set of REST APIs that you can call from any programming language to develop applications that make smarter decisions, solve tough problems, and improve user outcomes.

**SPSS analytics platform features**  
SPSS streams management and deployment with realtime scoring and batch processing options.

**Spark and Python Machine Learning features**  
Take advantage of Spark MLlib and scikit-learn machine learning models management and deployment - online, batch and streaming.

**Integration with Data Science Experience**  
Visit <http://datascience.ibm.com>. Create and train predictive analytics models with the best tools and the latest expertise in a social environment built by data scientists.

**Pricing Plan:** Monthly Process shown above reflect the: **United States**

Plan	Features	Pricing
<input checked="" type="radio"/> Lite	Service instance (5 models per instance) 5,000 predictions 5 compute hours	Free
<input type="radio"/> Standard	Predictions Compute hours	\$0.5 USD/1,000 predictions \$0.45 USD/hour
<input type="radio"/> Professional	Service instance 2,000,000 predictions included and then billed per 1,000 predictions 1,000 compute hours included and then billed per compute hour	\$1,000 USD/instance \$0.4 USD/1,000 predictions \$0.4 USD/hour

The lite plan instance of the IBM Watson Machine Learning service provides you with a maximum of 5 deployed models, 5,000 predictions per month, and 5 hours per month of compute time during which model can be trained, evaluated, and deployed to be available to accept prediction events.

**Terms**

Cancel Create

1.C. Click on **Confirm**.

## Confirm Creation

Organization: michael.cronk\_organization1


Plan  
**Lite** ▼

Space  
**space1** ▼


Service name  
predictive-modeling-fj

Cancel **Confirm**

1.D. Return to your SPSS flow. Right click on the Analysis node and then click on **Save as a model**.




2. Type in “**TitanicSPSS**” as the Model Name and click **Save**.



3. Click **Close**.



4. Navigate to your project “assets” page. In this example, click on **Watson Studio Labs**.



5. Note that the model you built is now saved as an asset and the work you have completed can be easily reused in the future.

The screenshot shows the IBM Data Science Experience interface. The top navigation bar includes the IBM logo, 'IBM Data Science Experience', and links for 'Projects', 'Tools', 'Community', and 'Services'. The right side of the bar shows 'US South', a document icon, a grid icon, a bell icon, and a user profile icon labeled 'MC'. Below the navigation bar, the breadcrumb 'My Projects / Titanic-SPSS-Lab' is visible. A green '+ Add to project' button is next to the breadcrumb. Below this, a message states '0 assets selected.' followed by a table with columns: NAME, SHARED, LAST EDITOR, LAST MODIFIED, and ACTIONS. The table body contains the text 'you currently have no dashboard'. Below this table, a section titled 'Models' is expanded, showing a table with columns: NAME, STATUS, TYPE, RUNTIME, LAST MODIFIED, and ACTIONS. The first row in the 'Models' table is 'TitanicSPSS', with status 'trained', type 'spss-modeler-18.1', runtime 'spss-modeler-18.1', and last modified '13 Feb 2018'. A yellow arrow points to the 'TitanicSPSS' entry in the 'NAME' column. A '+ New model' button is located to the right of the 'Models' section header.

NAME	STATUS	TYPE	RUNTIME	LAST MODIFIED	ACTIONS
TitanicSPSS	trained	spss-modeler-18.1	spss-modeler-18.1	13 Feb 2018	⋮