

# IBM Training

## Student Exercises

### Lab-3: Create a COVID-19 Chabot Hands-On Lab

Legal Copyright: © Copyright IBM Corp. 2020  
*Course materials may not be reproduced in whole or in part without the  
prior written permission of IBM*

## Table of Contents

Introduction.....	3
Objectives .....	3
Exercise 1: Create a Watson Assistant Instance .....	3
Exercise 2: Download the COVID-19 FAQ file.....	7
Intents.....	8
Entities .....	9
Dictionary-based method .....	9
Annotation-based method .....	9
Dialogs .....	10
Exercise 3: Create a Watson Assistant Skill .....	11
Exercise 4: Add a Search Skill.....	18
Exercise 5: Create Cloud Functions.....	29
Exercise 6: Integrate data sources via a Watson Assistant webhook.....	36
Exercise 7: Extend to other locations.....	44

## Introduction

This lab will build a chatbot to respond to questions about COVID-19. Watson Assistant and Watson Discovery services from IBM will be used to build the chatbot.

## Objectives


The goal of this lab is to familiarize the user with the Watson Assistant service. Watson Assistant is IBM's AI offering that lets you build, train, and deploy conversation interactions into any application, device, or channel. Watson Assistant can be deployed on any cloud or on-premises environment.

After completing this lab, you will be familiar with these features of Watson Assistant and IBM Cloud.


1. Provision an instance of Watson Assistant
2. Add a dialog skill to your Watson Assistant instance
3. Connect your Watson Assistant with Watson Discovery
4. Create Cloud Functions
5. Integrate data sources via a Watson Assistant webhook

## Exercise 1: Create a Watson Assistant Instance


1. Log into your IBM Cloud account by typing in the url **cloud.ibm.com** in your Firefox or Chrome browser.
2. Enter your **IBMid** and click **Continue**.




3. Enter your **Password** and click **Log in**.




4. Click **Create Resource**.




5. Enter **Watson Assistant** and click the <Enter> key.




6. Click on **Watson Assistant**.





7. Click on the **Trial** and click **Create**.




8. Click on **Launch Watson Assistant**.



9. Click on the assistant icon  .



10. The My first assistant is created automatically. Click on **Create assistant**.



11. Enter **COVID-19 Crisis Communication** for the **Name** and click **Create assistant**.

## Create assistant

Create an assistant to deploy the skill that addresses your customers' goals.

Name

COVID-19 Crisis Communication

Name your assistant, for example Banking or Customer Care.

Description (optional)

Add a description for this assistant

Web chat ⓘ

☒ Enable web chat

Preview link ⓘ

☒ Enable preview link

Create assistant


## Exercise 2: Download the COVID-19 FAQ file.

In this exercise, you will download a COVID-19 FAQ file. This file will contain the configuration for Watson Assistant to be able to respond to COVID-19 inquiries. The file consists of pre-defined intents, entities, and dialogs.

1. Click [here](#) to download the FAQ file.
2. Right-click on **Raw**, then click on **Save link as ...**



3. Navigate to the location that you want to save the file then click **Save**.



Intents, Entities, and Dialogs are discussed in more detail below to explain the content of the JSON file and how intents, entities, and dialogs are used to by Watson Assistant to implement a chatbot. The lab steps continue with Exercise 3: Create a Watson Assistant Skill.

## Intents

**Intents** are purposes or goals that are expressed in a customer's input, such as answering a question or processing a bill payment. By recognizing the intent expressed in a customer's input, the Watson Assistant service can choose the correct dialog flow for responding to it.

In planning the intents for your application, consider what your customers might want to do, and what you want your application to be able to handle on their behalf. For example, you might want your application to help your customers make a purchase. If so, you can add a `#buy_something` intent. (The `#` that is added as a prefix to the intent name helps to clearly identify it as an intent.)

After you decide which business requests that you want your application to handle for your customers, you must teach Watson about them. For each business goal (such as `#buy_something`), you must provide at least 5 examples of utterances that your customers typically use to indicate their goal. For example, `I want to make a purchase.`

Ideally, find real-world user utterance examples that you can extract from existing business processes. The user examples should be tailored to your specific business. For example, if you are an insurance company, a user example might look more like this, `I want to buy a new XYZ insurance plan.`

The examples that you provide are used by your assistant to build a machine learning model that can recognize the same and similar types of utterances and map them to the appropriate intent.



## Entities

**Entities** represent information in the user input that is relevant to the user's purpose.

If intents represent verbs (the action a user wants to do), entities represent nouns (the object of, or the context for, that action). For example, when the *intent* is to get a weather forecast, the relevant location and date *entities* are required before the application can return an accurate forecast.

Recognizing entities in the user's input helps you to craft more useful, targeted responses. For example, you might have a `#buy_something` intent. When a user makes a request that triggers the `#buy_something` intent, the assistant's response should reflect an understanding of what the *something* is that the customer wants to buy. You can add a `@product` entity, and then use it to extract information from the user input about the product that the customer is interested in. (The `@` prepended to the entity name helps to clearly identify it as an entity.)

Your assistant detects entities in the user input by using one of the following evaluation methods:

### Dictionary-based method

Your assistant looks for terms in the user input that match the values, synonyms, or patterns you define for the entity.

- **Synonym entity:** You define a category of terms as an entity (`color`), and then one or more values in that category (`blue`). For each value you specify a bunch of synonyms (`aqua`, `navy`). You can also pick synonyms to add from recommendations made to you by Watson.

At run time, your assistant recognizes terms in the user input that exactly match the values or synonyms that you defined for the entity as mentions of that entity.

- **Pattern entity:** You define a category of terms as an entity (`contact_info`), and then one or more values in that category (`email`). For each value, you specify a regular expression that defines the textual pattern of mentions of that value type. For an `email` entity value, you might want to specify a regular expression that defines a `text@text.com` pattern.

At run time, your assistant looks for patterns matching your regular expression in the user input, and identifies any matches as mentions of that entity.

- **System entity:** Synonym entities that are prebuilt for you by IBM. They cover commonly used categories, such as numbers, dates, and times. You simply enable a system entity to start using it.

### Annotation-based method

When you define an annotation-based entity, which is also referred to as a contextual entity, a model is trained on both the *annotated term* and the *context* in which the term is used in the sentence you annotate. This new contextual entity model enables your assistant to calculate a confidence score that identifies how likely a word or phrase is to be an instance of an entity, based on how it is used in the user input.

- **Contextual entity:** First, you define a category of terms as an entity (`product`). Next, you go to the *Intents* page and mine your existing intent user examples to find any mentions of the entity, and label them as such. For example, you might go to the `#buy_something` intent, and find a user example that says, I want to buy a Coach bag. You can label `Coach bag` as a mention of the `@product` entity.

For training purposes, the term you annotated, `Coach bag`, is added as a value of the `@product` entity.

At run time, your assistant evaluates terms based on the context in which they are used in the sentence only. If the structure of a user request that mentions the term matches the structure of an intent user example in which a mention is labeled, then your assistant interprets the term to be a mention of that entity type. For example, the user input might include the utterance, I want to buy a Gucci bag. Due to the similarity of the structure of this sentence to the user example that you annotated (I want to buy a Coach bag), your assistant recognizes `Gucci bag` as a `@product` entity mention.

When a contextual entity model is used for an entity, your assistant does *not* look for exact text or pattern matches for the entity in the user input but focuses instead on the context of the sentence in which the entity is mentioned.

If you choose to define entity values by using annotations, add at least 10 annotations per entity to give the contextual entity model enough data to be reliable.

## Dialogs

The **dialog** uses the intents that are identified in the user's input, plus context from the application, to interact with the user and ultimately provide a useful response. It defines the flow of your conversation in the form of a logic tree. It matches intents (what users say) to responses (what your virtual assistant says back). Each node of the tree has a condition that triggers it, based on user input.

The response might be the answer to a question such as `Where can I get some gas?` or the execution of a command, such as turning on the radio. The intent and entity might be enough information to identify the correct response, or the dialog might ask the user for more input that is needed to respond correctly. For example, if a user asks, `Where can I get some food?` you might want to clarify whether they want a restaurant or a grocery store, to dine in or take out, and so on. You can ask for more details in a text response and create one or more child nodes to process the new input.

## Exercise 3: Create a Watson Assistant Skill

Watson assistant receives user input and routes it to the appropriate skill. Two types of skills can be created in the assistant.

- The **dialog skill** interprets the user input and directs the flow of the conversation. The dialog gathers any information it needs to respond or perform a transaction on the user's behalf. This skill understands typical questions or requests from users and answers or fulfills them by following a dialog that is scripted by you.
- The **search skill** routes complex customer queries to Watson Discovery that are not handled by the dialog skill. Watson Discovery treats the user input as a search query. It finds information relevant to the query from the configured data sources, extracts the passage, and returns it so the assistant can share the information with the user as its response.

In this Exercise we will create a dialog skill. A search skill will be created in a later exercise.

### 1. Click **Add dialog skill**

← Assistants

## COVID-19 Crisis Communication

**Actions** Beta

**Build conversations easier than ever**

- Have an assistant ready to chat in less time, with less effort
- Compose step-by-step flows for any range of simple or complex conversations
- Focus more on your customer's goals and experience
- Collaborate and work more intuitively, made so that anybody can build

[Learn more](#)

[Add an actions skill](#)

**Dialog**

**Our full-feature conversation builder**

Dialog offers all the smarts, power, and flexibility you've come to trust. Select to keep building with the tools you know and love. [Learn more](#)

[Add dialog skill](#)

**Search** Plus


**Turn any content into answers**

- Create Q&A experiences in minutes
- Sync with websites and data sources for always up-to-date answers
- Handle even complex questions with inclusive, contextual responses

[Watch a brief demonstration](#) ©


[Add search skill](#)

2. Click **Upload skill**.




The screenshot shows the 'Add dialog skill' page. At the top, it says 'Add an existing skill, or create a new dialog skill to add to your assistant.' Below this are four tabs: 'Add existing skill', 'Create skill', 'Use sample skill', and 'Upload skill'. The 'Upload skill' tab is highlighted with a red oval. Below the tabs, it says 'Select the JSON file for the dialog skill with the data you want to upload.' There is a dashed box containing the text 'Drag and drop file here or click to select a file'. At the bottom left is an 'Upload' button.

3. Click on **Choose JSON File**.




This screenshot shows the same 'Add dialog skill' page as before, but within a browser window. The 'Upload skill' tab is highlighted with a blue border. The dashed box containing the text 'Drag and drop file here or click to select a file' is highlighted with a red oval. The browser's address bar shows the URL 'us-south.assistant.watson.cloud.ibm.com/cm/v1:bluemix:public:conversation:us-south:a%2F16a7ef31d76f44a7bf5a02bfa988f359:1f589565-d33e-4d8...'. The taskbar at the bottom shows several open applications, including 'NLP Intro - Watso...', 'IIT VoiceTech - AI...', and 'Compute Vulner...ipynb'.

4. Navigate to the directory where you stored the JSON file, click on the file, and click



5. Click **Upload**.



6. The file was successfully imported, and the CDC COVID FAQ skill was added. You can see there are 52 **Intents**, 7 **Entities**, and 73 **Dialog nodes**. Click on the **CDC COVID FAQ Skill**.

**Dialog**

**CDC COVID FAQ**

**LANGUAGE:** English (US)    **TRAINED DATA:** 52 Intents | 7 Entities | 73 Dialog nodes    **VERSION:** draft    **DESCRIPTION:** ---    **VERSION CREATED:** Nov 8, 2020 12:43 PM EST

**LINKED ASSISTANTS (1):** COVID-19 Crisis Communication

7. You can browse through the Intents. Click on one of them and view the examples provided to train the intent. #AttendingFuneral was selected in the figure below.

**CDC COVID FAQ** Version: Development

Intents

Intents (41) ↑	Description	Modified ↑	Conflicts ↑	Examples ↑
<input type="checkbox"/> #AnimalContact	Human - Animal interaction guidance	7 hours ago		7
<input type="checkbox"/> <b>#AttendingFuneral</b>	Funeral attendance guidance	7 hours ago		5
<input type="checkbox"/> #CDC_Response	Info about the CDC	7 hours ago		5
<input type="checkbox"/> #ChildrenAndFaceMasks	Guidance regarding Children wearing Facemas...	7 hours ago		5
<input type="checkbox"/> #ChildrenSocializing	Child Socialization guidance	7 hours ago		6
<input type="checkbox"/> #CommunitySpread	Defining Community Spread	7 hours ago		7

Showing 1–41 of 41 intents

8. Scroll down to view the examples.

**#AttendingFuneral** Last updated: 7 hours ago

User example  
Add unique examples of what the user might say. (Pro tip: Add at least 5 unique examples to help Watson understand)

Type a user example here, e.g. I want to pay my credit card bill

Add example Show recommendations


Annotate entities What's this?

User examples (5) ↑	Added ↑	Conflicts (0) ↑
<input type="checkbox"/> Am I at risk if I go to a funeral or visitation service for someone who died of COVID-19?	7 hours ago	
<input type="checkbox"/> Are funerals safe?	7 hours ago	
<input type="checkbox"/> Can I go to a funeral of someone who died of Corona Virus (COVID-19)?	7 hours ago	

Showing 1–5 of 5 examples

Sys-person and sys-location are deprecated. Update your dialog before they are removed. Act now

9. Click on the back arrow icon  to return to the **Intents** page.



#AttendingFuneral

Last updated: 7 hours ago

Try it

User example


Add unique examples of what the user might say. (Pro tip: Add at least 5 unique examples to help Watson understand)

Type a user example here, e.g. I want to pay my credit card bill

Add example Show recommendations

Annotate entities What's this?

10. Click on **Entities**.



CDC COVID FAQ Version: Development

Intents

Entities

Dialog

Options

Analytics

Intents (52) ↑

Description

Modified ↑↓


Confli

#AdditionalWorkplaceHygiene

Answer what to do and provide to decrea...

an hour ago

11. Six (6) entities are shown. Note, there is also 1 system entity enabled in the **System entities** tab. That adds up to the 7 total entities documented above. The entities all use the Dictionary-based evaluation method. Four entities (shown in Maroon) use dictionaries, 1 entity (shown in Blue) uses a regular expression, and 1 entity (shown in Green) uses a system entity and regular expression.



CDC COVID FAQ Version: Development

Save new version Try it

Intents

Entities

My entities

System entities

Dialog

Options

Analytics

Versions

Content Catalog

Entity (6) ↑

Values

Modified ↑↓

Create entity +

@coronavirus

coronavirus

7 hours ago

@landmark

empire state building, times square, grand central

7 hours ago

@phone

US Phone pattern

7 hours ago

@reply

no, yes

7 hours ago

@school\_type

high school, grade school, middle school, college, preschool

7 hours ago

@zip\_code


@sys-number

7 hours ago


Showing 1–6 of 6 entities


1 1 of 1 pages

12. Click on the Dialog option.




13. Browse through the dialog nodes to get a feel for the navigation logic.



14. Click on the Assistant icon  to return to the All Assistants page.




15. Click on COVID-19 Crisis Communication




16. Click on **Preview** link.






17. Type in “What is COVID-19” and then click on the right arrow icon. Type in “What are the symptoms and then click on the right arrow icon. You should see the responses shown in the figure below.



18. Click on the close icon (x) to close the **Preview** page.



## Exercise 4: Add a Search Skill

The data that is currently driving the chatbot is static data. You can connect your Watson Assistant chatbot to data sources to query dynamic data. Our crisis communication chatbot uses two different data sources.


- [Watson Discovery](#)
- [COVID-19 API](#)

This section will connect the Watson Assistant to a Watson Discovery collection by creating a **search skill**.


1. This lab is designed to be able to standalone. So, the assumption here is that a Discovery service needs to be created. If one already exists, please skip to step 7. Otherwise, click on the Watson Service browser tab.




2. Click on **Catalog**.




3. Enter discovery in the search box and click the <Enter> key.



4. Click **Discovery**.




5. Click **Create** to create the Discovery instance. **MAKE SURE TO CHANGE THE DISCOVERY INSTANCE TO BE THE SAME REGION AS THE WATSON ASSISTANT INSTANCE.**




- The service may take some time to create. The **Resource** list page is displayed with the Discovery service showing a status of Provision in progress. Wait until the status is **Active**, and then skip to step 9.



- If you already have an existing Watson Discovery service, click on the **IBM Watson Services** browser tab.




- Click on **Resources list**.




9. Click on the Discovery service.

Services (5)						
Discovery-33	Default	Dallas	Discovery	Active	—	
KnowledgeCatalog	Default	Dallas	Knowledge Catalog	Active	—	
Watson Assistant-qb	Default	Dallas	Watson Assistant	Active	—	
WatsonMachineLearning	Default	Dallas	Machine Learning	Active	—	
WatsonStudio	Default	Dallas	Watson Studio	Active	—	

10. Click **Launch Watson Discovery**.




11. Click **Create COVID-19 Kit**. This pre-built collection will jump-start your ability to answer people's COVID-19 questions. This collection uses trusted sources to automatically extract timely information related to COVID-19. You can customize for your users by adding your own URLs to pull answers.




12. Click **Create**.

The screenshot shows a modal dialog titled 'Name your new collection'. It has a close button (X) in the top right corner. The 'Collection name' field contains the text 'COVID-19 English (Global) 11-08-2020 9:25:48 PM'. Below this, the 'Select the language and region of your collection' dropdown menu is set to 'English (Global)'. The dialog provides information about the COVID-19 kit, stating it uses trusted sources to extract timely information. It also mentions customizing for users by adding URLs and integrating with Watson Assistant's Search Skill. At the bottom, there are two buttons: 'Cancel' and 'Create'. The 'Create' button is highlighted with a red circle.

13. Wait until the collection processing is completed.



14. Click on **Sync Settings**.



15. The sites indexed for this collection are listed. Several Harvard health sites are listed. Sites can be added (such as from the CDC)

COVID-19 English (Global) 11-09-2020 8:46:15 AM [🔗](#)













**Overview**   **Errors and warnings (0)**   **Sync settings**   **Search settings**

---

**Enter the URLs that you would like to sync**


URL to start at (e.g. <http://domain.com> or <http://domain.com/path/sub-path>)

Enter URL Add

<a href="https://www.who.int/news-room/q-a-detail/q-a-coronaviruses">https://www.who.int/news-room/q-a-detail/q-a-coronaviruses</a>	 
<a href="https://www.health.harvard.edu/diseases-and-conditions/treatments-for-covid-19">https://www.health.harvard.edu/diseases-and-conditions/treatments-for-covid-19</a>	 
<a href="https://www.health.harvard.edu/diseases-and-conditions/if-you-are-at-higher-risk">https://www.health.harvard.edu/diseases-and-conditions/if-you-are-at-higher-risk</a>	 
<a href="https://www.health.harvard.edu/diseases-and-conditions/if-youve-been-exposed-to-the-coronavirus">https://www.health.harvard.edu/diseases-and-conditions/if-youve-been-exposed-to-the-coronavirus</a>	 
<a href="https://www.health.harvard.edu/diseases-and-conditions/coronavirus-outbreak-and-kids">https://www.health.harvard.edu/diseases-and-conditions/coronavirus-outbreak-and-kids</a>	 
<a href="https://www.health.harvard.edu/diseases-and-conditions/coronavirus-resource-center">https://www.health.harvard.edu/diseases-and-conditions/coronavirus-resource-center</a>	 

16. The different sites that were indexed for this collection are listed in the Sync settings. We can see that a few different Harvard health sites are here, but let's say we want our Discovery instance to also pull information from other sources. We just need to copy the URL to the web page from which we want to pull information and add it to this list.

17. Click on the Watson Assistant browser tab.



IBM Watson Assistant

Adding a skill to

Solution-Starte

Build an AI Perso

IBM Asset Factory Ad

IBM Watson Servi

Coronavirus Disc

IBM Watson Assistant

ry.watson.cloud.ibm.com/regions/us-south/services/crn%3Av1%3Abluemix%3Apublic%3Adiscovery%3Aus-south%3

IBM Watson Discovery

Cookie Preferences

Instance:

COVID-19 English (Global) 11-09-2020 8:46:15 AM [🔗](#)

**Overview**   **Errors and warnings (0)**   **Sync settings**   **Search settings**

75 documents

0 documents failed [View details](#)

Sync complete

Next sync scheduled for 11/10/2020 2:46:00 am EST [View sync settings](#)

18. Click on **Add Search Skill**.



← Assistants

## COVID-19 Crisis Communication

### Actions Beta

#### Build conversations easier than ever

- Have an assistant ready to chat in less time, with less effort
- Compose step-by-step flows for any range of simple or complex conversations
- Focus more on your customer's goals and experience
- Collaborate and work more intuitively, made so that anybody can build

[Learn more](#)

Add an actions skill

### Dialog

#### CDC COVID FAQ

<b>LANGUAGE:</b> English (US)	<b>TRAINED DATA:</b> 52 Intents   7 Entities   73 Dialog nodes	<b>VERSION:</b> draft	<b>DESCRIPTION:</b> ---	<b>VERSION CREATED:</b> Nov 8, 2020 12:43 PM EST
----------------------------------	---	--------------------------	----------------------------	---

LINKED ASSISTANTS (1): COVID-19 Crisis Communication

### Search Plus

#### Turn any content into answers

- Create Q&A experiences in minutes
- Sync with websites and data sources for always up-to-date answers
- Handle even complex questions with inclusive, contextual responses

Add search skill

19. Enter **COVID19 Discovery** for the **Name**.

## Add search skill

Skills can be combined to improve your assistant's capabilities.

**Create skill**

Name

COVID19 Discovery

Name your skill; for example, Account application or Personal banking.

Description (optional)

Add a description for this skill

Continue

20. Watson Assistant will pre-fill the associated Discovery instance. Click on the radio button next to **COVID19 English** and click **Next**.

[← Back](#)

### Search Skill/COVID19 Discovery

[Cancel](#) [Next](#)

Choose a discovery instance to connect to [?](#)

Watson Discovery-fg

Choose which collection you want to use [?](#) [Create new collection](#) [+](#)

Collection name
<input checked="" type="radio"/> COVID-19 English (Global) 05-05-2021 6:06:54 PM <a href="#">?</a>

21. For the **Configure result content**, leave the mappings unchanged.

[← Back](#)

CancelCreate

## Search Skill/COVID19 Discovery

### Configure result content

Map your data schema from Discovery to the title, body, and URL fields below to define what results will be surfaced to end users in the card results.

Body

text | Example: Hydroxychloroquine is primarily used to treat malaria and several inflammatory diseases, including lupus and rhe...
x v

Title

title | Example: Is hydroxychloroquine safe and effective for treating COVID-19?
x v

URL

metadata.source.url | Example: https://www.health.harvard.edu/diseases-and-conditions/treatments-for-covid-19
x v

Preview▶

22. Scroll down. You have the option to (1) change the Message returned by the chat bot when searching the collection, (2) change the Message returned when no results are found, and (3) change the message returned when there is a connectivity issue. No changes are necessary.

[← Back](#)

CancelCreate

## Search Skill/COVID19 Discovery

### Configure result content

Map your data schema from Discovery to the title, body, and URL fields below to define what results will be surfaced to end users in the card results.

Body

text | Example: Hydroxychloroquine is primarily used to treat malaria and several inflammatory diseases, including lupus and rhe...
x v

Title

title | Example: Is hydroxychloroquine safe and effective for treating COVID-19?
x v

URL

metadata.source.url | Example: https://www.health.harvard.edu/diseases-and-conditions/treatments-for-covid-19
x v

Preview▶

23. Click on **Preview** to try out the search interface.

[← Back](#)

CancelCreate

## Search Skill/COVID19 Discovery

### Configure result content

Map your data schema from Discovery to the title, body, and URL fields below to define what results will be surfaced to end users in the card results.

Body

text | Example: Hydroxychloroquine is primarily used to treat malaria and several inflammatory diseases, including lupus and rhe...
x v

Title


title | Example: Is hydroxychloroquine safe and effective for treating COVID-19?
x v

URL


metadata.source.url | Example: https://www.health.harvard.edu/diseases-and-conditions/treatments-for-covid-19
x v

Preview▶


24. Enter **What are the tests for COVID-19?** and press the <Enter> key.




25. The response is shown below.



26. Click the minimize icon (-) to remove the Preview panel.



27. Click **Create** to create the search skill.




## Exercise 5: Create Cloud Functions

IBM Cloud Functions are a Functions-as-a-Service (FaaS) platform based on Apache OpenWhisk. You can run your application code without servers, scale it automatically, and pay nothing when not in use. We are going to create a Cloud Function that calls the Covid-19 API from Johns Hopkins to determine the total number of COVID-19 cases.

1. Click on the **Watson Service Page** browser tab.




2. Click on **Catalog**.




3. Type in **Functions** in the **Search** text box and press the <Enter> key.

# IBM Cloud products


Over 190+ products available for you to customize and build the solutions that you need for your business




4. Click on the **Functions** tile.




5. Click **Start Creating**.




6. You may get a pop-up to create a namespace. If so, click **Create Namespace**. Otherwise skip to step 9.




7. Click **Create**.



8. Click **Functions** and then **Start creating**.



9. Click **Action**.



10. Enter **COVID-19-News** for the **Action Name**, select **Node.js 10** for the **Runtime**, and click **Create**.



Functions / Create / Action

## Create Action

Actions contain your function code and are invoked by events or REST API calls.

Learn more about Actions

Learn more about Packages

Action Name

Enclosing Package  
 (Default Package) ▼ Create Package

Runtime  
 ▼

Looking for Java, .NET or Docker? [Docker](#) Actions can be created with the CLI

Previous Cancel Create

11. Copy and paste the code from [action/covid-webhook.js](#) and click **Save**.

Code Node.js 10 Edit mode - press ESC to exit Reset Save

```

1 - /**
2  *
3  * main() will be run when you invoke this action
4  *
5  * @param Cloud Functions actions accept a single parameter, which must be a JSON object.
6  *
7  * @return The output of this action, which must be a JSON object.
8  *
9  */
10 var request = require("request-promise");
11 const DiscoveryV1 = require("watson-developer-cloud/discovery/v1");
12
13 - function getRandomInt(max) {
14   return Math.floor(Math.random() * Math.floor(max));
15 }
16
17 - const statesMap = {
18   alaska: "99501:US",
19   alabama: "35801:US",
20   arkansas: "72201:US",
21   american_samoa: "96799:US",
22   arizona: "85001:US",
23   california: "90001:US",
24   colorado: "80201:US",
25   connecticut: "06101:US",
26   district_of_columbia: "20001:US",
27   delaware: "19901:US",
28   florida: "33124:US",
29   georgia: "30301:US",
30   guam: "GU:US",
31   hawaii: "96801:US",
32

```

12. The code will call the COVID-19 API on the [summary endpoint](#). It takes a type and a location parameter. Click on **Invoke with parameters**.

IBM Cloud Search resources and offerings... Catalog Docs

Functions / Actions / COVID-19-News

## COVID-19-News


Web Action

Code Node.js 10 Invoke with parameters Invoke


Parameters 1 / \*\*

13. Copy and paste the following into the **Action Input** field and then click **Apply**.


```
{"type":"api" , "location":"US"}
```



14. Click **Invoke**



15. Wait until the invoke completes to view the results.



**Activations**
Collapse
Clear

▼
✔
COVID-19-News
460 ms
11/10/2020, 19:59:38

**Activation ID:**  
5202ef9a78bb44c882ef9a78bb54c8e4

**Results:**  

```
{
  "result": "Total Cases: 10110552\nTotal Deaths: 238256\nTotal Recovered: 3928845\n\nSource: Johns Hopkins CSSE"
}
```

**Logs:**  

```
[]
```

16. Click on the **Endpoints** tab on the left.

IBM Cloud
Search resources and offerings...
Catalog
Docs
Support
Manage
Ulysses Doe's ...

Functions / Actions / COVID-19-New
COVID-19-New
Web Action
Namespace: wsuser44000@gmail.com\_dev(Dallas)

Code
Parameters
Runtime
**Endpoints**
Connected Triggers
Enclosing Sequences
Logs

Code
Node.js 10
Invoke with parameters
Invoke

```
1 /**
2  *
3  * main() will be run when you invoke this action
4  *
5  * @param Cloud Functions actions accept a single parameter, which must be a JSON object.
6  *
7  * @return The output of this action, which must be a JSON object.
8  *
9  */
10 var request = require("request-promise");
11 const DiscoveryV1 = require("watson-developer-cloud/discovery/v1");
12
13 = function getRandomInt(max) {
14   return Math.floor(Math.random() * Math.floor(max));
15 }
16
17 = const statesMap = {
18   alaska: "99501:US",
19   alabama: "35801:US",
20   arkansas: "72201:US",
21   american_samoa: "96799:US",
22   arizona: "85001:US",
23   california: "90001:US",
24   colorado: "80201:US",
25   connecticut: "06101:US",
26   district_of_columbia: "20001:US",
27   delaware: "19901:US",
28   florida: "33124:US",
29   georgia: "30301:US",
30   guam: "GU:US",
31   hawaii: "96801:US",
32 }
```

**Activations**
Collapse
Clear

▼
✔
COVID-19-New
1062 ms
6/7/2020, 14:29:02

**Activation ID:**  
612b3106f0694c4eab3106f0697c4e75


**Results:**  

```
{
  "result": "Total Cases: 10110552\nTotal Deaths: 238256\nTotal Recovered: 3928845\n\nSource: Johns Hopkins CSSE"
}
```

**Logs:**  

```
[]
```

17. Click on **Enable as a Web Action**, then click **Save**. Copy and paste the http url to a Notepad file. Add `.json?blocking=true` to the end of the url, as shown in blue below.




## Exercise 6: Integrate data sources via a Watson Assistant webhook.

A webhook is a mechanism that allows you to call out to an external program based on something happening in your Watson Assistant dialog skill. When used in a dialog skill, a webhook is triggered when the assistant processes a node that has a webhook enabled. The webhook collects data that you specify or that you collect from the user during the conversation and save in context variables. It sends the data as part of a HTTP POST request to the URL that you specify as part of your webhook definition. The URL that receives the webhook is the listener. It performs a predefined action using the information that you pass to it as specified in the webhook definition and can optionally return a response.


You can use a webhook to do the following types of things:

- Validate information that you collected from the user.
- Interact with an external web service to get information. For example, you might check on the expected arrival time for a flight from an air traffic service or get a forecast from a weather service.
- Send requests to an external application, such as a restaurant reservation site, to complete a simple transaction on the user's behalf.
- Trigger a SMS notification.
- Trigger a IBM Cloud™ Functions web action.


1. Click on **Watson Assistant**.




2. Click on the Skills icon




3. Click on the **CDC COVID FAQ** skill.




4. Click on **Options**.




5. Remove the text from the URL field. Then, copy and paste the Web Action url from the Notepad file into the **URL** field.




6. Click on **Dialog**.



7. Click on **Latest News on Covid19**




8. Add parameters **type** with value “**api**”, and **location** with value “**US**”, then click **Try It**.




9. Enter “What are the latest counts in the US” and then press <Enter>







10. The system responds with Irrelevant, meaning that it couldn't find an Intent. By hovering over the eye icon, you can see that #News\_Corona\_Virus intent had the highest confidence, but was below the cutoff threshold for relevance.



11. Click the down arrow icon next to Irrelevant and select the #New\_Corona\_Virus intent to train the assistant.




12. Wait until **Watson is Training** message disappears. Retype in the question, “What are the latest counts in the US” and press the <Enter> key. The system responds with the latest counts.




## Exercise 7: Extend to other locations

The implementation has currently hardcoded an intent to provide the latest COVID-19 counts for the US. In order to generalize this to other locations, we can create an entity (e.g @location) and provide a set of values and synonyms. We would then assign the @location value to a context variable (\$location) that would be used as the parameter to query the API.


1. Click [here](#) to download an entity import file that contains values for the US, Great Britain, France, Germany, and Brazil.
2. Right-click on **Raw**, then click on **Save link as ...**




3. Navigate to the location that you want to save the file then click **Save**.




4. Go back to the Watson Assistant, and click on **Entities**.




5. Click on the Upload icon 




## 6. Click on Drag and drop files here...




## 7. Navigate to where you saved the locations file, select the file, and click **Open**.



## 8. Click **Upload**.



9. Click **Done**.



10. Location values have been imported. Click on Dialog.

CDC COVID FAQ Version: Development Save new version

Intents

Entities

My entities

System entities

**Dialog**

Options

Analytics

Versions

Content Catalog

<input type="checkbox"/> Entity (7) ↑	Values	Modified ↑↓
<input type="checkbox"/> @coronavirus	coronavirus	3 days ago
<input type="checkbox"/> @landmark	times square, grand central, empire state building	3 days ago
<input type="checkbox"/> @location	FR, GB, US, BR, GE	a minute ago
<input type="checkbox"/> @phone	US Phone pattern	3 days ago
<input type="checkbox"/> @reply	no, yes	3 days ago
<input type="checkbox"/> @school_type	high school, preschool, college, grade school, middle school	3 days ago
<input type="checkbox"/> @zip_code	@sys-number	3 days ago

11. Click on Latest News


Latest News on Covid19  
#News\_Corona\_Virus

3 Responses / 0 Context Set / Does not return

12. Change the location value to @location.





If assistant recognizes

#News\_Corona\_Virus  +

---


Then callout to my webhook [Learn more](#)

**Parameters**

Key	Value	
type	"api"	
location	"@location"	

[Add parameter +](#)

13. Click **Try it**



The screenshot shows the IBM Watson Assistant interface. On the left, a sidebar lists navigation options: Intents, Entities, Dialog, Options, Analytics, Versions, and Content Catalog. The 'Dialog' section is selected, showing a list of nodes: '#Set confidence thresholds', 'Greetings', 'Goodbye', and 'api'. The 'api' node is highlighted. On the right, a preview of the assistant's response is shown. It includes a search bar with 'Latest News on Covid19', a 'Try it' button (circled in red), and a 'Customize' gear icon. Below this, the 'If assistant recognizes' section shows '#News\_Corona\_Virus' as a recognized intent. The 'Then callout to my webhook' section shows a table of parameters: 'type' with value 'api' and 'location' with value '@location'.


14. Wait until the “Watson is Training Message” disappears, and then type in “What is the latest count in Brazil” and hit the <Enter> key.

Hello, I'm the COVID Crisis Communication Bot  
ready to answer your questions about  
COVID-19. How can I help you?



What is the latest count for Brazil|

15. The assistant provides the results for Brazil.



## You have completed the Lab!

- ✓ Provisioned an instance of Watson Assistant
- ✓ Added a dialog skill to your Watson Assistant instance
- ✓ Connected your Watson Assistant with Watson Discovery
- ✓ Created Cloud Functions
- ✓ Integrated data sources via a Watson Assistant webhook

