Lattice — Feature Showcase

> **Open this file with Lattice** to see every feature rendered live.
> Switch between **Edit**, **Preview**, and **Dual** view with the toolbar selector.
> Try `Ctrl/Cmd+Shift+T` to auto-generate the Table of Contents below.

Table of Contents

- Table of Contents
- Text Formatting
- Highlight Marks
- Lists
  - Unordered
  - Ordered
  - Definition-style (using bold + indent)
- Task Lists (GFM)
- Tables
- Code
  - Inline code
  - Fenced code blocks
- Blockquotes
  - GitHub-style Alerts (rendered by GitHub and Lattice)
- Mathematics — KaTeX
  - Inline math
  - Display math — Calculus
  - Display math — Linear Algebra
  - Display math — Series & Limits
- Mermaid Diagrams
  - Flowchart — Lattice Edit Cycle
  - Sequence Diagram — File Open Flow
  - Class Diagram — Core Data Model
  - Pie Chart — Supported Platforms
- Images
- Links
- HTML in Markdown
- Keyboard Shortcuts Reference

Text Formatting

Normal paragraph text flows here. Lattice renders Markdown as **close to GitHub** as possible, so files look identical whether viewed in the editor preview, on GitHub, or printed.

Style	Syntax	Result
Bold	`**bold**`	**bold**
Italic	`*italic*`	*italic*
Bold + italic	`***both***`	***both***
Strikethrough	`~~strikethrough~~`	~~strikethrough~~
Inline code	`` `code` ``	`code`
Superscript	`X<sup>2</sup>`	X^2
Subscript	`H<sub>2</sub>O`	H$_2$O

> **Note — sub/superscript:** CommonMark/GFM has no native sub/superscript syntax. Lattice renders `<sup>` and `<sub>` HTML tags directly (GitHub and Obsidian do too). We recommend, though that you use alternatives that work everywhere: KaTeX math (`$X^2$` → X^2, `$H_2O$` → H_2O) or Unicode characters (`X²` , `H₂O`). The linter flags these tags as a portability hint — they may not render in all renderers.

Highlight Marks

Highlight marks are a Lattice-exclusive feature. Wrap any text in `==double equals==` to render it with a bright amber background.

This works in **any context** — inside a sentence, ==across *italic* and **bold** spans==, or on its own line:

This entire sentence is highlighted.

> [!NOTE] Highlight marks are **not** rendered inside code blocks or inline code — `==this stays raw==` .

Lists

Unordered

- First item
- Second item
  - Nested item A
  - Nested item B
    - Deeply nested
- Third item with **bold** and *italic* text

Ordered

1. Install Lattice from the releases page
2. Open any `.md` file — double-click or via **File** → **Open**
3. Choose your view:
   i. **Edit** — raw CodeMirror editor only
   ii. **Preview** — rendered HTML only
   iii. **Dual** — side-by-side (four layout variants)
4. Print with `Ctrl/Cmd+P` — always renders to a clean light theme

Definition-style (using bold + indent)

Local-first All files stay on your machine. No cloud sync required.

Documents as Code Plain-text `.md` files are diff-friendly, version-controlled, and AI-ready.

Task Lists (GFM)

GitHub Flavored Markdown task lists render as interactive checkboxes in Lattice.

- [x] Install Lattice
- [x] Open the demo file
- [x] Explore Edit / Preview / Dual views
- [ ] Try `Ctrl/Cmd+Shift+T` to regenerate the Table of Contents
- [ ] Try `Ctrl/Cmd+Shift+L` to auto-align a pipe table
- [ ] Paste a screenshot with `Ctrl/Cmd+V` — it auto-saves to a sibling folder
- [x] Open a second file in a new window (multi-window support)
- [ ] Try printing to PDF with `Ctrl/Cmd+P`

Tables

Lattice supports **GFM pipe tables** with left, center, and right alignment. Press `Ctrl/Cmd+Shift+L` with the cursor anywhere in the table to auto-format it.

Feature	Edit View	Preview View	Dual View
CodeMirror editor	✓	—	✓
Live rendered preview	—	✓	✓
Scroll sync	—	—	✓
Print (Ctrl+P)	✓	✓	✓
Highlight marks	✓	✓	✓
Mermaid diagrams	—	✓	✓
KaTeX mathematics	—	✓	✓

Code

Inline code

Use backticks for `inline code`. Great for `file/paths`, `commands`, and `variable_names`.

Fenced code blocks

Lattice passes code fences to the preview unchanged — syntax highlighting is provided by the renderer.

```
// Lattice highlight-mark plugin — converts ==text== to <mark> elements
export const MARK_RE = /==((?:[^=\n]|=(?!=))+?)==/g;

export function splitAtMarks(text: string): HastNode[] {
  const parts: HastNode[] = [];
  let lastIndex = 0;
  MARK_RE.lastIndex = 0;
  let match: RegExpExecArray | null;
  while ((match = MARK_RE.exec(text)) !== null) {
    if (match.index > lastIndex)
      parts.push({ type: 'text', value: text.slice(lastIndex, match.index) });
    parts.push({
      type: 'element', tagName: 'mark',
      properties: {},
      children: [{ type: 'text', value: match[1] }],
    });
    lastIndex = match.index + match[0].length;
```

```
  }
  if (lastIndex < text.length)
    parts.push({ type: 'text', value: text.slice(lastIndex) });
  return parts;
}
```

```
// Tauri command — read file with conflict detection
#[tauri::command]
pub async fn read_file(path: String) -> Result<FileReadResult, String> {
    let content = fs::read_to_string(&path)
        .map_err(|e| format!("Cannot read {path}: {e}"))?;
    let hash = compute_sha256(&content);
    Ok(FileReadResult { content, hash })
}
```

```
# Build a production release
export LATTICEBUILD_NO="MyBuild-001"
npm run tauri build
```

Blockquotes

> **Single-level blockquote.** Great for callouts, citations, or side notes.

> Nested blockquotes are also supported:
>
> > Inner quote — "*Documents as code, not documents as data.*"
> >
> > — Lattice design philosophy

GitHub-style Alerts (rendered by GitHub and Lattice)

> [!NOTE] Useful information that users should know, even when skimming.

> [!TIP] Optional advice for a better experience.

> [!IMPORTANT] Key information users need to know to achieve their goal.

> [!WARNING] Urgent information that needs immediate attention.

> [!CAUTION] Advises about risks or negative outcomes.

Mathematics — KaTeX

Lattice renders mathematics via **KaTeX**. Use `$...$` for inline and `$$...$$` for display math.

Inline math

Einstein's famous equation $E = mc^2$ and the quadratic formula $x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$ render inline.

The Euler identity $e^{i\pi} + 1 = 0$ is often called the most beautiful equation in mathematics.

Display math — Calculus

$$\int_{-\infty}^{\infty} e^{-x^2}\,dx = \sqrt{\pi}$$

$$\frac{d}{dx}\left[\int_{a}^{g(x)} f(t)\,dt\right] = f(g(x)) \cdot g'(x)$$

Display math — Linear Algebra

$$\mathbf{A}\mathbf{x} = \lambda\mathbf{x} \quad \Longrightarrow \quad \det(\mathbf{A} - \lambda\mathbf{I}) = 0$$

$$\begin{pmatrix} a & b \\ c & d \end{pmatrix}^{-1} = \frac{1}{ad - bc}\begin{pmatrix} d & -b \\ -c & a \end{pmatrix}$$

Display math — Series & Limits


$$e^x = \sum_{n=0}^{\infty} \frac{x^n}{n!} = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \cdots$$

$$\lim_{n \to \infty} \left(1 + \frac{1}{n}\right)^n = e$$


Mermaid Diagrams

Lattice renders ```` ```mermaid ``` ```` fenced blocks inline in the preview.


Flowchart — Lattice Edit Cycle




Sequence Diagram — File Open Flow



Class Diagram — Core Data Model



Pie Chart — Supported Platforms




Images

Paste images directly into Lattice with `Ctrl/Cmd+V`.
The image file is automatically saved to a sibling folder named after the current document, and a Markdown reference is inserted at the cursor position:


```
![Image](demo_assets/img_1780574419628.png)

![Image](demo_assets/img_1780575215039.png)
```

Here is how it renders in `Dual (edit on the left)` mode:



Here is how it renders in `Dual (edit on the bottom)` mode:




```
---

## Mathematics — KaTeX

Lattice renders mathematics via **KaTeX**. Use `$...$` for inline and `$$...$$` for display math.

### Inline math

Einstein's famous equation $E = mc^2$ and the quadratic formula
$x = \dfrac{-b \pm \sqrt{b^2 - 4ac}}{2a}$ render inline.

The Euler identity $e^{i\pi} + 1 = 0$ is often called the most beautiful equation in mathematics.

### Display math — Calculus

$$
\int_{-\infty}^{\infty} e^{-x^2}\, dx = \sqrt{\pi}
$$

$$
\frac{d}{dx}\left[\int_a^{g(x)} f(t)\, dt\right] = f\!\left(g(x)\right) \cdot g'(x)
$$

### Display math — Linear Algebra

$$
\mathbf{A}\mathbf{x} = \lambda\mathbf{x}
\quad\Longrightarrow\quad
\det(\mathbf{A} - \lambda\mathbf{I}) = 0
$$
```

> **Tip:** The assets folder name is derived from the document filename, keeping related files grouped together and easy to version-control.

Links

- Lattice on GitHub — source code and issue tracker
- Releases Page — download installers
- Release Site — GitHub Pages release portal
- Relative link: System Architecture Demo
- Relative link: Physics Equations Demo

Auto-link: https://github.com/blessia-blessini/lattice

HTML in Markdown

Lattice renders a **safe whitelist** of inline HTML tags and passes everything else through as literal text. The linter flags all inline HTML — whitelisted tags get a **hint** (portability risk), non-whitelisted tags get a **warning** (not rendered here).

HTML element	Lattice preview	GitHub	Portable alternative
`<sup>`	✅ rendered	✅	KaTeX: `$X^2$` → X^2 · Unicode: `X²`
`<sub>`	✅ rendered	✅	KaTeX: `$H_2O$` → H_2O · Unicode: `H₂O`
`<kbd>`	✅ rendered	✅	Inline code: `` `Ctrl+S` ``
` `	✅ rendered	✅	Two trailing spaces or blank line
`<mark>`	⚠️ plain text	✅	`==highlight==` (Lattice-native)
`<details>`	⚠️ plain text	✅	Headings + TOC (no universal equivalent)
Other HTML	⚠️ plain text	varies	Markdown equivalent (case-by-case)

Live examples of the whitelisted tags:

- Superscript: X^2 + Y^3
- Subscript: H_2O and CO_2
- Keyboard: press <kbd>Ctrl</kbd>+<kbd>S</kbd> to save

Keyboard Shortcuts Reference

Action	Windows / Linux	macOS
Save	`Ctrl+S`	`Cmd+S`
Open file	`Ctrl+O`	`Cmd+O`
New window	`Ctrl+N`	`Cmd+N`
Generate / refresh TOC	`Ctrl+Shift+T`	`Cmd+Shift+T`
Auto-align table	`Ctrl+Shift+L`	`Cmd+Shift+L`
Paste image from clipboard	`Ctrl+V`	`Cmd+V`
Print / Save as PDF	`Ctrl+P`	`Cmd+P`
Increase font size	`Ctrl++`	`Cmd++`
Decrease font size	`Ctrl+-`	`Cmd+-`