

Lattice — Feature Showcase

Open this file with Lattice to see every feature rendered live.

Switch between **Edit**, **Preview**, and **Dual** view with the toolbar selector.

Try `Ctrl/Cmd+Shift+T` to auto-generate the Table of Contents below.

Table of Contents

- [Table of Contents](#)
- [Text Formatting](#)
- [Highlight Marks](#)
- [Lists](#)
 - [Unordered](#)
 - [Ordered](#)
 - [Definition-style \(using bold + indent\)](#)
- [Task Lists \(GFM\)](#)
- [Tables](#)
- [Code](#)
 - [Inline code](#)
 - [Fenced code blocks](#)
- [Blockquotes](#)
 - [GitHub-style Alerts \(rendered by GitHub and Lattice\)](#)
- [Mathematics — KaTeX](#)
 - [Inline math](#)
 - [Display math — Calculus](#)
 - [Display math — Linear Algebra](#)
 - [Display math — Series & Limits](#)
- [Mermaid Diagrams](#)
 - [Flowchart — Lattice Edit Cycle](#)
 - [Sequence Diagram — File Open Flow](#)
 - [Class Diagram — Core Data Model](#)
 - [Pie Chart — Supported Platforms](#)
- [Images](#)
- [Links](#)
- [HTML in Markdown](#)
- [Keyboard Shortcuts Reference](#)

Text Formatting

Normal paragraph text flows here. Lattice renders Markdown as **close to GitHub** as possible, so files look identical whether viewed in the editor preview, on GitHub, or printed.

Style	Syntax	Result
Bold	**bold**	bold
Italic	<i>*italic*</i>	<i>italic</i>
Bold + italic	***both***	<i>both</i>
Strikethrough	~~strikethrough~~	strikethrough
Inline code	<code>`code`</code>	code
Superscript	X²	X ²
Subscript	H₂O	H ₂ O

Note — sub/superscript: CommonMark/GFM has no native sub/superscript syntax. Lattice renders `<sup>` and `<sub>` HTML tags directly (GitHub and Obsidian do too). We recommend, though that you use alternatives that work everywhere: KaTeX math (`$x^2$` → X^2 , `$H_{20}$` → H_2O) or Unicode characters (`x²` , `H₂O`). The linter flags these tags as a portability hint — they may not render in all renderers.

Highlight Marks

Highlight marks are a Lattice-exclusive feature. Wrap any text in `==double equals==` to render it with a **bright amber background**.

This works in **any context** — inside a sentence, `==across italic and bold spans==`, or on its own line:

This entire sentence is highlighted.

[!NOTE] Highlight marks are **not** rendered inside code blocks or inline code — `==this stays raw==` .

Lists

Unordered

- First item
- Second item
 - Nested item A
 - Nested item B
 - Deeply nested
- Third item with **bold** and *italic* text

Ordered

1. Install Lattice from the [releases page](#)
2. Open any `.md` file — double-click or via **File** → **Open**
3. Choose your view:
 - i. **Edit** — raw CodeMirror editor only
 - ii. **Preview** — rendered HTML only
 - iii. **Dual** — side-by-side (four layout variants)
4. Print with `Ctrl/Cmd+P` — always renders to a clean light theme

Definition-style (using bold + indent)

Local-first All files stay on your machine. No cloud sync required.

Documents as Code Plain-text `.md` files are diff-friendly, version-controlled, and AI-ready.

Task Lists (GFM)

GitHub Flavored Markdown task lists render as interactive checkboxes in Lattice.

- ☒ Install Lattice
- ☒ Open the demo file
- ☒ Explore Edit / Preview / Dual views
- ☐ Try `Ctrl/Cmd+Shift+T` to regenerate the Table of Contents
- ☐ Try `Ctrl/Cmd+Shift+L` to auto-align a pipe table
- ☐ Paste a screenshot with `Ctrl/Cmd+V` — it auto-saves to a sibling folder
- ☒ Open a second file in a new window (multi-window support)
- ☐ Try printing to PDF with `Ctrl/Cmd+P`

Tables

Lattice supports **GFM pipe tables** with left, center, and right alignment. Press `Ctrl/Cmd+Shift+L` with the cursor anywhere in the table to auto-format it.

Feature	Edit View	Preview View	Dual View
CodeMirror editor	✓	—	✓
Live rendered preview	—	✓	✓
Scroll sync	—	—	✓
Print (Ctrl+P)	✓	✓	✓
Highlight marks	✓	✓	✓
Mermaid diagrams	—	✓	✓
KaTeX mathematics	—	✓	✓

Code

Inline code

Use backticks for inline code. Great for file/paths, commands, and variable_names.

Fenced code blocks

Lattice passes code fences to the preview unchanged — syntax highlighting is provided by the renderer.

```
// Lattice highlight-mark plugin – converts ==text== to <mark> elements
export const MARK_RE = /==(?:[^\n]|(?:!))+?)==/g;

export function splitAtMarks(text: string): HastNode[] {
  const parts: HastNode[] = [];
  let lastIndex = 0;
  MARK_RE.lastIndex = 0;
  let match: RegExpExecArray | null;
  while ((match = MARK_RE.exec(text)) !== null) {
    if (match.index > lastIndex)
      parts.push({ type: 'text', value: text.slice(lastIndex, match.index) });
    parts.push({
      type: 'element', tagName: 'mark',
      properties: {},
      children: [{ type: 'text', value: match[1] }],
    });
    lastIndex = match.index + match[0].length;
  }
}
```

```

    }
    if (lastIndex < text.length)
      parts.push({ type: 'text', value: text.slice(lastIndex) });
    return parts;
  }

// Tauri command – read file with conflict detection
#[tauri::command]
pub async fn read_file(path: String) -> Result<FileReadResult, String> {
  let content = fs::read_to_string(&path)
    .map_err(|e| format!("Cannot read {path}: {e}"))?;
  let hash = compute_sha256(&content);
  Ok(FileReadResult { content, hash })
}

# Build a production release
export LATTICEBUILD_NO="MyBuild-001"
npm run tauri build

```

Blockquotes

Single-level blockquote. Great for callouts, citations, or side notes.

Nested blockquotes are also supported:

Inner quote — *"Documents as code, not documents as data."*

— Lattice design philosophy

GitHub-style Alerts (rendered by GitHub and Lattice)

[!NOTE] Useful information that users should know, even when skimming.

[!TIP] Optional advice for a better experience.

[!IMPORTANT] Key information users need to know to achieve their goal.

[!WARNING] Urgent information that needs immediate attention.

[!CAUTION] Advises about risks or negative outcomes.

Mathematics — KaTeX

Lattice renders mathematics via **KaTeX**. Use $\dots$ for inline and $\displaystyle \dots$ for display math.

Inline math

Einstein's famous equation $E = mc^2$ and the quadratic formula $x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$ render inline.

The Euler identity $e^{i\pi} + 1 = 0$ is often called the most beautiful equation in mathematics.

Display math — Calculus

$$\int_{-\infty}^{\infty} e^{-x^2} dx = \sqrt{\pi}$$

$$\frac{d}{dx} \left[\int_a^{g(x)} f(t) dt \right] = f(g(x)) \cdot g'(x)$$

Display math — Linear Algebra

$$\mathbf{Ax} = \lambda \mathbf{x} \implies \det(\mathbf{A} - \lambda \mathbf{I}) = 0$$

$$\begin{pmatrix} a & b \\ c & d \end{pmatrix}^{-1} = \frac{1}{ad - bc} \begin{pmatrix} d & -b \\ -c & a \end{pmatrix}$$

Display math — Series & Limits


$$e^x = \sum_{n=0}^{\infty} \frac{x^n}{n!} = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \dots$$

$$\lim_{n \rightarrow \infty} \left(1 + \frac{1}{n} \right)^n = e$$


Mermaid Diagrams

Lattice renders ````mermaid```` fenced blocks inline in the preview.


Flowchart — Lattice Edit Cycle



Sequence Diagram — File Open Flow




Class Diagram — Core Data Model



Pie Chart — Supported Platforms

Lattice Platform Coverage



Images

Paste images directly into Lattice with `Ctrl/Cmd+V`.

The image file is automatically saved to a sibling folder named after the current document, and a Markdown reference is inserted at the cursor position:

```
![Image](demo_assets/img_1780574419628.png)
```

```
![Image](demo_assets/img_1780575215039.png)
```

Here is how it renders in `Dual (edit on the left)` mode:

demo.md - lattice (v0.2.39 - windows-desktop-2026W23.0EEC)

%USERPROFILE%_prj\lattice-ws\lattice\docs\demo\demo.md

207

Mathematics — KaTeX

208

209 Lattice renders mathematics via **KaTeX**. Use ``$...$`` for inline and ``$$...$$`` for display math.

210

211 ### Inline math

212

213 Einstein's famous equation $E = mc^2$ and the quadratic formula

214 $x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$ render inline.

215

216 The Euler identity $e^{i\pi} + 1 = 0$ is often called the most

217 beautiful equation in mathematics.

218

219 ### Display math — Calculus

220

221 $\int_{-\infty}^{\infty} e^{-x^2} dx = \sqrt{\pi}$

222

223 $\frac{d}{dx} \left[\int_a^{g(x)} f(t) dt \right] = f(g(x)) \cdot g'(x)$

224

225 $\frac{d}{dx} \left[\int_a^{g(x)} f(t) dt \right] = f(g(x)) \cdot g'(x)$

226

227

228 ### Display math — Linear Algebra

229

230 $Ax = \lambda x \implies \det(A - \lambda I) = 0$

231 $\begin{pmatrix} a & b \\ c & d \end{pmatrix}^{-1} = \frac{1}{ad - bc} \begin{pmatrix} d & -b \\ -c & a \end{pmatrix}$

232

233 $\det(A - \lambda I) = 0$

234

235

236

237 $\begin{pmatrix} a & b \\ c & d \end{pmatrix}^{-1} = \frac{1}{ad - bc} \begin{pmatrix} d & -b \\ -c & a \end{pmatrix}$

238

239 $\begin{pmatrix} a & b \\ c & d \end{pmatrix}^{-1} = \frac{1}{ad - bc} \begin{pmatrix} d & -b \\ -c & a \end{pmatrix}$

240

241

242 ### Display math — Series & Limits

243

244 $e^x = \sum_{n=0}^{\infty} \frac{x^n}{n!} = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \dots$

245

246 $\lim_{n \rightarrow \infty} \left(1 + \frac{1}{n} \right)^n = e$

247

248

249

250

251

252

253

254

Mathematics — KaTeX

90%

Dual (edit on the left)

Menu

Lattice renders mathematics via **KaTeX**. Use ``$...$`` for inline and ``$$...$$`` for display math.

Inline math

Einstein's famous equation $E = mc^2$ and the quadratic formula $x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$ render inline.

The Euler identity $e^{i\pi} + 1 = 0$ is often called the most beautiful equation in mathematics.

Display math — Calculus

$$\int_{-\infty}^{\infty} e^{-x^2} dx = \sqrt{\pi}$$

$$\frac{d}{dx} \left[\int_a^{g(x)} f(t) dt \right] = f(g(x)) \cdot g'(x)$$

Display math — Linear Algebra

$$Ax = \lambda x \implies \det(A - \lambda I) = 0$$

$$\begin{pmatrix} a & b \\ c & d \end{pmatrix}^{-1} = \frac{1}{ad - bc} \begin{pmatrix} d & -b \\ -c & a \end{pmatrix}$$

Display math — Series & Limits

$$e^x = \sum_{n=0}^{\infty} \frac{x^n}{n!} = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \dots$$

$$\lim_{n \rightarrow \infty} \left(1 + \frac{1}{n} \right)^n = e$$

Mermaid Diagrams

Lattice renders `mermaid` fenced blocks inline in the preview.

Flowchart — Lattice Edit Cycle

```

graph LR
    A[Open and Edit] --> B[Edit in CodeMirror]
    B --> C[Save]
    C --> D[Lattice renders]
    D --> E[Preview]
    E --> B
    E --> F[Conflict]
    F --> G[Conflict during]
    G --> B
    E --> H[Conflict]
    H --> B
  
```

Here is how it renders in Dual (edit on the bottom) mode:

Tip: The assets folder name is derived from the document filename, keeping related files grouped together and easy to version-control.

Links

- [Lattice on GitHub](#) — source code and issue tracker
- [Releases Page](#) — download installers
- [Release Site](#) — GitHub Pages release portal
- Relative link: [System Architecture Demo](#)
- Relative link: [Physics Equations Demo](#)

Auto-link: <https://github.com/blessia-blessini/lattice>

HTML in Markdown

Lattice renders a **safe whitelist** of inline HTML tags and passes everything else through as literal text. The linter flags all inline HTML — whitelisted tags get a **hint** (portability risk), non-whitelisted tags get a **warning** (not rendered here).

HTML element	Lattice preview	GitHub	Portable alternative
<sup>	✓ rendered	✓	KaTeX: x^2 → X^2 · Unicode: x^2
<sub>	✓ rendered	✓	KaTeX: H_{20} → H_2O · Unicode: H_2O
<kbd>	✓ rendered	✓	Inline code: <code>Ctrl+S</code>
 	✓ rendered	✓	Two trailing spaces or blank line
<mark>	⚠ plain text	✓	<code>==highlight==</code> (Lattice-native)
<details>	⚠ plain text	✓	Headings + TOC (no universal equivalent)
Other HTML	⚠ plain text	varies	Markdown equivalent (case-by-case)

Live examples of the whitelisted tags:

- Superscript: $X^2 + Y^3$
- Subscript: H_2O and CO_2
- Keyboard: press `Ctrl` + `S` to save

Keyboard Shortcuts Reference

Action	Windows / Linux	macOS
Save	Ctrl+S	Cmd+S
Open file	Ctrl+O	Cmd+O
New window	Ctrl+N	Cmd+N
Generate / refresh TOC	Ctrl+Shift+T	Cmd+Shift+T
Auto-align table	Ctrl+Shift+L	Cmd+Shift+L
Paste image from clipboard	Ctrl+V	Cmd+V
Print / Save as PDF	Ctrl+P	Cmd+P
Increase font size	Ctrl++	Cmd++
Decrease font size	Ctrl+-	Cmd+-