ENGR 498: Design for the Internet of Things – Pipeline and Computer Organization

Dr. Jason Forsyth
Department of Engineering
James Madison University

Computer Engineering is really four things…

- Representation: binary, hex, 2’s complement
- Manipulation: binary/boolean operations, gates, and circuits
- Storage: registers, cache, RAM, Hard drive (more on that today)
- Exchange: bus, interfaces, networks... (more on that later)

Representation

Decimal	Hex	Binary
0	0x0	0000
1	0x1	0001
2	0x2	0010
3	0x3	0011
4	0x4	0100
5	0x5	0101
6	0x6	0110
7	0x7	0111

Decimal	Hex	Binary
8	0x8	1000
9	0x9	1001
10	0xA	1010
11	0xB	1011
12	0xC	1100
13	0xD	1101
14	0xE	1110
15	0xF	1111

Two's complement	Decimal
0111	7
0110	6
0101	5
0100	4
0011	3
0010	2
0001	1
0000	0
1111	−1
1110	−2
1101	−3
1100	−4
1011	−5
1010	−6
1001	−7
1000	−8

Manipulation

AND Gate

A	B	F
0	0	0
0	1	0
1	0	0
1	1	1

OR Gate

A	B	F
0	0	0
0	1	1
1	0	1
1	1	1

NOT Gate

A	F
0	1
1	0











$$F = (ABC)' \cdot (B' + D) = \overline{ABC} \cdot (\bar{B} + D)$$

What happens when you hit compile…

- High-level language
  - Level of abstraction closer to problem domain
  - Provides for productivity and portability
- Assembly language
  - Textual representation of instructions
- Hardware representation
  - Binary digits (bits)
  - Encoded instructions and data



MIPS Reference Data

CORE INSTRUCTION SET

NAME, MNEMONIC		FOR-MAT	OPERATION (in Verilog)		OPCODE / FUNCT (Hex)
Add	add	R	R[rd] = R[rs] + R[rt]	(1)	$0 / 20_{hex}$
Add Immediate	addi	I	R[rt] = R[rs] + SignExtImm	(1,2)	8_{hex}
Add Imm. Unsigned	addiu	I	R[rt] = R[rs] + SignExtImm	(2)	9_{hex}
Add Unsigned	addu	R	R[rd] = R[rs] + R[rt]		$0 / 21_{hex}$
And	and	R	R[rd] = R[rs] & R[rt]		$0 / 24_{hex}$
And Immediate	andi	I	R[rt] = R[rs] & ZeroExtImm	(3)	c_{hex}
Branch On Equal	beq	I	if(R[rs]==R[rt]) PC=PC+4+BranchAddr	(4)	4_{hex}
Branch On Not Equal	bne	I	if(R[rs]!=R[rt]) PC=PC+4+BranchAddr	(4)	5_{hex}
Jump	j	J	PC=JumpAddr	(5)	2_{hex}
Jump And Link	jal	J	R[31]=PC+8;PC=JumpAddr	(5)	3_{hex}
Jump Register	jr	R	PC=R[rs]		$0 / 08_{hex}$
Load Byte Unsigned	lbu	I	R[rt]={24'b0,M[R[rs] +SignExtImm](7:0)}	(2)	24_{hex}
Load Halfword Unsigned	lhu	I	R[rt]={16'b0,M[R[rs] +SignExtImm](15:0)}	(2)	25_{hex}
Load Linked	ll	I	R[rt] = M[R[rs]+SignExtImm]	(2,7)	30_{hex}
Load Upper Imm.	lui	I	R[rt] = {imm, 16'b0}		f_{hex}
Load Word	lw	I	R[rt] = M[R[rs]+SignExtImm]	(2)	23_{hex}
Nor	nor	R	R[rd] = ~ (R[rs] | R[rt])		$0 / 27_{hex}$
Nor	nor	R	R[rd] = ~ (R[rs] | R[rt])		$0 / 27_{hex}$
Or	or	R	R[rd] = R[rs] | R[rt]		$0 / 25_{hex}$
Or Immediate	ori	I	R[rt] = R[rs] | ZeroExtImm	(3)	d_{hex}
Set Less Than	slt	R	R[rd] = (R[rs] < R[rt]) ? 1 : 0		$0 / 2a_{hex}$
Set Less Than Imm.	slti	I	R[rt] = (R[rs] < SignExtImm)? 1 : 0	(2)	a_{hex}
Set Less Than Imm. Unsigned	sltiu	I	R[rt] = (R[rs] < SignExtImm) ? 1 : 0	(2,6)	b_{hex}
Set Less Than Unsig.	sltu	R	R[rd] = (R[rs] < R[rt]) ? 1 : 0	(6)	$0 / 2b_{hex}$
Shift Left Logical	sll	R	R[rd] = R[rt] << shamt		$0 / 00_{hex}$
Shift Right Logical	srl	R	R[rd] = R[rt] >> shamt		$0 / 02_{hex}$
Store Byte	sb	I	M[R[rs]+SignExtImm](7:0) = R[rt](7:0)	(2)	28_{hex}
Store Conditional	sc	I	M[R[rs]+SignExtImm] = R[rt]; R[rt] = (*atomic*) ? 1 : 0	(2,7)	38_{hex}
Store Halfword	sh	I	M[R[rs]+SignExtImm](15:0) = R[rt](15:0)	(2)	29_{hex}
Store Word	sw	I	M[R[rs]+SignExtImm] = R[rt]	(2)	$2b_{hex}$
Subtract	sub	R	R[rd] = R[rs] - R[rt]	(1)	$0 / 22_{hex}$
Subtract Unsigned	subu	R	R[rd] = R[rs] - R[rt]		$0 / 23_{hex}$

(1) May cause overflow exception
(2) SignExtImm = { 16{immediate[15]}, immediate }
(3) ZeroExtImm = { 16{1b'0}, immediate }
(4) BranchAddr = { 14{immediate[15]}, immediate, 2'b0 }
(5) JumpAddr = { PC+4[31:28], address, 2'b0 }
(6) Operands considered unsigned numbers (vs. 2's comp.)
(7) Atomic test&set pair; R[rt] = 1 if pair atomic, 0 if not atomic

A very basic computer…



Each pipeline stage has a purpose



How do the instructions ‘control’ the computer…




Add
4
0
M
u
x
1
Add
ALU result
Shift left 2
RegDst
Branch
MemRead
MemtoReg
ALUOp
MemWrite
ALUSrc
RegWrite
Control
Instruction [31–26]
PC
Read address
Instruction [31–0]
Instruction memory
Instruction [25–21]
Instruction [20–16]
Instruction [15–11]
Instruction [15–0]
Instruction [5–0]
Read register 1
Read register 2
Write register
Write data
Read data 1
Read data 2
Registers
16
Sign-extend
32
ALU control
Zero
ALU
ALU result
Address
Read data
Write data
Data memory

How quickly can this pipeline execute?



Pipelining speeds up the processor, by slowing it down?



Comparison of pipelined and single cycle



There are many possible architectures…



ARM Cortex-A8 Pipeline

Core i7 Pipeline



Computer Org and Memory Hierarchy

How do we keep this fed with information and how does it talk to the external world?



DDR4-3200 (3200 10^6 transfers/s)

DIMM / DRR



Cache RAM Flash HD

	Register (order)	SRAM	SDRAM	SSD	HD
Density	32x32 bits	~1 MB	~10 GB	~100 GB	~1 TB
Access Time	.1 ns	0.5-2.5 ns	50-70 ns	5,000-50,000	5,000,000 - 24,000,000
Distance (from desk)	~~book bag~~ Pocket / 1 ft	neighbor / 5 ft (5x)	500 ft / Fourth office	sq ft / River 10 miles	40,000 miles Darwin, Australia
$/GB	N/A	$500-$1000	$10-20	$.75-$100	Sydney is closer $.05-$0.10

Tech

SRAM



DRAM