



US007287736B2

(12) **United States Patent**  
**Hauck**

(10) **Patent No.:** **US 7,287,736 B2**  
(45) **Date of Patent:** **Oct. 30, 2007**

(54) **COROLLA PLANT HANGER**

(76) Inventor: **Robert F. Hauck**, 180 Claremont Dr.,  
Morgan Hill, CA (US) 95037

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 175 days.

(21) Appl. No.: **10/997,505**

(22) Filed: **Nov. 24, 2004**

(65) **Prior Publication Data**

US 2005/0279903 A1 Dec. 22, 2005

**Related U.S. Application Data**

(60) Provisional application No. 60/524,540, filed on Nov.  
24, 2003.

(51) **Int. Cl.**  
**A47H 1/10** (2006.01)

(52) **U.S. Cl.** ..... **248/318; 47/67**

(58) **Field of Classification Search** ..... 248/322,  
248/317, 318, 323, 324; 220/485, 660, 489;  
47/67, 66.6, 40; D6/512-514, 403, 405;  
D11/143, 148; D26/9

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

599,996 A \* 3/1898 Engle ..... 47/67  
1,815,195 A \* 7/1931 Favata, Jr. .... 47/67

2,064,826 A \* 12/1936 Gabriel ..... 220/660  
3,915,419 A \* 10/1975 Brown et al. .... 248/318  
4,349,172 A \* 9/1982 Banks, Jr. .... 248/318  
4,506,475 A 3/1985 Elliott  
4,779,377 A 10/1988 Davis  
4,956,937 A 9/1990 Haddox  
5,329,728 A 7/1994 Ray  
6,299,118 B1 10/2001 Farrell

\* cited by examiner

*Primary Examiner*—Gwendolyn Baxter

(74) *Attorney, Agent, or Firm*—Donald E. Schreiber

(57) **ABSTRACT**

A plant hanger includes several generally C-shaped arms having apertures passing therethrough at opposite ends of each arm. The plant hanger also includes a first plurality of beads each of which has an aperture passing therethrough. The arms and the beads are secured together by a ring which passes both:

1. through one of the apertures which pass through each of the arms; and
2. through the apertures which pass through each of the beads.

Lastly, the plant hanger includes at least a pair of flexible belts. Each of the belts passes through more than half of the apertures which pass through each of the arms and are located at ends of the arms furthest from the apertures through which the ring passes. Moreover, both belts pass coincidentally through apertures which pass through at least two (2) of the arms, which, preferably, are located on opposite sides of the plant hanger.

**19 Claims, 3 Drawing Sheets**

