



US010309097B2

(12) **United States Patent
Hill**

(10) **Patent No.: US 10,309,097 B2**

(45) **Date of Patent: Jun. 4, 2019**

(54) **ADJUSTABLE TIE ASSEMBLY FOR
STRUCTURAL MEMBERS**

USPC 52/465, 514
See application file for complete search history.

(71) Applicant: **Oz-Post International, LLC,**
Richardson, TX (US)

(56) **References Cited**

(72) Inventor: **Ian A. Hill,** Plano, TX (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Oz-Post International, LLC,**
Richardson, TX (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

3,885,084 A * 5/1975 Kaiserswerth H05K 9/0016
174/371
4,075,811 A * 2/1978 Keith E04B 7/22
52/395
4,733,986 A * 3/1988 Kenning E04B 1/5812
403/306
4,833,853 A * 5/1989 Deibele E04D 5/142
52/410
5,003,743 A * 4/1991 Bifano E04F 13/06
52/288.1
5,573,354 A * 11/1996 Koch E02D 5/60
405/216
6,023,899 A * 2/2000 Mecozzi E04B 1/617
52/396.04

(21) Appl. No.: **15/792,229**

(22) Filed: **Oct. 24, 2017**

(65) **Prior Publication Data**

US 2019/0119905 A1 Apr. 25, 2019

(Continued)

(51) **Int. Cl.**

E04B 1/19 (2006.01)

E04B 1/41 (2006.01)

E04F 10/08 (2006.01)

E04B 1/26 (2006.01)

A47G 29/00 (2006.01)

A47G 23/02 (2006.01)

E04B 1/32 (2006.01)

Primary Examiner — Beth A Stephan

(74) *Attorney, Agent, or Firm* — Foley & Lardner LLP

(52) **U.S. Cl.**

CPC **E04B 1/40** (2013.01); **A47G 29/00**
(2013.01); **E04B 1/2608** (2013.01); **E04F**
10/08 (2013.01); **A47G 23/0216** (2013.01);
A47G 23/0266 (2013.01); **E04B 1/32**
(2013.01); **E04B 2001/2644** (2013.01)

(57) **ABSTRACT**

In an embodiment, an assembly includes a first plate comprising a first primary portion and a first flange disposed orthogonally to the first primary portion. The first primary portion is configured to contact a first structural member and the first flange defining a first through hole. A second plate comprises a second primary portion and a second flange disposed orthogonally to the second primary portion. The second primary portion is configured to contact a second structural member and the second flange defines a second through hole. A cover receives the first and second flanges. A bolt is received through the first through hole, and tightening the bolt tends to draw the second plate towards the first plate.

(58) **Field of Classification Search**

CPC E04B 1/40; E04B 2001/405; E04B 1/1903;
E04B 2001/2403; E04B 1/2608; E04B
1/32; E04B 2001/2644; E04B 2001/2415;
E04G 23/02; A47G 29/00; A47G
213/0216; A47G 23/0266

13 Claims, 9 Drawing Sheets

