



US008020827B2

(12) **United States Patent**
Schieren

(10) **Patent No.:** **US 8,020,827 B2**
(45) **Date of Patent:** **Sep. 20, 2011**

(54) **SUSPENDABLE BLOW DRYER HOLDER**

(76) Inventor: **Susan M. Schieren**, Leeds, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/566,756**

(22) Filed: **Sep. 25, 2009**

(65) **Prior Publication Data**

US 2011/0073735 A1 Mar. 31, 2011

(51) **Int. Cl.**
A47H 1/10 (2006.01)

(52) **U.S. Cl.** **248/317**

(58) **Field of Classification Search** 248/317,
248/318, 339, 342, 176.2; 34/283, 487, 90,
34/97

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,344,027	A	6/1920	Evilsizor et al.	
1,396,507	A	11/1921	Coffman	
2,565,315	A	8/1951	Lieberman	
4,121,720	A	10/1978	Hayes	
D274,394	S *	6/1984	Elliott	D6/403
4,453,695	A	6/1984	Sennott et al.	
4,506,475	A *	3/1985	Elliott	47/67
4,561,547	A	12/1985	Estwanik, III	
4,728,016	A	3/1988	McPhee	
5,090,653	A *	2/1992	Theodorides	248/317
5,640,781	A	6/1997	Carson	
5,832,624	A	11/1998	Narrin	
6,273,277	B1	8/2001	Geldenhuys	

D482,490 S 11/2003 Fickas et al.
2008/0016712 A1 1/2008 Van
2009/0121108 A1* 5/2009 McFadden 248/318

FOREIGN PATENT DOCUMENTS

DE 20101519 1/2001

* cited by examiner

Primary Examiner — Ramon O Ramirez

(74) *Attorney, Agent, or Firm* — Schmeiser, Olsen & Watts, LLP

(57) **ABSTRACT**

A suspendable blow dryer holder includes a lower frame having a first opening located within the bounds of the lower frame, the first opening dimensioned to accept and secure a barrel of a first blow dryer such that the barrel is pointed at a floor when the suspendable blow dryer holder is suspended. The suspendable blow dryer holder includes an upper component having a connection mechanism, the connection mechanism configured to connect the suspendable blow dryer holder to a suspending mechanism. Finally, the suspendable blow dryer holder includes a plurality of elongated connecting elements attached to the upper component and extending to a perimeter of the lower frame, the plurality of elongated connecting elements each attached to the perimeter of the lower frame at a connection location, the plurality of elongated connecting elements each having a sufficient length for the first blow dryer to fit between the upper component and the lower frame when the suspendable blow dryer holder is suspended, the connection locations on the perimeter of the lower frame spaced apart for the first blow dryer to fit between at least two of the plurality of elongated connecting elements.

18 Claims, 4 Drawing Sheets

