



US005360193A

United States Patent [19] Cobb

[11] Patent Number: 5,360,193

[45] Date of Patent: Nov. 1, 1994

[54] DETACHABLE HANGING PLANT SUPPORT

[76] Inventor: David E. Cobb, 3920 Washakie,
Casper, Wyo. 82609

[21] Appl. No.: 157,976

[22] Filed: Nov. 29, 1993

[51] Int. Cl.⁵ A47H 1/10

[52] U.S. Cl. 248/318; 47/67

[58] Field of Search 248/318, 322, 312.1;
47/67; 211/113; 294/82.17

[56] References Cited

U.S. PATENT DOCUMENTS

246,145	8/1881	Keil .	
951,684	3/1910	Gillespie	47/67
1,154,627	9/1915	Hall .	
1,484,403	2/1924	Miller	47/67
1,527,281	2/1925	Stapfer	294/82.17 X
2,530,456	11/1950	Fracchia .	
3,981,099	9/1976	Dziewulski .	
4,032,102	6/1977	Wolf .	
4,159,094	6/1979	Stekoll	248/318
4,262,873	4/1981	Prenger	248/318
4,337,916	7/1982	Norris	248/318 X
4,349,172	9/1982	Banks	248/322
4,506,475	3/1985	Elliott	47/67

Primary Examiner—J. Franklin Foss

Attorney, Agent, or Firm—Risto A. Rinne, Jr.

[57] ABSTRACT

An apparatus for suspending a hanging plant that is housed in a container is described as including three or more flexible supports each of which has a first end and a second end. The first end of each flexible support is adapted for hanging from an overhead supporting hook. The second end of each flexible support is attached together to provide an enclosure for retaining and for supporting the container. At least one of the flexible supports includes a fastener that is disposed intermediate to the first end and the second end. The fastener includes a slideable sleeve. The slideable sleeve can be displaced along the longitudinal axis of the flexible support to expose a coupling which can then be separated. Once the coupling is separated the flexible support also separates into two halves and the container can be readily removed from or inserted into the apparatus through the opening provided by the separated flexible support. When the slideable sleeve is displaced so as to cover the coupling, the coupling is thereby prevented from decoupling.

18 Claims, 1 Drawing Sheet

