



US010648170B2

(12) **United States Patent
Hill**

(10) **Patent No.: US 10,648,170 B2**

(45) **Date of Patent: *May 12, 2020**

(54) **ADJUSTABLE TIE ASSEMBLY FOR
STRUCTURAL MEMBERS**

(71) Applicant: **Oz-Post International, LLC,**
Richardson, TX (US)

(72) Inventor: **Ian A. Hill,** Plano, TX (US)

(73) Assignee: **Oz-Post International, LLC,**
Richardson, TX (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **16/409,181**

(22) Filed: **May 10, 2019**

(65) **Prior Publication Data**

US 2019/0330840 A1 Oct. 31, 2019

Related U.S. Application Data

(63) Continuation of application No. 15/792,229, filed on
Oct. 24, 2017, now Pat. No. 10,309,097.

(51) **Int. Cl.**

E04B 1/19	(2006.01)
E04B 1/41	(2006.01)
E04F 10/08	(2006.01)
E04B 1/26	(2006.01)
A47G 23/02	(2006.01)
A47G 29/00	(2006.01)
A47G 7/04	(2006.01)
E04B 1/32	(2006.01)
E04G 23/02	(2006.01)
F16B 7/04	(2006.01)

(52) **U.S. Cl.**

CPC **E04B 1/40** (2013.01); **A47G 7/045**
(2013.01); **A47G 23/0266** (2013.01); **A47G**
29/00 (2013.01); **E04B 1/2608** (2013.01);
E04F 10/08 (2013.01); **A47G 23/0216**
(2013.01); **E04B 1/32** (2013.01); **E04B**
2001/2644 (2013.01); **E04G 23/0225**
(2013.01); **F16B 7/04** (2013.01)

(58) **Field of Classification Search**

CPC **E04B 1/40**; **E04B 1/2608**; **A47G 29/00**;
E04F 10/08

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,885,084 A	5/1975	Kaiserswerth et al.
4,075,811 A	2/1978	Keith
4,733,986 A	3/1988	Kenning et al.
4,833,853 A	5/1989	Deibele et al.
5,003,743 A	4/1991	Bifano et al.
5,573,354 A	11/1996	Koch
6,023,899 A	2/2000	Mecozzi

(Continued)

Primary Examiner — Beth A Stephan

(74) Attorney, Agent, or Firm — Foley & Lardner LLP

(57)

ABSTRACT

In an embodiment, an assembly includes a first plate comprising a first primary portion and a first flange disposed orthogonally to the first primary portion. The first primary portion is configured to contact a first structural member and the first flange defining a first through hole. A second plate comprises a second primary portion and a second flange disposed orthogonally to the second primary portion. The second primary portion is configured to contact a second structural member and the second flange defines a second through hole. A cover receives the second flange. A bolt is received through the first through hole, and tightening the bolt draws the first flange toward the second flange.

20 Claims, 9 Drawing Sheets

