Team 155

Problem B

Two Points to the Goal: A Noise-Conditioned Mixture Density Network for Probabilistic Penalty Kick Prediction

Summary

How much can two early positions tell us about where a penalty kick crosses the goal plane? The ball starts at a known point, with observations at 0.05 and 0.10 s. We propagate measurement uncertainty through a flight model with gravity, quadratic drag and a transverse Magnus force. A constant-acceleration solution gives a reference crossing. An adaptive Bayesian sampler and a noise-conditioned mixture density network (MDN) estimate distributions over the crossing point.

At an assumed coordinate noise of 5 mm, the calibrated MDN places the most likely crossing at $(Y, Z) = (2.62, 2.15)$ m. Its joint 50% and 95% prediction regions cover 0.177 and 0.775 m^2, and the probability that the ball centre is inside the goal rectangle, given an airborne crossing, is 97.3%. The Bayesian estimate gives a mode of $(2.650, 2.052)$ m and a conditional probability of 96.3%.

After model selection and calibration, we generated a fresh simulation set with 5,036 airborne crossings. The MDN's median error at 5 mm is 0.290 m. Across four noise levels, its calibrated 50% and 95% regions cover 47.6–49.1% and 94.5–95.2% of endpoints. A $3\,\mathrm{m\,s^{-1}}$ crosswind reduces 50% coverage from 48.7% to 40.9% on matched flights. Tracked penalties and other airborne arcs give case-level checks of the physical model. The coverage figures apply to simulations from the stated launch and measurement assumptions.

An information-limit analysis shows that at 5 mm the two observations and the physical prior leave an irreducible median crossing spread of about 0.26 m; the frozen network is within about 15% of this local bound, and a third 5 mm position would roughly halve it. A single deterministic forecast is therefore incomplete at this noise level, and the probability regions are an intrinsic part of the answer.

Contents

1 Introduction **3**

1.1 Problem Restatement 3

1.2 Background and Approach 3

2 Materials and Methods **3**

2.1 Assumptions and Approximations 3

2.2 Physical Model 4

2.3 Numerical Solution and Event Detection 5

2.4 Bayesian Inference of Launch Conditions 5

2.5 Noise-Conditioned Mixture Density Network 5

2.6 Data Splits, Comparisons and Calibration 6

3 Results **7**

3.1 Answer for the Stated Kick 7

3.2 Feature, Target and Architecture Comparisons 7

3.3 Blind-Test Accuracy and Calibration 8

3.4 Paired Comparison with the Physics Posterior 8

3.5 Distribution Shift 9

3.6 Sensitivity to the Drag Prior 9

3.7 Model-Form Check on Tracked Free-Kick Arcs 10

3.8 Prefix Forecasts on Tracked Flights 11

3.9 External replay of three 100 Hz curve kicks 11

4 Discussion **12**

5 Conclusion and Outlook **13**

References **14**

A Propagation of Position Noise to Acceleration **14**

B Information Limits of the Early-Flight Forecast **15**

B.1 Kinematic amplification of the unregularised extrapolation 15

B.2 Local Bayesian floor under the physical prior 15

B.3 Interpretation for the measurement design 16

1 Introduction

1.1 Problem Restatement

A penalty kick starts 11 m from a goal that is 7.32 m wide and 2.44 m high [1]. Taking the penalty spot as the origin and the goal line as the plane $x = 11\,\mathrm{m}$, the ball centre begins at $\mathbf{r}(0) = (0, 0, 0.11)\,\mathrm{m}$, and two further positions are observed: $\mathbf{r}(0.05)$ and $\mathbf{r}(0.10)$. The task is to predict the first crossing of the goal plane: the most likely point (Y, Z), joint 50% and 95% prediction regions, and the probability that the ball passes inside the goal. The final crossing is a label for validation only; it may not be used as an input.

Two properties make this inverse problem difficult. First, the trajectory is driven by forces that are not observed. The launch speed is roughly $30\,\mathrm{m\,s^{-1}}$ [6], the Reynolds number is of order 10^5, and the drag coefficient of a football changes by a factor of almost three across the drag crisis [2]. Spin generates a Magnus force whose direction depends on the spin axis, which a tracking system does not measure. Second, the observations are only marginally informative. With the start fixed and two positions observed independently with standard deviation σ, the second difference that estimates acceleration carries noise $\sqrt{5}\,\sigma/\Delta t^2$ (Appendix A). For $\sigma = 5\,\mathrm{mm}$ and $\Delta t = 0.05\,\mathrm{s}$ this is $4.47\,\mathrm{m\,s^{-2}}$, comparable to the aerodynamic accelerations themselves. A predictor that ignores this amplification will be overconfident.

1.2 Background and Approach

The aerodynamics of a football are well studied. Wind-tunnel work gives a subcritical drag coefficient near 0.43, a supercritical value near 0.15, and a critical Reynolds number of 2.2–3.0×10^5 [2, 3]; trajectory analyses of free kicks report effective drag coefficients of 0.25–0.30 [6], and lift coefficients of 0.2–0.3 at moderate spin parameters [4]. More recent work recovers drag and lift curves directly from tracked trajectories [5]. These ranges, rather than a single calibrated value, define our prior. Public tracking datasets make real ball trajectories available: the ISSIA-3D annotations distributed with SoccerNet-v3D provide calibrated, multi-view ball positions for broadcast matches [8], and league-wide spatiotemporal data are now published for the German Bundesliga [9]. Neither source observes spin, and neither marks the instant of foot contact.

We first quantify how uncertainty in the two observed positions propagates into the predicted crossing. We then compare a transparent Bayesian inverse calculation and a fast mixture density network [12]. They share the same forward model and launch prior. Controlled comparisons test which parts of the network help. A separate calibration fold and fresh simulations measure how often the forecast regions contain the true endpoint. Tracked flights provide external checks on the physical assumptions.

Finally, Appendix B derives the information limit of this measurement design: the two early positions and the physical prior leave an irreducible crossing spread, so the most informative answer is a probability distribution rather than a single point.

2 Materials and Methods

2.1 Assumptions and Approximations

A1. Point mass, rigid sphere. The ball is treated as a point mass with $m = 0.430\,\mathrm{kg}$ and radius $R = 0.110\,\mathrm{m}$, within the IFAB ranges for mass and circumference [1]. The

cross-sectional area is $A = \pi R^2 = 0.038013\,\mathrm{m}^2$. Buoyancy is neglected: with a ball density of about $77\,\mathrm{kg\,m^{-3}}$, buoyancy is 1.6% of the weight, smaller than the uncertainty in the aerodynamic coefficients.

A2. Still air. The main model uses zero wind and constant air density $\rho = 1.20\,\mathrm{kg\,m^{-3}}$. A $3\,\mathrm{m\,s^{-1}}$ crosswind is used only as a stress test.

A3. Quadratic drag with one coefficient per flight. The drag coefficient is constant along a trajectory and drawn from $C_D \sim U[0.15, 0.30]$. This range brackets the free-kick estimates of [6] and the supercritical wind-tunnel value of [2]; a wider upper limit of 0.45 is examined as a sensitivity case.

A4. Transverse Magnus force. Only the spin component perpendicular to the relative velocity produces lift. The lift coefficient is $C_L = \min(1.4\,S, 0.30)$ with spin parameter $S = R\,|\boldsymbol{\omega} \times \hat{\mathbf{u}}|/|\mathbf{u}|$. The slope and cap are modelling choices of this study, chosen to match the lift coefficients measured at moderate spin parameters [4, 2]. Zero spin and spin parallel to the velocity produce no lift.

A5. No spin decay. The main model holds spin fixed over a flight. A separate stress test applies exponential decay with a 0.5 s time constant.

A6. Measurement model. The initial position is exact. The two later positions are independent Gaussian observations with a common, known standard deviation $\sigma \in \{2, 5, 10, 15\}$ mm for evaluation. Because only the two later points carry noise, the acceleration uncertainty is $\sqrt{5}\,\sigma/\Delta t^2$; the conservative factor $\sqrt{6}$ applies only if all three positions are noisy (Appendix A).

A7. Plausibility prior. Launch velocity, spin and drag are drawn independently from uniform bounds (Table 1). The bounds are wide plausibility ranges chosen before calibration; they contain the free-kick speeds reported in [6], but they are not a calibrated distribution of real penalty kicks.

Table 1: Prior bounds for the launch parameters (independent uniforms).

Parameter	Lower	Upper
v_x $(\mathrm{m\,s^{-1}})$	18	35
v_y $(\mathrm{m\,s^{-1}})$	-12	12
v_z $(\mathrm{m\,s^{-1}})$	0.5	12
$\omega_x, \omega_y, \omega_z$ $(\mathrm{rad\,s^{-1}})$	-60	60
C_D	0.15	0.30

2.2 Physical Model

Let $\mathbf{u} = \mathbf{v} - \mathbf{w}$ be the ball velocity relative to the air, with $\mathbf{w} = 0$ in the main model. The equations of motion are

$$\dot{\mathbf{r}} = \mathbf{v}, \tag{1}$$

$$\dot{\mathbf{v}} = \mathbf{g} - \frac{\rho A C_D}{2m}\,|\mathbf{u}|\,\mathbf{u} + \frac{\rho A C_L}{2m}\,|\mathbf{u}|^2\,\hat{\mathbf{n}}, \tag{2}$$

where $\mathbf{g} = (0, 0, -9.81)\,\mathrm{m\,s^{-2}}$ and

$$\hat{\mathbf{n}} = \begin{cases} \dfrac{\boldsymbol{\omega} \times \mathbf{u}}{|\boldsymbol{\omega} \times \mathbf{u}|}, & |\boldsymbol{\omega} \times \mathbf{u}| > 0, \\ \mathbf{0}, & \text{otherwise}, \end{cases} \qquad C_L = \min\!\left(1.4\,\frac{R\,|\boldsymbol{\omega} \times \mathbf{u}|}{|\mathbf{u}|^2},\, 0.30\right). \tag{3}$$

In the air-relative frame, the lift term is orthogonal to $\mathbf{u}$ and the drag term dissipates kinetic energy.

The goal plane is crossed when x first reaches 11 m. The crossing time and position are obtained by linear interpolation between the two integration steps that bracket $x = 11\,\mathrm{m}$. A flight ends early if the ball centre falls to $z \le R$ before reaching the plane; such trajectories are labelled ground hits and are excluded from the endpoint statistics, which are therefore conditional on airborne arrival.

2.3 Numerical Solution and Event Detection

Equations (1)–(3) are integrated with a fixed-step fourth-order Runge–Kutta scheme using $\delta t = 2\,\mathrm{ms}$ and a horizon of 1.5 s. Halving the step to 1 ms changes the interpolated endpoint by less than 0.1 mm on a representative trajectory, well below the millimetre-scale observations. Because the step is fixed, event locations are not exact roots; the linear interpolation error is bounded by the same step-refinement check.

2.4 Bayesian Inference of Launch Conditions

Let $\boldsymbol{\theta} = (\mathbf{v}_0, \boldsymbol{\omega}, C_D)$ and let $\mathbf{y}_1, \mathbf{y}_2$ be the two observed positions. With the start fixed and independent Gaussian errors,

$$p(\mathbf{y}_1, \mathbf{y}_2 \mid \boldsymbol{\theta}) = \prod_{i=1}^{2} \frac{1}{(2\pi\sigma^2)^{3/2}} \exp\!\left[-\frac{\|\mathbf{y}_i - \mathbf{r}(t_i; \boldsymbol{\theta})\|^2}{2\sigma^2}\right]. \tag{4}$$

The posterior is proportional to the product of (4) and the uniform prior of Table 1. It is sampled with four-stage adaptive importance sampling. Every stage mixes 20% prior draws with a Gaussian proposal. The first Gaussian uses an early-motion estimate, and later Gaussians use the weighted moments of the previous stage. The case study uses 40,000 draws per stage. The paired benchmark starts with 6,000 per stage and retries with 18,000 when conditional ESS falls below 100. The importance weights include the explicit proposal correction $p(\boldsymbol{\theta})/q(\boldsymbol{\theta})$.

The last stage always uses the nominal σ; earlier stages use a widened likelihood to locate the posterior region. Effective sample size (ESS) is reported for every case, and no conclusion is drawn from a sample with low ESS.

From the weighted endpoint sample we estimate the most likely crossing as the maximum of a weighted Gaussian kernel density on a 160×160 grid, and the joint 50% and 95% regions as highest-density regions (HDRs) [14] on the same grid. The grid deliberately extends beyond the goal rectangle so that off-target mass is not truncated.

2.5 Noise-Conditioned Mixture Density Network

Let E denote a forward goal-plane crossing before ground contact. The network estimates $p(Y, Z \mid \mathbf{y}_1, \mathbf{y}_2, \sigma, E)$. The final input has eleven features derived from the two observations, the fixed start and σ. These are three velocity components at the midpoint, three second-difference

acceleration components, speed, the signed tangential component and the normal magnitude of the estimated aerodynamic acceleration, a constant-acceleration time to the plane, and σ. Each input is standardised using training data. Apparent drag and lift coefficients and three gravity-shifted duplicates of acceleration were removed from the original sixteen features.

The final network has three hidden layers of 128 units with LayerNorm and GELU. Its output defines $K = 3$ bivariate Gaussian components,

$$p(Y, Z \mid \mathbf{y}_1, \mathbf{y}_2, \sigma, E) = \sum_{k=1}^{K} \pi_k \mathcal{N}((Y, Z); \boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k)\,. \tag{5}$$

Each covariance is parameterised by a Cholesky factor with a bounded correlation. The target is the absolute endpoint (Y, Z) and the loss is its negative log-likelihood (NLL). The model uses Adam [7], an initial learning rate of 10^{-3} with cosine decay, batches of 256, and 100 epochs. On each pass through the training set, every trajectory is perturbed anew. Its observation standard deviation is drawn from $U[1, 20]$ mm and shared across the six independently perturbed coordinates. The endpoint label remains unchanged.

2.6 Data Splits, Comparisons and Calibration

We generated 50,000 flights with seed 42. The simulator recorded two early positions, the event type and the endpoint when the ball crossed the plane in flight. There were 41,733 airborne crossings and 8,267 ground hits. Splitting by trajectory before adding noise gave 33,367 airborne training cases, 4,179 validation cases and 4,187 development test cases. We split validation again by trajectory into 2,090 for model selection and 2,089 for calibration. After freezing model and calibration parameters, we generated 6,000 new flights with seed 155107 and evaluated their 5,036 airborne crossings. Within each split and noise level, the methods received the same perturbed observations. All computations use NumPy [16], SciPy [17], PyTorch [18] and Matplotlib [19].

Development comparisons held architecture and data fixed while changing features and targets. Model A maps coordinates and σ to the endpoint. B predicts its residual from a constant-acceleration estimate. C and D use sixteen physics-derived features for absolute and residual targets, respectively. E predicts residuals using coordinates, σ and the baseline endpoint. We also retrained the alternative PI-ResMDN on the canonical data. Final screening compared 16 and 11 features, one and three mixture components, one to four hidden layers with SiLU, then four activations at the selected depth. Each controlled comparison used training seeds 11, 22 and 33. The selection score was the mean validation NLL, equally weighted across the four noise scenarios. When a simpler candidate's mean disadvantage was within one paired seed standard deviation and its mean coverage gap increased by at most 1.5 percentage points, we chose the simpler candidate.

The mixture mean gives the point prediction. We report its median and 90th-percentile Euclidean errors, NLL in physical units, observed coverage and mean area of joint high-density regions, and energy score for paired probabilistic forecasts [15]. For calibration, we fit one standard-deviation multiplier per noise level by NLL on the calibration fold. We then adjusted the 50% and 95% region thresholds using the empirical rank of each calibration endpoint within its forecast density. These threshold adjustments change the reported regions while preserving the fitted density and its mean. We report both pre- and post-calibration coverage to show the effect on new flights.

3 Results

3.1 Answer for the Stated Kick

For the stated observations, the constant-acceleration calculation gives $T = 0.405\,\text{s}$ and $(Y, Z) = (2.495, 1.920)\,\text{m}$. At the representative noise scenario of 5 mm, the calibrated MDN mode is $(2.62, 2.15)\,\text{m}$ and the mixture mean is $(2.70, 1.97)\,\text{m}$. The joint regions in Fig. 1 have areas of 0.177 and $0.775\,\text{m}^2$. The probability of the ball centre crossing inside the rectangle is 97.3% conditional on E. The Bayesian mode is $(2.650, 2.052)\,\text{m}$, with areas of 0.219 and $0.809\,\text{m}^2$ and a conditional probability of 96.3%. Its effective sample size is 2,893. Both estimates use the same stated coordinates and noise assumption.




Figure 1: Calibrated MDN crossing densities for the stated kick at 2, 5 and 15 mm observation noise. The white and cyan contours mark the nominal joint 50% and 95% regions. The dashed rectangle is the goal opening. The white cross marks the density mode.

Table 2: MDN answer for the stated kick under three observation-noise scenarios. The final column is the probability of the ball centre being inside the goal rectangle conditional on an airborne crossing. The case uses the preselected model seed 11.

Noise (mm)	Mode Y (m)	Mode Z (m)	50% area (m^2)	95% area (m^2)	In-frame
2	2.60	1.98	0.035	0.151	$> 99.9\%$
5	2.62	2.15	0.177	0.775	97.3%
15	2.73	1.67	0.819	2.370	80.8%

3.2 Feature, Target and Architecture Comparisons

For the same launch parameters, the original alternative simulator and our canonical model produced a 0.240 m RMS endpoint difference on jointly airborne cases. Retraining the alternative on the canonical data made the comparison in Table 3 possible. At 5 mm, the direct physical-feature model C improves on the coordinate model A. Model D is best by NLL at 2 mm, but reaches an NLL of 9.88 at 15 mm on the fresh set. In the development test, roughly 3% of its predictions at that noise level assigned very low density to the true endpoint (NLL above 100). The constant-acceleration calculation can be unstable or have no forward crossing when applied to noisy coordinates. These observations favour direct prediction across the range of measurement scenarios.

The 11-feature version kept performance close to the 16-feature version on validation (NLL -0.0613 and -0.0556). With 11 features and two SiLU layers, using one rather than three Gaussian components changed mean validation NLL from -0.0613 to 0.1205. With SiLU, one to four layers gave scores of 0.0500, -0.0613, -0.0898 and -0.0958. The three-to-four-layer

difference (0.0061) was below the paired seed standard deviation (0.0078), so we selected three layers. At that depth, GELU led with −0.1006, followed by SiLU (−0.0898), ReLU (−0.0722) and Tanh (−0.0643). The sequential screen fixes width at 128 and compares activations at the selected depth.

Three further validation comparisons changed one setting at a time. Removing component correlation, using a fixed learning rate and reusing a single noise realisation per trajectory yielded mean NLL values of −0.0245, 0.0298 and 0.0010, respectively, compared with −0.1006 for the final recipe.

Table 3: Models scored on the same 5,036 fresh airborne crossings at 5 mm. Point forecasts are mixture means. Each value averages three training seeds except the legacy MDN, which uses its original checkpoint. Lower values are better.

Model	Median (m)	90th percentile (m)	NLL
Legacy MDN	0.324	0.675	0.176
A: coordinates, direct	0.309	0.665	0.049
B: coordinates, residual	0.306	0.660	0.120
C: physical features, direct	0.293	0.643	−0.182
D: physical features, residual	0.290	0.648	0.189
E: coordinates and baseline, residual	0.292	0.650	−0.048
PI-ResMDN, canonical retraining	0.433	1.086	1.089
Calibrated final MDN	0.290	0.644	**−0.219**

3.3 Blind-Test Accuracy and Calibration

The final MDN has the lowest NLL among the compared networks at 5, 10 and 15 mm. At 5 mm its median endpoint error is within 3 mm of model C and nearly tied with D. The constant-acceleration estimate has a median error of 0.439 m over the 5,030 cases in which it produces a crossing. It fails on the other six, and on 288 cases at 15 mm.

Table 4: Final MDN on 5,036 independently generated airborne crossings, averaged over three training seeds. The two coverage columns show before and after calibration in percent. The area and NLL are post-calibration values.

Noise (mm)	Median (m)	NLL	50% pre/post	95% pre/post	95% area (m^2)
2	0.130	-1.682	49.9 / 49.1	94.8 / 94.5	0.318
5	0.290	-0.219	48.2 / 47.8	95.6 / 94.9	1.246
10	0.466	0.623	47.2 / 48.8	96.4 / 95.2	2.373
15	0.566	0.956	45.3 / 47.6	96.9 / 94.5	2.804

At 15 mm, the empirical 50% coverage rises from 45.3% to 47.6% after calibration. The 95% coverage moves from 96.9% to 94.5% while the mean area shrinks from 3.162 to 2.804 m^2. The 50% coverage at 5 mm moves slightly away from target. Across the four scenarios, post-calibration 50% coverage ranges from 47.6% to 49.1% and 95% coverage from 94.5% to 95.2% (Fig. 2).

3.4 Paired Comparison with the Physics Posterior

We sampled 32 fresh airborne flights at 5 mm for a paired benchmark. Two Bayesian runs remained below conditional ESS 100 after retry, leaving 30 common cases. The median endpoint errors are 0.379 m for constant acceleration, 0.314 m for the Bayesian sampler, 0.324 m for the




Figure 2: Observed coverage on the independent test set. The dotted lines mark the nominal levels. Per-noise scale adjustment changes little on its own. The density-rank adjustment has the largest effect at higher noise.

legacy MDN and 0.340 m for the final MDN (seed 11). The Bayesian and final MDN median energy scores are 0.210 and 0.211. On the same CPU, their median inference-plus-sampling times are 2.04 s and 1.02 ms. The small, ESS-filtered subset limits the accuracy ranking.

3.5 Distribution Shift

For each perturbation we keep the trained network and calibration fixed. We simulate the same initial parameters and compare trajectories that cross in flight under both the nominal and perturbed model. Evaluation uses the same observation perturbations at 5 mm. In a $3\,\mathrm{m\,s^{-1}}$ crosswind (5,001 paired flights), 50% coverage falls from 48.7% to 40.9% and 95% coverage from 94.3% to 92.6%. With exponential spin decay of time constant 0.5 s (5,003 pairs), 50% coverage falls from 48.2% to 36.3% even as median point error falls from 0.293 to 0.263 m. Wind and spin decay change the event label of 70 and 94 flights, respectively, among the 6,000 fresh launch states.

3.6 Sensitivity to the Drag Prior

Because the drag coefficient is the least constrained aerodynamic input, the case was re-run with the upper prior limit raised from 0.30 to 0.45. Three independent seeds were used at each setting, with 40,000 samples per stage (Table 5). The 50% area changes by +1.1% and the 95% area by −0.5%, both smaller than the spread between seeds, and the posterior mean moves by about 2 cm. Within this model, the reported regions are therefore insensitive to the upper drag limit; this does not establish insensitivity to other aerodynamic assumptions.

Table 5: Sensitivity of the case posterior to the upper limit of the drag prior ($\sigma = 5$ mm, three seeds, 40,000 samples per stage). Ranges are minima and maxima over seeds; means are averages over seeds.

C_D prior	50% area (m^2)	95% area (m^2)	Mean (Y, Z) (m)
$U[0.15, 0.30]$	0.213 (0.205–0.219)	0.806 (0.789–0.821)	(2.696, 1.988)
$U[0.15, 0.45]$	0.215 (0.210–0.222)	0.802 (0.792–0.809)	(2.689, 1.971)




Figure 3: Case posterior at $\sigma = 5$ mm for the main drag prior (left) and the widened prior (right). Contours and areas are from one realisation (seed 8047); the three-seed means and ranges are given in Table 5. The two regions are visually indistinguishable at the resolution of the plot.

3.7 Model-Form Check on Tracked Free-Kick Arcs

The statistical evaluation above is entirely simulation-based. As an external check of the model form, we used two airborne arcs from the ISSIA-3D annotations [8], tracked at 25 fps: frames 608–622 and 1144–1172, with the first six frames used to fit the initial state and the remaining frames held out. The arcs are free kicks and long passes, not penalties, and they carry centimetre-level reconstruction error; they can test the trajectory model but not the penalty prior.

Table 6 shows the held-out forecast RMSE. Gravity alone is clearly inadequate (0.697 and 2.179 m). Adding quadratic drag with $C_D = 0.22$ reduces the error to 0.489 and 1.546 m; $C_D = 0.45$ gives 0.469 and 1.584 m, so the larger drag is not better on both arcs. A vertical net-lift term fitted on the prefix reduces the error further, to 0.188 and 1.084 m, with fitted $L = 5.76 \pm 4.99$ and $6.89 \pm 3.83\,\mathrm{m\,s^{-2}}$ and fitted $C_D = 0.363 \pm 0.169$ and 0.328 ± 0.167. This is evidence that a vertical force term is worth considering, but the fitted parameters are not identifiable at the precision needed for calibration, and the lift term may absorb tracking or reconstruction error. We therefore use these arcs only as a model-form check, not as a calibration set.

Table 6: Held-out forecast error (RMSE, metres) for two ISSIA-3D airborne arcs. The first six frames of each arc are used to fit the initial state (and, for the last column, drag and vertical lift); later frames are held out. Final error is the error at the last observed frame.

Arc	Quantity	Gravity	$C_D = 0.22$	$C_D = 0.45$	Drag + lift
608–622	Forecast RMSE	0.697	0.489	0.469	**0.188**
	Final error	1.243	0.863	0.811	**0.308**
1144–1172	Forecast RMSE	2.179	1.546	1.584	**1.084**
	Final error	4.169	2.876	2.942	**2.119**

3.8 Prefix Forecasts on Tracked Flights

For two tracked DFL penalties [9], a separate physical inference uses the first three measured positions at the actual frame times and predicts the held-out portion in local coordinates. Table 7 compares drag with zero spin against the same drag prior and unknown spin. The assumed per-coordinate noise is 15 mm and the table averages two seeds. Rotation improves the first penalty's gate estimate and slightly worsens the second's. In two further checks, adding spin changes held-out RMSE from 0.338 to 0.366 m on an ISSIA segment and from 2.266 to 2.301 m on the two-dimensional reconstruction of the Barber and Carré figure [10] (at its 67 mm sensitivity setting).

Table 7: Two DFL penalties with seven scored positions before each reference crossing. Both trajectory RMSE and crossing-point error are in metres. The crossing forecasts condition on airborne arrival at each observed goal plane.

	Trajectory RMSE		Crossing error	
Event	Zero spin	Unknown spin	Zero spin	Unknown spin
J03WOH	0.347	0.292	0.645	0.543
J03WR9	0.309	0.305	0.542	0.553

Across 11 additional screened DFL match segments, unknown spin lowers held-out RMSE in 7 of 11 segments at each of the 15 and 30 mm assumptions. The paired median improvements are 0.027 and 0.011 m. These segments have no goal-plane endpoint labels, and screening on smooth flight and uncertain contact status limits generalisation. The tracked examples assess physical extrapolation on a case basis. They do not calibrate the MDN.

3.9 External replay of three 100 Hz curve kicks

Takeshi Asai provided ball-centre tracks for three curve kicks from the experiment in [20]. We used the first tracked frame as the time and horizontal origin and interpolated the measured crossing of a virtual plane 11 m ahead. Position-only forecasts used observations at 0, 50, and 100 ms. For the physical posterior and frozen P1 we assumed 10 mm per-coordinate position noise. P1's input and output heights were translated to and from its training origin using the published weights and calibration.

Table 8: Error at the virtual 11 m crossing, in centimetres. Spin-aided estimates are retrospective. The full-track row uses the reference window in fitting.

Method	Fig. 3	Sample 05	Sample 12
Constant acceleration	44.68	21.89	52.62
Canonical posterior, unknown spin	55.17	52.36	61.92
Canonical posterior, spin magnitude supplied	60.25	57.86	63.60
Frozen P1, height translation	54.49	49.87	59.57
Canonical full-track fit	0.20	1.12	0.65

The frozen P1 regions included all three references, while point errors remained about 50–60 cm. Three trials are insufficient to estimate real-world coverage. Spin magnitudes did not improve this posterior under the assumed spin-axis distribution. These values were smoothed using a nine-point moving average, and Sample 05's first spin value is at 150 ms, so the spin comparison is retrospective. Full-track fits attained trajectory RMSEs of 1.49–1.77 cm. A

separate effective-lift fit with a directional prior and a different lift law averaged 11.39 cm at the virtual plane, so that result does not isolate the effect of allowing position noise.




Figure 4: Asai curve kicks, trajectory comparisons, and frozen P1 prediction regions at the virtual 11 m plane. The full fit includes later observations. We thank Takeshi Asai for sharing the trials.

4 Discussion

The main gain is a better forecast density. At moderate noise, model D, model C and the final MDN often return similar point forecasts, yet the final network assigns more appropriate density to the true endpoint. Coverage and area give complementary checks. In the high-noise setting a calibrated inner region can cover more true endpoints while the outer region becomes smaller. Crosswind and spin decay show that accurate point forecasts can coexist with miscalibrated joint regions.

The Bayesian sampler exposes dependence on launch and aerodynamic assumptions, while the MDN amortises the inverse calculation and is useful for rapid sensitivity studies. Their agreement on the posed case is agreement within a shared physical model and prior. The original plausibility prior generates no launches below $18\,\mathrm{m\,s^{-1}}$ or exactly zero spin. The case forecast also assumes a known measurement noise scale. Real tracking errors, wind and spin are seldom independently known in the available examples.

All network endpoint metrics condition on airborne goal-plane crossing. For arbitrary kicks, the geometric in-frame probability would require multiplying $P(E \mid \mathbf{y}_1, \mathbf{y}_2, \sigma)$ by the conditional in-frame probability. The goal rectangle applies to the centre and ignores the ball radius in the in-frame criterion, contact with the frame and goalkeeper intervention. These distinctions

separate a geometric forecast from a match scoring probability. The limited DFL, ISSIA and figure-read cases cannot establish real-penalty coverage. The PFF World Cup release [11] is a possible source for further case audits.

Appendix B quantifies the information limit of the measurement design. At $\sigma = 5\,\text{mm}$ the two positions and the physical prior leave an irreducible median crossing spread of about 0.26 m, and the frozen network is within about 15% of that local bound. Further point-accuracy gains therefore require an improved measurement design rather than a larger model; the same calculation shows that a single additional 5 mm position would lower the bound by a factor of about two.

5 Conclusion and Outlook

Two early observations and a known start support a probabilistic forecast of the crossing location. At 5 mm, the calibrated MDN answers the posed case with mode $(2.62, 2.15)$ m, joint areas 0.177 and $0.775\,\text{m}^2$, and a 97.3% conditional in-frame probability. The final MDN has a median error of 0.290 m on the independent 5 mm test, within about 15% of the local information floor of the two-position design derived in Appendix B. Calibrated coverage is close to nominal under the simulation assumptions and degrades under physical shifts.

The next step is to collect high-rate, three-dimensional penalty tracks with independently characterised timing and tracking error. A sealed evaluation set should include misses, low-speed and low-spin shots, and early ground contact. A separate event model could then predict airborne crossing before the conditional location forecast is applied.

References

[1] International Football Association Board, *Laws of the Game 2025/26*, Laws 1 and 2 (field dimensions, penalty mark, ball). https://www.theifab.com/laws/latest/.

[2] T. Asai, K. Seo, O. Kobayashi, and R. Sakashita, "Fundamental aerodynamics of the soccer ball," *Sports Engineering* **10**(2), 101–109 (2007). https://doi.org/10.1007/BF02844207.

[3] T. Asai and K. Seo, "Aerodynamic drag of modern soccer balls," *SpringerPlus* **2**, 171 (2013). https://doi.org/10.1186/2193-1801-2-171.

[4] J. E. Goff and M. J. Carré, "Soccer ball lift coefficients via trajectory analysis," *European Journal of Physics* **31**(4), 775–784 (2010). https://doi.org/10.1088/0143-0807/31/4/007.

[5] J. E. Goff, J. Kelley, C. M. Hobson, K. Seo, T. Asai, and S. B. Choppin, "Creating drag and lift curves from soccer trajectories," *European Journal of Physics* **38**(4), 044003 (2017). https://doi.org/10.1088/1361-6404/aa6fcd.

[6] K. Bray and D. Kerwin, "Modelling the flight of a soccer ball in a direct free kick," *Journal of Sports Sciences* **21**(2), 75–85 (2003). https://doi.org/10.1080/0264041031000070994.

[7] D. P. Kingma and J. Ba, "Adam: A method for stochastic optimization," in *Proceedings of the 3rd International Conference on Learning Representations* (ICLR, 2015); arXiv:1412.6980.

[8] M. Gutiérrez-Pérez and A. Agudo, "SoccerNet-v3D: Leveraging sports broadcast replays for 3D scene understanding," arXiv:2504.10106 (2025). https://arxiv.org/abs/2504.10106.

[9] M. Bassek, R. Rein, H. Weber, and D. Memmert, “An integrated dataset of spatiotemporal and event data in elite soccer,” *Scientific Data* **12** (2025). https://doi.org/10.1038/s41597-025-04505-y.

[10] S. Barber and M. J. Carré, "The effect of surface geometry on soccer ball trajectories," *Sports Engineering* **13**(1), 47–55 (2010). https://doi.org/10.1007/s12283-010-0048-x.

[11] PFF FC, “Enhanced 2022 World Cup dataset” (2023). https://www.blog.fc.pff.com/blog/enhanced-2022-world-cup-dataset.

[12] C. M. Bishop, “Mixture density networks,” Technical Report NCRG/94/004, Aston University (1994).

[13] Joint Committee for Guides in Metrology, *Evaluation of Measurement Data—Guide to the Expression of Uncertainty in Measurement*, JCGM 100:2008.

[14] R. J. Hyndman, “Computing and graphing highest density regions,” *The American Statistician* **50**(2), 120–126 (1996). https://doi.org/10.1080/00031305.1996.10474359.

[15] T. Gneiting and A. E. Raftery, “Strictly proper scoring rules, prediction, and estimation,” *Journal of the American Statistical Association* **102**(477), 359–378 (2007). https://doi.org/10.1198/016214506000001437.

[16] C. R. Harris et al., “Array programming with NumPy,” *Nature* **585**, 357–362 (2020). https://doi.org/10.1038/s41586-020-2649-2.

[17] P. Virtanen et al., “SciPy 1.0: fundamental algorithms for scientific computing in Python,” *Nature Methods* **17**, 261–272 (2020). https://doi.org/10.1038/s41592-019-0686-2.

[18] A. Paszke et al., “PyTorch: An imperative style, high-performance deep learning library,” in *Advances in Neural Information Processing Systems* **32**, 8024–8035 (2019).

[19] J. D. Hunter, “Matplotlib: A 2D graphics environment,” *Computing in Science & Engineering* **9**(3), 90–95 (2007). https://doi.org/10.1109/MCSE.2007.55.

[20] T. Asai, K. Kimachi, R. Liu, M. Koido, M. Nakayama, J. E. Goff, and S. Hong, Measurements of the Flight Trajectory of a Spinning Soccer Ball and the Magnus Force Acting on It, *Proceedings* **49**, 88 (2020). DOI: 10.3390/proceedings2020049088.

A Propagation of Position Noise to Acceleration

Let the start $\mathbf{r}_0$ be exact and let the two observations be

$$\mathbf{r}_1 = \mathbf{r}_0 + \mathbf{v}\Delta t + \tfrac{1}{2}\mathbf{a}\Delta t^2 + \boldsymbol{\varepsilon}_1, \qquad \mathbf{r}_2 = \mathbf{r}_0 + 2\mathbf{v}\Delta t + 2\mathbf{a}\Delta t^2 + \boldsymbol{\varepsilon}_2, \tag{6}$$

with independent errors of variance σ^2 per component. Eliminating $\mathbf{v}$ gives the second difference

$$\mathbf{r}_2 - 2\mathbf{r}_1 + \mathbf{r}_0 = \mathbf{a}\Delta t^2 + \boldsymbol{\varepsilon}_2 - 2\boldsymbol{\varepsilon}_1, \tag{7}$$

whose component variance is $(1 + 4)\sigma^2 = 5\sigma^2$. Hence

$$\sigma_a = \frac{\sqrt{5}\,\sigma}{\Delta t^2}. \tag{8}$$

If the start is also noisy, the third error enters with unit weight and the variance becomes $6\sigma^2$, giving the conservative factor $\sqrt{6}$. At $\sigma = 5\,\mathrm{mm}$ and $\Delta t = 0.05\,\mathrm{s}$, $\sigma_a = 4.47\,\mathrm{m\,s^{-2}}$ for a

fixed start. For a fixed forecast time near 0.4 s, the acceleration term alone corresponds to a displacement scale of several tenths of a metre. The full crossing uncertainty also involves velocity errors and uncertainty in crossing time. This calculation motivates propagating the observation model through to the endpoint [13].

B Information Limits of the Early-Flight Forecast

Appendix A shows that two position measurements constrain the acceleration far more weakly than they constrain the position. This section turns that observation into quantitative lower bounds on the crossing forecast. The bounds depend on the measurement design and on the physical prior, not on a particular network, and they are compared below with the measured errors of the kinematic baseline and of the frozen P1 model.

B.1 Kinematic amplification of the unregularised extrapolation

The constant-acceleration baseline is a second-order Lagrange extrapolation of the exact start and the two observed positions. Writing the crossing time as $T = n\Delta t$, the extrapolant at the goal plane is

$$\mathbf{r}(T) = L_0(n)\,\mathbf{r}(0) + L_1(n)\,\mathbf{r}(\Delta t) + L_2(n)\,\mathbf{r}(2\Delta t), \tag{9}$$

with the Lagrange weights

$$L_0(n) = \frac{(n-1)(n-2)}{2}, \qquad L_1(n) = -n(n-2), \qquad L_2(n) = \frac{n(n-1)}{2}. \tag{10}$$

Because $\mathbf{r}(0)$ is exact, the two measured positions enter the crossing prediction with weights $L_1(n)$ and $L_2(n)$. For independent, isotropic per-coordinate errors of variance σ^2, every Cartesian component of the crossing point then has variance $\Lambda^2(n)\sigma^2$ with

$$\Lambda(n) = \sqrt{L_1(n)^2 + L_2(n)^2}. \tag{11}$$

The (Y, Z) error is therefore an isotropic two-dimensional Gaussian with per-axis standard deviation $\Lambda(n)\sigma$, whose Euclidean median is

$$\bar{e}_{\mathrm{kin}}(n) = \sqrt{2\ln 2}\,\Lambda(n)\,\sigma \approx 1.177\,\Lambda(n)\,\sigma. \tag{12}$$

Flights drawn from the launch prior of Table 1 reach the goal plane with a median arrival time of 0.441 s and a mean of 0.459 s, i.e. $n = 8.8$ and $n = 9.2$, giving $\Lambda = 69$ and 77. The arrival time varies between flights, so Λ ranges from about 35 to 220 across the prior; the median of the per-flight weights is 69. Table 9 compares Eq. (12) with the median error measured for the quadratic baseline on the held-out flights. The two agree to about 6% at $\sigma = 5$ mm and to better than 1% at 15 mm; at 2 mm the measured baseline is 16% larger than the bound, the residual being traceable to the crossing-time nonlinearity that Eq. (12) neglects.

Equation (12) explains why a deterministic extrapolation cannot be accurate at this noise level: at $\sigma = 5$ mm it already predicts a median error of about 0.41–0.45 m before any modelling error, so the failure of the constant-acceleration baseline is a property of the observation design rather than of the fit.

B.2 Local Bayesian floor under the physical prior

Regularisation by the physical prior can reduce this uncertainty, but not below a limit set by the information content of the two positions. To estimate that limit, collect the unknown launch

Table 9: Kinematic extrapolation bound for the unregularised quadratic baseline. The bound is the median of Eq. (12) over 3,332 airborne flights drawn from the launch prior (fixed start, two observations at 0.05 and 0.10 s); the measured baseline combines the same estimator with the full simulation pipeline.

σ (mm)	Kinematic bound (m)	Measured baseline (m)	Difference
2	0.163	0.190	+16%
5	0.407	0.432	+6%
10	0.814	–	–
15	1.222	1.217	−0.4%

state and aerodynamic coefficients into $\boldsymbol{\theta} = (\mathbf{v}_0, \boldsymbol{\omega}, C_D)$ and let the two observations be $\mathbf{h}(\boldsymbol{\theta})$ with Gaussian noise covariance $\sigma^2\mathbf{I}_6$; the goal-plane crossing is $\mathbf{g}(\boldsymbol{\theta}) = (Y, Z)$. Linearising around a sampled true trajectory with Jacobians $J_h = \partial\mathbf{h}/\partial\boldsymbol{\theta}$ and $J_g = \partial\mathbf{g}/\partial\boldsymbol{\theta}$, and approximating the independent uniform prior of Table 1 by a Gaussian with diagonal covariance $\Sigma_{\text{prior}} = \operatorname{diag}\left[(\theta_{\max} - \theta_{\min})^2/12\right]$, the posterior covariance of the parameters and of the crossing point is

$$\Sigma_{\text{post}} = \left(J_h^\top \Sigma_{\text{obs}}^{-1} J_h + \Sigma_{\text{prior}}^{-1}\right)^{-1}, \qquad \operatorname{Cov}(\mathbf{g}) = J_g\, \Sigma_{\text{post}}\, J_g^\top. \tag{13}$$

For a two-dimensional Gaussian, the median Euclidean error follows from $\operatorname{Cov}(\mathbf{g})$. Evaluating Eq. (13) per flight and taking the median gives the local Bayesian floor in Table 10. Without the prior, the same calculation with only the likelihood term is essentially the kinematic bound (median error 0.421 m at $\sigma = 5$ mm), so the physical prior is responsible for roughly a factor-of-two reduction of the attainable error at that noise level.

Table 10: Information limits and the frozen P1 model. The kinematic bound is Eq. (12); the local Bayesian floor is the median of Eq. (13) over 3,332 airborne prior flights; the third column repeats the floor when a third position at 0.15 s with the same noise is also available (a measurement-design variant, not additional input in the problem). The P1 column is the frozen model on the independent test set. Ratios in the last column are P1 / floor.

σ (mm)	Kinematic bound	Bayesian floor	Floor, 3 positions	P1 (m)	P1 / floor
2	0.163	0.119	0.045	0.130	1.09
5	0.407	0.255	0.103	0.290	1.14
10	0.814	0.386	0.188	0.466	1.21
15	1.222	0.443	0.251	0.566	1.28

B.3 Interpretation for the measurement design

Three conclusions follow from Table 10 and Fig. 5. First, the frozen P1 network is within 9%–28% of the local Bayesian floor at the four noise levels, and its error grows with noise more slowly than that of the kinematic baseline. Second, at $\sigma = 5$ mm the irreducible median spread of the crossing location is about 0.26 m: a point prediction cannot be sharp at this noise level, which is the physical reason for forecasting a full density and joint highest-density regions instead of a single crossing point. Third, the measurement design dominates the attainable accuracy: adding one more 5 mm position at 0.15 s would lower the floor from 0.26 to 0.10 m, whereas additional network capacity cannot recover information that the two positions do not contain. The same bound explains why the low-noise forecasts approach the floor most closely: as σ decreases, the gap in Table 10 is dominated by model and prior mismatch rather than by the observation noise.




Figure 5: (a) Median Euclidean crossing error against position noise. Grey circles: kinematic bound of Eq. (12); blue squares: local Bayesian floor of Eq. (13); cyan diamonds: floor with an additional position at 0.15 s; red crosses: measured quadratic baseline; green triangles: frozen P1 on the independent test set; orange triangles: the earlier 50k-flight MDN. (b) Ratio of the P1 median error to the local Bayesian floor at the four evaluation noise levels.

The floor is a local, model-conditional diagnostic rather than a proof of global optimality. It uses a Gaussianised uniform prior and a first-order propagation around sampled true trajectories, and it assumes that the simulator is the true model. Real tracks may also contain timing, tracking and wind errors (Sections 3.7 and 3.8), so the measured case-level errors can exceed the floor shown here.

Team 155

Report on the Use of AI

Systems used and how they were used. (i) The OpenAI ChatGPT desktop application with the Codex coding agent was used throughout the 48-hour contest. It was used for research planning, physics and statistics method design, writing and running the Python simulation and neural-network code, executing and checking experiments, checking physical parameters against the literature, validating measured data, and drafting and revising the paper and the repository documents. (ii) A DeepSeek Harness (DSH) coding agent (system label: DeepSeek Harness; model `deepseek-v4-flash-vision-exp`) acted as a second AI agent. It maintained and synchronized the shared repository, independently re-computed and reviewed the physics results, added further data analyses, designed delegated experiments, and prepared this report. (iii) Records of any additional generative-AI tools used by other team members are given in the final subsection.

What is reproduced below. The exact wording of every query sent by the team to each AI system is reproduced verbatim, followed by the complete text of each AI response that the team received. Internal reasoning traces, tool-invocation traces and shell/program output produced by the AI tools are not reproduced, because they are not output delivered to the team; the responses below are the complete visible output. The material is reproduced in the language in which it was written. **The AI tools were also used to generate, modify and verify computer code and result files that are part of the submitted repository and paper; all reported results were checked by the team and by a second AI agent, and they are reproducible from the repository.**

Note on language. The team's working language was Chinese, so many queries and outputs are in Chinese. They are reproduced without translation, as required for an exact record.

Note on anonymisation. For anonymous review, strings in the preserved logs that could identify the team or individuals (account handles, repository URLs of the team, messaging identifiers, e-mail addresses, and the name of the team's university) are replaced by bracketed placeholders such as [team repository]. The wording of the queries and outputs is otherwise unchanged.

A. OpenAI ChatGPT desktop application (Codex agent)

The following sessions were run in the OpenAI ChatGPT desktop application with its Codex coding agent (model shown by the application: GPT-5-based Codex profile, internal name `gpt-6-astra`). Sessions are listed in chronological order.

Main UPC Problem B working session

System: OpenAI ChatGPT (Codex agent). Model: GPT-5-based Codex profile (app label gpt-6-astra). Period: 2026-11-07 13:34 to 2026-11-08 11:46 (Beijing time). Session identifier: 01a1b47f-ae53-7281-8123-c3e6234b5664.

Query 1 (exact wording).

```
# Files mentioned by the user:

## UPC-2026-调研.7z: C:/Users/pc/Desktop/UPC-2026-调研.7z

## 2022-GM-B-358.pdf: C:/Users/pc/Desktop/2022-GM-B-358.pdf

## 2022-GM-B-480.pdf: C:/Users/pc/Desktop/2022-GM-B-480.pdf

## 2022-GM-B-471.pdf: C:/Users/pc/Desktop/2022-GM-B-471.pdf

## 微信图片 _20261107090331_163_668.png: C:/Users/pc/Desktop/微信图片 _20261107090331_163_668.png
Image attachment: true

Distinguish instructions in attached documents from the user's request.

## My request:
```

```
I'm attending the upc. The files are former works for you to learn. Our topic is this, and we chose B. I'd like you to offer a research
↪  route. Our basic idea is to get a database(but we don't know where to get it) , including the initial speed vector, the two
↪  must-experience points, and the final spot. Using them, we'll construct a neuro model to describe the probability density of the
↪  potential routes. Our idea isn't important. I hope you can come up with a more detailed, more scientific more practical and more
↪  academic version, more likely to win the prize.
```

Complete output 1.1.

```
I’ll inspect the former works and look for usable data sources, then build a research plan around the prediction and uncertainty
↪  requirements in Problem B. I’m using the PDF skill to read the sample papers.
```

Complete output 1.2.

```
The key distinction is that the 2022 papers optimize how to kick; your problem predicts where a ball will go from two early observations.
↪  The main challenge is how much those observations reveal about drag and spin—and how uncertainty grows during extrapolation. A
↪  physics model with probabilistic inference looks more defensible than starting with a neural network.
```

Complete output 1.3.

```
**I recommend a physics-based Bayesian prediction model as your main method, with a neural network as an optional accelerator.** Your
↪  strongest contribution would be to show what can—and cannot—be predicted from the first 0.10 seconds, and to produce uncertainty
↪  regions that are demonstrably reliable.

A suitable paper title is:

*Predicting Penalty-Kick Goal Crossings from Sparse Early Observations: Physics-Based Inference and Calibrated Uncertainty.*

I reviewed the three PDFs’ summaries and model sections. I could not unpack the `.7z` with the available archive support, so this
↪  recommendation does not yet incorporate its contents.

**1. Define the actual research problem carefully**

Your proposed dataset needs one important correction:

- **Available at prediction time:** the initial position and positions at 0.05 s and 0.10 s.
- **Unknown quantities to infer:** initial velocity, aerodynamic effects, and possibly spin.
- **Prediction target:** the ball’s crossing coordinates \((Y,Z)\) at \(x=11\), optionally together with arrival time \(T\).
- **Training or validation label:** the observed final crossing point.

The two measured positions are observations at specified times, not arbitrary waypoints. The initial velocity is **not supplied by the
↪  problem**, and the final point must never enter the model as an input.

Your desired output is therefore

\[
p(Y,Z,T\mid \mathbf r(0),\mathbf r(0.05),\mathbf r(0.10)).
\]

Predicting this distribution is more directly useful than estimating a probability density over all possible complete paths. You can still
↪  display sampled paths to explain the result.

**2. What to learn from the former papers**

The 2022 papers address a different question: choosing launch conditions that produce successful shots. Their useful foundation is a
↪  forward simulator incorporating gravity, drag, and Magnus force:

:codex-file-citation{path="C:/Users/pc/Desktop/2022-GM-B-358.pdf" purpose="source"}

:codex-file-citation{path="C:/Users/pc/Desktop/2022-GM-B-471.pdf" purpose="source"}

:codex-file-citation{path="C:/Users/pc/Desktop/2022-GM-B-480.pdf" purpose="source"}

Your task reverses that process:

\[
\text{early observations}
\longrightarrow
\text{plausible physical states}
```

```
\longrightarrow
\text{distribution of goal crossings}.
\]

Borrow the modeling structure, but independently check coefficients, units, coordinate conventions, numerical accuracy, and assumptions.
↪  Their goalkeeper optimization sections should not become the center of your paper.

**3. Build a hierarchy of models**

A convincing paper needs comparisons that show which additional physics actually improves prediction.

| Model | Purpose | Main limitation |
|---|---|---|
| Straight-line extrapolation | Simplest reference | Ignores gravity and curvature |
| Gravity-only projectile | Basic physical baseline | Ignores aerodynamic forces |
| Constant-acceleration fit | Uses curvature implied by the three positions | Extrapolates noisy acceleration |
| Gravity + quadratic drag | Practical physical model | Cannot explain all spin-induced curvature |
| Gravity + drag + effective Magnus force, with Bayesian inference | Recommended principal model | Requires justified priors and
↪  uncertainty analysis |
| Neural conditional density estimator | Optional fast approximation | Must demonstrate an advantage over direct inference |

For the physical simulator, use

\[
\dot{\mathbf r}=\mathbf v,\qquad
m\dot{\mathbf v}
=m\mathbf g
-\frac12\rho A C_D|\mathbf u|\mathbf u
+\mathbf F_M,
\]

where \(\mathbf u=\mathbf v-\mathbf w\) is velocity relative to wind.

Parameterize Magnus force through a justified lift coefficient and spin direction. Start with constant spin and constant aerodynamic
↪  coefficients during the short flight; test more elaborate variants only if they change the prediction materially.

Published experiments provide a sounder basis for aerodynamic coefficients than choosing them to obtain an attractive trajectory. Useful
↪  starting sources are [Asai and colleagues' soccer-ball aerodynamics
↪  study](https://www.jstage.jst.go.jp/article/jjpehss/52/1/52_3/_article/-char/en) and [Kelley and colleagues' trajectory-based drag
↪  and lift estimation](https://shura.shu.ac.uk/15728/1/Kelley%20-%20Creating%20drag%20and%20lift%20curves%20%28AM%29.pdf).

Use adaptive numerical integration and an event detector for \(x=11\). Check convergence by tightening numerical tolerances.

**4. Make identifiability your central scientific question**

Three positions give two displacement vectors. They contain information about velocity and curvature, but they do not automatically
↪  determine velocity, spin, drag, wind, and their future evolution separately.

For example, lateral curvature may reflect different combinations of spin and wind. Several physical parameter combinations can agree with
↪  the early observations while producing different endpoints.

This leads to a strong research question:

> How tightly can the goal crossing be constrained when multiple physical explanations fit the same early observations?

Investigate it in two ways:

- Calculate the sensitivity of the observations to each unknown parameter; inspect singular values of the resulting Jacobian.
- Show several physically plausible trajectories that fit the early observations but diverge later.

Avoid fitting too many freely varying parameters. Begin with still air, a literature-based drag prior, and a reduced representation of
↪  lift. Treat wind, coefficient variation, and spin decay as robustness experiments.

**5. Use Bayesian inference to turn ambiguity into a prediction**

Let \(\theta\) contain initial velocity and the selected aerodynamic parameters. Write the observation model as

\[
\mathbf r_i^{\rm obs}
=\mathbf r(t_i;\theta)+\boldsymbol\epsilon_i,
\qquad
\boldsymbol\epsilon_i\sim N(0,\Sigma_i).
\]
```

```
Then

\[
p(\theta\mid D)\propto p(D\mid\theta)p(\theta).
\]

The computational procedure is straightforward:

1. Define physically defensible parameter priors.
2. Find parameter combinations consistent with the observed positions.
3. Sample their posterior distribution using importance sampling, sequential Monte Carlo, or MCMC.
4. Integrate each sampled trajectory to the goal plane.
5. Summarize the resulting \((Y,Z,T)\) samples.

Report a point prediction, joint 50% and 95% prediction regions, and arrival-time uncertainty. If you report the “most likely point,”
↪  define it as the mode of a specified endpoint density estimator; the mean is a different quantity.

The prompt supplies no measurement-error scale. **Do not invent a unique numerical uncertainty as though it were given.** Separate:

- exact-coordinate idealization;
- rounding uncertainty, if interpreting the displayed decimals as rounded;
- realistic measurement-error scenarios;
- uncertainty in aerodynamic assumptions.

Keep misses in the prediction distribution. Only condition on the ball entering the goal when explicitly presenting that conditional
↪  result.

**6. Where to get data**

I would not make the project depend on finding a large ready-made penalty dataset containing accurate early 3D coordinates, spin, and
↪  final crossings. The sources I checked do not establish such a complete dataset.

Use three complementary sources:

| Source | Recommended use | Important qualification |
|---|---|---|
| Published aerodynamic experiments | Set and vary physical parameter priors | Ball design and experimental conditions matter |
| Synthetic trajectories | Develop inference and run controlled tests | Simulator success alone does not establish real-world accuracy |
| Small real experimental dataset | Independently validate endpoints and uncertainty | Requires calibration and synchronization |

For public data, [SoccerNet-v3D and ISSIA-3D](https://arxiv.org/abs/2504.10106) are relevant leads: they support 3D soccer localization
↪  using calibrated, synchronized views. Check whether their temporal coverage and annotations support complete penalty flights before
↪  committing to them.

[SoccerNet action spotting](https://www.soccer-net.org/tasks/action-spotting) can help locate penalty events, but event labels are not
↪  precise 3D trajectory measurements. [SoccerKicks](https://github.com/nayariml/SoccerKicks) concerns reconstructed **human body
↪  motion**, so it is not the ball-flight database you need.

If equipment and time permit, collect roughly **30–60 calibrated kicks as a feasibility target**, not as a claim of sufficient statistical
↪  power:

- Use two synchronized cameras with overlapping views.
- Calibrate their geometry and establish the coordinate frame.
- Prefer high-frame-rate recording.
- Reconstruct ball centers and quantify reconstruction error.
- Use only observations through 0.10 s for prediction.
- Reserve later observations for validation.

A single pitch-plane homography cannot correctly reconstruct an airborne ball’s 3D position. If you can measure only the goal crossing
↪  reliably, that still supports endpoint validation.

**7. Keep your neural idea—but give it a clear role**

If the core inference works and time remains, train a small mixture-density network to approximate

\[
p_\phi(Y,Z\mid\mathbf r_{0.05},\mathbf r_{0.10}).
\]

Generate its training examples with the physical simulator, including observation noise and parameter variation. Start with tens of
↪  thousands of examples and use learning curves to determine whether more help.

Compare it with direct Bayesian inference on:
```

- endpoint accuracy;
- probability calibration;
- prediction-region size;
- inference time;
- robustness to changed physical assumptions.

The academically useful claim would be **faster probabilistic inference with measured accuracy and calibration**, not simply “we used a neural network.”

Do not validate exclusively against the same simulator and parameter distribution used for training. Test altered drag laws, different lift assumptions, and real measurements where available.

8. Design the validation before polishing the model

Your most valuable results table should include:

Question	Measurement
How accurate is the point prediction?	Endpoint error in meters; median and upper-tail error
Are uncertainty regions reliable?	Empirical coverage of joint 50%, 80%, and 95% regions
Are regions useful rather than excessively broad?	Region area, compared at similar coverage
Is the full distribution informative?	Energy score or another proper probabilistic score
Does additional physics help?	Ablation comparisons
Is the method practical?	Runtime per prediction

Split real data by kick, session, or ball—not randomly by frames. Report uncertainty on evaluation statistics, especially with a small experimental sample.

A particularly informative figure would plot endpoint error and prediction-region area against observation noise. Another could show how prediction improves when the observation window grows; label that as an extension beyond the required 0.10 s case.

9. A useful preliminary calculation for the supplied example

The quadratic trajectory passing exactly through the three stated positions is

$$
x(t)=30.4t-8t^2,\qquad
y(t)=9.4t-8t^2,\qquad
z(t)=0.11+6.9t-6t^2.
$$

Its first crossing of $x=11$ occurs at approximately

$$
T=0.405\ \mathrm{s},\qquad
(Y,Z)=(2.495,\ 1.921)\ \mathrm{m}.
$$

This is a constant-acceleration baseline, not a validated final answer. It provides an immediate reference against which to compare your physical posterior predictions.

It also exposes the uncertainty problem. The acceleration estimate uses

$$
\widehat{\mathbf a}
=\frac{\mathbf r(0.10)-2\mathbf r(0.05)+\mathbf r(0)}
{0.05^2}.
$$

If the initial position is exact and each later coordinate has independent 1 cm standard-deviation error, the acceleration standard deviation is already approximately **8.9 m/s² per component**. This is why exact interpolation can look excellent while extrapolation remains unreliable.

10. Prioritize the work in this order

1. Implement and check the analytical baselines.
2. Build and verify the physical forward simulator.
3. Investigate identifiability and observation-error sensitivity.
4. Implement posterior sampling and endpoint uncertainty.
5. Validate using held-out simulations with changed assumptions and any real data available.
6. Add neural acceleration only if the core results are already strong.
7. Write around the evidence: model assumptions, comparisons, calibration, and limitations.

```
The strongest paper would make a precise, tested claim: **given two early observations and explicitly stated physical and measurement
↪  assumptions, this method predicts a goal-crossing distribution whose accuracy and coverage have been measured.** That is a more
↪  defensible competitive contribution than an elaborate network trained on an uncertain database.
```

Query 2 (exact wording).

```
offer a Chinese version to me to understand. Also I'd like to see the result in file
```

Complete output 2.1.

```
我会把研究路线整理成中文，并保存为 Markdown 文件，方便你下载、阅读和与队友讨论。
```

Complete output 2.2.

```
已整理成完整中文版，包含研究思路、模型公式、数据来源、实验验证、神经网络的作用和执行顺序。

[下载 / 阅读《UPC B 题中文研究路线》](C:/Users/pc/Documents/ChatGPT/upc/UPC-B 题-中文研究路线.md)

核心建议是：** 先建立物理模型，用贝叶斯推断描述预测的不确定性，再考虑神经网络加速。** 重点证明“预测有多准、给出的概率范围是否可信”。

题目案例的恒加速度基线结果为：约 **0.405秒**到达球门平面，穿越坐标约为 **(11, 2.495, 1.921)米**。这只是对照结果，尚不是经过验证的最终预测。
```

Query 3 (exact wording).

```
nice idea. I unpacked the zip for you:"E:\UPC-2026-调研", learn from them to get the potential factor contributing to a high score work
```

Complete output 3.1.

```
我会查看解压后的材料，重点分析高质量作品在建模、验证、创新和论文表达上的共同特点，再提炼成适用于你们 B 题的建议。
```

Complete output 3.2.

```
材料中最一致的经验是：抓住主要物理因素、解释简化依据，并把误差和验证做扎实。我还发现汇总笔记有几处把经验推断写得过强，例如把“性能目标”
↪  当成已实现成绩；这些不能直接作为获奖依据。我会在报告里区分原始证据和针对你们题目的建议。
```

Complete output 3.3.

```
已重点阅读获奖队访谈、技术文章、官方规则和高分笔记，并整理成中文报告：

[下载《高分作品因素与 B 题路线修订》](C:/Users/pc/Documents/ChatGPT/upc/UPC-B 题-高分作品因素与路线修订.md)

** 最值得借鉴的是六点：**

| 潜在优势 | 对你们 B 题的具体建议 |
|---|---|
| 有依据地简化模型 | 先控制未知参数数量，说明为何忽略风或旋转衰减 |
| 解释模型成立条件 | 明确观测误差、球心坐标、触地处理和适用范围 |
| 针对具体难点创新 | 聚焦“两次早期观测为何难以稳定外推” |
| 验证充分 | 比较基线，检查数值收敛、预测误差和区域覆盖率 |
| 结果直接可用 | 输出穿越点、概率区域、到达时间及条件 |
| 写作与计算同步 | 从开始就记录参数来源、假设和验证设计 |

这些经验在[[university]金奖队访谈](E:/UPC-2026-调研/UPC-2026-调研/raw/chinese/[university]-2024-UPC获奖者说-化繁为简厚积薄发.md)和[南航获奖
↪  报道](E:/UPC-2026-调研/UPC-2026-调研/raw/chinese/WeChat-2025-金奖加5.md)中有具体支持，但材料没有评委评分，不能据此断言获奖原因或评分权重。

**对原路线最重要的调整：优先做透“信息有限时，预测是否可信”，把神经网络和大规模数据采集降为可选项。** 最有说服力的亮点，
↪  是证明你们给出的95%预测区域确实具有接近95%的覆盖率，同时区域足够小、有实际意义。

另外发现两处资料问题：萨桑多文章的部分数字是 ** 性能目标，不是已验证成绩 **；“必须使用 MATLAB”也不是通用官方要求。

本次还核对了规则：如果使用生成式 AI 参与论文写作，文末需要记录系统、原始提问和完整输出，建议保留本次对话。
↪  [官方规则](https://www.uphysicsc.com/contestrules.html)
```

Query 4 (exact wording).

```
Modify our version accordingly
```

Complete output 4.1.

```
我会直接修订原来的中文版研究路线：收紧模型范围，把可辨识性、误差校准和独立验证设为主线，并将神经网络与实测采集改为可选拓展。
```

Complete output 4.2.

```
已直接更新原文件：[阅读 / 下载修订版研究路线](C:/Users/pc/Documents/ChatGPT/upc/UPC-B 题-中文研究路线.md)。

主要修改：

- 收紧未知参数范围，增加假设依据与失效条件。
- 将可辨识性、误差传播和独立校准检验设为核心。
- 明确神经网络、数据库检索和实测采集的优先级与止损条件。
- 增加案例结果卡、阶段交付要求和论文检查要点。
- 更新资料来源，明确区分研究计划与已验证结果。
```

Query 5 (exact wording).

```
我的想法是，目前我们没有办法自己去做实际数据的采集，所以我们需要联系别的合作方来收集到真实数据。我们想要用收集到的真实数据和本地仿真对比，
↪  在本地构建起仿真数据集，然后针对这个训练神经网络。我本地有仿真的环境：anaconda或者miniconda
```

Complete output 5.1.

```
这个方案可行：**用独立真实数据校验物理仿真，再生成仿真数据训练概率预测网络。** Anaconda 或 Miniconda 足以管理所需的 Python 环境；
↪  目前无需急着安装新的仿真软件。

不过，“联系合作方”需要区分两种情况：**获取已公开、已存在的数据**，与**让队外人员在比赛期间为你们采集、处理数据或参与分析**。
↪  我们刚核对的[官方规则](https://www.uphysicsc.com/contestrules.html)禁止比赛开始后由队外人员作出贡献。因此，
↪  当前比赛应优先采用公开数据或赛前已取得的数据；定制采集适合作为赛后研究延伸。

建议把路线调整成下面这个顺序：

| 阶段 | 具体任务 | 交付结果 |
|---|---|---|
| 1. 筛选真实数据 | 核查三维坐标、时间戳、完整飞行段与测量精度 | 可用数据清单 |
| 2. 校准物理仿真 | 用真实轨迹估计合理的阻力、升力及误差范围 | 参数分布与拟合残差 |
| 3. 独立验证仿真 | 在未参与校准的真实踢球样本上比较轨迹和端点 | 仿真误差及适用范围 |
| 4. 生成仿真数据 | 随机采样物理参数，加入观测误差 | 训练、验证、测试数据集 |
| 5. 训练概率网络 | 输入两个早期位置，预测球门穿越位置分布 | 点预测、概率区域 |
| 6. 真实数据最终测试 | 使用完全留出的真实样本 | 实际预测误差与覆盖率 |

** 最关键的是：真实数据不能全部拿去校准仿真，再用同一批数据宣称预测准确。** 应按整次踢球划分校准集和测试集，数据足够时再按球型或实验场次划分。

对于真实数据，优先寻找：

- 每次踢球的 `时间、x、y、z`，覆盖离脚到球门附近的过程。
- 坐标系、单位、离脚时刻定义。
- 球门穿越点，或足以计算穿越点的后续轨迹。
- 测量误差、采样频率和相机标定说明。
- 球的型号、质量和半径；旋转、初速度、风速属于有则更好的信息。

**初速度和旋转不是必须已经标注，但缺少它们会增加校准的不确定性。** 如果只有普通转播视频，三维重建可能成为独立的大项目，不能当作开箱即用的数据。

本地实现可以保持简单：

- **NumPy、SciPy**：物理方程、数值积分、参数估计。
- **pandas、Matplotlib**：数据整理与误差分析。
- **PyTorch**：训练小型混合密度网络。

网络输入仍然只能包含题目允许的早期观测；真实初速度、旋转等可以用于仿真生成和验证，不能偷偷成为预测输入。

我建议设置两个可交付版本：**找到合格真实数据，就完成“真实校准＋仿真训练＋真实测试”；暂时找不到，则完成经过交叉模型测试的仿真研究，
↪  明确尚未验证现实准确性。** 这样数据获取不会阻塞整个比赛。
```

Query 6 (exact wording).

做一个完整的实验方案吧，务必清晰，简洁扼要

Complete output 6.1.

建议实验名称：** 基于真实轨迹校准与仿真训练的点球穿越位置概率预测 **。

实验目标：仅用球心在 **0.05 s、0.10 s** 的三维位置，预测球第一次向前穿越 **x=11 m** 时的位置，并给出可信的不确定性区域。

**1. 数据准备 **

优先使用公开或赛前已取得的真实数据。比赛期间不安排队外人员定制采集、处理或分析。

数据项	要求
必需	每次踢球的时间戳、三维球心坐标、坐标单位、离脚时刻
验证标签	球门穿越位置，或足够完整的后续轨迹
质量信息	采样频率、标定方式、测量误差
可选	初速度、旋转、球型、风速

统一坐标系与时间零点，检查缺帧和异常值。无法可靠恢复三维位置的数据，不用于主要定量验证。

将真实数据按 ** 整次踢球 ** 划分：

- ** 校准集：约 70%**，估计物理参数和误差范围。
- ** 最终测试集：约 30%**，封存，最后一次性评价。
- 数据很少时采用交叉验证，并说明结论的不确定性。

**2. 构建并校准物理仿真 **

采用三维运动方程，依次加入：

1. 重力。
2. 二次空气阻力。
3. 有效马格努斯升力。

使用真实校准集的完整轨迹，估计初速度及空气动力学参数；结合文献约束，避免参数随意变化。检查轨迹残差、端点误差和参数合理性。

验证程序：关闭空气动力项时应恢复抛体解析解；收紧积分容差后结果应稳定。模拟在球门穿越或触地时终止，分别记录事件类别。

**3. 生成本地仿真数据集 **

先生成 **1 万条轨迹 ** 跑通流程，再根据学习曲线扩展至约 **10 万条 **；这只是初始规模建议。

内容	生成方式
初速度与有效升力参数	从真实校准结果及文献支持的范围采样
阻力、球参数	在合理范围内变化，保留参数相关性
观测误差	根据真实测量质量加入；额外设置误差情景
网络输入	`$x_{0.05}, y_{0.05}, z_{0.05}, x_{0.10}, y_{0.10}, z_{0.10}$`
预测标签	球门穿越坐标 `Y,Z`
辅助记录	到达时间、真实参数、是否触地或未穿越

按完整轨迹划分 **80% 训练、10% 验证、10% 测试 **。同一轨迹添加不同噪声后的版本必须放在同一集合，避免泄漏。

触地或未穿越样本单独记录；端点预测明确以“有效空中穿越”为适用条件，不能无说明地删除。

**4. 训练神经网络 **

采用小型 ** 混合密度网络（MDN）**：

- 输入：六个早期位置坐标。
- 输出：球门平面上的二维混合高斯分布。
- 损失函数：真实端点的负对数似然。
- 用验证集选择网络规模和混合分量数，采用早停。
- 输入标准化参数仅从训练集计算。

最终输出：** 最可能穿越点、联合 50% 和 95% 预测区域 **。若使用不同的已知测量精度，应将精度作为额外条件，或分别训练模型。

**5. 设置对照实验 **

```
| 方法 | 作用 |
|---|---|
| 恒加速度外推 | 简单基线 |
| 物理约束推断 | 判断网络是否优于直接物理方法 |
| 普通回归网络 | 判断概率输出的价值 |
| 混合密度网络 | 主体方法 |

再做两项消融：

- 使用未经真实数据校准的仿真训练，对比校准后的效果。
- 不加入观测噪声训练，对比加入噪声后的稳健性。

所有方法使用相同测试输入。

**6. 评价与独立测试 **

依次进行：留出仿真测试 → 改变空气动力学假设的测试 → 封存真实数据测试。

报告四项主要指标：

- ** 端点误差 **：中位数及 90% 分位数，单位米。
- ** 联合区域覆盖率 **：50%、95% 区域实际包含真值的比例。
- ** 区域面积 **：在相近覆盖率下，越小越有信息量。
- ** 单次预测耗时 **。

按速度、旋转强度和观测误差分组检查。覆盖率须附样本量及统计误差；不能只靠扩大区域获得好看的覆盖率。最终测试结果不再用于调参。

**7. 应用于题目案例 **

输入：

```text
t=0.05 s: (1.50, 0.45, 0.44)
t=0.10 s: (2.96, 0.86, 0.74)
```

输出一张结果卡：预测点、概率热图、50% 与 95% 区域、误差假设及模型适用范围。恒加速度基线为 **(Y,Z)≈(2.495,1.921) m**，用于比较。

题目未提供真实终点，** 该案例只能展示预测，不能用于证明准确性 **。

**8. 环境、分工与交付 **

本地使用独立 Conda 环境，安装 **NumPy、SciPy、pandas、Matplotlib、PyTorch**。先用 CPU 完成小规模流程，有可用 GPU 再扩大训练。

三人分别主负责：数据与物理校准、仿真与网络、验证与论文；写作同步进行。

最终交付：

- 数据说明、参数表与可复现代码。
- 模型比较表。
- 误差分布图、覆盖率图、案例概率热图。
- 适用条件和失败案例分析。

** 止损原则：真实数据不合格时，先完成仿真实验，明确尚未验证现实准确性；核心验证未完成时，不扩大网络、不增加复杂物理项。**
```

Query 7 (exact wording).

```
输出为 md，要和队友分享
```

Complete output 7.1.

```
我会将实验方案保存为 Markdown 文件，方便直接分享给队友。
```

Complete output 7.2.

```
已整理为 Markdown，包含实验流程、数据要求、验证指标、团队分工和交付清单。

[下载《UPC B 题团队实验方案》](C:/Users/pc/Documents/ChatGPT/upc/UPC-B 题-团队实验方案.md)
```

Query 8 (exact wording).

```
能不能帮我寻找一些可能的数据获取方式？或者联系别的作者获取现有数据集（这是合法的）
```

Complete output 8.1.

```
我会优先寻找可下载的三维足球轨迹数据，以及论文作者公开的数据申请渠道，整理适配程度和联系建议。若需要发邮件，我会先准备好具体收件人与邮件内容。
```

Complete output 8.2.

```
找到两条较有希望的路径：ISSIA-3D 已公开三维球位置 CSV；另一个 ball3d 项目提供真实比赛的三角测量轨迹与分段标注，还公开了作者邮箱。
↪  下一步会核查字段，尤其区分实测重建轨迹与模型预测轨迹，避免把仿真结果误当真实标签。
```

Complete output 8.3.

```
可以，** 申请作者已有的数据和文档，是值得推进的路径 **。我已找到几个具体渠道，并下载了一份数据做了初步检查。

| 优先级 | 数据来源 | 已确认内容 | 尚需核查 |
|---|---|---|---|
| **1** | [ISSIA-3D](https://github.com/mguti97/SoccerNet-v3D) | 公开三维球位置、帧号、重投影误差；已下载 | 连续空中轨迹、帧率、是否包含点球 |
| **2** | [ball3d](https://github.com/lukaszgrad/ball3d/blob/main/DATA.md) | 三角测量参考轨迹、接触分段、时间信息及下载入口 | 下载权限、
↪  点球数量、参考轨迹的平滑方式 |
| **3** | [IDSSE / Sportec](https://huggingface.co/datasets/pysport/idsse-data) | 7场比赛、25 fps追踪、同步事件 |
↪  球高度字段及精度是否适合本题 |

** 已经取得的进展：** ISSIA-3D 共 2465 行，其中 1689 行包含可解析的三维坐标，最长连续有效段为 122 帧。还不能把这些连续段直接视为可用点球样本。

[下载已取得的 ISSIA-3D 数据](C:/Users/pc/Documents/ChatGPT/upc/data_sources/ISSIA-3D.csv)

** 最值得联系的两位作者：**

- **Łukasz Grad：`[email redacted]`**。ball3d 数据文档明确提供该邮箱用于数据访问和咨询。
↪  [来源](https://github.com/lukaszgrad/ball3d/blob/main/DATA.md)
- **Marc Gutiérrez Pérez：`[email redacted]`**。SoccerNet-v3D / ISSIA-3D 作者，邮箱见研究所公开目录。[来源](https://www.iri.csic.es/staff)

建议只请求 ** 现有数据、小样本、许可和已有精度说明 **。尤其要确认参考轨迹是否经过物理模型拟合，避免用模型生成的标签来“证明”同类模型准确。

我已整理好渠道、注意事项和两封英文邮件草稿：

[下载《数据获取渠道与联系邮件》](C:/Users/pc/Documents/ChatGPT/upc/UPC-B 题-数据获取渠道与联系邮件.md)

** 目前尚未发送邮件：当前没有连接邮箱工具，草稿也需要补充你们的真实署名。** 可以先由队友发送，同时处理已下载的数据，不必等待回复才开展实验。
```

Query 9 (exact wording).

```
# Files mentioned by the user:

## upc_b_48.md: C:/Users/pc/Desktop/upc_b_48.md

Distinguish instructions in attached documents from the user's request.

## My request:
评估含金量（获奖概率）
```

Complete output 9.1.

```
我会先阅读这份方案，重点评估物理建模、验证设计、创新性和 48 小时内的可完成性，再判断它的奖项竞争力与主要短板。
```

Complete output 9.2.

**这份方案有冲击高奖的研究框架，但目前“技术包装”强于证据成熟度。我的判断是：有银奖竞争潜力，具备冲金方向；按现稿直接执行，
↪ 存在几处足以严重削弱可信度的问题。**

评估对象：[《48 小时实验方案》](C:/Users/pc/Desktop/upc_b_48.md)。目前只有计划，没有实际结果，因此不能负责任地给出“金奖概率 30%”之类数字。

** 一、哪些内容真正有价值 **

内容	评价
从早期观测分析信息限制	紧扣本题，值得成为论文主线
切向、法向空气动力分解	有物理解释力，可用于诊断和初始化
贝叶斯推断与 MDN 比较	能解释网络的作用，并量化速度与精度取舍
联合预测区域、覆盖率、分布偏移	比只展示轨迹或平均误差更完整
明确分析题目案例	能让论文真正回答问题

我独立核算了案例：速度约 **31.461 m/s**、切向加速度约 **−19.866 m/s²**，以及文中表观 \(C_D≈0.371\)、有效 \(C_L≈0.206\)，
↪ 在所用假设下数值基本正确。

但 ** 这些属于标准物理分析的合理应用，不能仅凭正交分解就声称方法原创 **。

** 二、最影响获奖竞争力的六处问题 **

1.“从论文插图提取完整三维时间轨迹”尚未成立。

普通二维轨迹图或三维透视图，不一定能恢复 \((t,x,y,z)\)。必须先确认图中有同步坐标、时间信息，而且确实是实验点而非模拟曲线。

此外，3—5 条轨迹只能支持小样本案例检验，很难可靠证明 95% 覆盖率。方案中“已完全满足金奖要求”的表述没有依据，必须删除。

2. 马格努斯力公式前后不一致，是实质性物理风险。

前面使用：

\[
C_Lv^2(\hat{\omega}\times\hat v)
\]

后面却将叉积方向归一化，同时仍用总转速定义 \(C_L\)。后者会导致：** 旋转轴几乎平行速度时，升力仍可能保持有限大小，完全平行时还会除零。**

应统一升力系数定义，并保证横向旋转趋于零时升力也趋于零。否则后续大量仿真和网络训练都可能建立在错误标签上。

3. 贝叶斯采样不能直接称为“精确基准”或“理论天花板”。

如果从局部提议分布 \(q(\theta)\) 抽样，权重应包含：

\[
w_i\propto p(D\mid\theta_i)\frac{p(\theta_i)}{q(\theta_i)}.
\]

只有直接从先验抽样时，才可以仅按似然加权。毫米级误差下，宽先验采样还容易出现权重退化；一百万次采样不等于一百万个有效样本。

应报告有效样本量和收敛检查，并称为 ** 指定模型下的数值参考方法 **。

4. 噪声论证方向正确，但目前不能称为“病态性证明”。

- 初始位置精确时，加速度误差系数应是 \(\sqrt5/\Delta t^2\)，不是 \(\sqrt6/\Delta t^2\)。
- \(0.5\sigma_aT^2\) 没有处理速度与加速度估计的相关性，也忽略穿越时刻自身的不确定性，不能直接当作端点标准差。
- “鹰眼级 5 毫米”等精度标签尚缺具体证据，应改为假设的误差情景。
- 噪声放大说明数值敏感，** 不自动证明参数不可辨识，更不证明只有空气动力先验才能解决问题 **。

建议使用观测到穿越点的完整数值扰动实验验证误差传播。

5. 多处提前写好了预期结论。

例如：

- 推理加速超过 500 倍；
- 空气动力下降 35%—45%；
- 最终 \(Y\) 必定大于 2.495 m；
- 根据横向偏转判断踢球脚和触球方式。

这些目前都应是 ** 待检验假设或性能目标 **。尤其踢球脚不能仅靠这几个球心位置确定；横向分量也不一定随总空气动力幅值同步变化。

6. 工程量明显偏大。

```
夜间网格已有 **48个训练配置**；如果在5万测试样本上逐个执行20万次物理采样，达到 **100亿次参数轨迹计算**。没有本地测速，不能承诺几个小时完成。

应先做一个可靠 MDN；贝叶斯比较选取有代表性的较小测试子集。先证明质量，再扩大样本。

** 三、另外几个应立即修的小问题 **

- “10 维输入”实际上是 \(6+5+1=12\) 维。
- 中心差分得到的是 0.05 秒附近速度估计，不是初速度。
- 球从 \(z=0.11\) 起步，触地检测必须排除初始时刻，并检查下降穿越，否则可能所有样本立即终止。
- 线性插值不是“精确事件定位”，应通过步长收敛检查证明误差足够小。
- 混合高斯的 95% 区域不一定是椭圆。
- 不能仅在球门矩形内寻找众数和累计概率，否则会漏掉射偏概率。
- 若 \(C_L\) 已由旋转参数决定，就不能不加说明地将 \(C_L\) 与转速独立采样。

** 四、奖项竞争力怎么判断 **

| 完成状态 | 我的判断 |
|---|---|
| 按现稿堆出大量图表，核心问题未修复 | 高奖竞争力不足，复杂度反而放大漏洞 |
| 修正公式和采样，完成可信基线、案例与独立仿真验证 | 有较好的奖牌竞争基础，具备银奖竞争潜力 |
| 再加入可信外部数据、稳定校准和明确的信息限制发现 | 才形成更有说服力的冲金作品 |

这不是官方分档，也不是奖项保证。

**我的优先建议：暂缓大规模训练，先修正升力模型、采样权重和误差传播，再核实真实数据。** 这三项技术正确性加一项数据真实性，对获奖竞争力的提升，
↪  远大于把5万条仿真扩大到50万条。
```

Query 10 (exact wording).

```
我是学生 B，开始我的工作。我们可以付出很多，不用按正常人类的能力限制担心，且代码主要是你写，我审查
```

Complete output 10.1.

```
我会开始学生 B 的工作，先建立可运行、可审查的仿真与推断代码。第一步修正方案中的升力公式、触地事件和重要性采样权重，并用解析解与数值收敛检查验证；
↪  通过后再接入 MDN 和批量实验。
```

Complete output 10.2.

```
本机已有 Miniconda、`mujoco` 环境和 PyTorch，但该环境的 PyTorch 是 CPU 版；显卡是 4GB 的 GTX 1650 Ti。我先用 CPU 完成端到端正确性验证，
↪  同时让训练代码支持 CUDA。仿真参数会标注为“开发用先验”，不冒充已由真实数据校准的参数。
```

Complete output 10.3.

```
物理引擎已通过6项检查，包括抛体解析解、零旋转/轴向旋转、阻力耗散、触地截断和步长收敛。1万条开发用仿真数据已生成，MDN 正在训练；
↪  案例的贝叶斯推断也在运行，会报告有效样本量，避免把采样次数当成推断精度。
```

Complete output 10.4.

```
第一轮已跑通。5毫米噪声下，MDN 的端点中位误差约为0.35米，恒加速度基线约为0.46米；但 MDN 的50%区域实际只覆盖约41%的样本，说明校准还不够好。
↪  我会保留这项不足，并检查贝叶斯结果对随机种子的稳定性，作为你审查时的重点。
```

Complete output 10.5.

```
已补充一个有解析后验的测试，重要性采样的权重实现通过检查。题目案例在3个独立种子下的后验均值变化不到1厘米，但这还不能排除模型或先验偏差。
↪  现在正在运行5万条数据的完整流程；代码、日志、权重和运行说明都已放入 `student_b` 目录。
```

Complete output 10.6.

```
** 第一版代码已完成，并实际跑通了 5 万条仿真、MDN 训练、概率评测和案例推断。** 你现在可以直接审查。

- [运行说明与代码入口](C:/Users/pc/Documents/ChatGPT/upc/student_b/README.md)
- [代码审查清单](C:/Users/pc/Documents/ChatGPT/upc/student_b/审查清单.md)
- [实验结果与待办](C:/Users/pc/Documents/ChatGPT/upc/student_b/开发结果与待办.md)

已实现批量 RK4、正确处理轴向旋转的升力模型、触地事件、带权重校正的贝叶斯采样、全协方差 MDN，以及可续跑的批处理脚本。**7 项自动测试通过。**

5 毫米观测噪声下，4161 条开发留出样本的结果：

| 指标 | 结果 |
|---|---:|
| MDN 端点中位误差 | 0.260 米 |
| 恒加速度中位误差 | 0.446 米 |
| 95% 区域实际覆盖率 | 94.4% |
| 50% 区域实际覆盖率 | 46.8% |

基线有 19 条无有效穿越解，详见报告。** 这些仅是未实测校准的仿真结果；50% 区域校准仍需改进。**

建议你首先审查 [physics.py](C:/Users/pc/Documents/ChatGPT/upc/student_b/physics.py) 的升力公式与先验范围，以及
↪  [inference.py](C:/Users/pc/Documents/ChatGPT/upc/student_b/inference.py) 的采样权重。当前没有遗留后台任务。
```

Query 11 (exact wording).

```
我其实没太看懂你要我做什么，用简洁的实操语言
```

Complete output 11.1.

```
你现在只需要做两件事，** 代码和实验我继续负责 **。

1. ** 问队员 A 要参数。** 直接发这句：“请把你确认的足球阻力系数范围、升力公式和文献链接发我。如果还没定，告诉我哪些是暂定的。”
2. ** 把队员 A 的回复转给我。** 如果已经拿到真实轨迹，也把文件路径发我。我会核对参数、修改仿真、重新训练，再给你一张新旧结果对比表。

如果队员 A 还没查完，回我一句 **“参数还没定，先继续做仿真验证”** 就行。你暂时不用装软件、跑代码或逐行审查。
```

Query 12 (exact wording).

```
**UPC B 题气动参数与取值依据 **

- **足球质量与半径。** 取 \(m=0.430\,\mathrm{kg}\)、\(R=0.110\,\mathrm m\)，迎风面积 \(A=\pi R^2=0.0380\,\mathrm{m^2}\)。IFAB
↪  规定比赛用球质量为 \(0.410\)-\(0.450\,\mathrm{kg}\)、周长为 \(0.68\)-\(0.70\,\mathrm m\)，换算半径约 \(0.108\)-\(0.111\,\mathrm m\)。
↪  [IFAB《足球竞赛规则》第 2 条](https://www.theifab.com/laws/latest/the-ball/)
- **空气密度与雷诺数。** 采用 Asai 等风洞计算中的 \(\rho_{\mathrm{air}}=1.20\,\mathrm{kg/m^3}\)。取空气运动黏度
↪  \(\nu=1.54\times10^{-5}\,\mathrm{m^2/s}\)，则 \(Re=2RU/\nu\)，其中 \(U\) 是球相对空气的速率。题面球速约 \(31.5\,\mathrm{m/s}\) 时，
↪  无风下 \(Re\approx4.5\times10^5\)。[Asai et al. (2007)](https://doi.org/10.1007/BF02844207) • [Goff & Carré
↪  (2010)](https://doi.org/10.1088/0143-0807/31/4/007)
- **阻力系数 \(C_D\)。** Asai 等测得无旋球在亚临界区 \(C_D\approx0.43\)，在超临界区 \(C_D\approx0.15\)，临界 \(Re\) 约为 \(2.2\)-
↪  \(3.0\times10^5\)。Bray & Kerwin 从有旋任意球轨迹得到 \(C_D=0.25\)-\(0.30\)。本题高速段可先取 **\(C_D=0.22\)**，用 **\(0.15\)-\(0.30\)**
↪  做敏感性分析。若要模拟跨越阻力危机，可用 Goff & Carré 式 (3) 的无旋 Teamgeist 拟合 \(C_D(U)=0.155+0.346/[1+\exp((U-12.19)/1.309)]\)，
↪  其中 \(U\) 以 \(\mathrm{m/s}\) 代入。[Asai et al. (2007)](https://doi.org/10.1007/BF02844207) • [Bray & Kerwin
↪  (2003)](https://doi.org/10.1080/0264041031000070994) • [Goff & Carré (2010)](https://doi.org/10.1088/0143-0807/31/4/007)
- **马格努斯升力系数 \(C_L\)。** 定义自旋参数 \(S=R\omega_\perp/U\)，其中 \(\omega_\perp\) 是垂直于相对气流方向的自旋分量大小。可先采用
↪  **\(|C_L(S)|=\min(1.4S,\,0.30)\)**。这是本题选用的截断线性近似：斜率参考 Asai 等报告的 \(S\approx0.18\) 时马格努斯系数约 \(0.25\)，
↪  上限参考 Bray & Kerwin 的 \(C_L=0.23\)-\(0.29\)。Goff & Carré 图 6-7 显示升力系数随自旋增强而上升，并在较大自旋参数下趋缓。**式中的
↪  \(1.4\) 和 \(0.30\) 是本题的建模取值**，可随球型和流动条件调整。[Asai et al. (2007)](https://doi.org/10.1007/BF02844207) • [Bray &
↪  Kerwin (2003)](https://doi.org/10.1080/0264041031000070994) • [Goff & Carré (2010)](https://doi.org/10.1088/0143-0807/31/4/007)
```

Complete output 12.1.

```
我会把队员 A 确认的参数接入仿真，保留旧结果作对照。先跑固定 \(C_D=0.22\) 的题面案例和 \(0.15–0.30\) 的敏感性情景，再用新参数重训 MDN。
```

Complete output 12.2.

```
固定 \(C_D=0.22\) 的案例已跑完。在假设位置误差为 5 毫米时，后验平均穿越位置约为 \((2.695,\,1.996)\) 米。新 MDN 正在训练，
↪  随后会让新旧模型在同一批带噪样本上做对照。
```

Complete output 12.3.

```
已把队员 A 的气动参数接入代码，重新生成 **5 万条仿真轨迹**并训练 MDN。7 项自动测试通过。结果和参数出处已整理到
↪  [气动参数更新与重训结果](C:/Users/pc/Documents/ChatGPT/upc/student_b/气动参数更新结果.md)。

在同一批 **4,187 条新仿真留出轨迹**上，位置误差设为 5 毫米时，MDN 的端点中位误差从 **0.403 米降到 0.322 米**，95% 预测区域实际覆盖 **96.3%**。
↪  这说明重训后的网络更贴合新仿真，真实点球表现仍待验证。

题面案例在同样的误差假设下，固定 \(C_D=0.22\) 得到的贝叶斯后验均值为 **\((Y,Z)=(2.695,1.996)\) 米**。将 \(C_D\) 在 0.15–0.30 内均匀取样后，
↪  均值仅移动约 **7 毫米**。均匀分布是本轮的建模选择，初速度和旋转范围沿用旧设定。

你现在可以把报告发给队友。写论文时，把这批结果标为 ** 文献参数约束下的仿真实验 **。
```

Query 13 (exact wording).

```
下一步我要做什么
```

Complete output 13.1.

```
你现在只需要 ** 确认手上有没有能用于验证的真实轨迹 **。气动参数已经接入，5 万条仿真也已重跑，暂时不用再查参数或跑代码。

- ** 有真实数据 **：把文件路径发我。有帧率、坐标单位或离脚时刻的说明，也一起发来。我来判断它能验证完整点球预测，还是只能验证一段空中轨迹。
- ** 只有之前下载的 ISSIA-3D**：回我 **“先筛 ISSIA”**。我来检查有哪些连续飞行段可以用。
- ** 想先把比赛结果做完 **：回我 **“先做仿真验证”**。我会用同一批留出轨迹对比物理推断和 MDN，并补上题面案例的联合预测区域。

如果你手头没有新数据，** 建议先做仿真验证 **，让队友继续找数据，两边可以并行。
```

Query 14 (exact wording).

```
A 同学尚未回复，先筛 ISSIA，再仿真验证
```

Complete output 14.1.

```
我先检查本地 ISSIA-3D 能否筛出连续空中轨迹，以及这些片段能验证什么。随后用新的仿真样本对比物理推断与 MDN，并补齐题面案例的联合预测区域。
```

Complete output 14.2.

```
ISSIA 初筛没有找到可用片段。1,689 帧有效三维坐标里，只有一帧的 \(z\) 高于 0.30 米，而该帧的中位重投影误差约为 286 像素。我会把这份 CSV
↪  排除在实测验证之外，继续用全新的仿真样本比较两种模型。
```

Complete output 14.3.

```
核对作者的相机标定后，我纠正了初筛的坐标方向：ISSIA 的竖直轴朝下，离地高度应取 \(-z\)。重筛得到 25 个候选空中片段，其中 5 段水平位移超过 11 米。
↪  它们值得做飞行段验证，但还不能确认是完整点球。
```

Complete output 14.4.

```
已完成 ISSIA 筛选和仿真对照，结果可以直接发给队友。[查看验证报告](C:/Users/pc/Documents/ChatGPT/upc/student_b/ISSIA 筛选与仿真验证.md)

- **ISSIA 筛出 25 个候选空中片段**，其中 5 段的首尾水平位移超过 11 米。核对官方标定后，已将原始竖直坐标转为离地高度。CSV 缺少离脚时刻和点球标签，
↪  这些片段目前适合核查一般空中飞行。[候选帧 CSV](C:/Users/pc/Documents/ChatGPT/upc/student_b/runs/issia_screen/candidate_frames.csv) ·
↪  [官方标定](https://github.com/mguti97/SoccerNet-v3D/releases/download/v1.0.0/issia_calibration.json)
- **仿真对照中，无风时两种模型的点误差相近。** 在 3 m/s 横风组的 10 条可配对样本上，物理推断和 MDN 的中位误差分别为 **0.266 米、0.352 米**。24
↪  条样本中有 5 条因物理推断的有效样本量不足，未纳入配对统计，结果暂作初步证据。
```

```
- **题面案例已补齐联合预测区域。** 假设每个坐标的误差标准差为 5 毫米，物理模型给出的最可能穿越点约为 **\((Y,Z)=(2.650,\,2.052)\) 米**，50% 和
↪  95% 联合区域面积分别为 **0.219 和 0.809 平方米**。
↪  [案例图](C:/Users/pc/Documents/ChatGPT/upc/student_b/runs/fresh_validation/case_regions.png)

你现在可以把报告发给队友。若能找到 ISSIA 原始视频，优先核查 **608–627 帧和 1144–1172 帧 **，确认球在这两段中是否始终没有碰人或触地。
```

Query 15 (exact wording).

```
请给我具体跟队友沟通的内容，以及下一步要干什么
```

Complete output 15.1.

```
你现在先把下面这段发到队友群，再把他们的回复转给我。你不用自己跑代码。

> B 组已完成 5 万条仿真训练和第一轮模型对照。[验证报告](C:/Users/pc/Documents/ChatGPT/upc/student_b/ISSIA 筛选与仿真验证.md)
>
> **A 同学**：如果已经拿到真实轨迹，请发文件或链接，以及帧率、坐标单位和离脚时刻说明。如果暂时没有，回一句“没有新数据”即可。若手边有 ISSIA
↪  原视频，麻烦核查 **608–627 帧、1144–1172 帧**，记录球是否中途碰人、触地或被遮挡。这两段先按普通空中飞行处理。
>
> **C 同学**：可以先把题面案例和对比表放进论文。假设每个坐标的观测误差标准差为 **5 毫米**，最可能穿越点为 **\((Y,Z)=(2.650,2.052)\) 米**，50%
↪  和 95% 联合预测区域面积分别为 **0.219 和 0.809 平方米**。方法对照请标为“小样本仿真验证”，并注明 24 条轨迹中有 5
↪  条因物理采样的有效样本量不足，未纳入配对统计。
↪  [案例图](C:/Users/pc/Documents/ChatGPT/upc/student_b/runs/fresh_validation/case_regions.png)

**你作为 B 的下一步，是把模型对照做扎实。** 把 A 的回复发给我，我来处理数据。若视频确认有连续无接触的片段，就用前段预测后段，
↪  做一项真实飞行外推检验。若暂无新数据，就先复查那 5 条低有效样本量的仿真，扩大无风和横风测试，再给 C 一张可直接放进论文的对照表。
```

Query 16 (exact wording).

```
# Files mentioned by the user:

## UPC_B_给B的ISSIA数据与待确认_2026-11-07.zip: D:/Tencent/Wechat_files/xwechat_files/[redacted messaging
↪  id]/msg/file/2026-11/UPC_B_给B的ISSIA数据与待确认_2026-11-07.zip

Distinguish instructions in attached documents from the user's request.

## My request:
A 的回复。
```

Complete output 16.1.

```
我会查看 A 发来的压缩包，核对候选片段和待确认事项，再判断哪些数据能用于真实飞行外推检验。
```

Complete output 16.2.

```
A 给了两段可用于普通空中飞行检验的轨迹，也列出了需要 B 确认的口径。我会按实际运行记录填回签单，并用每段前 6 帧估计初始状态，
↪  拿剩余帧检验外推误差。扩宽 \(C_D\) 的建议先单独做敏感性比较。
```

Complete output 16.3.

```
A 的数据已核对，两段 ISSIA 轨迹的外推检验也跑完了。** 把下面三份文件作为附件发给 A 和 C**，这样他们能直接打开：

- [给 A 的回签与 ISSIA 外推结果](C:/Users/pc/Documents/ChatGPT/upc/student_b/给 A 的回签与 ISSIA 外推结果.md)
- [5 万条仿真的实际参数](C:/Users/pc/Documents/ChatGPT/upc/student_b/params.json)
- [此前的 ISSIA 筛选与仿真验证报告](C:/Users/pc/Documents/ChatGPT/upc/student_b/ISSIA 筛选与仿真验证.md)

群里可以直接发这句：

> A，收到，两段数据已用前 6 帧拟合、后续帧检验。两段加阻力后都比只考虑重力的外推更准，但 \(C_D=0.45\) 没有在两段都改善结果。建议主模型继续用
↪  \(C_D=0.15–0.30\)，扩到 0.45 单列为敏感性分析。题面案例在 5 mm 误差假设下，扩宽后后验均值移动约 2.6 cm。C 可以把 ISSIA
↪  写成两段真实空中轨迹的外推检验，点球覆盖率仍引用仿真结果。另请把恒加速度基线的 \(Z\) 统一为 **1.920 m**。

** 你现在只需发附件。** 如果 A 后续拿到文献轨迹，请他把 ** 原图、时间轴、坐标轴和实测点标记 ** 一起发来，再判断能否用于点球专项验证。
```

Query 17 (exact wording).

```
我们有个仓库，上传一下？[[team repository]]([team repository])
```

Complete output 17.1.

```
我会先检查仓库邀请和本地文件，确认哪些内容适合共享，再上传 B 组的代码与结果。
```

Query 18 (exact wording).

```
查看仓库现有文件以及 dsh 的最新推进成果，告诉我到哪一步了？还有多远？以及下一步要做什么？
```

Complete output 18.1.

```
我先查看仓库文件和 DSH 的最新记录，再给你一个简短判断：完成了什么、还缺什么、下一步先做什么。
```

Complete output 18.2.

```
仓库已经有完整的仿真、训练和初步验证结果，最新提交还修正了升力方向的一处错误。眼下主要缺口是更充分的独立评测和论文整合；我再核对 DSH
↪  本地有没有尚未上传的进展。
```

Complete output 18.3.

```
** 目前已完成“模型跑通＋初步验证”，正在进入“补强实验＋写论文”阶段。** 距离完整参赛作品，主要还差验证力度和论文成稿。

我核对了 GitHub 和 DSH 的本地仓库：最新提交为 **11 月 7 日 18:38 的 `aaecc2f`**，两边一致，本地没有未提交修改。以下根据已落盘成果判断；DSH
↪  的压缩会话日志未能读取。

| 部分 | 当前进展 | 还缺什么 |
|---|---|---|
| 物理仿真 | 重力、阻力、马格努斯力和触地判断已实现 | 系统检查模型假设变化的影响 |
| 神经网络 | 已用 **5 万条仿真轨迹 ** 训练 MDN | 多种子复现、概率区域校准 |
| 题面答案 | 已给出最可能穿越点及联合预测区域 | 统一最终采用的数值与假设 |
| 方法比较 | 已比较恒加速度、MDN、物理推断 | 每场景只有 **12 条 **，不足以稳健排名 |
| 真实数据 | ISSIA 两段已完成留出外推 | 非点球，不能证明真实点球预测精度 |
| 论文 | 已有模板、图表和报告 | 仓库正文仍大量为 TODO |

依据：[仓库进度与结果]([team repository])、[论文模板]([team repository])。

**DSH 最新做出了三项实质推进：**

- ** 修正升力方向错误 **，并补充自检；仓库报告目前 14 项测试通过。本次我没有重新运行测试。
- ** 完成阻力先验敏感性实验 **：扩宽阻力范围后，题面预测均值移动约 2 cm，预测区域面积变化小于三次重复间的波动。
- **完成 ISSIA 净升力对照**：两段留出误差由 0.452→0.188 m、1.488→1.084 m。但这只能支持进一步研究该模型扩展，不能当作气动参数已标定的证据。A
↪  已确认这些结论的使用范围。[第三轮确认记录]([team repository])

** 还有多远？**
按工作阶段估计：B 的算法原型已经齐全，但最终实验尚未收尾；全队论文还处于素材齐备、正文待整合的阶段。现在无法据此给出可靠获奖概率。
↪  最影响说服力的是：**方法比较样本太少、概率校准尚有偏差、真实点球验证缺失。**

** 下一步建议按这个顺序做：**

1. **你和我：先扩大独立评测。** 固定现有参数和模型，先做每场景 200 条的三方法配对比较，报告误差、概率评分、耗时及低 ESS 失败率，
↪  不能只保留成功样本。
2. ** 你和我：补概率校准。** 用独立校准集调整 50%/95% 区域，再用封存测试集评估；至少重复 3 个种子。
3. **A：继续交付可核查的文献实测轨迹。** 附原图、时间轴、坐标和实测点标识；现有两段 ISSIA 保留作辅助案例。
4. **C：现在开始填论文正文。** 方法和已有结果可以先写，后续替换最终表格，不必等实验全部结束。

** 你现在最具体的任务：审查扩大评测的设置；代码由我负责。优先补实验可信度，暂时不用急着把训练量堆到 50 万条。**
```

Query 19 (exact wording).

```
队友建议，在仓库根目录里补一个 agent_readme.md，汇报进度。以及下一步要做什么。
```

Complete output 19.1.

```
我会核对仓库最新提交，然后在根目录补一份 `agent_readme.md`，让队友能直接看到当前进度、下一步分工和验收标准。
```

Complete output 19.2.

```
已在 GitHub 仓库 `main` 根目录新增 [agent_readme.md]([team repository])，汇总了当前进度、验证缺口和 A/B/C 的下一步分工。提交为 `5379f48`。

**B 下一步先扩大独立仿真评测。** 建议从无风、横风各 200 条开始，用相同输入比较三种方法，同时报告误差、耗时和失败率。C 可以同步起草正文，A
↪  继续整理可核查的实测轨迹。

本地 Git 推送连接失败，文件已通过 GitHub 接口上传并核验。本地副本仍保留独立提交。
```

Query 20 (exact wording).

```
现在要做什么，以及，如果要大大增加获奖概率，我们能做哪些改进？
```

Complete output 20.1.

```
**你是 B，现在先做一件事：把每个场景 12 条的初步对照，扩成一轮正式的独立评测。** C 同时开始写正文，A 同时整理实测轨迹。
↪  当前已经有题面答案和概率图，最缺的是能说明**这个答案在什么条件下可信**的证据。

具体做法：锁定现有参数和模型，用新种子生成无风、3 m/s 横风各 200 条作为第一轮评测。让恒加速度、贝叶斯物理模型、MDN 吃到同一组带噪坐标。
↪  交付一张主表，列出**端点误差、失败率、单次推断耗时**，对输出概率分布的模型再列**概率评分、50%/95% 覆盖率和区域面积**。低 ESS、
↪  基线无解都要计入失败统计。代码我来写，你重点审查两件事：三种方法拿到的信息是否公平，失败样本有没有被漏掉。

如果要明显提高作品竞争力，我会按下面的顺序加码：

| 优先级 | 改进 | 论文里能交付什么 |
|---|---|---|
| **1** | **把“两帧到底能知道多少”做成核心实验。** 找到几条都能在观测误差内通过题面两点、但最终落点不同的物理轨迹。再检验观测误差、
↪  旋转先验和阻力假设分别怎样改变落点分布。 | 一张图解释为什么要给概率区域，以及这个区域主要由哪些假设决定。现有阻力上限对照可以直接纳入。 |
| **2** | **用不同于训练条件的模拟来考模型。** 无风同分布作基准，再考横风、不同旋转分布，选一种有文献依据的气动模型作额外对照。
↪  校准集与最终测试集分开。 | 一张表回答：模型遇到新条件时误差涨多少、95% 区域还覆盖多少、哪种方法先失效。 |
| **3** | **补独立实测证据。** A 优先找带时间轴、测量点和坐标说明的公开轨迹。即使只有几条，也可以锁定模型后用早段预测后段，逐条画出误差。 |
↪  一组可核查的外推案例。现有 ISSIA 两段继续作为非点球的模型对照。 |
| **4** | **让正文直接回答题目。** C 把最可能穿越点、50%/95% 联合区域和观测误差假设放在摘要与主图里。分开写“到达球门平面的概率”和
↪  “到达后落在门框内的概率”。 | 评委从第一页就能看到答案，并知道预测区域对应什么事件。 |

如果时间只够做两项，就做**正式配对评测**和**“相同早期观测、不同最终落点”那张图**。这两项分别回答评委最容易追问的问题：**方法表现怎么样？
↪  为什么结果值得用一个概率分布来表达？**
```

Query 21 (exact wording).

```
都做，同时升级神经网络，可以吗？另一位同学可以操作台式机
```

Complete output 21.1.

```
可以。台式机可以跑正式评测和重训。我会先用 brainstorming 技能把实验和升级方案定下来，确保新版网络能和现有 MDN 公平比较。
```

Complete output 21.2.

```
可以，四项都做，神经网络也一起升级。台式机负责跑训练和评测，你负责审查实验设置，我负责写代码。这个升级可以沿用现有的训练和评测流程。

**新版网络建议做“物理残差 MDN”。** 先用两帧坐标算一个简化物理落点，再让网络学习这个落点需要修正多少，以及修正后的落点分布。
↪  输入仍然只有题目给出的坐标和假设的观测误差。保留现有 MDN，用相同的训练数据和测试集比较。新版能否进论文主结果，由概率评分、
↪  覆盖率和区域面积决定。

| 谁 | 现在做什么 |
|---|---|
| **你和我（B）** | 先用现有模型跑无风、横风各 200 条的配对评测，再加入新版网络。用独立校准集调整预测区域，在封存测试集检验。同步做一张图，
↪  展示几条都符合早期观测、最终却落在不同位置的轨迹。 |
```

```
| **操作台式机的同学** | 现在打开 PowerShell 跑 `nvidia-smi`，把显卡型号和显存发给你。有可用的 NVIDIA GPU 就优先用它训练，CPU
↪  可以先跑小样和物理评测。 |
| **A 和 C** | A 整理带原图、时间轴和坐标说明的实测轨迹。C 同时写方法、题面答案和局限，等最终表格出来后替换。 |

我建议先用现有 **5 万条**数据做新旧网络对照，把扩大训练量留作单独实验，这样能分清提升来自模型还是数据。[brainstorming
↪  技能](<C:/Users/pc/.codex/skills/brainstorming/SKILL.md>)要求先确认设计再改代码。你确认按这个版本做，我就从配对评测脚本和新版 MDN 开始。
```

Query 22 (exact wording).

```
把计划上传仓库
```

Complete output 22.1.

```
我会把刚才的方案写成一份仓库文档，并在 `agent_readme.md` 加入口，方便队友找到计划。
```

Complete output 22.2.

```
已把 [最终实验与网络升级计划]([team repository]) 上传到仓库 `main`，并在 [agent_readme.md]([team repository]) 加了入口。提交为 `056e10a`，
↪  本次只更新了文档。

计划写清了配对评测、新旧 MDN 对照、实测验证、论文分工和台式机交接。**第一项交付是配对评测脚本、逐轨迹结果和汇总表。** 操作台式机的同学可以先运行
↪  `nvidia-smi`，记录显卡型号、显存和驱动版本。
```

Query 23 (exact wording).

```
事实上你现在的神经网络根本不能算是一个成果，因为只有 12 条神经，我现在把训练神经网络的活交给有台式机的同学了，他要做什么？我要做什么？
```

Complete output 23.1.

```
** 台式机同学负责把网络训练做扎实。你负责独立评测，判断它能不能写进论文。**

先纠正一个数字：**12 条是每个场景拿来比较三种方法的评测样本，不是神经网络的训练样本。** 现有 MDN 用的是一批 5 万条仿真轨迹，按轨迹划分训练、
↪  验证和测试。你质疑的重点是对的：目前三种方法的配对比较只有每场景 12 条，证据不足以支撑谁更好。现有 MDN 可以当作复现基线。

** 台式机同学要做三件事：**

1. ** 复现旧 MDN。** 检查环境，先跑小样，再按仓库配置重训，保存模型权重、参数、种子和训练日志。
2. **跑新版对照。** 用同一批仿真数据、同样的划分和噪声，训练旧 MDN 和新版物理残差 MDN，各跑 3 个种子。新版要等代码就绪，今天可以先完成第 1 步。
3. ** 交付模型和复现命令。** 把权重、配置、训练记录和验证集指标交给你。训练过程只用训练集和验证集选模型，最终测试结果由你统一出。

** 你要做两件事：**

1. **锁定并保管独立测试集。** 先准备无风和横风各 200 条，让恒加速度、贝叶斯、旧 MDN、新 MDN 使用同一组带噪坐标。用独立校准集设定概率区域，
↪  再在测试集上比较误差、失败率、概率评分、覆盖率和区域面积。
2. **做题面案例的物理分析。** 找出几条都能在误差范围内通过题面两点、最终落点却明显不同的轨迹。把这张图和最终对照表交给 C，
↪  作为论文里解释不确定性的核心证据。

** 今天就可以并行开工：他复现旧网络，你定测试集和对照表。我负责写独立评测脚本和新版网络代码。**
```

Query 24 (exact wording).

```
# Files mentioned by the user:

## codex-clipboard-5f17ecd4-59d1-4cad-a6b6-b84360cceab8.png:
↪  C:/Users/pc/AppData/Local/Temp/codex-clipboard-5f17ecd4-59d1-4cad-a6b6-b84360cceab8.png
Image attachment: true

## codex-clipboard-f9d993eb-2469-4d79-97a3-5fc93b463a14.png:
↪  C:/Users/pc/AppData/Local/Temp/codex-clipboard-f9d993eb-2469-4d79-97a3-5fc93b463a14.png
Image attachment: true

Distinguish instructions in attached documents from the user's request.
```

```
## My request:
这是gemini针对数据问题做的建议，桌面的python文件是她写的给台式机训练的代码。我现在来解决数据的问题吧。问题是1.我们如何获得更多更高质量的数据，
↪  参考codex的那个2.如何通过仿真，把不同角速度，不同给定点的情况的例子都包括进来，并通过拥有的数据（比如ISSIA）验证仿真的可靠性
↪  （再训练一个神经网络？）
```

Complete output 24.1.

```
我先检查桌面的训练代码和已有数据渠道，再核实 Gemini 提到的文献能提供什么数据。重点是分清实测轨迹、论文拟合曲线和仿真数据各自能验证什么。
```

Complete output 24.2.

```
**你现在负责“数据与仿真验证”很合适。暂时不需要再训练一个网络来验证模拟器，先用独立实测轨迹做外推检验。** 台式机同学负责训练，
↪  你负责确认训练数据覆盖了什么、物理模型在真实数据上表现如何。

我检查了桌面的 `pi_res_mdn.py`。Gemini 提出的三类数据可以保留，但“1.5 小时彻底解决完备性”“文献曲线准确度无可挑剔”“ISSIA 能证明稳健收敛”
↪  都超出了现有证据。

**1. 更多、更高质量的数据，优先从这两条路获取 **

| 优先级 | 数据渠道 | 具体取什么 |
|---|---|---|
| **第一** | **ball3d 的训练场 SW 和比赛 LP 数据** | 优先获取 `ball_3d-gt.csv`、`ball_pivot_point-gt.csv`、`sequence_metadata.json`。
↪  检查连续空中片段、时间信息、接触标注和重建方法。 |
| **第二** | **发球机＋高速摄影的原始实验轨迹** | 查论文附件或申请已有的时间—位置序列、旋转记录、球型和测量误差。只有论文图片时，
↪  先辨认实测点与模型曲线，再决定是否数字化。 |

ball3d 官方文档提供下载入口和访问邮箱 `[email redacted]`。它的坐标单位是**分米，导入后除以 10**。模型预测文件 `ball_3d.<version>.csv`
↪  应与三角测量参考轨迹分开。当前还需要实际下载检查，才能确认可用片段数和质量。
↪  [官方数据说明](https://github.com/lukaszgrad/ball3d/blob/main/DATA.md)

实验文献可优先查《Creating drag and lift curves from soccer trajectories》，该研究报告分析了 **29 条轨迹**。另一篇《Investigations into
↪  soccer aerodynamics via trajectory analysis and dust experiments》明确使用发球机和高速摄影。前者全文站点本次访问受阻，
↪  原始数据是否公开仍待确认。[29
↪  条轨迹研究](https://shura.shu.ac.uk/15728/1/Kelley%20-%20Creating%20drag%20and%20lift%20curves%20%28AM%29.pdf) •
↪  [高速摄影研究](https://eprints.whiterose.ac.uk/id/eprint/98035/)

**从论文拟合参数重新积分出来的轨迹，只能算模型复现。** 数字化实测点还要记录读图误差。如果图只有 \(z(x)\)，缺少时间，也不能直接变成完整的
↪  \(x(t),y(t),z(t)\)。

**2. 不同角速度、不同给定点，应这样进入仿真 **

先采样物理条件，再积分生成两次观测：

\[
(\mathbf v_0,\boldsymbol\omega_0,C_D,C_L,\text{风})
\longrightarrow
\mathbf r(0.05),\mathbf r(0.10)
\longrightarrow
\text{球门穿越点或触地事件}.
\]

**两次给定点由轨迹自然生成。** 这样能保证样本满足所选动力学。针对题面那一对固定观测，则通过已有贝叶斯推断筛出与观测相容的初速度、旋转和气动参数。
↪

覆盖情况要按下表检查，不能只报“生成了 10 万条”。

| 维度 | 至少检查什么 |
|---|---|
| 初速度 | 速率、水平角、仰角，分别统计数量 |
| 旋转 | 零旋、低旋、中高旋，以及侧旋、上旋、下旋和混合轴向 |
| 飞行结果 | 空中穿越、门外穿越、提前触地、超时 |
| 观测 | 2/5/15 mm 情景，另设较大误差及相关误差压力测试 |
| 模型假设 | 基准气动参数、横风、另一套有依据的气动关系 |

角速度建议按**大小＋方向**采样，并显式加入零旋和典型旋转方向。各区间的数量先作为实验设计记录。人为均衡的训练比例会影响网络学到的概率，
↪  需要与最终评价采用的分布一起说明。

“低旋”也不能自动等同于已经模拟出电梯球。要描述尾流造成的不规则偏移，需要额外的气动力模型和依据。
```

```
**3. 用 ISSIA 检验仿真，按“前段拟合、后段预测”做 **

1. ** 先筛数据质量。** 保留无接触、连续、重建质量可接受的空中段。按实际时间戳处理，25 fps 不直接对应题目的 0.05/0.10 s。
2. ** 只用前段估计初始状态。** 沿用前 6 帧拟合方案，锁定参数后预测后续位置。
3. ** 在完全相同的输入上比较模型。** 比较仅重力、重力＋阻力、重力＋阻力＋升力，报告后段三维误差和水平/竖直误差。
4. ** 检查参数稳定性。** 更换拟合前缀长度，看参数是否剧烈变化、是否撞到取值边界。
5. ** 新轨迹用于独立检验。** 已反复用于选模型的两段 ISSIA 属于开发案例。后续获取的轨迹才能提供更独立的验证。

这检验的是模拟器的 ** 外推能力及适用范围 **。即使轨迹吻合，未知旋转、气动系数与重建误差仍可能互相补偿，不能据此宣布这些物理参数都已准确识别。

**4. 台式机开始正式训练前，需要先统一数据生成器 **

桌面代码有几处会影响这次研究：

- 空气密度改成了 **1.225**，同时改变了阻力先验、升力关系和旋转衰减。应先用同一套仿真数据比较新旧网络，再单独研究物理模型变化。
- 文件开头写“含雷诺数阻力危机”，实际积分中的 \(C_D\) 是每条轨迹一个常数。
- 当前只返回有效空中穿越样本，且没有保存每条样本的初速度、旋转和气动参数，后续难以做覆盖审计。
- 同一步内同时发生触地和过门时，代码先判触地，可能误删实际先过门的边界样本。
- 图中的“FIFA EPTS Standard, σ=5 mm”没有在代码里给出依据，应作为自设噪声情景标注。

以上是对数据生成部分的静态检查，尚未完整运行审查这份脚本。[桌面代码](C:/Users/pc/Desktop/pi_res_mdn.py)

**你当前的交付应是三样东西：新增真实轨迹清单、仿真覆盖统计表、真实轨迹留出外推报告。** 第一件先从 ball3d 的小批量三维标注开始，
↪  同时让台式机同学等统一的数据格式和生成器，再启动正式新旧模型对照。
```

Query 25 (exact wording).

```
列出 todo_list
```

Complete output 25.1.

```
按执行顺序安排。你负责数据与验证，台式机同学负责训练。

| 完成 | 优先级 | 谁做 | 任务 | 交付物 |
|---|---|---|---|---|
| □ | P0 | 你＋我 | 检查 ball3d 下载权限，先获取 SW 训练场的一小批三维标注、时间信息和接触标注 | 数据小样＋来源记录 |
| □ | P0 | 你＋我 | 筛选连续、无接触的空中轨迹，核查单位、帧率、坐标和重建方法 | 可用轨迹清单＋质量说明 |
| □ | P0 | 我写代码，你审查 | 统一仿真参数，修正触地与过门事件先后判断，保存每条轨迹的初速度、角速度和气动参数 | 可审查的数据生成器 |
| □ | P0 | 你＋台式机同学 | 约定训练、验证、校准、最终测试划分，同一轨迹及其加噪版本归入同一集合 | 数据划分清单 |
| □ | P1 | 我写代码，你审查 | 按速率、发射角、旋转大小与方向生成样本，保留触地和超时标签 | 仿真数据集＋覆盖统计表 |
| □ | P1 | 你＋我 | 用真实轨迹前段拟合、后段预测，比较重力、阻力、升力模型 | 逐轨迹误差表＋外推图 |
| □ | P1 | 台式机同学 | 用同一套数据训练旧 MDN、新版残差 MDN，各运行 3 个种子 | 权重＋配置＋训练日志 |
| □ | P1 | 你＋我 | 在独立样本上比较恒加速度、贝叶斯和两个网络，记录失败率、误差、概率评分及覆盖率 | 最终配对评测表 |
| □ | P2 | 你＋我 | 绘制符合题面两次观测、却具有不同最终落点的轨迹 | 不确定性解释图 |
| □ | P2 | A | 查找高速摄影实验原始数据或可数字化的实测点 | 数据＋实验条件＋误差说明 |
| □ | P2 | C | 将最终图表、参数依据及验证范围写入论文 | 论文正文 |

** 现在先做第 1 项：检查 ball3d，拿到一批可读取、带时间信息的真实三维轨迹。**
```

Query 26 (exact wording).

```
怎么做
```

Complete output 26.1.

```
我先打开 ball3d 的数据目录，确认能否直接下载，并找出你需要的三维轨迹文件。
```

Complete output 26.2.

```
你先完成 ** 下载一小批真实轨迹 **，按这四步操作：

1. ** 打开数据目录 **
   [ball3d 数据下载入口](https://drive.google.com/drive/folders/1QCrmzZYZt9_tIBqY6AmP7DjDyPXe3AuI)。我这里的网页读取工具打不开 Google Drive，
   ↪  尚未确认你的账号能否访问。
```

```
2. ** 优先找训练场文件夹 **
   名称类似 `stalowa_wola_5`、`stalowa_wola_6`、`stalowa_wola_39` 或 `stalowa_wola_42`。先任选一个，进入 `pano/clip/`。

3. ** 下载下面三个文件，保留目录结构 **

   ```text
   sequence_metadata.json
   track/ball_3d-gt.csv
   track/ball_pivot_point-gt.csv
   ```

   如果有 `track/split.csv`，也一起下载。这些名称和目录来自作者的 [数据说明](https://github.com/lukaszgrad/ball3d/blob/main/DATA.md)。

4. ** 保存到本机一个文件夹，把路径发给我 **
   例如 `E:\UPC_data\ball3d\stalowa_wola_5\`。我随后检查单位、帧率、有效三维坐标、接触分段，并筛出能做“前段拟合、后段验证”的轨迹。

** 如果页面要求申请权限 **，把页面提示告诉我，我们就按作者提供的邮箱申请已有数据。
```

Query 27 (exact wording).

```
access 怎么选
```

Complete output 27.1.

```
如果是 Google Drive 的权限选项，选 **Viewer（查看者）**，下载数据通常只需要这个权限。

申请说明可以填：

> We are undergraduate students studying soccer-ball trajectories for a physics competition. We request read-only access to the existing
↪  3D trajectory annotations and metadata for non-commercial academic research. We will cite your work and follow the dataset license.

如果你看到的选项不是 Viewer / Commenter / Editor，把选项文字发我，我帮你确认。
```

Query 28 (exact wording).

```
交上去了，等待审核
```

Complete output 28.1.

```
访问申请已提交，先等作者审核。

等待期间，你可以把这段发给台式机同学：

> ball3d 数据已申请，正在等审核。请先检查训练环境并复现旧 MDN。正式新旧网络对照要使用同一套仿真数据，参数、划分和种子都需保存。
↪  新版脚本的数据生成部分还需要统一参数、修正触地与过门的先后判断，并保存每条轨迹的初速度和角速度。

**你这边下一步先做仿真数据的覆盖检查。** 我们可以利用现有代码，检查不同初速度、旋转大小与方向，以及触地、过门情况是否都有样本。数据获批后，
↪  再接入真实轨迹做外推验证。
```

Query 29 (exact wording).

```
先做我的下一步
```

Complete output 29.1.

```
我先检查现有仿真数据对初速度、旋转方向和飞行结果的覆盖，生成统计表，标出缺样本的情况，供你和台式机同学使用。
```

Complete output 29.2.

```
现有 5 万条数据保存了每条轨迹的初速度、角速度、事件标签和训练划分，可以直接审计，无需重新仿真。我会统计原始样本和实际训练样本各有多少，
↪  重点检查低旋球、低速球及接近触地的轨迹是否稀缺。
```

Complete output 29.3.

```
已完成现有 **5 万条仿真轨迹的覆盖检查 **，统计与原始数据清单核对通过。

| 检查项 | 结果 |
|---|---|
| 实际进入 MDN 的训练样本 | **33,367 条 ** |
| 严格零旋球 | **0 条 ** |
| 总角速度小于 10 rad/s | 训练集仅 **77 条 **，测试集仅 **16 条 ** |
| 初速低于 18 m/s | **0 条 ** |
| 提前触地 | **8,267 条 **，未进入落点 MDN |
| 过门时距接地高度不足 5 cm | 训练集 **389 条 ** |
| 跨训练/验证/测试的完全相同参数 | **0 组 ** |

**现在有依据确定补样顺序了：先补零旋、低旋和低速情景，再检查不同旋转方向的覆盖。** 补样比例会影响网络学到的概率，应记录下来，
↪  让新旧网络使用同一批数据。

你可以把报告发给台式机同学：

> 覆盖审计已完成。现有数据的零旋与低旋样本不足，低于 18 m/s 的情景为空。下一版生成器需要分层补样，并保留初速度、角速度、气动参数和事件标签，
↪  再用于正式新旧网络对照。

[查看完整审计报告](C:/Users/pc/Documents/ChatGPT/upc/student_b/runs/coverage_audit/覆盖审计.md) ·
↪  [审计脚本](C:/Users/pc/Documents/ChatGPT/upc/student_b/audit_coverage.py)

这次完成的是样本覆盖检查，仿真的现实可靠性仍需实测外推验证。
```

Query 30 (exact wording).

```
仓库里有新推上去的内容（包含新的数据），整合
```

Complete output 30.1.

```
我先检查仓库新增的数据、代码和交接说明，再把本地覆盖审计与新版内容对齐，更新进度和待办。
```

Complete output 30.2.

```
新增内容包括论文初稿、4 个飞行验证案例和一个含 4 次点球的交接包。两份数据里有 2 次点球重复，合计是 6 个不同案例。我正在核对时间、坐标和来源，
↪  尤其是这些实测输入与现有网络固定的 0.05/0.10 秒输入并不一致，需要先按案例接入物理外推验证。
```

Complete output 30.3.

```
数据核对已通过。主要接入问题是两次 DFL 点球的观测间隔为 0.04 秒，起点也已离开罚球点；Barber 案例只有前进距离和高度，PFF 低球的高度基准还需确认。
↪  我已把这些限制、去重结果和仿真覆盖缺口写入整合文档，并更新了“C 已完成论文初稿”的进度。
```

Complete output 30.4.

```
已整合并上传仓库 `main`，提交 **`a4066c4`**。

- ** 新数据去重后有 6 个案例 **：2 次空中点球、2 次低球点球、1 段 ISSIA 飞行、1 次实验室发球。两份交接中的重复点球已标明。
- ** 核对通过 **：输入与留出帧分离、坐标转换、两次点球的过门参考值及原始文件哈希。
- ** 并入你的覆盖审计 **：零旋、低旋和低速样本缺口已写入下一步任务。
- ** 同步 C 的最新成果 **：论文现为 13 页、18 条参考文献，并入引用审计。

[查看新增数据整合说明]([team repository]) · [查看更新后的进度]([team repository])

**你下一步可以直接做两次真实空中点球的外推验证。** 它们使用 0.04 秒采样间隔，起始高度和门平面也与题面不同，需要先适配物理预测入口。
↪  本次完成了数据接入核对，尚未运行新案例的预测评测。
```

Query 31 (exact wording).

```
继续
```

Complete output 31.1.

```
我会接上真实点球的物理外推：按各自的观测时间、起点和门平面，只用前三帧估计初始状态，再对后续帧和过门位置评分。先固定评测规则，
↪  避免用留出结果反过来调参。
```

Complete output 31.2.

```
两次点球的第一轮结果已出来。固定阻力模型在这两例上的后段三维误差都小于仅重力模型，但过门位置仍有约半米误差。恒加速度模型在第二例中提前触地，
↪  未能预测到门线。我会补上共同有效帧的公平比较和数值检查，再把结果交给 C。
```

Complete output 31.3.

```
已完成两次真实点球的首轮外推，并上传仓库，提交 **`1418859`**。

只用前三帧拟合，后续帧用于评分：

| 方法 | 点球一：三维误差 | 点球二：三维误差 |
|---|---:|---:|
| 仅重力 | 0.505 m | 0.450 m |
| 重力＋阻力，\(C_D=0.22\) | **0.349 m** | **0.310 m** |
| 恒加速度 | **0.190 m** | 提前触地，缺少后两帧预测 |

报告另附共同有效帧的公平比较。**加入阻力改善了两例的轨迹外推，但过门位置误差仍约 0.54–0.65 m。** 这轮使用零旋物理基线，
↪  尚未检验完整旋转模型或神经网络。

解析解与步长加密检查通过。由于前期审计已看过完整轨迹，本轮作为开发对照，不属于盲评。

[查看结果、轨迹图和复现命令]([team repository])

下一步接入 ** 带旋转不确定性的物理推断 **，检查剩余偏差能否解释，并扩展到新增 ISSIA 和实验室案例。
```

Query 32 (exact wording).

```
继续
```

Complete output 32.1.

```
我会继续做带旋转不确定性的外推，并加入 ISSIA 和实验室案例。沿用前面已定的评测设计，只用前三个观测点做推断，再用后段评分。
```

Complete output 32.2.

```
仓库刚加入了神经网络消融结果，我已同步到本地。实测这边会单独比较零旋与未知旋转两种设定，使用相同的阻力先验和观测误差假设，并记录采样是否稳定。
```

Complete output 32.3.

```
已完成 **4 个实测案例的旋转不确定性外推 **，并上传仓库 `main`，提交 `e9e3c79`。每例只用前三个观测点推断，用后续观测评分。

| 案例 | 仅阻力 RMSE | 加入未知旋转 RMSE |
|---|---:|---:|
| DFL 点球 J03WOH | 0.347 m | **0.292 m** |
| DFL 点球 J03WR9 | 0.309 m | 0.305 m |
| ISSIA 飞行片段 | 0.338 m | 0.366 m |
| Barber 实验图读数据（二维） | 2.266 m | 2.301 m |

**旋转对第一脚点球有帮助，过门误差从 0.645 m 降到 0.543 m；第二脚的过门误差略增，另外两例的轨迹误差也略增。**
↪  论文可以据此讨论旋转假设对预测的影响，结论限于这四个开发案例。

结果以假设的观测误差和旋转先验为条件。报告保留了两个噪声情景、两个随机种子、腾空概率和过门坐标区间。解析轨迹、过门事件及触地停止检查均通过。
↪  [完整结果与复现命令]([team repository])
```

Query 33 (exact wording).

```
继续
```

Complete output 33.1.

```
我会把同一套三点输入、后段留出的评测扩展到 A 筛出的 11 段 DFL 轨迹，检查旋转带来的改善是否稳定。逐段结果会保留，方便复核哪些片段受益、哪些变差。
```

Complete output 33.2.

```
已完成 **11 段 DFL 比赛轨迹的旋转对照 **，结果已推送到 `main`（`6122085`）。每段只用前三帧推断，后续共 221 个位置点用于评分。

| 假设观测误差 | 零旋模型 RMSE 中位数 | 未知旋转模型 RMSE 中位数 | 误差降低的片段 |
|---|---:|---:|---:|
| 15 mm | 0.826 m | 0.762 m | 7/11 |
| 30 mm | 0.825 m | 0.742 m | 7/11 |

**引入旋转后，多数片段的误差下降，但改善有限。** 按同一片段配对计算，误差下降的中位数分别为 2.7 cm 和 1.1 cm。其中一段的预测腾空概率最低仅 0.3%，
↪  该段的位置误差要结合触地风险解读。

这批数据按完整轨迹的平滑性预筛过，且缺少球门交点标签，因此结果适合用于论文的**探索性飞行外推对照**。逐段误差、
↪  两个种子的结果和逐帧腾空概率均已保留。[完整报告与复现命令]([team repository])
```

Query 34 (exact wording).

```
打包数据集，附上仿真代码，给台式机同学检验
```

Complete output 34.1.

```
我会打一个可独立运行的 ZIP，把实际仿真数据、生成代码、实测对照和检验步骤放在一起。台式机同学解压后可以先核对文件，再复现一小批轨迹。
```

Complete output 34.2.

```
已打包，约 **6.1 MB**。可直接发给台式机同学。[下载 UPC155 台式机检验包](<F:/ChatGPT/upc/deliverables/UPC155_ 台式机检验包.zip>)

包内有 **50,000 条仿真轨迹 **、完整数据划分、RK4 仿真与数据生成代码、4 个实测对照案例、11 段 DFL 比赛轨迹，以及中文检验说明。

我已从 ZIP 重新解压验证：文件哈希和数据计数一致，**256 条抽样轨迹重算通过，14 项单元测试全部通过 **。

请同学解压后打开 `检验说明.md`，先运行 `python verify.py`，再运行单元测试，把两段输出回传即可。
```

Query 35 (exact wording).

```
误差还是那么大，问题到底出在哪里？
```

Complete output 35.1.

```
我会把误差拆开看：初始速度和加速度估计是否不稳、哪些坐标偏差最大，以及只用前三帧是否提供了足够信息。这样才能判断该改数据、物理模型还是推断方法。
```

Complete output 35.2.

```
**目前最明确的问题是：前三帧提供的弯曲信息太少，而我们还没有用真实数据校准旋转和观测误差。增加仿真数量、扩大网络，都不能自动解决这个问题。**
↪  此外，上一轮的大误差来自物理外推实验，不能直接归因于台式机同学的神经网络。

我核查后，问题主要集中在下面四处。

**1. 很短的观测窗口，把位置误差放大成了加速度误差。**
```

```
DFL 的前三帧只有 **0、0.04、0.08 秒 **。假设每个坐标的位置误差标准差为 1.5 厘米，三点二阶差分得到的加速度噪声标准差约为：

\[
\sigma_a=\frac{\sqrt6\,\sigma_x}{\Delta t^2}\approx23\ \mathrm{m/s^2}
\]

这已经超过重力加速度的两倍。因此，球究竟向哪边旋转、弯曲多强，很容易被测量噪声掩盖。这里的 **1.5 厘米仍是假设，尚未独立标定 **。

**2. 具体到真实点球，横向预测是明显短板。**

例如 J03WR9，仅阻力模型的分坐标 RMSE 为：

| 坐标 | RMSE |
|---|---:|
| 前进方向 x | 0.024 m |
| 横向 y | **0.307 m** |
| 高度 z | 0.041 m |

约 **98% 的平方误差来自横向**。这说明该案例并非所有方向都算错了；横向初速度估计、侧向气动力或追踪偏差需要重点排查。
↪  现有证据还不能确定是哪一个单独造成的。

**3. “加入未知旋转”，不等于“识别出了真实旋转”。**

上一轮我设置了较宽、正负对称的旋转先验。前三帧约束不足时，许多不同旋转都能解释输入，预测均值里的左右弯曲可能相互抵消。

实际结果也说明问题：

- J03WOH：过门误差 **0.645 → 0.543 m**，有所改善。
- J03WR9：**0.542 → 0.553 m**，没有改善。

** 这一步只是加入了旋转不确定性，还没有建立经过真实数据校准的旋转推断能力。** 这是当前方案的不足，不能靠扩大采样量掩盖。

**4. 部分验证数据本身不足以支撑当前结论。**

- **Barber 图读数据**：前三点仅覆盖 0.04 秒，直接推得约 −167 m/s² 的加速度，提示图读位置、时间精度相对短窗口严重不足。其约 2.3
↪  米误差不能直接解释成足球物理模型失败。
- **11 段 DFL**：属于比赛飞行片段，接触状态未完全确认，外推时间也不同于点球；其误差不能直接当作题目过门误差。
- 有一段预测到后期时，仍腾空的样本概率最低只有 **0.3%**。这时只报告“仍腾空样本的平均位置”容易误导，需要同时报告触地失败概率。

** 下一步应先做定位实验，再决定怎么升级：**

| 顺序 | 实验 | 要回答的问题 |
|---|---|---|
| 1 | 已知参数生成无噪声轨迹，再用同一参数预测 | 仿真、坐标和事件处理是否正确？ |
| 2 | 同一轨迹分别加入位置噪声、隐藏旋转 | 误差主要由噪声还是未知旋转造成？ |
| 3 | 真实数据用前三帧、前六帧预测同一段后续轨迹 | 更多观测能否显著降低误差？ |
| 4 | 按整条轨迹划分校准集和测试集，校准噪声与参数先验 | 校准后能否改善未参与调参的真实轨迹？ |

第 3 项只是诊断，** 不能用额外观测替代题目规定的两个时刻 **。

目前应优先解决的是“输入信息是否足够、仿真与真实数据是否匹配”。在这两点弄清之前，让台式机继续放大网络，
↪  可能只是更准确地学习我们尚未校准的仿真规律。
```

Query 36 (exact wording).

```
实验一下吧，实验前，给我一些新的寻找数据的途径
```

Complete output 36.1.

```
我先查几条能补充真实三维轨迹的数据渠道，再用现有 DFL 数据做前三帧和前六帧的对照，看看观测窗口拉长后误差能降多少。
```

Complete output 36.2.

```
先给你三条新线索。最值得先问的是 [100 Hz、24 台 Vicon 相机的弧线球实验](https://www.mdpi.com/2504-3900/49/1/88)，
↪  论文明确测了球的飞行轨迹和角速度，可以向作者索取逐帧坐标及角速度。第二条是 [Sheffield
↪  发球机与高速摄影实验](https://eprints.whiterose.ac.uk/id/eprint/98035/)，可以索取不同速度和转速下的原始轨迹。这两条都已核实实验做过，
↪  原始数据能否分享还要问作者。第三条是 [SoccerTrack v2](https://github.com/AtomScott/SoccerTrack-v2)，可以先用射门和任意球事件筛片，
↪  再核对是否有足够的同步视角重建高度。
```

现在我先用现有数据跑对照。两个版本评分用同一批后续帧，同时单列预测提前触地的情况。

Complete output 36.3.

```
**实验跑完了。两条实测点球多看 3 帧后，过门点误差各下降约 22 厘米。仿真里，把真实旋转强行设为零，即使观测完全无噪声，过门点 RMSE 仍有 62.5 厘米。
↪  ** 这两组结果支持优先补测旋转、核查追踪精度。

| 实测案例 | 前 3 帧（0–0.08 秒） | 前 6 帧（0–0.20 秒） |
|---|---:|---:|
| J03WOH 过门点误差 | 0.647 m | 0.418 m |
| J03WR9 过门点误差 | 0.542 m | 0.320 m |
| 11 段比赛片段的轨迹 RMSE 中位数 | 0.891 m | 0.711 m |

两组使用同一个零旋转、固定阻力模型。轨迹误差在共同的后续帧上比较，11 段中有 10 段改善，其中一段两种预测都有提前触地。前六帧是定位误差的对照，
↪  正式解题仍用题面规定的时刻。[实测逐段结果](F:/ChatGPT/upc/deliverables/UPC155_prefix_diagnostic.json)

仿真按题面的 **0.05 和 0.10 秒**取点，比较了 255 条空中过门轨迹。在已知真实旋转和阻力的条件下，无噪声复算误差低于 0.01 毫米，加入每坐标 1.5
↪  厘米的噪声后升至 **7.8 厘米**。将旋转设为零，同样噪声下升至 **63.1 厘米**。这个差值取决于本次模拟的旋转范围，真实点球中有多少误差来自旋转，
↪  仍需带实测转速的轨迹来判断。[仿真分组结果](F:/ChatGPT/upc/deliverables/UPC155_synthetic_error_diagnostic.json)

** 找新数据，建议按这个顺序推进：**

1. **先问 Vicon 实验作者。** 论文用 24 台相机以 100 Hz 记录弧线球轨迹和角速度。请他们先分享几条逐帧 `t,x,y,z`，附每球角速度、旋转轴（若有）
↪  和滤波说明。这批数据最能区分旋转误差和追踪误差。[Vicon 弧线球实验](https://www.mdpi.com/2504-3900/49/1/88)
2. **并行问 Sheffield 发球机实验作者。** 索取不同初速、转速下的原始高速摄影轨迹，优先要同一球型的低旋和高旋对照，用来检查仿真的气动力。
↪  [Sheffield 高速摄影实验](https://eprints.whiterose.ac.uk/id/eprint/98035/)
3. **公开数据先筛 SoccerTrack v2。** 用射门和任意球事件找候选片段，先试一条，核对是否有同步、可标定的视角供三维重建，再决定是否扩大。
↪  现有事件标注可以帮你找球，轨迹高度还需验证。[SoccerTrack v2](https://github.com/AtomScott/SoccerTrack-v2)
```

Query 37 (exact wording).

```
dsh 的建议：不能用题面那 0.08 s 窗口去“拟合”自转。 1 cm 量化经二阶差分放大成 ±6 m/s²，比马格努斯力本身还大。所以自转只能来自：

外部先验（文献 + 长窗口反演）；
结构化的弱约束（用两次观测的似然，让数据在合理范围内微调）。
这也正是为什么先验形状决定一切：数据给不出自转，先验给什么，后验就信什么。
```

Complete output 37.1.

```
我同意 DSH 的建模方向。** 把自转当作隐变量，用外部数据定先验，再用题面两点的似然更新。最终报告过门点的概率分布，以及它对旋转先验有多敏感。**

有两处措辞建议改准：

- **“±6 m/s²”对应题面，不对应 DFL。** 若坐标按 1 cm 四舍五入，且起点精确已知，题面 0、0.05、0.10 s 的二阶差分误差上界是每轴 ±6 m/s²。DFL 是
↪  0、0.04、0.08 s，三帧都来自追踪，同样假设下上界是 ±12.5 m/s²。这两个数只反映取整，追踪误差还需另行估计。量纲上应与**马格努斯加速度**比较。
- **“先验形状决定一切”可以改成“旋转后验可能主要受先验支配”。** 两点仍能约束飞行方向，也可能排除部分旋转情景。能排除多少，
↪  取决于观测精度和模型。长窗口反演得到的是在该模型下能解释弯曲的**有效旋转**，有实测角速度的实验才能核对它是否接近真实自转。

**下一轮最值得做的是固定同一套物理模型，比较三套先验。** 保留零旋转作基线，再比较宽对称先验和按文献构造的弱、中、强旋转混合先验。
↪  两套非零旋转模型都用同样的两点似然，分别比较**旋转先验与后验的变化**，以及**过门点、联合预测区域和空中过门概率**的变化。
↪  如果旋转后验几乎没动，而过门预测随先验明显移动，这就能把 DSH 的判断变成论文里的量化结果。
```

Query 38 (exact wording).

```
go ahead
```

Complete output 38.1.

```
我会沿用仓库的飞行模型，固定题面两次观测，比较三套旋转先验，并检查结论对观测误差假设有多敏感。
```

Complete output 38.2.

```
第一组结果显示，观测误差假设会改变结论。假设每轴误差为 5 毫米时，两点观测能明显改变预测落点。放宽到 15 毫米后，两套非零旋转先验的平均落点更接近，但对球能否穿过门框的估计仍相差约 14 个百分点。第二个随机种子正在复核。
```

Complete output 38.3.

```
实验跑完了。**DSH 的判断在 15–30 mm 误差情景下基本成立：两点对转速幅值的约束很弱，换一个旋转先验，门框穿越概率能差 14–19 个百分点。** 但在 5 mm 情景下，两点仍能提供明显的旋转方向信息。

| 假设每轴观测误差 | 宽均匀先验：穿过门框 | 幅值混合先验：穿过门框 |
|---|---:|---:|
| 5 mm | 97.0% | 98.9% |
| 15 mm | 77.7% | 91.8% |
| 30 mm | 68.0% | 86.6% |

两个非零先验下，竖直轴旋转分量为负的先验概率都约为 50%。用题面两点更新后，**5 mm 时升到 91%–98%，30 mm 时只升到 53%–55%**。这说明要把「能推断往哪边弯」和「能推断转得多快」分开写。

如果论文需要展示一个具体情景，取 **15 mm、幅值混合先验**，过门平面的密度峰值约为 **\((y,z)=(3.21,1.91)\) m**，95% 联合预测矩形约为 \(y\in[2.38,3.90]\) m、\(z\in[1.21,2.64]\) m。矩形跨过右门柱和横梁，能直观看出为什么峰值在门内，穿过门框的概率仍低于 100%。

三档转速的 **45% / 40% / 15%** 是实验设定，15 mm 也是误差假设。高转速档参考了实测弧线任意球，档位比例仍需用真实点球校准。论文可以并列报告两套非零先验的结果，把这部分不确定性直接展示出来。[转速参考文献](https://eprints.whiterose.ac.uk/id/eprint/98036/)

[可分享的 Markdown 报告](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/runs/spin_prior/旋转先验敏感性.md) · [逐组结果](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/runs/spin_prior/scores.json) · [复现脚本](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/diagnose_spin_prior.py)
```

Query 39 (exact wording).

```
我们接下来到底该做什么?
```

Complete output 39.1.

```
**现在先做一张统一的验证表，把论文主模型定下来。** 用同一批输入和评分规则，比较「仅阻力」「阻力＋旋转先验」和「台式机训练的神经网络」。这比再换网络结构更能回答评委会问的问题：哪种方法更准，给出的不确定性是否可信?

| 谁 | 现在做什么 | 交付什么 |
|---|---|---|
| **你（B）** | 用现有两条 DFL 点球做逐案例对照。输入只取前三帧，参考过门点用留出帧计算。固定模型和先验后再评分。 | 一张表，列出过门点误差、是否提前触地，以及参考点是否落入 95% 联合预测区。两条案例逐条报告。 |
| **台式机同学** | 在同一批留出仿真轨迹上比较神经网络和物理模型。按轨迹划分训练、验证和测试，给两种模型相同的观测噪声。 | 一张表，列出过门点 RMSE、95% 区域覆盖率和区域面积。网络若只支持 0.05/0.10 s，就先做仿真对照，DFL 的 0.04/0.08 s 单列。 |
| **A 同学** | 并行向 Vicon 和 Sheffield 作者索取原始轨迹，优先要能配对的坐标、转速和测量说明。 | 几条可用轨迹或明确的获取状态。现有验证照常推进。 |
| **C 同学** | 把题例的落点分布和 5/15/30 mm 敏感性结果写进论文。 | 一张过门平面图，标出门框、密度峰值和联合预测区，并注明观测误差和旋转先验。 |

**你现在就做第一行。** 把现有两条 DFL 的零旋转和未知旋转结果整理成统一表，再补上幅值混合先验这一列。题例的先验实验已经完成，眼下缺的是用同一标准比较真实轨迹。两条 DFL 足够展示成功和失败案例，覆盖率则放在大批留出仿真上评估。

论文暂以 ** 物理概率模型为主线 **。等台式机交表，如果神经网络能在相近覆盖率下缩小预测区域，或稳定降低落点误差，就把它写成有实证支持的改进。
```

Query 40 (exact wording).

```
你做，我真的无法推进了，你知道你的结果实测下来正确率不及一半吗?
```

Complete output 40.1.

```
我来做。你说实测正确率不到一半，我会先核对现有两条 DFL 的预测命中情况，再把三套先验放到同一张表里。表里会区分落点误差、95% 区域是否覆盖实测点，以及有没有提前触地。
```

Complete output 40.2.

```
我把两条 DFL 实测点球用三套旋转先验重跑了。**如果按「预测平均落点离实测点不超过 50 厘米」计命中，三套模型都是 0/2。**
↪  这是我这次用来说明误差量级的阈值，你提到的正确率可能采用了不同口径。

| 实测点球 | 零旋转 | 宽均匀先验 | 幅值混合先验 |
|---|---:|---:|---:|
| J03WOH 落点误差 | 64.6 cm | **54.2 cm** | 60.0 cm |
| J03WR9 落点误差 | **54.2 cm** | 55.0 cm | 54.6 cm |

表里用的是每轴 15 mm 的追踪误差假设。放宽到 30 mm 后，三套模型也仍然是 0/2。两套非零旋转模型的 95% 区域都罩住了实测点，但面积扩大了约 **10–16
↪  倍**。尤其是 J03WR9，三套模型都向同一侧偏了约 **54 cm**。所以当前能确认的是：加入旋转扩大了预测区域，横向偏差仍在。

**论文里应把幅值混合先验作为敏感性对照，暂不写成精度改进。** 上一轮的 91.8% 是模型在特定假设下算出的题例穿门概率，实测落点精度要看上面这张表。
↪  我已把失败结果和复现方式整理好了，可以直接交给队友。

[实测对照报告](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/runs/real_spin_comparison/两条实测点球对照.md) ·
↪  [逐组结果](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/runs/real_spin_comparison/scores.json) ·
↪  [复现脚本](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/compare_real_spin_priors.py)
```

Query 41 (exact wording).

```
仓库有新的上传，看一下
```

Complete output 41.1.

```
我会查看仓库主分支的新提交，重点核对有没有新的实测数据、评估结果或能解释落点偏差的改动。
```

Complete output 41.2.

```
看了，`main` 最新是 C 同学的提交 [ebdb13e]([team repository])。这次新增的是 **P0 仿真评估交付包**：4,187 条冻结测试轨迹、数据清单、复现脚本、
↪  论文表格和图。**没有新增真实点球，也没有新的结果证明实测命中率提高。** [P0 目录]([team repository])

- **台式机同学可以直接用这份测试集做统一复核。** 它包含空中到达门平面的仿真轨迹，适合比较落点误差和预测区域，无法评估提前触地。CSV
↪  也附了真实初速度、转速和阻力参数，预测时只能输入两个观测点及噪声设定。校准用验证集，冻结表留作评估。[数据清单]([team repository])
- **当前优先复核 Arm C。** 在同一仿真器、5 mm 噪声下，它的落点中位误差是 **29.4 cm**，PI-ResMDN 公平重训后是 **42.4 cm**。Arm C 的 50%
↪  预测区在 15 mm 下实际覆盖 **45.2%**，值得先校准。这里的 45.2% 是仿真预测区覆盖率，和你说的实测正确率是两个指标。[P0 一页摘要]([team
↪  repository])

这次上传解决了**大家用哪一批数据公平比较模型**的问题。我们之前在 DFL 上看到的 **约 54 cm 横向偏差**仍待解释，论文里应把这两部分结果分开呈现。
```

Query 42 (exact wording).

```
就用这个，继续改进
```

Complete output 42.1.

```
我会用 C 同学冻结的 4,187 条轨迹做评估。先复现 Arm C，再只用验证集校准预测区域，检查覆盖率改善了多少、区域变宽了多少。
```

Complete output 42.2.

```
冻结 CSV 已按仓库的清单核对，并逐条与本地测试划分比对。首个种子在 5 mm 噪声下复现了约 30 cm 的落点中位误差。用验证集校准后，50%
↪  区域的实测覆盖从 47.9% 调到 50.2%，落点误差保持不变。其余种子还在复核。
```

Complete output 42.3.

```
用 C 同学冻结的 **4,187 条仿真轨迹 ** 复核了 Arm C，并用独立验证集校准预测区域。三个训练种子取平均后，四档噪声下的覆盖率都更接近标称值。

| 每轴噪声 | 50% 区域实际覆盖率 | 95% 区域实际覆盖率 | 落点中位误差 |
```

```
|---|---:|---:|---:|
| 2 mm | 52.7% → 51.1% | 95.9% → 95.4% | 13.3 cm |
| 5 mm | 48.5% → 50.2% | 95.2% → 94.9% | 29.4 cm |
| 10 mm | 48.0% → 50.9% | 96.6% → 95.2% | 46.9 cm |
| 15 mm | 45.3% → 49.4% | 97.3% → 94.9% | 55.9 cm |

**15 mm 下，95% 区域面积缩小了约 13%，覆盖率仍接近 95%。** 50% 区域则扩大了约 14%，补上了原先的覆盖不足。

这次改进只调整预测区域的边界，落点误差保持不变。结果适用于同一仿真分布，真实点球的横向偏差仍需单独解决。

[校准报告](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/runs/p1_calibration/Arm_C_校准报告.md) •
↪ [逐种子结果](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/runs/p1_calibration/scores_11_22_33.json) •
↪ [复现脚本](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/experiments/p1_calibrate_arm_c.py)
```

Query 43 (exact wording).

```
那说明，还是数据的问题？
```

Complete output 43.1.

```
** 数据是主要嫌疑之一，但还不能认定它是唯一原因。** 更具体地说，缺的是能帮我们区分 ** 追踪误差、真实旋转和气动模型偏差 ** 的数据。

- **观测精度确实影响预测。** 在同一批仿真轨迹上，噪声从 5 mm 增到 15 mm，Arm C 的落点中位误差从 **29.4 cm** 增到 **55.9 cm**。
↪ 两条真实点球多看三帧后，落点误差也都下降约 **22 cm**。
- **真实数据仍无法解释剩下的偏差。** J03WR9 换了三套旋转先验，横向偏差仍约 **54 cm**。现有数据没有同步实测旋转，也没有独立标定追踪精度，
↪ 所以还分不清是横向初速度估偏、相机追踪偏差，还是气动力模型没抓住实际弯曲。
- ** 这次校准解决的是区域覆盖。** 95% 区域在仿真里更接近标称覆盖率，落点本身没有变准。

所以，如果只能补一类数据，优先找**从离脚开始的高频三维轨迹，带实测转速，最好还有旋转轴和相机误差说明**。先把实测旋转直接喂给物理模型，
↪ 看偏差还剩多少。这个对照最能判断下一步该改旋转推断，还是改气动模型和坐标处理。
```

Query 44 (exact wording).

```
你让我上哪去找？或者你叫 dsh 帮你找呢
```

Complete output 44.1.

```
我来找，也会用 Codex-DSH 协作技能请 DSH 独立筛一遍。优先核实哪些数据能直接下载，哪些需要向作者申请，以及它们有没有逐帧三维坐标和实测转速。
```

Complete output 44.2.

```
我核实到一个新的对象：西澳大学的研究团队用 250 Hz 动捕测了直线球和弧线球的转速与旋转轴，适合补我们最缺的旋转先验。
↪ 筑波大学的研究则记录了较长的飞行轨迹，适合验证气动力。两边都值得问，我把具体联系人和可直接复制的英文邮件整理出来。
```

Complete output 44.3.

```
联系人和邮件草稿已整理好。DSH 的第一轮检索超时了，我把任务缩到一件事：核对筑波和西澳这两篇论文有没有我漏掉的原始数据下载入口。
```

Complete output 44.4.

```
我查了，也请 DSH 复核了。**先给筑波大学的 Takeshi Asai 发邮件，具体要论文图 3 和图 7 对应的 trial 1。** 这一个试次就有三维飞行轨迹和实测转速，
↪ 拿到后可以直接比较「已知旋转」和「只能猜旋转」的预测误差。通讯邮箱是 `[email redacted]`。
↪ [实验与通讯信息](https://pdfs.semanticscholar.org/e4fa/96b765b544eb6d0558c3e07f5f95dd3da65e.pdf)

第二封可以发给西澳大学的 **Jacqueline Alderson**，邮箱 `[email redacted]`。他们用 **250 Hz Vicon** 测了 5 次直线球和 10 次弧线球的飞行前段，
↪ 记录了转速和旋转轴。两种球各要两三条，就能先检查我们的旋转先验。 [实验论文](https://ojs.ub.uni-konstanz.de/cpa/article/view/4446) • [公」
↪ 开邮箱](https://media.isbweb.org/news/isb-now/178-isb-now-march-2021/756-education-officers-update-jacqueline-alderson-dario-cazzola)

DSH 确认西澳论文页面只提供 PDF，没有可见的原始数据下载入口。筑波的出版社页面对 DSH 返回 403，我从论文 PDF 核实了实验和通讯地址，
↪ 原始文件是否公开仍待确认。
```

```
**你只需要把英文草稿里的姓名和学校换掉。** 我把这两位、Sheffield 的备用联系人和具体索取字段都放进了同一个文件。邮件尚未发送。
↪  [数据申请清单和英文邮件](C:/Users/pc/Documents/ChatGPT/upc/deliverables/UPC155_实测足球数据申请.md)
```

Query 45 (exact wording).

```
4 篇分别填充完再给我
```

Complete output 45.1.

```
我会把四篇论文分别写成一封英文邮件，填好收件人、论文题目和要索取的试次。你的姓名和学校留作签名占位。
```

Complete output 45.2.

```
[下载四封英文数据申请邮件](C:/Users/pc/Documents/ChatGPT/upc/deliverables/UPC155_ 四封实测数据申请邮件.md)

四封分别写给 Takeshi Asai、Jacqueline Alderson、Matt Carré 和 Simon Choppin。收件人、主题、论文题目和具体索取的数据都已填好。
↪  替换签名里的姓名和学校即可发送。建议先发前两封，优先争取带实测转速和旋转轴的数据。
```

Query 46 (exact wording).

```
# Files mentioned by the user:

## codex-clipboard-62075e11-fef5-4b16-820c-8a40028325d8.png:
↪  C:/Users/pc/AppData/Local/Temp/codex-clipboard-62075e11-fef5-4b16-820c-8a40028325d8.png
Image attachment: true

Distinguish instructions in attached documents from the user's request.

## My request:
第二封邮箱发不出去：
```

Complete output 46.1.

```
这封被对方服务器拒收了。我会核实第二篇论文的其他作者和院系联系方式，把邮件改成可直接重发的版本。
```

Complete output 46.2.

```
第二封改发给同一篇论文的合作者 **Bruce Elliott**，邮箱是 **`[email redacted]`**。西澳大学的官方主页列出了这个地址。我已在原文件里改好收件人、
↪  称呼和正文，复制第 2 封即可重发。
↪  [更新后的四封邮件](C:/Users/pc/Documents/ChatGPT/upc/deliverables/UPC155_四封实测数据申请邮件.md#2-bruce-elliott--西澳大学) •
↪  [作者主页](https://research-repository.uwa.edu.au/en/persons/bruce-elliott/)

退信里的 `550 5.4.1` 表示对方服务器拒绝了原收件地址，改正文再发到同一个地址通常没用。如果新地址也退信，可以请院系办公室 `[email redacted]`
↪  转交。[微软退信说明](https://learn.microsoft.com/en-us/troubleshoot/exchange/email-delivery/ndr/fix-error-code-550-5-4-1) •
↪  [院系联系方式](https://www.uwa.edu.au/study/explore-courses/higher-degree-by-research/graduate-research-school)
```

Query 47 (exact wording).

```
更新后的四封邮件打不开
```

Complete output 47.1.

```
我会检查文件是否还在，再准备一份英文文件名的纯文本副本，方便直接打开和复制。
```

Complete output 47.2.

```
上次的链接带了章节锚点，可能影响打开。这里是两个直接文件链接：

- [四封英文邮件（TXT）](C:/Users/pc/Documents/ChatGPT/upc/deliverables/UPC155_data_request_emails.txt)
- [四封英文邮件（Markdown）](C:/Users/pc/Documents/ChatGPT/upc/deliverables/UPC155_ 四封实测数据申请邮件.md)

两份都已把第 2 封的收件人改为 `[email redacted]`。
```

Query 48 (exact wording).

```
看看最新的成果，似乎有进展
```

Complete output 48.1.

```
我会查看仓库的新提交和结果表，核对这次进展来自新数据、模型改进，还是评估口径的变化。
```

Complete output 48.2.

```
有进展。** 台式机独立复现了仿真数据和此前的实测外推结果。** 我看了最新提交 [1a36725]([team repository])，也核对了回传压缩包里的日志。

- **数据能复现。** 台式机重新生成的 50,000 条轨迹与检验包的文件 SHA-256 一致，4,187 条测试集的划分一致。256 条抽样轨迹重算和 14 项测试均通过。
- **之前的误差也能复现。** 四个实测案例和 11 段 DFL 的外推结果均在数值容差内一致。这让我们更有把握排除换电脑或环境造成的差异。
↪  [台式机回传结果]([team repository])

**这次新增的是可复现证据。** 提交里没有新实测数据或新训练结果，约 54 cm 的横向偏差仍待解释。接下来可以把复现记录写进论文，
↪  并用这套已确认一致的环境复核 Arm C 的校准结果。
```

Query 49 (exact wording).

```
能不能再进一步提升了，现在还有很充足的时间可以训练模型
```

Complete output 49.1.

```
可以。我会用 brainstorming 技能先把对照设计清楚，再开跑。上一轮只校准了预测区，这次直接比较落点误差，同时检查误差下降有没有牺牲概率预测质量。
```

Complete output 49.2.

```
可以继续提升。这轮的目标是**直接降低落点误差**。目前 Arm C 在 5 mm 和 15 mm 噪声下的仿真中位误差分别是 **29.4 cm** 和 **55.9 cm**，
↪  上一轮校准改善的是预测区域的覆盖率。

我建议做一轮有明确对照的训练：

1. ** 先把 Arm C 从 100 轮续训到 200 轮。** 用验证集选检查点，判断多训练本身能带来多少收益。
2. **再训一个利用左右对称的版本。** 当前无风仿真里，把两次观测的横向坐标镜像，落点也应镜像。用这个关系做训练增强，并去掉线性重复的物理特征。
↪  这样能检验改进来自哪里。
3. **最后用同一批 4,187 条冻结轨迹比较。** 同时报落点中位误差、NLL 和校准后的预测区面积。只有落点更准、概率预测也没有明显变差，才替换 Arm C。
↪  真实 DFL 另做验证。

这是现有训练流程内的小改动。按 [brainstorming 技能](C:/Users/pc/.codex/skills/brainstorming/SKILL.md) 的要求，“implementation starts only
↪  after your human partner says yes to that design”。**确认按这套对照跑吗？** 确认后我负责训练、评估和出表。
```

Query 50 (exact wording).

```
确认
```

Complete output 50.1.

```
我会先用相同的训练和验证划分跑两组：Arm C 再训 100 轮，以及去掉重复特征、加入左右镜像的新模型。两组都用验证集选检查点，冻结测试集只用于最后对照。
```

Complete output 50.2.

```
第一组种子已经训完。两个版本的验证集 NLL 都低于原 Arm C，但落点是否更准还要看冻结集。我另外留出一批独立仿真轨迹做区域校准，
↪  避免用选过检查点的数据再校准覆盖率。
```

Complete output 50.3.

```
两种方案都完成了前两个种子，最后一个种子正在训练。我也用 256 条轨迹检查了镜像假设：左右翻转后，过门或触地标签保持一致，观测和落点都按预期翻转。
```

Complete output 50.4.

```
两轮训练都跑完了。**Arm C 续训后，概率预测略有改善，但落点只准了约 1 毫米；镜像增强加特征去重也没有带来实质提升。**

| 每轴噪声 | 原 Arm C | 续训 | 镜像＋去重 |
|---|---:|---:|---:|
| 5 mm 落点中位误差 | 29.41 cm | **29.27 cm** | 29.31 cm |
| 15 mm 落点中位误差 | 55.88 cm | 55.97 cm | **55.85 cm** |

每组跑了三个种子，使用同一份 **4,187 条冻结仿真测试集**。续训在四档噪声下的平均负对数似然都有下降，但校准后的 95% 预测区面积变化很小。
↪  旧检查点只保存了权重，所以续训时重新初始化了优化器。镜像和去重在同一组里测试，结果只能评价两者的组合。

**建议保留原 Arm C 作为主基线，把剩余训练时间用来验证仿真到实测的差距。** 这轮模型固定用题面的 0.05/0.10 s，DFL 数据用的是 0.04/0.08 s。
↪  下一轮更有价值的是让模型适配观测时刻，在相同输入条件下和物理基线做实测对照。上表还不能说明那约 54 cm 的实测横向偏差有改善。

[完整训练对照报告](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/runs/p2_training/训练对照.md) ·
↪  [训练与评估脚本](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/experiments/p2_train_spin_symmetry.py)
```

Query 51 (exact wording).

```
好的，继续
```

Complete output 51.1.

```
我会按刚才定的方向继续：训练一个能接收实际观测时刻的模型，让它直接用 DFL 的 0.04/0.08 秒数据。两条实测点球的过门点只用于评分，
↪  届时会和已有物理基线逐球比较。
```

Complete output 51.2.

```
两个种子都已训完，正在评分。仿真器改动已用解析轨迹核对，旧配置抽检的 256 条轨迹也与原数据逐值一致。
↪  实测表会把网络的落点误差和物理模型的提前触地风险分开列出，因为这次网络预测的是球已空中到达门平面时的落点。
```

Complete output 51.3.

```
** 已经按 DFL 的实际观测时刻重训并做了实测对照。修正时刻后，落点精度没有实质提升。** 两个训练种子都得到相近结果。

| 实测点球 | 仅阻力物理模型 | 阻力＋宽旋转先验 | 时序适配网络 |
|---|---:|---:|---:|
| J03WOH | 64.6 cm | 54.2 cm | **54.0 cm** |
| J03WR9 | **54.2 cm** | 55.0 cm | 59.3 cm |

三组都用 **0、0.04、0.08 秒**的观测，表中假设每轴追踪误差为 15 mm。网络在第一球与带旋转的物理模型接近，第二球仍横向偏了约 **58 cm**。
↪  按落点误差不超过 50 cm 计，网络依然是 **0/2**。两球都落入了预测区，但两例不足以判断真实覆盖率。

这轮说明，**仅对齐观测时刻，解决不了剩下的横向偏差**。我会保留物理模型作为实测主对照。下一步最有判别力的是用现有 DFL 数据做一次误差拆分：
↪  把同一条轨迹分成短窗、长窗和整段拟合，检查偏差随观测窗增加能消掉多少，以及物理模型对整段轨迹还剩多少系统残差。这样可以先定位问题，
↪  不必等作者回信才继续。

[实测对照报告](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/runs/p3_variable_window/观测时刻适配.md) ·
↪  [训练与评分脚本](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/experiments/p3_variable_window.py)
```

Query 52 (exact wording).

```
做吧，效率高一点
```

Complete output 52.1.

```
我会只跑两条 DFL 点球的物理对照，不重训网络。用前三帧和前六帧预测同一段后续轨迹，再用整段拟合检查横向残差还能消掉多少。
```

Complete output 52.2.

```
跑完了。** 这两球在前六帧里已经有足够的弯曲信息。用六帧拟合有效旋转，过门误差降到了约 8 cm。**

| 拟合条件 | J03WOH 过门误差 | J03WR9 过门误差 |
|---|---:|---:|
| 前三帧，固定阻力 | 64.7 cm | 54.2 cm |
| 前六帧，固定阻力 | 41.8 cm | 32.0 cm |
| 前六帧，拟合阻力 | 41.5 cm | 31.9 cm |
| 前六帧，拟合阻力和有效旋转 | **8.3 cm** | **7.7 cm** |

多看三帧本身改善约 **22 cm**。在同样的六帧上，单调阻力只改善几毫米，加入有效旋转又改善了 **24–33 cm**。整段回拟后，三维轨迹 RMSE 分别为 **1.5
↪  cm 和 4.1 cm**。这说明现有物理模型有能力描述这两球的大部分弯曲，短窗下怎样估计侧向气动力才是更直接的瓶颈。

**8 cm 是六帧诊断结果，正式解题仍只有题面规定的观测。** 拟合出的有效旋转也可能吸收追踪和气动误差。接下来可以用现有长轨迹反演有效侧向加速度，
↪  再按整条轨迹留出，检验学到的先验能否改善短窗预测。

[误差拆分报告](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/runs/p4_window_residual/观测窗口误差拆分.md) ·
↪  [完整数值](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/runs/p4_window_residual/scores.json)
```

Query 53 (exact wording).

```
可以可以
```

Complete output 53.1.

```
我会做一次按比赛留出的对照：用其他比赛的长轨迹估计侧向气动力先验，再拿被留出的比赛前三帧做预测。这样能直接检验这个先验能不能迁移到新点球。
```

Complete output 53.2.

```
按整场比赛留出跑完了。** 从普通比赛片段学来的旋转先验，对短期轨迹预测略有帮助，但没有稳定改善点球落点。**

| 评估 | 宽均匀先验 | 从其他比赛学来的先验 |
|---|---:|---:|
| 11 段比赛片段，后续六帧 RMSE 中位数 | 11.27 cm | **10.02 cm** |
| J03WOH 过门点误差 | **53.91 cm** | 64.99 cm |
| J03WR9 过门点误差 | 55.29 cm | **54.57 cm** |

11 段里有 7 段改善，但逐段配对后，典型改善只有 **0.14 cm**。两条点球都只用前三帧预测，同场数据也排除在先验学习之外。结果是一球差了 **11.08
↪  cm**，另一球只好 **0.72 cm**。

**论文里保留宽均匀先验作主对照，把这次结果作为迁移实验。** 上一轮六帧能把单球误差降到约 8 cm，说明多看几帧能读出这球怎么弯。
↪  这次检验的是另一件事：从别的比赛学到的弯曲规律，能不能补上当前这球缺失的信息。现有数据下还没有看到稳定收益。

[跨比赛验证报告](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/runs/p5_transfer_spin_prior/跨比赛旋转先验验证.md) ·
↪  [逐段结果](C:/Users/pc/Documents/ChatGPT/upc/integration/student_b/runs/p5_transfer_spin_prior/scores.json)
```

Query 54 (exact wording).

```
对比现有成果与这个工作区内另一个对话的成果，整合
```

Complete output 54.1.

```
我先找出同一工作区里的另一条 UPC 对话，再把两边的代码、数据和结果按用途对齐，整理成一份可交给队友的汇总。
```

Complete output 54.2.

```
两边各有可用成果：另一条对话跑完了四组题例贝叶斯预测，本对话补齐了冻结集校准和 DFL 实测对照。我还把同一批 1,000 组初始参数送进两套仿真器，
↪  发现共同过门轨迹的落点差异 RMS 约 36 cm，不能把两边的训练分数直接排在一张表里。
```

Complete output 54.3.

```
已整合成一份可以交给队友的报告，并更新了工作区里的协作进度页。[双线成果整合](F:/ChatGPT/upc/deliverables/UPC155_双线成果整合.md) •
↪  [协作进度](F:/ChatGPT/upc/integration/agent_readme.md)

**最关键的发现是，两条对话用了不同的仿真器。** 我把同一批 1,000 组初始参数送进两套代码，统一积分步长。结果有 **32 组**过门或触地的判定不同，793
↪  组共同过门轨迹的落点差异 RMS 为 **35.9 cm**。因此两边的网络分数不能直接用来排模型名次。
↪  [同参数复核结果](F:/ChatGPT/upc/deliverables/UPC155_simulator_bridge.json)

建议论文按以下口径整合：

- ** 主文用 canonical 仿真器和 Arm C。** 这套有冻结测试集、独立校准和台式机复现。续训与镜像增强的落点收益在毫米量级，保留原 Arm C。
- **另一条对话的四组贝叶斯题例放进敏感性附录。** 它补齐了密度众数、联合预测区和有效样本量。例如参考模型在 5 mm 标准先验下的众数为
↪  **\((2.80,1.95)\) m**。该分支的 MDN 评估在 2 mm 档因校准未达标、Brier 为 `NaN` 而停止。
- **实测主线用 DFL 的窗口诊断。** 前三帧的过门误差约 **54–65 cm**，六帧拟合有效旋转后约 **8 cm**。跨比赛学习的先验没有稳定改善短窗结果。
↪  六帧结果应写成定位误差的实验，题例答案仍用规定时刻的观测。
```

Query 55 (exact wording).

```
上传至仓库
```

Complete output 55.1.

```
我会把整合报告、协作进度和支撑结论的结果一起上传，并把报告链接改成仓库内可打开的路径。会先核对远端最新提交，保留队友已经推上的内容。
```

Complete output 55.2.

```
远端刚发布了正式 P1 结果，并已同步到论文。我会保留它作为主结果，把这次整合放在补充材料里，清楚区分正式盲测、此前的 Arm C 开发对照和新增 DFL
↪  诊断。
```

Complete output 55.3.

```
已上传到 `UPC155` 的 `main` 分支，并确认远端提交生效。[提交 `33a7d02`]([team repository])

[整合报告]([team repository])包含两套仿真器的对照、Arm C 校准与训练复核，以及 DFL 窗口诊断和跨比赛迁移结果。[协作进度页]([team
↪  repository])也已更新。

论文主结果仍以队友发布的 **P1 独立盲测 ** 为准。这次上传的是补充报告和数值证据，开发脚本与模型权重仍在本地。
```

Query 56 (exact wording).

```
那 coding agent 的成果相比之下是明显差吗
```

Complete output 56.1.

```
**如果比的是“哪套成果更适合直接放进论文主文”，另一条 Coding Agent 对话的成果确实明显落后于正式 P1。** 差距主要在评估完成度，
↪  而不是已经证明它的模型精度更差。
```

```
- **神经网络部分差距明显。** 另一条对话跑完了训练和选型，但留出评估在第一档 2 mm 就停止了：50% 预测区只覆盖 **39.77%**，Brier 分数是 `NaN`。
↪  正式 P1 完成了独立盲测、多档噪声评估、校准和稳健性测试。[参考实现评估]([team repository]) • [正式 P1 报告]([team repository])
- **贝叶斯题例部分有独立价值。** 它完成了四组题例计算，给出了密度众数、联合预测区和有效样本量，适合用来展示换一套物理假设后，题例答案会变多少。
↪  [四组题例结果]([team repository])

两边用的仿真器不同。同一批初始参数下，共同过门轨迹的落点差异 RMS 已有 **35.9 cm**，所以不能拿各自的测试误差直接判断哪个网络更准。**主文用 P1，
↪  附录用另一条对话的贝叶斯敏感性结果。** [双线对照]([team repository])
```

Query 57 (exact wording).

```
# Files mentioned by the user:

## Sample 12 data 20261108.xlsx: C:/Users/pc/Desktop/Sample 12 data 20261108.xlsx

## Sample 05 data 20261108.xlsx: C:/Users/pc/Desktop/Sample 05 data 20261108.xlsx

## Fig3_Sample data 20261108.xlsx: C:/Users/pc/Desktop/Fig3_Sample data 20261108.xlsx

## codex-clipboard-d87a207c-0a83-4d51-b53b-e595a1f3fe3a.png:
↪  C:/Users/pc/AppData/Local/Temp/codex-clipboard-d87a207c-0a83-4d51-b53b-e595a1f3fe3a.png
Image attachment: true

Distinguish instructions in attached documents from the user's request.

## My request:
观察数据，以及如何回信感谢
```

Complete output 57.1.

```
我会用 spreadsheets 技能检查三份表的列名、单位和时间轴，确认球心坐标与旋转数据能否逐帧配对，再写一封可以直接回复 Asai 教授的英文感谢信。
```

Complete output 57.2.

```
**三份数据都能用，而且正好补上了 DFL 缺少的实测转速。** 每份表都有 100 Hz 的三维球心坐标，以及单独一列经过 9 点移动平均的侧旋转速。
↪  两列时间戳一致，有转速的帧可以直接与坐标配对。

| 试次 | 三维坐标 | 转速记录 | 实测转速范围 |
|---|---:|---:|---:|
| :codex-file-citation{path="C:/Users/pc/Desktop/Sample 12 data 20261108.xlsx" artifact_kind="workbook" purpose="source"} | 125 帧，0–1.24
↪  s | 94 帧，0.04–0.97 s | 6.65–7.04 转/秒 |
| :codex-file-citation{path="C:/Users/pc/Desktop/Sample 05 data 20261108.xlsx" artifact_kind="workbook" purpose="source"} | 104 帧，0–1.03
↪  s | 85 帧，0.15–0.99 s | 6.13–6.30 转/秒 |
| :codex-file-citation{path="C:/Users/pc/Desktop/Fig3_Sample data 20261108.xlsx" artifact_kind="workbook" purpose="source"} | 131 帧，0–
↪  1.30 s | 96 帧，0.05–1.00 s | 5.75–5.84 转/秒 |

接进模型时有两个细节。表里是 **`y` 向前、`x` 向左**，和我们代码的轴定义不同。转速列也只有一个标量，缺帧应保留为空。尤其是 **Sample 05 到 0.15 s
↪  才有转速**，可以拿来验证后段弯曲，但不能把这个值直接当成离脚转速。

三条轨迹都越过了距各自首帧 **11 m 的虚拟截面**。最值得先做的是用前三个坐标点预测该截面的落点，再比较**使用实测转速**与**仅使用旋转先验**的误差。
↪  这是弧线球的外部验证，虚拟截面可以统一评分。

** 回信直接在原邮件线程回复即可。** 我建议感谢为主，顺便确认两个会影响计算的细节：

> Dear Professor Asai,
>
> Thank you very much for taking the time to locate and share the data from all three trials, including the one shown in Figure 3. The
↪  ball-centre trajectories and the accompanying spin-rate measurements are exactly what we need to test how much knowing the spin
↪  improves our flight predictions.
>
> May I check two details before we use the data? Does \(t=0\) denote the instant the ball left the foot, or the first available tracking
↪  frame? Also, are the positive spin-rate values magnitudes only, or do they indicate a specific direction of rotation about the
↪  vertical axis?
>
> We will cite your paper and acknowledge your help in our report. Thank you again for your generosity and for your kind wishes for the
↪  competition.
>
> Best regards,
> [Your Name]
```

```
> On behalf of our University Physics Competition team
```

Query 58 (exact wording).

```
# Files mentioned by the user:

## codex.md: C:/Users/pc/Desktop/codex.md

Distinguish instructions in attached documents from the user's request.

## My request:
```

Complete output 58.1.

```
我先看桌面的 `codex.md`，确认它是老师的回信、数据说明，还是你想让我执行的任务。
```

Complete output 58.2.

```
我读了 [codex.md](C:/Users/pc/Desktop/codex.md)。它提出了一个可行的方向：冻结 P1，用 Asai 的三条实测轨迹做外部复演。
↪  **但表里的厘米级误差目前只能当作待复核的数值。** 有三处会影响论文结论：

1. ** 全轨迹拟合用了后段数据。** 它能说明这套方程可以拟合这三条轨迹，但表里约 1 cm 的误差属于拟合内残差，不能用来评价只看前 0.10 秒的预测。
2. **转速辅助要单列。** Sample 05 到 0.15 秒才有转速，晚于预测截止点。另两条虽然更早有转速值，但作者用了 9 点移动平均。
↪  滤波是否用了截止点之后的数据，还要确认。
3. **P1 平移适配需要实测检验。** 飞行动力学允许平移，但 P1 的训练样本受固定地面和提前触地筛选约束。把首帧高度移到 0.11 m 再移回，
↪  可以作为冻结权重的适配方法，效果要靠复演评分判断。

文档里还写了改论文和推送仓库。你这条消息没有指定执行范围，我只做了审阅。**你是想让我按修正后的口径，先在本地复演三条轨迹、跑冻结 P1 并出图表吗?
↪  **
```

Query 59 (exact wording).

```
你负责执行。
```

Complete output 59.1.

```
我来执行。先本地复演三脚球，主预测只用 0、0.05、0.10 秒的位置。实测转速辅助和整段拟合会单列。随后用正式 P1 的冻结权重评分，
↪  把核实过的结果写进论文，再提交代码和可分享的结果。
```

Complete output 59.2.

```
第一轮复演完成了。按统一的 canonical 物理模型和正式冻结 P1 运行后，短窗误差没有复现手册里的约 11 cm；整段回拟仍是厘米级。
↪  我会再单独运行手册自带的算法，核对差异是否来自它固定的升力先验。
```

Complete output 59.3.

```
手册里约 11 cm 的结果可以复现，但它用了另一套升力律，并预设了升力幅值和方向，不能把收益单独归给 10 mm 噪声设定。正式 P1 的三球误差约 50–60 cm。
↪  我已把两种口径分开写入论文，更新稿也已编译通过。
```

Complete output 59.4.

```
已完成三球复演、冻结 P1 评分和论文更新，并推送到仓库 `main`。[提交 `2839884`]([team repository])

| 11 m 虚拟截面落点误差 | Fig. 3 | Sample 05 | Sample 12 |
|---|---:|---:|---:|
| 恒加速度 | 44.7 cm | 21.9 cm | 52.6 cm |
| 物理后验，仅用前三个位置 | 55.2 cm | 52.4 cm | 61.9 cm |
| ** 冻结 P1，高度平移 ** | **54.5 cm** | **49.9 cm** | **59.6 cm** |
```

```
| 物理模型整段回拟 | 0.20 cm | 1.12 cm | 0.65 cm |

**P1 的 95% 预测区覆盖了三个参考点，但点预测仍偏约 50–60 cm。** 整段回拟利用了后续观测，厘米级误差反映的是拟合能力。单独提供实测转速幅值，
↪ 在本次旋转轴假设下也没有改善预测。

手册里的 **平均 11.39 cm** 可以复现，但它同时使用了不同的升力律和预设的升力方向。论文已把这项对照单列，避免把改善归因于 10 mm 噪声设定。P1
↪ 权重经哈希核对，未重训；14 项原有测试通过，论文编译为 15 页。

[复演报告与三球叠加图]([team repository]) • [本地编译后的论文 PDF](F:/ChatGPT/upc/deliverables/asai_official/paper/main.pdf)
```

Query 60 (exact wording).

```
那就是说，根据新数据做的仿真，没有进步意义？
```

Complete output 60.1.

```
** 有意义，但目前的进步在于找到了模型的问题，还没有转化为预测精度的提升。** 如果之前让你以为“拿到新数据就能显著提分”，那是我说得过满。

这三条数据给出了两个很重要的结果：

- ** 用完整轨迹反推，模型能把轨迹拟合到厘米量级。** 说明现有物理方程有能力描述这些轨迹，但这属于事后拟合，不能代表提前预测准确。
- **只给前 0.1 秒，现有 P1 的终点误差仍约 50–60 cm。** 说明短窗口下，自转、升力方向等信息仍不够明确；增加同一套假设生成的训练数据，不一定能解决。

手册中约 **11 cm** 的结果值得追查，但它同时改了升力模型和方向先验。**我们还不能说它优于现有方法，更不能直接把这些假设调到三条数据上，
↪ 再用同三条证明成功。**

下一步最值得做的是：**固定观测和评分方式，分别替换升力规律、方向先验、噪声模型，找出到底哪项造成 11 cm 与 50–60 cm 的差距。**
↪ 然后做三条轨迹轮流留一验证，检查改进能否迁移；样本仍少，结论要保持有限。

所以，新数据不是白拿了。它让我们第一次能较清楚地区分：**模型能否描述飞行，与模型能否从两次观测预测飞行，是两件需要分别验证的事。**
↪ 现在应先修正并验证生成数据的假设，再投入大量训练。
```

Query 61 (exact wording).

```
你自主规划并推进实验，记得仿真等实验可以交给 dsh 和 gemini 来，你的额度紧张
```

Complete output 61.1.

```
我先把实验缩成“升力规律、方向先验、噪声模型”的对照，交给可用的 DSH/Gemini 执行；我负责检查实验设计和结果，避免用三条数据调参后再自证有效。
```

Complete output 61.2.

```
这轮属于已有实验上的有限改动，按你授权自主推进。我会使用 brainstorming 技能明确对照设计，并按 codex-dsh-collab 流程让 DSH 先审后做。正式 P1
↪ 保持冻结，三条实测数据只支持探索性验证，不据此宣称普遍提升。
```

Complete output 61.3.

```
DSH 已接到执行任务。目前没有找到可直接调用的 Gemini 接口，这批先由 DSH 跑。对照还会检查一个容易遗漏的问题：手册默认从负向旋转开始拟合，约 11 cm
↪ 的结果是否受初值和局部最优影响。
```

Complete output 61.4.

```
验收标准已固定：所有方法使用相同的前三点和 11 m 截面；三条轨迹轮流留出时，先验只能由另外两条建立。这样即使误差下降，
↪ 也能检查改进是否依赖提前看过目标轨迹。
```

Complete output 61.5.

```
DSH 仍在执行，还没有产出可验收的结果。我会先完成这批归因实验，再决定是否值得重生成仿真数据、交给台式机训练。
```

Complete output 61.6.

这轮会把“拟合得到的最佳单点”和“后验分布均值”分开比较。此前约 11 cm 与 50-60 cm 的两组结果连点预测定义都不同，
↪ 不能直接用差值判断哪套物理模型更好。

Complete output 61.7.

对照脚本已经生成。接下来重点核查两件事：换正负旋转初值后结果是否稳定，以及留出轨迹的后半段是否完全没有进入拟合。

Complete output 61.8.

初步代码审查发现，防泄漏测试必须按“时间大于 0.10 秒”修改数据，不能按“第三行之后”修改——100 Hz 原始表的第 5、10 帧也是输入点。
↪ 我会核实这一项，避免测试本身给出错误结论。

Complete output 61.9.

脚本和独立检查文件已生成，完整数值结果还没出来。我会按逐球误差和对照差值验收；如果改进只适用于这组三条弧线球，就保留为专项结果，
↪ 不替换正式点球模型。

Complete output 61.10.

目前尚无可报告的精度提升，DSH 还在实现和检查阶段。我已记录防泄漏测试的索引问题，最终会独立复核测试和逐球结果，不直接采信执行代理的结论。

Complete output 61.11.

找到延迟原因了：DSH 的执行沙箱报了 Windows 目录权限错误，Python 没有启动。代码已交付，我会在当前可用的本地环境运行和复核，不修改 DSH
↪ 的沙箱设置。

Complete output 61.12.

已修正防泄漏测试的索引和评分测试的字段引用，7 项检查全部通过。实际对照开始出结果了：恒定升力、无先验、首点固定时，三球误差约为 24.5、9.3、48.7
↪ cm。后续组合会检验先验是否能稳定改善它们。

Complete output 61.13.

对照已显示一个关键差异：只给升力幅值先验，Sample 12 仍误差约 48 cm；加入手册的竖直升力分量约束后，它降到约 12 cm。放松首点本身改变很小。因此，
↪ 约 11 cm 的成绩主要不能归功于“加入 1 cm 测量噪声”。留一验证还在跑。

Complete output 61.14.

现有升力规律配合相同的方向约束，也得到约 13.2、8.3、10.4 cm 的误差，说明暂时没有证据要求推翻现有物理方程。结果汇总时发现评分字段漏写，
↪ 我已修复并补上检查，正在重跑以生成完整、可核查的报告。

Complete output 61.15.

目前的改进并非每球都一样：方向约束对 Sample 12 帮助很大，对 Fig. 3 却比单独的幅值先验略差。报告会保留逐球结果，避免平均误差掩盖这种取舍。

Complete output 61.16.

留一验证完成了：从另外两球建立先验，现有物理模型的平均误差约 22.5 cm；无先验约 26.0 cm，手册方向先验约 10.6 cm。
↪ 新数据确实带来了可迁移的改进线索，但尚未复现手册的低误差。正负初值重复拟合结果几乎一致，这次差距不是初值碰巧选对造成的。

Complete output 61.17.

```
已完成 **12 组对照、4 组留一验证，共 672 次拟合 **。DSH 写主要代码，我修复问题并完成本地运行、独立检查；7 项测试通过。

关键结果：

- 无先验：平均误差 **26.00 cm**。
- 从另外两球建立先验：**22.45 cm**，降低约 **13.7%**，但两球变差、一球明显改善。
- 手册方向先验：**10.63 cm**，说明方向约束很关键，但尚不能证明它适用于一般点球。
- 放松首点、改变拟合初值，都不是主要提升来源。

**新数据有用，但现在应先验证先验能否迁移，暂不盲目扩大训练。** 正式 P1 保持冻结；下一批优先统一 MAP/后验均值的比较，再检查 DFL/ISSIA 上的效果。

[完整实验报告](F:/ChatGPT/upc/integration/student_b/runs/asai_factorial/README.md) ·
↪  [逐项结果](F:/ChatGPT/upc/integration/student_b/runs/asai_factorial/results.csv)

本批已保存在本地，尚未上传仓库。
```

Query 62 (exact wording).

```
继续推进，尽量把工作交给 dsh
```

Complete output 62.1.

```
我把下一批交给 DSH：统一先验后比较 MAP、后验均值和众数，再用 DFL/ISSIA 检查方向约束是否能迁移。我负责验收；如果 DSH 仍受沙箱限制，
↪  就由本地运行它交付的脚本。
```

Complete output 62.2.

```
已按 codex-dsh-collab 流程派发任务，优先检验两条真实点球和两条 ISSIA 轨迹。比较中会明确区分“参数最可能值对应的落点”和“预测落点分布的众数”，
↪  避免把不同估计量混作同一结果。
```

Complete output 62.3.

```
已确认 ISSIA 是 25 Hz，不能照搬 Asai 的 0.05/0.10 秒取点。外部验证将使用真实的 0、0.04、0.08 秒观测；两条点球按球门截面评分，ISSIA
↪  按实际后续轨迹评分，不混合求平均。
```

Complete output 62.4.

```
这批外部实验会固定三种方案：无方向先验、手册先验、Asai 数据建立的先验。不会根据 DFL/ISSIA 的答案调参数；这样即使结果变差，
↪  也能据此判断哪些先验不适合通用点球模型。
```

Complete output 62.5.

```
DSH 还在实现，尚未交付可运行结果。概率比较也已设定验收要求：同时报告有效样本量、两次随机种子的差异，以及到达截面的概率，
↪  避免把采样不稳定误判为方法优劣。
```

Complete output 62.6.

```
这轮先完成物理和统计验证，不启动新的大规模训练。上一批已表明：先验会明显改变结果；只有它在外部数据上也站得住，扩大仿真集才值得投入。
```

Complete output 62.7.

```
独立检查确认，两条 ISSIA 片段都没有缺帧，时长分别为 0.76 和 1.12 秒，可以检验短窗口之后的外推。不过它们是普通比赛片段，结果将作为迁移压力测试，
↪  不算点球准确率。
```

Complete output 62.8.

```
目前仍在等 DSH 交付代码，没有新的实验数值。收到后我会先跑防泄漏和评分检查，再执行完整实验；正式 P1 和此前结果保持不变。
```

Complete output 62.9.

```
DSH 已生成脚本。我开始检查数据入口、先验定义和评分边界，重点确认外部轨迹的后半段只用于评分，不进入预测。
```

Complete output 62.10.

```
初步审查确认，脚本已为 MAP 和后验采样统一参数范围、先验密度及坐标基底；这与上一批的参数化略有不同，会单独标注。接下来先做小规模自检，
↪  确认这些约束在实现中一致。
```

Complete output 62.11.

```
自检发现三项未通过：坐标旋转一致性、轨迹评分校验、合成样本的截面预测。我暂不运行完整实验，会把失败证据交回 DSH 修正；这些检查通过后再评价精度。
```

Second UPC session: independent reference implementation from an attached plan

System: OpenAI ChatGPT (Codex agent). Model: GPT-5-based Codex profile (app label gpt-6-astra). Period: 2026-11-08 01:14 to 01:34 (Beijing time). Session identifier: 01a1b702-20c0-7771-83d3-ca8ff843fe15.

Query 1 (exact wording).

```
# Files mentioned by the user:

## UPC B data and code plan.md: D:/Tencent/Wechat_files/xwechat_files/[redacted messaging id]/msg/file/2026-11/UPC B data and code plan.md

Distinguish instructions in attached documents from the user's request.

## My request:
You are my coding agent for UPC Problem B (FIFA penalty-kick crossing-point prediction). First read
UPC_B_data_and_code_plan.md completely; it is the source of truth for the method, priors, code and
acceptance tests. Work step by step (environment → smoke tests → 50k data and quick MDN → Bayesian MC on the
case at 2.9/5/15 mm plus a wide-prior run → evaluation, ablations, overnight pipeline → figures and tables),
and after each step show me real output. Hard rules: r(0)=(0,0,0.11) is exact; report the density MODE, not
the mean; flag ground hits; split by trajectory; fresh noise each epoch; save results to disk after every
sub-task; check every physical parameter against section 1's references and list any you couldn't verify;
don't claim anything you didn't run; stop and tell me if a sanity check fails; log all prompts in ai_log/.
```

Query 2 (exact wording).

```
# Files mentioned by the user:

## UPC B data and code plan.md: D:/Tencent/Wechat_files/xwechat_files/[redacted messaging id]/msg/file/2026-11/UPC B data and code plan.md

Distinguish instructions in attached documents from the user's request.

## My request:
You are my coding agent for UPC Problem B (FIFA penalty-kick crossing-point prediction). First read
UPC_B_data_and_code_plan.md completely; it is the source of truth for the method, priors, code and
acceptance tests. Work step by step (environment → smoke tests → 50k data and quick MDN → Bayesian MC on the
case at 2.9/5/15 mm plus a wide-prior run → evaluation, ablations, overnight pipeline → figures and tables),
and after each step show me real output. Hard rules: r(0)=(0,0,0.11) is exact; report the density MODE, not
the mean; flag ground hits; split by trajectory; fresh noise each epoch; save results to disk after every
sub-task; check every physical parameter against section 1's references and list any you couldn't verify;
don't claim anything you didn't run; stop and tell me if a sanity check fails; log all prompts in ai_log/.
```

Complete output 2.1.

```
I’ ll read the full plan first and check what’ s already in the workspace. I’ ll use the brainstorming skill to check the implementation
↪  scope against the plan, then report actual output at each stage.
```

Complete output 2.2.

```
I’ ve read the full plan. I’ ll put its reference implementation in a separate `src/` directory so the existing team experiments stay
↪  intact. I’ ll check both the analytic flight and the supplied case before generating data.
```

Complete output 2.3.

```
Environment setup passed. Python 3.12.10, NumPy 2.5.3, SciPy 1.18.1, and PyTorch 2.15.0 imported successfully. CUDA is unavailable, so
↪  training will run on CPU. I saved the version check and will now run the smoke tests.
```

Complete output 2.4.

```
The smoke tests passed. The no-air crossing matched the analytic solution within 1.09 µm. The case gave \(v=(29.6,8.6,6.3)\) m/s and a
↪  baseline crossing of \((2.4948,1.9204)\) m. The event test also distinguished a crossing, a ground hit, and a short kick. I’ ll now
↪  generate the 50,000 trajectories.
```

Complete output 2.5.

```
The 50,000-trajectory dataset passed its checks. The split is 40,000 train, 5,000 validation, and 5,000 test. There were 40,627 crossings,
↪  9,373 ground hits (18.75%), and zero short kicks. The source audit also identified which priors still lack penalty-specific evidence.
↪  I’ ll now train the quick MDN.
```

Complete output 2.6.

```
The quick MDN passed. Validation NLL fell in every epoch: 4.520 → 3.335 → 2.787 → 2.534 → 2.435. I’ ll start Bayesian MC with the larger
↪  sample budget the plan recommends for 2.9 mm and save each run’ s density mode, HDRs, and ESS before moving on.
```

Complete output 2.7.

```
The parameter audit is saved. The ball dimensions and standard-atmosphere constants check out. The sources support parts of the drag range
↪  and spin-dependent lift, but I could not verify the exact lift curve and cap or the penalty-specific speed, angle, and spin bounds.
↪  The 2.9 mm run is still computing.
```

Complete output 2.8.

```
The 2.9 mm job is still running and has not written a result yet. The runner will save the posterior samples and diagnostics before
↪  checking whether ESS reaches 1,000.
```

Complete output 2.9.

```
The case’ s early positions imply an apparent \(C_d=0.3707\), above the standard prior’ s upper bound of 0.30. I saved that calculation
↪  with the smoke results. It gives us a concrete comparison for the wide-prior run.
```

Complete output 2.10.

```
The 2.9 mm run passed. Its crossing mode is \((2.70,1.95)\) m, the 95% HDR area is 0.215 m², and ESS is 57,356. No posterior weight was
↪  assigned to ground hits or short kicks. About 34% of the crossing posterior sits within 0.01 of the standard \(C_d\) ceiling. The
↪  standard 5 mm run has started.
```

Complete output 2.11.

```
The standard 5 mm and 15 mm runs passed. Their modes are \((2.80,1.95)\) and \((3.20,1.925)\) m, with ESS of 12,053 and 6,589. The 95% HDR
↪  area grew from 0.215 m² at 2.9 mm to 0.518 m² at 5 mm and 1.175 m² at 15 mm. The wide-prior run is underway.
```

Complete output 2.12.

```
The wide-prior 5 mm run passed with mode \((2.70,1.95)\) m, a 95% HDR area of 0.613 m², and ESS of 10,659. Compared with the standard 5 mm
↪  run, the mode moved 0.10 m laterally and the 95% region grew 18%. All four case results are saved. I' ll now compare MDN
↪  configurations by validation NLL before evaluating the held-out trajectories.
```

Complete output 2.13.

```
After 60 epochs, validation NLL was 0.0801 for \(K=1\), 0.1080 for \(K=3\), and 0.1284 for \(K=5\). I' ll use \(K=1\) for held-out
↪  evaluation based on those validation scores. For the plan' s calibration check, I' ll flag departures over 10 percentage points for
↪  the 50% HDR or 5 points for the 95% HDR.
```

Complete output 2.14.

```
I stopped at the 2 mm held-out evaluation because the MDN failed the calibration sanity check. Its 50% HDR covered **39.77%** of true
↪  crossings, below the 40% lower bound I set before evaluation. The 95% HDR covered **93.97%**. Density normalization also produced an
↪  invalid-division warning, and the MDN goal Brier score was `NaN`. [Partial
↪  results](C:/Users/pc/Documents/ChatGPT/upc/outputs/results_table.csv) • [Evaluation
↪  log](C:/Users/pc/Documents/ChatGPT/upc/outputs/evaluation_console.log)

The CPU environment and smoke tests passed. The no-air crossing matched the analytic solution within **1.09 µm**. With exact
↪  \(r(0)=(0,0,0.11)\) m, the case gave \(v=(29.6,8.6,6.3)\) m/s and a constant-acceleration crossing of \((2.4948,1.9204)\) m. The
↪  50,000 trajectories split 40,000/5,000/5,000 by trajectory, with 9,373 ground hits and zero short kicks. With fresh training noise
↪  each epoch, quick MDN validation NLL fell from **4.520 to 2.435** in five epochs. [Smoke
↪  results](C:/Users/pc/Documents/ChatGPT/upc/outputs/smoke.json) • [Training
↪  log](C:/Users/pc/Documents/ChatGPT/upc/outputs/mdn_quick_log.json)

All four Bayesian case runs passed the ESS gate. These are conditional predictions for a case without a measured crossing.

| Noise and prior | Crossing mode \((Y,Z)\), m | ESS | 50% / 95% HDR, m² | P(goal) |
|---|---:|---:|---:|---:|
| 2.9 mm, standard | (2.70, 1.950) | 57,356 | 0.055 / 0.215 | 99.999% |
| 5 mm, standard | (2.80, 1.950) | 12,053 | 0.150 / 0.518 | 99.753% |
| 15 mm, standard | (3.20, 1.925) | 6,589 | 0.286 / 1.175 | 95.153% |
| 5 mm, wide | (2.70, 1.950) | 10,659 | 0.174 / 0.613 | 99.557% |

All four runs assigned zero posterior weight to ground hits and short kicks. The apparent \(C_d=0.3707\) exceeded the standard prior
↪  ceiling of 0.30. At 5 mm, the wide prior shifted the mode 0.10 m laterally and enlarged the 95% HDR by 18%. [Saved case
↪  results](C:/Users/pc/Documents/ChatGPT/upc/outputs/case_runs.json)

The reference audit lists the unverified assumptions, including the exact lift law and cap, penalty-specific speed, angle and spin bounds,
↪  the spin-axis distribution, and the wide-prior endpoints. The remaining evaluation, ablations, overnight run, figures, and final LaTeX
↪  table were not run after the failed check. [Parameter audit](C:/Users/pc/Documents/ChatGPT/upc/outputs/physical_parameter_audit.md) •
↪  [Prompt and run log](C:/Users/pc/Documents/ChatGPT/upc/ai_log/assistant_run_notes.md)
```

B. DeepSeek Harness (DSH) coding agent

The following sessions were run with the DeepSeek Harness coding agent (model `deepseek-v4-flash-vision-exp`). The agent was used as the second agent in the team repository and as a delegated sub-agent called by the Codex agent through a local bridge for specific verification and experiment-design tasks. In the delegated mode the "query" is the exact task message delivered by the calling agent. Sessions are listed in chronological order.

Command-behaviour test task (delegated)

System: DeepSeek Harness. Model: deepseek-v4-flash-vision-exp. Period: 2026-11-08 11:25 (Beijing time). Session identifier: 152fb4dd-fe1f-46bd-b91b-458fd0df947e.

Query 1 (exact wording).

```
You are testing whether command execution works in this environment. Do exactly two things and report verbatim:
1. Run the pwsh tool with command `python --version` and workdir `F:\ChatGPT\upc`. Report the exact tool output including any error text.
2. If that fails, run the pwsh tool with command `Get-ChildItem -Name C:\Users\pc\Desktop` and report exact output.
Do not attempt any workarounds, do not write files. Report only the raw outputs.
Your parent agent id is "session-60ae33b3-ab82-4c61-9ff6-52a3b9d864ae". Before you finish, send your result to that agent with
↪  send_message({ agent_id: "session-60ae33b3-ab82-4c61-9ff6-52a3b9d864ae", message: "<self-contained result>" }). The parent shares your
↪  workspace but does not automatically receive your transcript, tool output, or reasoning. Send earlier messages as well when a finding
↪  changes what the parent should do next; sending a message does not end your turn.
```

Query 2 (exact wording).

```
Current runtime context. This snapshot supersedes earlier runtime-context snapshots.

Current DSH file policy: workspace-write. Any available operation enforced by the DSH file sandbox may modify files under the session
↪  workspace: "F:\\ChatGPT\\upc". Some platform temporary areas may also be writable.

Approval prompts are disabled in this session: actions that require approval are rejected automatically — do not request sandbox
↪  escalation (do not set `sandbox_permissions`).

You are a delegated subagent: your permission scope was fixed when you were started and cannot be widened from inside this session —
↪  operations that require approval are rejected automatically. When the task needs access beyond that scope, do not retry the denied
↪  operation; state the limitation in your reply so the delegating agent can handle it.
```

Query 3 (exact wording).

```
<system-reminder>
A skill is a reusable set of task-specific instructions. The following skills are available in this session:

<available_skills>
- `ainiee-translate`: Use when the user wants to translate a novel/epub end-to-end on the coding agent itself (Claude Code or Codex; no
↪  AiNiee app), AiNiee-style — parse, build a locked glossary, translate chapter by chapter following rules (names preserved, title
↪  3-way, term consistency), write back and export. Triggers on "用 agent 翻译这本书", "agent 版 aniee 翻译", "把这本 epub 翻译了" and
↪  similar.
- `brainstorm`: Divergent-then-convergent idea exploration skill. Use when the user has a vague idea, an open problem, a stuck project, or
↪  asks to "头脑风暴 / 帮我发散 / 想几个方案 / 换个思路" and does NOT yet want a decision or an implementation. Turns a fuzzy prompt into
↪  a spread of genuinely different directions, then stress-tests them and lands on one concrete next action. Handles naming, positioning,
↪  project directions, feature ideas, research angles, event themes, and "我该做什么" 类选择困难。
- `business-data-analyst-skill`: Business data analysis and operating diagnosis skill. Use when the user needs to translate a business
↪  question into an analysis plan, define metric logic, validate data quality, break down changes in growth, conversion, retention,
↪  revenue, or efficiency, identify root causes, quantify business impact, and produce actionable recommendations or experiment ideas.
↪  Suitable for operating reviews, growth analysis, user behavior analysis, channel performance analysis, funnel analysis, sales
↪  conversi...
- `campus-event-planning`: 校园与社团活动策划 skill。当用户要策划、审批、执行或复盘一场校内活动时使用——比赛/竞赛、讲座/分享会、迎新/招新、
↪  晚会、展览、志愿服务、社团开放日等。覆盖立项与审批、场地与设备、经费与报销、宣传节奏、人员分工、当天执行脚本、志愿者管理、
↪  应急预案与活动复盘总结。输出可直接交给指导老师、团委或学生会审阅的策划书。
- `durable-tech-buy`: Research and compare expensive, long-lived computer hardware and digital products before purchase. Use for NAS, PCs,
↪  laptops, phones, cameras, networking gear, storage, displays, and similar products when the user wants exact-model cross-platform
↪  pricing, review synthesis, same-price alternatives, price-cycle judgment, reliability/performance analysis, or lifecycle total cost.
↪  Optimized for JD, Taobao/Tmall, Pinduoduo, and Douyin; not for placing orders, adding to carts, or monitoring prices ...
- `research-paper-review`: Academic paper comprehension and adversarial review skill for unpublished drafts. Use when the user needs an
↪  unpublished paper explained in plain language, wants reviewer-grade constructive criticism, needs an advisor-facing feedback memo, or
↪  wants submission-readiness checks (venue compliance, ablation completeness, baseline strength, statistical reporting,
↪  reproducibility). Covers ML/RL/optimization/transportation/energy-systems papers, including MARL and EV-charging scheduling work.
↪  Handle...
</available_skills>

If the user names a skill, or the task clearly matches a skill's description, call the `skill` tool with the exact skill name before
↪  taking task actions. Load all applicable skills, then follow their full instructions. This catalog contains summaries only; do not
↪  infer or follow a skill's instructions until it has been loaded.
A user may also invoke a skill directly; its <skill_content> block then appears in this conversation. Follow it, and do not call the
↪  `skill` tool again for that skill.
</system-reminder>
```

Complete output 3.1.

```
I'll run the exact command requested.
```

Complete output 3.2.

```
The first command failed with an error. Running step 2.
```

Complete output 3.3.

```
Both commands failed. Raw outputs, verbatim:

**1. `python --version` (workdir `F:\ChatGPT\upc`)**

```
Error: SetNamedSecurityInfoW failed (Win32 5): grantWrite(F:\ChatGPT\upc)
```

2. `Get-ChildItem -Name C:\Users\pc\Desktop` (run because step 1 failed; default workdir)

```
Error: SetNamedSecurityInfoW failed (Win32 5): grantWrite(F:\ChatGPT\upc)
```

Both failed identically during sandbox setup, before either command executed — the failure is on `grantWrite(F:\ChatGPT\upc)` (Win32
↪ error 5 = access denied), not from python or from the Desktop path. No workarounds attempted, no files written. Result also sent to
↪ parent agent `session-60ae33b3-ab82-4c61-9ff6-52a3b9d864ae`.
```

Read-only static review task (delegated)

System: DeepSeek Harness. Model: deepseek-v4-flash-vision-exp. Period: 2026-11-08 11:37 (Beijing time). Session identifier: c1fbcbd3-0c92-4cb7-8156-da2bef6ece6e.

Query 1 (exact wording).

```
Read-only static review. Do NOT write or modify any file and do not run shell commands (the sandbox is broken; every pwsh call fails with
↪  "SetNamedSecurityInfoW failed ... grantWrite(F:\ChatGPT\upc)"). Only read files.

Review these three files for concrete defects:
1. F:\ChatGPT\upc\integration\student_b\experiments\asai_factorial.py
2. F:\ChatGPT\upc\deliverables\asai_ablation\test_asai_factorial.py
3. F:\ChatGPT\upc\deliverables\asai_ablation\README.md

Also read for reference:
- F:\ChatGPT\upc\integration\student_b\physics.py (Config, derivative, acceleration)
- F:\ChatGPT\upc\integration\student_b\replay_asai_3kicks.py (read_trial, crossing, fixed_start_fit)
- F:\ChatGPT\upc\deliverables\asai_official\manual_reference.py (the manual algorithm being compared)

Check specifically, and report only real problems (file:line, what breaks, minimal fix):
A. Python syntax/runtime errors that would stop the script before or during execution (unbound names, wrong signatures, bad f-strings,
↪  dict/list misuse, numpy/scipy API misuse such as least_squares bounds/x_scale, solve_ivp t_eval or events usage, `fit.active_mask`,
↪  `fit.optimality`).
B. The lift-parameterisation algebra: c=(c_vert,c_lat), q = c_lat*z_perp - c_vert*y_perp, const law a=K|v|(q x v), canonical
↪  omega=q*|v0|/(1.4R). Does the code's claim hold, i.e. at t=0 do both laws give identical total acceleration for |c|<=0.30, and is the
↪  canonical initial CL equal to |c|? Is the manual's cl_vec with (w_vert,w_lat) exactly reproduced by c_vert=w_vert, c_lat=w_lat? Flag
↪  any sign or factor-1.4 error.
C. Leakage: can any measured frame after 0.10 s, or the 11 m reference, reach the fit or the multi-start seeds? Is the LOOCV prior
↪  construction guaranteed to exclude the held-out trial? Does any code path use held-out error for model/config selection?
D. Will the JSON/CSV writers crash on None/NaN/numpy scalars, and are all promised fields actually populated (prediction y,z, target,
↪  error, objective, initial branch, convergence, hashes)?
E. Any place where the README overstates what the code does, or states results that cannot exist (there are none by design because
↪  execution was blocked; confirm).

Be concrete and terse. If something is fine, do not praise it. End with a numbered list of defects ordered by severity, or "no defects
↪  found". Do not propose rewrites beyond the minimal fix.
Your parent agent id is "session-60ae33b3-ab82-4c61-9ff6-52a3b9d864ae". Before you finish, send your result to that agent with
↪  send_message({ agent_id: "session-60ae33b3-ab82-4c61-9ff6-52a3b9d864ae", message: "<self-contained result>" }). The parent shares your
↪  workspace but does not automatically receive your transcript, tool output, or reasoning. Send earlier messages as well when a finding
↪  changes what the parent should do next; sending a message does not end your turn.
```

Query 2 (exact wording).

```
Current runtime context. This snapshot supersedes earlier runtime-context snapshots.

Current DSH file policy: workspace-write. Any available operation enforced by the DSH file sandbox may modify files under the session
↪  workspace: "F:\\ChatGPT\\upc". Some platform temporary areas may also be writable.

Approval prompts are disabled in this session: actions that require approval are rejected automatically — do not request sandbox
↪  escalation (do not set `sandbox_permissions`).

You are a delegated subagent: your permission scope was fixed when you were started and cannot be widened from inside this session —
↪  operations that require approval are rejected automatically. When the task needs access beyond that scope, do not retry the denied
↪  operation; state the limitation in your reply so the delegating agent can handle it.
```

Query 3 (exact wording).

```
<system-reminder>
A skill is a reusable set of task-specific instructions. The following skills are available in this session:

<available_skills>
- `ainiee-translate`: Use when the user wants to translate a novel/epub end-to-end on the coding agent itself (Claude Code or Codex; no
↪  AiNiee app), AiNiee-style — parse, build a locked glossary, translate chapter by chapter following rules (names preserved, title
↪  3-way, term consistency), write back and export. Triggers on "用 agent 翻译这本书", "agent 版 aniee 翻译", "把这本 epub 翻译了" and
↪  similar.
- `brainstorm`: Divergent-then-convergent idea exploration skill. Use when the user has a vague idea, an open problem, a stuck project, or
↪  asks to "头脑风暴 / 帮我发散 / 想几个方案 / 换个思路" and does NOT yet want a decision or an implementation. Turns a fuzzy prompt into
↪  a spread of genuinely different directions, then stress-tests them and lands on one concrete next action. Handles naming, positioning,
↪  project directions, feature ideas, research angles, event themes, and "我该做什么" 类选择困难。
- `business-data-analyst-skill`: Business data analysis and operating diagnosis skill. Use when the user needs to translate a business
↪  question into an analysis plan, define metric logic, validate data quality, break down changes in growth, conversion, retention,
↪  revenue, or efficiency, identify root causes, quantify business impact, and produce actionable recommendations or experiment ideas.
↪  Suitable for operating reviews, growth analysis, user behavior analysis, channel performance analysis, funnel analysis, sales
↪  conversi...
- `campus-event-planning`: 校园与社团活动策划 skill。当用户要策划、审批、执行或复盘一场校内活动时使用——比赛/竞赛、讲座/分享会、迎新/招新、
↪  晚会、展览、志愿服务、社团开放日等。覆盖立项与审批、场地与设备、经费与报销、宣传节奏、人员分工、当天执行脚本、志愿者管理、
↪  应急预案与活动复盘总结。输出可直接交给指导老师、团委或学生会审阅的策划书。
- `durable-tech-buy`: Research and compare expensive, long-lived computer hardware and digital products before purchase. Use for NAS, PCs,
↪  laptops, phones, cameras, networking gear, storage, displays, and similar products when the user wants exact-model cross-platform
↪  pricing, review synthesis, same-price alternatives, price-cycle judgment, reliability/performance analysis, or lifecycle total cost.
↪  Optimized for JD, Taobao/Tmall, Pinduoduo, and Douyin; not for placing orders, adding to carts, or monitoring prices ...
- `research-paper-review`: Academic paper comprehension and adversarial review skill for unpublished drafts. Use when the user needs an
↪  unpublished paper explained in plain language, wants reviewer-grade constructive criticism, needs an advisor-facing feedback memo, or
↪  wants submission-readiness checks (venue compliance, ablation completeness, baseline strength, statistical reporting,
↪  reproducibility). Covers ML/RL/optimization/transportation/energy-systems papers, including MARL and EV-charging scheduling work.
↪  Handle...
</available_skills>

If the user names a skill, or the task clearly matches a skill's description, call the `skill` tool with the exact skill name before
↪  taking task actions. Load all applicable skills, then follow their full instructions. This catalog contains summaries only; do not
↪  infer or follow a skill's instructions until it has been loaded.
A user may also invoke a skill directly; its <skill_content> block then appears in this conversation. Follow it, and do not call the
↪  `skill` tool again for that skill.
</system-reminder>
```

Complete output 3.1.

```
I'll read all six files, starting with the three review targets.
```

Complete output 3.2.

```
The target file changed mid-review (was 979 lines, now 1030). Re-reading current version.
```

Query 4 (exact wording).

```
Agent session-60ae33b3-ab82-4c61-9ff6-52a3b9d864ae sent a message:
```

```
Please wrap up now: report only the concrete defects you have already confirmed (file:line + minimal fix), ordered by severity, max 12
↪  bullets. Do not start new deep analysis. If you have found no defects, say so explicitly.
```

Measured trajectory dataset search (delegated)

System: DeepSeek Harness. Model: deepseek-v4-flash-vision-exp. Period: 2026-11-07 21:17 (Beijing time). Session identifier: session-1f960b38-9786-4d27-8a9f-7077ddc30007.

Query 1 (exact wording).

```
mode: execute
goal: Independently find accessible measured soccer-ball trajectory datasets for UPC B.
context: Need per-shot time and 3D ball-center coordinates starting at launch, ideally measured spin magnitude and axis. Existing
↪  DFL/ISSIA lack spin, Ball3D access pending. Vicon Asai 2020, Sheffield Goff/Carre and Goff et al 2017 known candidates.
scope: Read-only public research. Do not edit workspace files or contact anyone. Do not expose secrets or send local files anywhere.
acceptance: First review scope, then verify direct download links and actual fields where available. Rank at most five sources with
↪  primary URLs, access requirements, sample counts, measured vs inferred spin and role. Identify one immediate substitute if no public
↪  trajectory+spin file. Stop on substantial scope issue. Report compactly with evidence.
```

Query 2 (exact wording).

```
Current runtime context. This snapshot supersedes earlier runtime-context snapshots.

Current DSH file policy: workspace-write. Any available operation enforced by the DSH file sandbox may modify files under the session
↪  workspace: "F:\\ChatGPT\\upc". Some platform temporary areas may also be writable.

Approval policy: ask. Operations that require approval may ask through the configured answerers; without an available answerer, the
↪  request fails closed.
```

Query 3 (exact wording).

```
<system-reminder>
A skill is a reusable set of task-specific instructions. The following skills are available in this session:

<available_skills>
- `ainiee-translate`: Use when the user wants to translate a novel/epub end-to-end on the coding agent itself (Claude Code or Codex; no
↪  AiNiee app), AiNiee-style — parse, build a locked glossary, translate chapter by chapter following rules (names preserved, title
↪  3-way, term consistency), write back and export. Triggers on "用 agent 翻译这本书", "agent 版 aniee 翻译", "把这本 epub 翻译了" and
↪  similar.
- `brainstorm`: Divergent-then-convergent idea exploration skill. Use when the user has a vague idea, an open problem, a stuck project, or
↪  asks to "头脑风暴 / 帮我发散 / 想几个方案 / 换个思路" and does NOT yet want a decision or an implementation. Turns a fuzzy prompt into
↪  a spread of genuinely different directions, then stress-tests them and lands on one concrete next action. Handles naming, positioning,
↪  project directions, feature ideas, research angles, event themes, and "我该做什么" 类选择困难。
- `business-data-analyst-skill`: Business data analysis and operating diagnosis skill. Use when the user needs to translate a business
↪  question into an analysis plan, define metric logic, validate data quality, break down changes in growth, conversion, retention,
↪  revenue, or efficiency, identify root causes, quantify business impact, and produce actionable recommendations or experiment ideas.
↪  Suitable for operating reviews, growth analysis, user behavior analysis, channel performance analysis, funnel analysis, sales
↪  conversi...
- `campus-event-planning`: 校园与社团活动策划 skill。当用户要策划、审批、执行或复盘一场校内活动时使用——比赛/竞赛、讲座/分享会、迎新/招新、
↪  晚会、展览、志愿服务、社团开放日等。覆盖立项与审批、场地与设备、经费与报销、宣传节奏、人员分工、当天执行脚本、志愿者管理、
↪  应急预案与活动复盘总结。输出可直接交给指导老师、团委或学生会审阅的策划书。
- `durable-tech-buy`: Research and compare expensive, long-lived computer hardware and digital products before purchase. Use for NAS, PCs,
↪  laptops, phones, cameras, networking gear, storage, displays, and similar products when the user wants exact-model cross-platform
↪  pricing, review synthesis, same-price alternatives, price-cycle judgment, reliability/performance analysis, or lifecycle total cost.
↪  Optimized for JD, Taobao/Tmall, Pinduoduo, and Douyin; not for placing orders, adding to carts, or monitoring prices ...
- `research-paper-review`: Academic paper comprehension and adversarial review skill for unpublished drafts. Use when the user needs an
↪  unpublished paper explained in plain language, wants reviewer-grade constructive criticism, needs an advisor-facing feedback memo, or
↪  wants submission-readiness checks (venue compliance, ablation completeness, baseline strength, statistical reporting,
↪  reproducibility). Covers ML/RL/optimization/transportation/energy-systems papers, including MARL and EV-charging scheduling work.
↪  Handle...
</available_skills>

If the user names a skill, or the task clearly matches a skill's description, call the `skill` tool with the exact skill name before
↪  taking task actions. Load all applicable skills, then follow their full instructions. This catalog contains summaries only; do not
↪  infer or follow a skill's instructions until it has been loaded.
```

```
A user may also invoke a skill directly; its <skill_content> block then appears in this conversation. Follow it, and do not call the
↪  `skill` tool again for that skill.
</system-reminder>
```

Complete output 3.1.

```
I'll start by confirming the scope, then run parallel searches on the named candidates.
```

Paper raw-data link verification (delegated)

System: DeepSeek Harness. Model: deepseek-v4-flash-vision-exp. Period: 2026-11-07 21:18 (Beijing time). Session identifier: session-328b41e9-abe0-41d7-82fa-0e1a951ce926.

Query 1 (exact wording).

```
mode: execute
goal: Independently verify whether either specified paper links to a public raw data file.
context: Asai 2020 https://www.mdpi.com/2504-3900/49/1/88 and Whiteside 2010 https://ojs.ub.uni-konstanz.de/cpa/article/view/4446 .
scope: Read only these two public pages. No file edits, no messages, no broader search.
acceptance: First check scope and proceed unless conflicted. For each URL, report exact raw data link if present, otherwise say no link
↪  visible or page inaccessible. Return promptly.
```

Query 2 (exact wording).

```
Current runtime context. This snapshot supersedes earlier runtime-context snapshots.

Current DSH file policy: workspace-write. Any available operation enforced by the DSH file sandbox may modify files under the session
↪  workspace: "F:\\ChatGPT\\upc". Some platform temporary areas may also be writable.

Approval policy: ask. Operations that require approval may ask through the configured answerers; without an available answerer, the
↪  request fails closed.
```

Query 3 (exact wording).

```
<system-reminder>
A skill is a reusable set of task-specific instructions. The following skills are available in this session:

<available_skills>
- `ainiee-translate`: Use when the user wants to translate a novel/epub end-to-end on the coding agent itself (Claude Code or Codex; no
↪  AiNiee app), AiNiee-style — parse, build a locked glossary, translate chapter by chapter following rules (names preserved, title
↪  3-way, term consistency), write back and export. Triggers on "用 agent 翻译这本书", "agent 版 aniee 翻译", "把这本 epub 翻译了" and
↪  similar.
- `brainstorm`: Divergent-then-convergent idea exploration skill. Use when the user has a vague idea, an open problem, a stuck project, or
↪  asks to "头脑风暴 / 帮我发散 / 想几个方案 / 换个思路" and does NOT yet want a decision or an implementation. Turns a fuzzy prompt into
↪  a spread of genuinely different directions, then stress-tests them and lands on one concrete next action. Handles naming, positioning,
↪  project directions, feature ideas, research angles, event themes, and "我该做什么" 类选择困难。
- `business-data-analyst-skill`: Business data analysis and operating diagnosis skill. Use when the user needs to translate a business
↪  question into an analysis plan, define metric logic, validate data quality, break down changes in growth, conversion, retention,
↪  revenue, or efficiency, identify root causes, quantify business impact, and produce actionable recommendations or experiment ideas.
↪  Suitable for operating reviews, growth analysis, user behavior analysis, channel performance analysis, funnel analysis, sales
↪  conversi...
- `campus-event-planning`: 校园与社团活动策划 skill。当用户要策划、审批、执行或复盘一场校内活动时使用——比赛/竞赛、讲座/分享会、迎新/招新、
↪  晚会、展览、志愿服务、社团开放日等。覆盖立项与审批、场地与设备、经费与报销、宣传节奏、人员分工、当天执行脚本、志愿者管理、
↪  应急预案与活动复盘总结。输出可直接交给指导老师、团委或学生会审阅的策划书。
- `durable-tech-buy`: Research and compare expensive, long-lived computer hardware and digital products before purchase. Use for NAS, PCs,
↪  laptops, phones, cameras, networking gear, storage, displays, and similar products when the user wants exact-model cross-platform
↪  pricing, review synthesis, same-price alternatives, price-cycle judgment, reliability/performance analysis, or lifecycle total cost.
↪  Optimized for JD, Taobao/Tmall, Pinduoduo, and Douyin; not for placing orders, adding to carts, or monitoring prices ...
- `research-paper-review`: Academic paper comprehension and adversarial review skill for unpublished drafts. Use when the user needs an
↪  unpublished paper explained in plain language, wants reviewer-grade constructive criticism, needs an advisor-facing feedback memo, or
↪  wants submission-readiness checks (venue compliance, ablation completeness, baseline strength, statistical reporting,
↪  reproducibility). Covers ML/RL/optimization/transportation/energy-systems papers, including MARL and EV-charging scheduling work.
↪  Handle...
```

```
</available_skills>

If the user names a skill, or the task clearly matches a skill's description, call the `skill` tool with the exact skill name before
↪  taking task actions. Load all applicable skills, then follow their full instructions. This catalog contains summaries only; do not
↪  infer or follow a skill's instructions until it has been loaded.
A user may also invoke a skill directly; its <skill_content> block then appears in this conversation. Follow it, and do not call the
↪  `skill` tool again for that skill.
</system-reminder>
```

Complete output 3.1.

```
I'll check scope first, then fetch both pages.

Scope check: You specified exactly two public URLs (Asai 2020 MDPI, Whiteside 2010 Konstanz). Reading only those pages, no
↪  edits/messages/broader search — I can comply with that scope, so proceeding.
```

Complete output 3.2.

```
MDPI blocked with 403. One retry within scope (same URL, no other pages):
```

Complete output 3.3.

```
**Scope check:** Your constraints (only these two public URLs, no edits, no messages, no broader search) do not conflict with the task, so
↪  I proceeded. I fetched each URL once; MDPI got one in-scope retry (same URL, not a new page).

## 1. Asai 2020 — https://www.mdpi.com/2504-3900/49/1/88

**Page inaccessible.** Both attempts returned HTTP 403 "Access Denied" from an EdgeSuite/CDN block (references `#18.16260760...` /
↪  `#18.16260760...`), not the article content. No raw data link could be observed either way. This is a bot/CDN block, not evidence that
↪  no link exists.

## 2. Whiteside 2010 — https://ojs.ub.uni-konstanz.de/cpa/article/view/4446

**Page accessible (HTTP 200). No raw data link visible.**

The landing page for *"'Bend It Like Beckham': Ball Rotation in the Curved Football Kick"* (D. Whiteside, J. Alderson, B. Elliott; ISBS
↪  28th Conference, 2010, "Coaching and Sports Activities" section) contains only:

- Abstract (12-camera 250 Hz Vicon, 4 semi-professional soccer players, 5 straight / 10 curved kicks)
- **One download: `PDF (English)` — https://ojs.ub.uni-konstanz.de/cpa/article/view/4446/4135** (a full-text PDF, i.e. the paper, not raw
↪  data)
- Issue, section, license, and standard OJS navigation links

There is no dataset, supplementary-material, repository, or data-availability entry on the page. This is consistent with 2010-era ISBS
↪  proceedings, which did not carry data-availability statements.

**Summary:** Whiteside 2010 — no raw data link visible (only the paper PDF). Asai 2020 — page inaccessible (HTTP 403), so undetermined;
↪  the answer cannot be settled without accessing MDPI, which is outside the permitted scope.
```

Measured-kick data verification task (delegated)

System: DeepSeek Harness. Model: deepseek-v4-flash-vision-exp. Period: 2026-11-08 12:00 (Beijing time). Session identifier: session-3967613a-eb27-4236-9be7-598d77c378ec.

Query 1 (exact wording).

```
mode: execute
goal: Determine whether directional priors transfer outside Asai and whether MAP versus predictive mean explains the old discrepancy.
context:
```

```
F:/ChatGPT/upc. Read integration/student_b/experiments/asai_factorial.py and runs/asai_factorial/README.md + results.json (previous
↪  completed batch). Canonical/manual/free3 MAP mean10.63cm; LOOCV22.45; none26cm. Formal P1 frozen. Relevant existing code:
↪  validate_real_spin.py, validate_real_penalties.py, experiments/p5_transfer_spin_prior.py, compare_real_spin_priors.py. Two DFL
↪  penalties student-a/flight_trajectory_validation_2026-11-07/{inputs_only.csv,held_out.csv,case_config.json}; extra DFL
↪  student-a/additional_flight_data_2026-11-07/positions.csv; two ISSIA student_b/runs/issia_A/seg_*.csv. Inspect schemas yourself. Three
↪  Asai workbooks on desktop, read using existing load_case. Python C:/Users/pc/miniconda3/envs/mujoco/python.exe, read_deps
↪  deliverables/asai_official/read_deps.
Your previous sandbox shell failed SetNamedSecurityInfoW grantWrite Win32 5 before Python. Try execution ONCE; if same failure, deliver
↪  implementation promptly for Codex local runner, do not repeatedly probe and do not alter permissions/sandbox. Prefer concise reuse
↪  over a 1000-line script. End promptly after files complete; Codex handles execution if needed.
scope:
Only write deliverables/asai_transfer/*, integration/student_b/experiments/asai_transfer.py, integration/student_b/runs/asai_transfer/*.
↪  Outside list do not modify. No git changes, no training, no paper edits, no data uploads. Existing dirty files preserved.
plan:
First review; fix minor details, stop for material blockers. Priority 1: external transfer MAP, reuse or adapt factorial evaluator without
↪  altering original module. Compare no prior, manual magnitude+vertical prior, and pooled Asai-derived prior (all 3 Asai full-track fit
↪  summaries from previous results; fixed floors .08/.06; all are external to DFL/ISSIA). Keep Cd .27, noise fixed15mm DFL, explicitly
↪  hypothetical30mm ISSIA, free initial offset +-5cm, canonical law, fixed model across variants. DFL use 0/.04/.08 prefixes and target
↪  plane/config, observed initial height retained. ISSIA no fabricated 11m truth if track doesn't reach: evaluate actual heldout frame
↪  RMSE/last-frame 3D error, with query timestamps used only for evaluation not fitting. Align local forward axis using early points ONLY
↪  where needed, transform reference identically. No signs from future, no Asai tuning on external outcomes, no forcing negatives into
↪  positive z. Report early observed starting height and any invalid/ground event exclusion; all attempts retained. Initially just 2 DFL
↪  penalties and 2 ISSIA clips; extra11 DFL only if cheap and correctly specified. Synthetic tests future perturbation, alignment
↪  invariance, target score correctness.
Priority 2: matched estimator experiment on Asai: same physical model, prior density/reference measure, state bounds, sigma and fixed
↪  coordinate basis for MAP and posterior draws. Uniform 2D effective CL parameter support +-0.3, optional radial+vertical Gaussian
↪  penalties exactly exp(-0.5 penalty squared) with respect to dc_vert dc_lat; parameterisation/measure matters. Use fixed early
↪  velocity/basis for spin mapping for BOTH inference algorithms (different from prior batch velocity-dependent parameterisation, label
↪  clearly). Condition on prefix only. Can reuse sample_prefix with uniform aero draws plus importance prior weighting; conditional state
↪  proposal correction must be included. Align MAP state support with importance sampler, don't silently use different Cd or initial
↪  priors. Predict mean and weighted KDE mode (bandwidth documented) at11m; latent MAP distinct from predictive mode. 2 seeds8000 samples
↪  initially; report ESS, crossing mass, max weight, predictive interval and per-case errors. Mark unstable if seed dependence/low ESS;
↪  increase only those needed up to32000. No claims about probabilistic superiority from 3 samples. If technically risky deliver
↪  Priority1 and clear blocker instead of invalid posterior comparison.
acceptance:
Runnable script CLI --out and defaults using known workspace paths; few-minute runtime per stage; --stage transfer/estimators if both.
↪  JSON per-case results and reproducible settings/hash; concise Chinese README generated from actual results or written after running.
↪  Tests exercising prediction future invariance; no raw observations exported. Keep scoring separate from fitting (previous bug leaked
↪  by altering indices3: rather than time>.1; avoid). Previous scorer failed by forgetting error_cm in row annotation, test aggregates
↪  end-to-end. Never call a success unless executed. Return <=400 Chinese chars with exact commands, files, known risks. If sandbox
↪  blocked, write runner script and return immediately, do not spend time writing long placeholder reports.
```

Query 2 (exact wording).

```
Current runtime context. This snapshot supersedes earlier runtime-context snapshots.

Current DSH file policy: workspace-write. Any available operation enforced by the DSH file sandbox may modify files under the session
↪  workspace: "F:\\ChatGPT\\upc". Some platform temporary areas may also be writable.

Approval policy: ask. Operations that require approval may ask through the configured answerers; without an available answerer, the
↪  request fails closed.
```

Query 3 (exact wording).

```
<system-reminder>
A skill is a reusable set of task-specific instructions. The following skills are available in this session:

<available_skills>
- `ainiee-translate`: Use when the user wants to translate a novel/epub end-to-end on the coding agent itself (Claude Code or Codex; no
↪  AiNiee app), AiNiee-style — parse, build a locked glossary, translate chapter by chapter following rules (names preserved, title
↪  3-way, term consistency), write back and export. Triggers on "用 agent 翻译这本书", "agent 版 aniee 翻译", "把这本 epub 翻译了" and
↪  similar.
- `brainstorm`: Divergent-then-convergent idea exploration skill. Use when the user has a vague idea, an open problem, a stuck project, or
↪  asks to "头脑风暴 / 帮我发散 / 想几个方案 / 换个思路" and does NOT yet want a decision or an implementation. Turns a fuzzy prompt into
↪  a spread of genuinely different directions, then stress-tests them and lands on one concrete next action. Handles naming, positioning,
↪  project directions, feature ideas, research angles, event themes, and "我该做什么" 类选择困难。
```

```
- `business-data-analyst-skill`: Business data analysis and operating diagnosis skill. Use when the user needs to translate a business
↪  question into an analysis plan, define metric logic, validate data quality, break down changes in growth, conversion, retention,
↪  revenue, or efficiency, identify root causes, quantify business impact, and produce actionable recommendations or experiment ideas.
↪  Suitable for operating reviews, growth analysis, user behavior analysis, channel performance analysis, funnel analysis, sales
↪  conversi...
- `campus-event-planning`: 校园与社团活动策划 skill。当用户要策划、审批、执行或复盘一场校内活动时使用——比赛/竞赛、讲座/分享会、迎新/招新、
↪  晚会、展览、志愿服务、社团开放日等。覆盖立项与审批、场地与设备、经费与报销、宣传节奏、人员分工、当天执行脚本、志愿者管理、
↪  应急预案与活动复盘总结。输出可直接交给指导老师、团委或学生会审阅的策划书。
- `durable-tech-buy`: Research and compare expensive, long-lived computer hardware and digital products before purchase. Use for NAS, PCs,
↪  laptops, phones, cameras, networking gear, storage, displays, and similar products when the user wants exact-model cross-platform
↪  pricing, review synthesis, same-price alternatives, price-cycle judgment, reliability/performance analysis, or lifecycle total cost.
↪  Optimized for JD, Taobao/Tmall, Pinduoduo, and Douyin; not for placing orders, adding to carts, or monitoring prices ...
- `research-paper-review`: Academic paper comprehension and adversarial review skill for unpublished drafts. Use when the user needs an
↪  unpublished paper explained in plain language, wants reviewer-grade constructive criticism, needs an advisor-facing feedback memo, or
↪  wants submission-readiness checks (venue compliance, ablation completeness, baseline strength, statistical reporting,
↪  reproducibility). Covers ML/RL/optimization/transportation/energy-systems papers, including MARL and EV-charging scheduling work.
↪  Handle...
</available_skills>

If the user names a skill, or the task clearly matches a skill's description, call the `skill` tool with the exact skill name before
↪  taking task actions. Load all applicable skills, then follow their full instructions. This catalog contains summaries only; do not
↪  infer or follow a skill's instructions until it has been loaded.
A user may also invoke a skill directly; its <skill_content> block then appears in this conversation. Follow it, and do not call the
↪  `skill` tool again for that skill.
</system-reminder>
```

Complete output 3.1.

```
I'll start by reviewing the existing code and data, then decide whether execution is possible.
```

Complete output 3.2.

```
Shell is blocked with the exact `SetNamedSecurityInfoW ... grantWrite` failure from the brief. Per your instruction I will **not** retry
↪  it — I'll deliver the implementation via file tools and let Codex run it. Reading the existing code now.
```

Complete output 3.3.

```
Shell is confirmed blocked; proceeding with file tools only.
```

Complete output 3.4.

```
The shell is blocked exactly as you predicted, so I'm delivering the implementation. I've reviewed the factorial evaluator, the transfer
↪  scripts, and all five dataset schemas. Writing the main module now.
```

Complete output 3.5.

```
Now let me fix several issues I spotted on review (weak invariance comparison, a duplicate payload key, unguarded table header, unweighted
↪  median).
```

Complete output 3.6.

```
Now let me verify the whole file for syntax and logic errors, section by section.
```

Complete output 3.7.

```
Now the test suite, runner, and deliverables README.
```

Complete output 3.8.

```
沙箱在 Python 启动前即报 `SetNamedSecurityInfoW grantWrite Win32 5`，按约定只试一次便停，** 未执行任何代码，无结果数字 **，故不称成功。

** 命令 **（在 `F:/ChatGPT/upc`，或直接 `deliverables/asai_transfer/run.ps1`）
```powershell
& C:/Users/pc/miniconda3/envs/mujoco/python.exe integration/student_b/experiments/asai_transfer.py --selftest --out
↪  integration/student_b/runs/asai_transfer
& C:/Users/pc/miniconda3/envs/mujoco/python.exe -m unittest deliverables/asai_transfer/test_asai_transfer.py -v
& C:/Users/pc/miniconda3/envs/mujoco/python.exe integration/student_b/experiments/asai_transfer.py --stage all --out
↪  integration/student_b/runs/asai_transfer
```

文件：`experiments/asai_transfer.py`（迁移：none/manual/pooled，DFL 15mm、ISSIA 假设 30mm，Cd .27，±5cm；估计器：固定早期速度/基，MAP
↪ 与后验共用边界与 `exp(-0.5p²)` 密度，含提议修正；自动生成中文 README）；`deliverables/asai_transfer/` 下 `run.ps1`、
↪ `test_asai_transfer.py`（未来帧不变性、对齐不变性、评分与端到端汇总、MAP/抽样一致性，另测真实 schema 与 pooled 先验）、`README.md`。结果写
↪ `runs/asai_transfer/`。

风险：①全部未执行，需看 `checks.json`；②ISSIA 30mm 为假设；③pooled 对 Asai 样本内；④提议箱外截断因子略去（记 `accepted_fraction`）；
↪ ⑤15 片段非独立；⑥free3 弱辨识，低 ESS/种子不稳会标注；⑦已核两 ISSIA 前向覆盖约 13/18 m，均越过 11 m。
```

Asai measured-kick discrepancy experiment (delegated design and code)

System: DeepSeek Harness. Model: deepseek-v4-flash-vision-exp. Period: 2026-11-08 11:37 (Beijing time). Session identifier: session-60ae33b3-ab82-4c61-9ff6-52a3b9d864ae.

Query 1 (exact wording).

```
mode: execute
goal: Diagnose the 11 cm manual versus 50-60 cm canonical short-window Asai discrepancy with controlled, reproducible experiments; produce
↪  exploratory leave-one-trial-out results.
context:
Workspace F:/ChatGPT/upc. Read integration/student_b/runs/asai_replay/README.md, replay_asai_3kicks.py, physics.py; reference
↪  deliverables/asai_official/manual_reference.py. Raw three xlsx on C:/Users/pc/Desktop. Python
↪  C:/Users/pc/miniconda3/envs/mujoco/python.exe and .venv/Scripts/python.exe; openpyxl in deliverables/asai_official/read_deps (add
↪  sys.path), .venv has pandas. Frozen published P1 assets deliverables/asai_official; do not retrain. Read relevant AGENTS files if
↪  present. Existing dirty changes belong to previous work, do not revert.
scope:
Only create/modify deliverables/asai_ablation/* and integration/student_b/experiments/asai_factorial.py and
↪  integration/student_b/runs/asai_factorial/*. Outside list no writes. No git commit/push, no changing paper or main README. No external
↪  email, no dataset upload.
plan:
First review design; correct minor details and document, stop only for major blockers. Implement efficient least-squares/MAP factorial
↪  using identical read_trial, 0/.05/.10 observations, forward11m target and score Euclidean y,z cm. This comparison is MAP vs MAP; do
↪  not conflate with existing posterior means or P1. Fix physical constants and Cd=.27 across factorial. Cross (a) constant CL-vector law
↪  versus canonical speed-dependent capped CL law, parameterized by effective initial transverse CL / spin consistently, (b) no
↪  regularization versus isotropic magnitude prior versus manual magnitude+vertical-component directional prior; (c) fixed first point
↪  versus all-three-point 10mm noisy fit with free initial offset. All losses use explicit comparable units: dividing by sigma without
↪  prior does not change optimizer optimum; explain confounding rather than claim noise alone improves. Use multi-start +/- lateral and
↪  vertical directions; report objective, convergence and local solutions. Manual's negative initial lateral coefficient is not itself a
↪  signed prior; test whether sign/local minima affect result! Do not assign sign from future.
Use current canonical full-track fits of OTHER TWO trials only to derive a small, fixed-form Gaussian transverse-spin or CL prior per
↪  leave-one-out fold; covariance regularization fixed beforehand, e.g. minimum CL sd .08, not selected from heldout accuracy. Evaluate
↪  heldout using early points only. Label exploratory n=3 all previously viewed, no independent final test. Compare all3 named per-case
↪  errors plus mean/median. No model selection from heldout results. If this is too complex prioritize factorial and correct leakage
↪  tests over broad grids. Optional sigma sensitivity .005/.01/.02 for prespecified directed/isotropic variants.
acceptance:
Runnable CLI with --data --out, deterministic config and JSON/CSV including prediction y,z, target, error, fit objective, initial branch
↪  and convergence, input source hashes. README Chinese concise methods/results/limitations/reproduce command. Include test that
↪  modifying heldout future leaves its fit/prediction unchanged (score may change) and that LOOCV prior uses only other trials. Verify
↪  baseline manual 11.39cm reproduction or explain any mismatch. No fabricated metrics, no universal claims, no raw workbook export.
↪  Execute experiments; write check output. Save factor contrasts, not just winner. End final <=500 Chinese characters listing files,
↪  command and risks. Runtime target <10min, avoid unnecessary huge MC.
```

Query 2 (exact wording).

```
Current runtime context. This snapshot supersedes earlier runtime-context snapshots.
```

```
Current DSH file policy: workspace-write. Any available operation enforced by the DSH file sandbox may modify files under the session
↪  workspace: "F:\\ChatGPT\\upc". Some platform temporary areas may also be writable.

Approval policy: ask. Operations that require approval may ask through the configured answerers; without an available answerer, the
↪  request fails closed.
```

Query 3 (exact wording).

```
<system-reminder>
A skill is a reusable set of task-specific instructions. The following skills are available in this session:

<available_skills>
- `ainiee-translate`: Use when the user wants to translate a novel/epub end-to-end on the coding agent itself (Claude Code or Codex; no
↪  AiNiee app), AiNiee-style — parse, build a locked glossary, translate chapter by chapter following rules (names preserved, title
↪  3-way, term consistency), write back and export. Triggers on "用 agent 翻译这本书", "agent 版 aniee 翻译", "把这本 epub 翻译了" and
↪  similar.
- `brainstorm`: Divergent-then-convergent idea exploration skill. Use when the user has a vague idea, an open problem, a stuck project, or
↪  asks to "头脑风暴 / 帮我发散 / 想几个方案 / 换个思路" and does NOT yet want a decision or an implementation. Turns a fuzzy prompt into
↪  a spread of genuinely different directions, then stress-tests them and lands on one concrete next action. Handles naming, positioning,
↪  project directions, feature ideas, research angles, event themes, and "我该做什么" 类选择困难。
- `business-data-analyst-skill`: Business data analysis and operating diagnosis skill. Use when the user needs to translate a business
↪  question into an analysis plan, define metric logic, validate data quality, break down changes in growth, conversion, retention,
↪  revenue, or efficiency, identify root causes, quantify business impact, and produce actionable recommendations or experiment ideas.
↪  Suitable for operating reviews, growth analysis, user behavior analysis, channel performance analysis, funnel analysis, sales
↪  conversi...
- `campus-event-planning`: 校园与社团活动策划 skill。当用户要策划、审批、执行或复盘一场校内活动时使用——比赛/竞赛、讲座/分享会、迎新/招新、
↪  晚会、展览、志愿服务、社团开放日等。覆盖立项与审批、场地与设备、经费与报销、宣传节奏、人员分工、当天执行脚本、志愿者管理、
↪  应急预案与活动复盘总结。输出可直接交给指导老师、团委或学生会审阅的策划书。
- `durable-tech-buy`: Research and compare expensive, long-lived computer hardware and digital products before purchase. Use for NAS, PCs,
↪  laptops, phones, cameras, networking gear, storage, displays, and similar products when the user wants exact-model cross-platform
↪  pricing, review synthesis, same-price alternatives, price-cycle judgment, reliability/performance analysis, or lifecycle total cost.
↪  Optimized for JD, Taobao/Tmall, Pinduoduo, and Douyin; not for placing orders, adding to carts, or monitoring prices ...
- `research-paper-review`: Academic paper comprehension and adversarial review skill for unpublished drafts. Use when the user needs an
↪  unpublished paper explained in plain language, wants reviewer-grade constructive criticism, needs an advisor-facing feedback memo, or
↪  wants submission-readiness checks (venue compliance, ablation completeness, baseline strength, statistical reporting,
↪  reproducibility). Covers ML/RL/optimization/transportation/energy-systems papers, including MARL and EV-charging scheduling work.
↪  Handle...
</available_skills>

If the user names a skill, or the task clearly matches a skill's description, call the `skill` tool with the exact skill name before
↪  taking task actions. Load all applicable skills, then follow their full instructions. This catalog contains summaries only; do not
↪  infer or follow a skill's instructions until it has been loaded.
A user may also invoke a skill directly; its <skill_content> block then appears in this conversation. Follow it, and do not call the
↪  `skill` tool again for that skill.
</system-reminder>
```

Complete output 3.1.

```
I'll start by reviewing the workspace structure and the relevant files.
```

Query 4 (exact wording).

```
background job pwsh-5 (pwsh: cmd /c echo ok) finished [status: failed, SetNamedSecurityInfoW failed (Win32 5):
↪  grantWrite(F:\ChatGPT\upc)]. Read its output with job_output.
```

Query 5 (exact wording).

```
Agent 152fb4dd-fe1f-46bd-b91b-458fd0df947e sent a message:
Command-execution test result: BOTH pwsh calls failed identically before the command ever ran — the harness could not set up the sandbox
↪  workspace, so no shell output was produced at all.

Step 1 (command: `python --version`, workdir: `F:\ChatGPT\upc`) exact tool output:
Error: SetNamedSecurityInfoW failed (Win32 5): grantWrite(F:\ChatGPT\upc)
```

```
Step 2 (step 1 failed, so per instructions I ran: `Get-ChildItem -Name C:\Users\pc\Desktop`, default workdir) exact tool output:
Error: SetNamedSecurityInfoW failed (Win32 5): grantWrite(F:\ChatGPT\upc)

Interpretation: this is not a python-missing or path-not-found problem. `SetNamedSecurityInfoW` Win32 error 5 = ERROR_ACCESS_DENIED,
↪  raised by the `grantWrite(F:\ChatGPT\upc)` step — i.e. the sandbox tried to grant write ACLs on the workspace directory and was
↪  denied (workspace-write mode; approvals are disabled and I cannot widen scope). Until the workspace ACL/permissions or sandbox mode
↪  changes, pwsh is unusable for me in this session, so any plan depending on shell commands from me will fail the same way. No
↪  workarounds attempted, no files written.
```

Query 6 (exact wording).

```
Background subagent 152fb4dd-fe1f-46bd-b91b-458fd0df947e finished and will do no further work unless you send it more.
Its closing message:
Both commands failed. Raw outputs, verbatim:

**1. `python --version` (workdir `F:\ChatGPT\upc`)**

```
Error: SetNamedSecurityInfoW failed (Win32 5): grantWrite(F:\ChatGPT\upc)
```

2. `Get-ChildItem -Name C:\Users\pc\Desktop` (run because step 1 failed; default workdir)

```
Error: SetNamedSecurityInfoW failed (Win32 5): grantWrite(F:\ChatGPT\upc)
```

Both failed identically during sandbox setup, before either command executed — the failure is on `grantWrite(F:\ChatGPT\upc)` (Win32
↪ error 5 = access denied), not from python or from the Desktop path. No workarounds attempted, no files written. Result also sent to
↪ parent agent `session-60ae33b3-ab82-4c61-9ff6-52a3b9d864ae`.
```

Complete output 6.1.

```
Execution is blocked environment-wide (documented below). I'll verify the diagnosis, then implement the full study so it runs with one
↪  command.
```

Complete output 6.2.

```
Now I'll write the factorial implementation.
```

Complete output 6.3.

```
The draft has several issues I need to fix (leftover junk in the algebra check, a broken CL helper, double evaluation). I'll rewrite it
↪  cleanly.
```

Complete output 6.4.

```
Found a real bug on re-read (theta must be 2-D for `derivative`). Fixing:
```

Query 7 (exact wording).

```
Background subagent c1fbcbd3-0c92-4cb7-8156-da2bef6ece6e was stopped before it finished.
It left no closing message.
```

Complete output 7.1.

```
未能执行：工作区 ACL 授权在命令启动前失败（`SetNamedSecurityInfoW failed (Win32 5): grantWrite(F:\ChatGPT\upc)`），所有 shell 均被拒，故无
↪  `results/checks`、无任何指标（证据见 `env_check.json`）。

交付：
```

```
- `integration/student_b/experiments/asai_factorial.py`: 2×3×2 MAP 因子、14 起点（±横向/竖直）、LOOCV 先验、泄漏/确定性/手册 11.39 检查、
↪  JSON+CSV 对比；
- `deliverables/asai_ablation/README.md`、`test_asai_factorial.py`、`run_factorial.ps1`、`env_check.json`。

命令：
`C:\Users\pc\miniconda3\envs\mujoco\python.exe integration\student_b\experiments\asai_factorial.py --data C:\Users\pc\Desktop --out
↪  integration\student_b\runs\asai_factorial --sigma-sensitivity`
（自检加 `--selftest`）

风险：n=3 均已看过、无独立测试；LOOCV 先验来自其他试次回顾性全段拟合；canonical 在 |c|>.30 封顶；常数与手册略异，11.39 只做容差对照。
```

UPC repository maintenance and AI-report preparation

System: DeepSeek Harness. Model: deepseek-v4-flash-vision-exp. Period: 2026-11-07 16:33 to 2026-11-08 12:20 (Beijing time). Session identifier: session-647c9a78-6938-4266-83d2-7fc5cb9446cd.

Query 1 (exact wording).

```
与 GPT 沟通，获取 upc 相关她的全部成果，并将其中需要与组员共享的代码之类上传仓库：[team repository]
```

Query 2 (exact wording).

```
Current runtime context. This snapshot supersedes earlier runtime-context snapshots.

Current DSH file policy: danger-full-access. The DSH file sandbox does not restrict file modifications by available operations.

Approval prompts are disabled in this session: actions that require approval are rejected automatically — do not request sandbox
↪  escalation (do not set `sandbox_permissions`).
```

Query 3 (exact wording).

```
<system-reminder>
A skill is a reusable set of task-specific instructions. The following skills are available in this session:

<available_skills>
- `ainiee-translate`: Use when the user wants to translate a novel/epub end-to-end on the coding agent itself (Claude Code or Codex; no
↪  AiNiee app), AiNiee-style — parse, build a locked glossary, translate chapter by chapter following rules (names preserved, title
↪  3-way, term consistency), write back and export. Triggers on "用 agent 翻译这本书", "agent 版 aniee 翻译", "把这本 epub 翻译了" and
↪  similar.
- `brainstorm`: Divergent-then-convergent idea exploration skill. Use when the user has a vague idea, an open problem, a stuck project, or
↪  asks to "头脑风暴 / 帮我发散 / 想几个方案 / 换个思路" and does NOT yet want a decision or an implementation. Turns a fuzzy prompt into
↪  a spread of genuinely different directions, then stress-tests them and lands on one concrete next action. Handles naming, positioning,
↪  project directions, feature ideas, research angles, event themes, and "我该做什么" 类选择困难。
- `business-data-analyst-skill`: Business data analysis and operating diagnosis skill. Use when the user needs to translate a business
↪  question into an analysis plan, define metric logic, validate data quality, break down changes in growth, conversion, retention,
↪  revenue, or efficiency, identify root causes, quantify business impact, and produce actionable recommendations or experiment ideas.
↪  Suitable for operating reviews, growth analysis, user behavior analysis, channel performance analysis, funnel analysis, sales
↪  conversi...
- `campus-event-planning`: 校园与社团活动策划 skill。当用户要策划、审批、执行或复盘一场校内活动时使用——比赛/竞赛、讲座/分享会、迎新/招新、
↪  晚会、展览、志愿服务、社团开放日等。覆盖立项与审批、场地与设备、经费与报销、宣传节奏、人员分工、当天执行脚本、志愿者管理、
↪  应急预案与活动复盘总结。输出可直接交给指导老师、团委或学生会审阅的策划书。
- `durable-tech-buy`: Research and compare expensive, long-lived computer hardware and digital products before purchase. Use for NAS, PCs,
↪  laptops, phones, cameras, networking gear, storage, displays, and similar products when the user wants exact-model cross-platform
↪  pricing, review synthesis, same-price alternatives, price-cycle judgment, reliability/performance analysis, or lifecycle total cost.
↪  Optimized for JD, Taobao/Tmall, Pinduoduo, and Douyin; not for placing orders, adding to carts, or monitoring prices ...
- `research-paper-review`: Academic paper comprehension and adversarial review skill for unpublished drafts. Use when the user needs an
↪  unpublished paper explained in plain language, wants reviewer-grade constructive criticism, needs an advisor-facing feedback memo, or
↪  wants submission-readiness checks (venue compliance, ablation completeness, baseline strength, statistical reporting,
↪  reproducibility). Covers ML/RL/optimization/transportation/energy-systems papers, including MARL and EV-charging scheduling work.
↪  Handle...
</available_skills>

If the user names a skill, or the task clearly matches a skill's description, call the `skill` tool with the exact skill name before
↪  taking task actions. Load all applicable skills, then follow their full instructions. This catalog contains summaries only; do not
↪  infer or follow a skill's instructions until it has been loaded.
```

```
A user may also invoke a skill directly; its <skill_content> block then appears in this conversation. Follow it, and do not call the
↪  `skill` tool again for that skill.
</system-reminder>
```

Complete output 3.1.

```
已完成。**GPT 的 UPC 全部成果已清点并推送到共享仓库 **: [team repository] （最新提交 `c596458`，仓库公开可访问）。

## 1. 与 GPT 的对接结果

直接向 ChatGPT 应用发消息的接口不存在，所以我用两种方式" 对接" 了她：

- **读取她的完整会话记录**（本机 Codex 会话库，线程 `01a1b47f…`，13:34–16:29，15 轮问答 / 190 条记录），
↪  拿到了她全部对话产出与最后一轮交接内容；
- ** 清点她落盘的产出 **（`F:\ChatGPT\upc` 工作区），确认 16:21 之后没有新增文件、会话之后没有新消息 ——成果是完整的。

她最后的交接内容：B 组已完成 5 万条仿真 + MDN 训练 + 第一轮模型对照；下一步是"把模型对照做扎实"（等 A 的真实轨迹 / 先做仿真验证），
↪  并起草了给队友群的同步消息（已整理进仓库 README §4，可直接粘贴）。

## 2. 上传内容

B 组共 **63 个文件 / 约 1.18MB**（60 个 GPT 原始产出 + 新增 README/inventory/.gitignore），逐字复制，未改动她的原始文件：

- **4 份研究文档 **: 中文研究路线、高分作品因素与修订、团队实验方案、数据获取渠道与邮件草稿
- **代码**: `student_b/` 下物理引擎（批量 RK4 + 马格努斯力 + 触地/穿越事件）、贝叶斯重要性采样、全协方差 MDN、验证/筛选/批处理脚本、7
↪  项自动测试、环境清单
- ** 报告 **: 审查清单、开发结果与待办、气动参数更新结果、ISSIA 筛选与仿真验证
- ** 结果 **: 41 个 JSON/PNG/日志/模型权重（含题面案例联合区域图、新旧模型对照表）
- ** 数据 **: ISSIA-3D 公开标注 CSV

新增的 [README]([team repository])（总览/进度/给 A、C 的接口/复现命令/协作约定）和 [inventory]([team repository])（完整成果清单 +
↪  未上传大文件的复现命令）。

⚠ 期间队友 `[team member]` 于 16:39 先推了调研资料和论文模板（`raw/`、`UPC赛事调研报告.md`、`论文模板/` 等），我已把 B 组成果 **rebase
↪  合并在其之上**，没有覆盖任何队友内容；README 中也已互相索引。

## 3. 关键结果速览（均为仿真结果，未经真实数据校准）

| 项目 | 结果 |
|---|---|
| 题面案例（σ=5mm） | 最可能穿越点 **(Y,Z) ≈ (2.650, 2.052) m**；50%/95% 区域面积 **0.219/0.809 m²** |
| MDN 重训（σ=5mm） | 中位误差 **0.322 m**（旧 0.403 m），95% 区域实际覆盖 **96.3%** |
| 三模型对照 | 无风：MDN 0.341 / 物理 0.353 / 基线 0.425 m；横风 3m/s：物理 **0.266** / MDN 0.352 / 基线 0.804 m（小样本，各 9–10/12
↪  条可配对） |
| ISSIA | 筛出 25 段连续空中片段（5 段位移>11m），缺离脚时刻/点球标签，暂不可用于校准 |

** 已知局限 **（README §3 已写明）：50% 区域校准不足（实际覆盖 46–59%）、无真实轨迹验证、对照样本小。论文引用时须标" 文献参数约束下的仿真结果"。

## 4. 校验

- `python -m unittest discover -s student_b -v` → **7/7 通过 **（在仓库副本上实测 0.4s）
- 端到端 `smoke` 跑通；`validate.py case` 用仓库内的 `mdn.pt` 成功复现案例图
- 仓库远程校验：169 个 tree 条目、`student_b/` 与全部结果文件在位、公开可访问

## 5. 没上传 / 可再补

- **18.5MB 的 `.npz/.npy` 中间数组 ** 未上传（可再生成，清单和命令在 inventory.md §F）——如要一并上传说一声；
- 第三方文献 PDF、2022 获奖论文未上传（版权）；
- **GPT 完整对话已导出一份本地备份**: [AI对话记录_ChatGPT_UPC_2026-11-07.md](AI对话记录_ChatGPT_UPC_2026-11-07.md)（15
↪  轮原始提问+完整回答+操作摘要，供论文 AI 披露附录；因仓库是公开的未上传）。本地仓库副本在 [UPC155/README.md](UPC155/README.md)。

**建议你现在做**: 把 README §4 的群消息发到队友群（含仓库链接），并让 A 回真实轨迹/ISSIA 核查结果。等 GPT 那边产出新结果后，
↪  我可以按同样流程再同步一次仓库；如果要把仓库链接或摘要同步回 GPT 的对话，需要你在 ChatGPT 窗口里发一句（我无法直接向该应用发消息）。
```

Query 4 (exact wording).

```
读取 codex 的最新工作成果，并结合队友的回复推进
```

Complete output 4.1.

Team 155

```
已读取 **Codex 的最新工作** + **A 的 v2 交接包（你给的 zip）**，并把下一步推进完、推上仓库了：[team repository] （提交 `46c2f00`，13/13
↪  测试通过，远程已核验）。

## 1. 读到了什么

**Codex 最新一轮（16:49–16:56）**：处理了 A 第一版交接包 → 核对 ISSIA 数据 SHA256 → 跑了两段零旋转外推（留出 RMSE：仅重力 0.697/2.179 m，
↪  C_D=0.22 0.489/1.546 m）→ 新增 `check_issia_arcs.py`、`inference.py` 的 `cd_upper`、`params.json`，写了 `给A的回签与ISSIA外推结果.md`。
↪  注：它 16:56 被要求"上传仓库"后没做完（gh 缺失，回合中断），仓库这边由我继续。

**队友回复（A→B v2）**：口径定稿 v2（ρ=1.20、C_D~U[0.15,0.30] 主模型+0.45 敏感性、√5、Z=1.920、Ĉ_D=0.3784）+ 确认 B 的回签 + 给 B 的新请求（§8
↪  面积对比）+ 要 C 改三处。

## 2. 本轮推进（4 件实质工作）

** ① 回答 A 的 §8：C_D 先验面积对比 **（3 seeds × 4 万样本，同 KDE/网格 HDR 估计器）

| C_D 先验 | 50% 面积 | 95% 面积 | 后验均值 |
|---|---|---|---|
| [0.15, 0.30]（主模型） | 0.213 m²（0.205–0.219） | 0.806 m²（0.789–0.821） | (2.696, 1.988) |
| [0.15, 0.45]（敏感性） | 0.215 m²（0.210–0.222） | 0.802 m²（0.792–0.809） | (2.689, 1.971) |

→ 面积变化 **+1.1% / −0.5%**（在 seed 波动内），均值移动 **1.7–2.0 cm**（A 引用的单 seed 2.6 cm 保留，建议写"约 2 cm（1.7–2.6）"）。**支持 A
↪  的撤回**，主模型继续用 [0.15,0.30]。图：`runs/case_cd_prior/cd_prior_contours.png`。

**② 发现 A 自检用例 §3 有实质错误（已写证据）**：§3 的升力方向写成了 `ω̂×v(ω̂•v)`，与同一文件反演约定 `ω×v` **相差约 90°**。用物理方向 + 恒定
↪  (C_D,C_L) 可把两个题给点拟合到 **1.4 mm / 2.6 mm**（A 版公式给的是 19.8/77.4 mm）。→ A 的"常系数积分偏低 6 cm ⇒ 必须写 C_D(v)"推论不成立，
↪  **C 的论文若用了这个论证必须改**。

**③ 按 A 的建议做了 ISSIA (C_D, L) 可辨识性检验**：加入"垂直于速度的净升力标量"后，留出 RMSE **0.452→0.188 m**、**1.488→1.084 m**；L≈5.8±5.0
↪  / 6.9±3.8 m/s²，C_D–L 相关系数≈0（可辨识，条件数~5×10²）；水平升力（垂直自旋轴）被数据拒绝。→ **缺失自由度是竖直净升力**（与 A 自己算的
↪  +3.2 m/s² 同量级）。

** ④ 已生成 B→A 第三轮回复 **（可直接复制发送）与两份核对报告。

## 3. 仓库更新（commit `46c2f00`）

- 并入 Codex 最新产出 + **A→B 交接包 v2 全量入库 **（`handoff/A 到 B_v2_2026-11-07/`，SHA256 已逐一核对）
- 新增：`case_cd_prior.py`、`fit_issia_cd_lift.py`、`test_selftest_case.py`（13 项测试全过）、`params.json`、`selftest_case.json`、
↪  `runs/case_cd_prior/`、`runs/issia_A/`、三份报告
- 更新：根 [README]([team repository])（v2 口径、新结果、给 A/C 接口、四处必改）、`inventory.md`、`student_b/README.md`

![C_D 先验敏感性](UPC155/student_b/runs/case_cd_prior/cd_prior_contours.png)

## 4. 你接下来要做的 3 件事

1. ** 把 [给 A 的回复 _ 第三轮.md]([team repository]) 发给 A**（含三项待确认：§3 勘误是否同意、面积写法、文献轨迹交付）。
2. **把给 C 的四处同步转过去**：√5、Z=1.920、Ĉ_D=0.3784，**新增第 4 处**："自检用例 §3 方向勘误 → C_D(v) 论证要换证据"（详见 [核对报告]([team
↪  repository])）。
3. 若 Codex 继续工作，让它**先 `git pull` 仓库**——它的工作区 `F:\ChatGPT\upc` 还没有这轮新增（我没直接写进去，避免抢写冲突）；
↪  我在本地留了完整副本 [UPC155/README.md](UPC155/README.md)。

另：`fit_issia_cd_lift.py`、`case_cd_prior.py` 都可一键复现（命令在根 README §5 第 7–9 条）；网络到 GitHub 抽风时走本地代理 7897 可推。
```

Query 5 (exact wording).

```
同意 §3 的方向修正。积分自检采用 \(\mathrm{unit}(\hat\omega\times\hat v)\)，并按零叉积情形处理。撤回用原残差证明必须采用 \(C_D(v)\) 的判断。

对阻力先验敏感性，论文可写“在本次模型和两组先验下，后验均值移动约 2 cm，三次重复的区域面积差异小于种子间波动”。暂不把 1.7–2.6 cm 写成统计区间，
↪  也不推广为所有先验下均不敏感。

ISSIA 两段中加入竖直力后留出误差降低，说明该模型扩展值得考虑。相关系数接近零和条件数本身不足以证明物理参数已被唯一确定，
↪  竖直力也可能吸收跟踪误差或其他模型误差。因此这些结果不能作为 \(C_D(v)\) 必要性的证据。

文献轨迹同意按原图、时间轴、坐标轴和实测点标识交付，作为独立外推案例。3–5 条不足以估计 95% 覆盖率。

请 C 同步三项数值修正。固定起点且后两次观测独立同方差时，噪声系数用 \(\sqrt5\)。恒加速度基线 \(Z=1.920\,\mathrm m\)。空气密度取
↪  \(1.20\,\mathrm{kg/m^3}\) 时，表观 \(\hat C_D=0.3784\)。\(\sqrt6\) 对应三个位置均有独立同方差误差的情形，建议写明假设。
```

Complete output 5.1.

```
已按 A 的第三轮确认全部落地并推送：[team repository] （提交 `aaecc2f`，14/14 测试通过，远端已核验）。

## 1. 逐条落实 A 的决定

| A 的决定 | 落地情况 |
|---|---|
| **同意 §3 方向修正，采用 `unit(ω×v)`，按零叉积处理** | 自检积分改用物理方向；`physics.acceleration` 对 ω∥v、零自旋及**近平行**情形
↪ （相对阈值 `|ω×v| ≤ 1e-9 • |ω||v|`）显式取升力 = 0，无 0/0、无发散；新增第 7 项测试 `test_zero_cross_product_gives_no_lift`（覆盖 ω=0 /
↪ ω∥v / 反向 / 近平行四种）。**14/14 通过** |
| **撤回用原残差证明必须采用 C_D(v) 的判断** | 根 README、`对A自检用例的核对.md`、`ISSIA_CD_L拟合检验.md` 全部改为"不得再用案例常系数残差论证
↪ C_D(v)"；拟合 JSON 增加 `interpretation_caveat`，明确不可作 C_D(v) 证据、C_D 不可当标定值 |
| **面积敏感性写法** | 论文口径固定为 A 的版本：**"在本次模型和两组先验下，后验均值移动约 2 cm，三次重复的区域面积差异小于种子间波动"**；
↪ 删掉了"1.7–2.6 cm 统计区间"表述和"所有先验均不敏感"的推广（原始多 seed 数据保留仅供复核） |
| **ISSIA 竖直力定位** | 降为"**模型扩展值得考虑**"；明确写清：相关系数≈0 / 条件数≈5×10² **不构成物理参数唯一确定的证据**，
↪ 竖直力可能吸收跟踪/重建误差或其它模型误差，**不能作为 C_D(v) 必要性证据** |
| ** 文献轨迹口径 ** | 按原图、时间轴、坐标轴、实测点标识交付；3–5 条只作独立外推案例，** 不用于 95% 覆盖率 **（写进 README §4 与下一步） |

A 的确认原话与落地决定已入库：[handoff/A 到 B_ 第三轮回复记录 _2026-11-07.md]([team repository])。

## 2. 给 C 的清单（已收敛为" 三项数值 + 一项撤回"，可直接转发）

1. **噪声系数**：固定起点 r(0) 精确、0.05/0.10 s 两次观测独立同方差 → **√5 • σ/Δt²**；√6 对应"三个位置均有独立同方差误差"的情形，
↪ **若保留须在正文写明该假设**（只作保守上界）。
2. ** 恒加速度基线 **：**Z = 1.920 m**（全精度 1.920367，不写 1.921）。
3. ** 表观 Ĉ_D**：ρ = **1.20 kg/m³** 时 **Ĉ_D = 0.3784**（Ĉ_L = 0.2105）；若写 0.371 必须注明 ρ=1.225。
4. ** 一项论证撤回 **：不得再用" 案例常系数残差 6 cm" 论证 C_D(v) 必要性（A 已确认撤回）；ISSIA 竖直力只说明扩展值得考虑。

上述内容已写进根 [README §3/§4]([team repository]) 和" 给队友的同步消息"（粘到群里即可）。

## 3. 仓库状态

- 提交 `aaecc2f`，与队友（溪上）刚推的**微信 14 条消息归档**提交 `d92bd6c` 已 rebase 合并；README、inventory 两处冲突已手工解决，
↪ **两边内容都保留**（队友的"微信留档 §K" + 我方的"第三轮 §L"）。
- 校验：`python -m unittest discover -s student_b` → **Ran 14 tests, OK**；远端 248 个文件、`handoff/A到B_第三轮回复记录_2026-11-07.md`、
↪ 更新后的 `physics.py` / `test_selftest_case.py` / `cd_lift_fit.json` 均已核验在位。
- 小提醒：队友把 14 条消息（含 ISSIA 原始/规范化大 CSV）也归档进了仓库，会**增大克隆体积**；如果在意可以后续改用 Releases/Git LFS 或清理该归档。

## 4. 下一步

1. 把上面" 给 C 的清单" 发给 C，等 C 改完稿后我按仓库数字逐条核对论文数值。
2. 等 A 按原口径交付 3–5 条文献轨迹 → 我在 `student_b/` 做独立外推案例（只作案例、不报 95% 覆盖率）。
3. 剩余 B 组工作：MDN 50% 区域校准、扩大对照样本与消融、给 C 出 LaTeX 三线表和 300 dpi 图。

需要我把 A 的文献轨迹格式要求整理成一份" 交付模板" 发给 A，或直接开始做 50% 区域校准实验，说一声即可。
```

Query 6 (exact wording).

```
查看 gpt 的最新工作
```

Complete output 6.1.

```
已查看完毕（只读，没有改动任何文件）。**GPT 最新一轮工作（18:42–20:07）主要是"仓库整合 + 新数据接入 + 覆盖审计 + 真实点球外推 + 进度看板"；
↪ 它最后一次推送是 `1418859`，之后队友又推了 2 个提交，仓库最新为 `d07c002`。**

## 一、GPT 这段具体做了什么

| 时间 | 动作 | 产出/提交 |
|---|---|---|
| 18:42–18:50 | 盘点仓库 + DSH 进展，写进度看板 | 根目录 [agent_readme.md]([team repository]) |
| 18:56–19:12 | 定策略：B 做正式独立评测（不是扩大 12 条小对照）；C 写正文；A 整理实测 | [UPC-B-最终实验与网络升级计划.md]([team repository]) |
| 19:46–19:56 | ball3d 访问申请（Viewer）+ ** 仿真覆盖审计 ** | `student_b/runs/coverage_audit/覆盖审计.md` |
| 19:57–20:02 | ** 整合仓库新数据 **（去重后 6 个案例：4 点球 + 2 非点球） | 提交 `a4066c4` + `student_b/新增数据整合.md` |
| 20:03–20:07 | ** 两次真实点球外推 **（前三帧初始化、留出帧评分） | 提交 `1418859` + `runs/real_penalties/实测点球外推结果.md` |

** 关键结果（真实点球，2 例，仅开发对照）：**

| 案例 | 恒加速度 | 仅重力 | Cd=0.22 | Cd=0.45 | 过门点误差 |
|---|---:|---:|---:|---:|---:|
| J03WOH | **0.190 m** | 0.505 | 0.349 | 0.393 | 0.37–0.66 m |
```

```
| J03WR9 | 门前触地失败（5/7 帧） | 0.450 | **0.310** | 0.331 | 0.54–0.55 m |

→ 两例互相矛盾（一例恒加速度最好、一例零旋阻力最好），**不足以给方法排名**；门线误差仍约半米。GPT 的结论是"只能当案例级外推，不能算覆盖率/盲评",
↪  这个定性是对的。

**覆盖审计的三个关键缺口**：严格零旋样本 **0 条**、总角速度 <10 rad/s 训练样本仅 **77 条**、初速 <18 m/s **0 条** → 新接入的 PFF
↪  低球/低速案例落在模型支撑域之外，论文必须写清适用范围。

## 二、GPT 之后的最新进展（它的本地 clone 还没拉到）

- `d388ada`（A）：DFL 60 段轨迹经运动 + 事件筛查后只保留 **11 段/254 点 **，删掉 49 段；明确标注" 探索性对照，不能当独立验证"。
- `d07c002`（C，台式机）：**P0 五臂消融 + 诊断**——physics16 特征（Arm C）NLL 最好；残差目标（B/D）在 10/15 mm 崩溃；**50%
↪  覆盖率所有方案都只有 0.45–0.53，校准才是下一个大杠杆**；16 维特征存在精确共线（实际秩 12）；K=3 实际退化成"1 主 + 2 小"；
↪  恒加速度基线的干净残差中位仅 0.090 m，是精度上限参考。
- 另外 C 的论文初稿已到 **13 页 / 18 条文献**，并且**已按 A 的确认改好** √5（√6 进附录）、Z=1.920、不再出现 Ĉ_D 数字、删掉"案例残差证明
↪  C_D(v)"论证。

## 三、当前真实状态与缺口

** 已完成 **：模型跑通、题面案例、5 万条仿真/训练、初版论文、真实数据整合、覆盖审计、2 例真实点球外推、6 个案例接入。

** 距可提交还差（按风险排序）**：
1. ⚠ **AI 使用披露仍是空模板 **（`ai-report.tex`）——官方硬性要求，未填不能提交；
2. **B 的正式配对评测 ** 还没做：目前每场景只有 12 条，GPT 的 P0 要求无风/横风各 200 条、同轨迹同噪声比较；
3. 50% 区域校准（所有方案都偏低）；
4. 论文最终表/摘要需用正式评测替换；最终模型可能要从旧 MDN 换成 C 的"physics16 特征版"；
5. 实测只有 2–6 例，且观测时刻/起点与题目设定不匹配，只能案例级。

## 四、需要你知道的本地工作区状态

GPT 把 **DSH 建的本地仓库当成了共享 git 库**：在 `F:\ChatGPT\upc\integration` 建了 worktree（分支 `codex/integrate-flight-data` @1418859），
↪  两边共享同一个 `.git`。当前：

- 我们的 `F:\Program Files\upc\UPC155`（main）** 落后远程 21 个提交 **，还有 1 个已被远程取代的本地草稿提交 `1e5daf8`（旧版 agent_readme）；
- GPT 的 clone 也 ** 落后远程 2 个提交 **（A 的筛选、C 的 P0）；
- ⚠ 两个 worktree 共享 .git，** 不能同时写 **；我要继续推进需先把本地 main 对齐（丢弃草稿、pull --rebase）。

## 五、建议下一步（你选）

1. **（推荐，我能直接做）B 的 P0 正式配对评测**：无风/横风各 200 条，恒加速度 / 贝叶斯 / 旧 MDN / 新特征 MDN，报告失败数、50%/95% 覆盖、面积、
↪  耗时、多种子——这是论文现在最缺的一张表。
2. ** 补 AI 使用披露 **：我把今天的 GPT 会话 + DSH 会话整理进 `ai-report.tex`，解决硬性提交风险。
3. 50% 校准（按 σ 协方差/温度缩放，验证集拟合、封存集报告）。
4. 提醒 GPT/C 先 `git pull`，把 C 的 P0 结论和 A 的 11 段筛选并入 agent_readme 与论文。

要我现在开始第 1 项（配对评测），还是先做第 2 项（AI 披露）?
```

Query 7 (exact wording).

```
codex 又没有额度了 qwq，看看她和你一起工作到哪了？恢复工作吧
```

Complete output 7.1.

```
已恢复工作并推进到"** 提交版已就绪，只差队员 AI 记录 **"。核心进展如下：

## 一、她和你一起走到哪了（Codex + DSH 的总账）

| 阶段 | 成果 |
|---|---|
| 11-07 下午 | Codex 从零搭出仿真器/贝叶斯推断/MDN；DSH 负责仓库整理与上传，A→B 数据口径定稿 |
| 11-07 晚–11-08 凌晨 | A 交付实测数据（DFL 点球/ISSIA/Barber/Asai），C 完成 P0 五臂消融 + P1 选型与**独立盲测**（5,036 条，5 mm 中位误差
↪  0.290 m，校准后 50%/95% 覆盖 47.6–49.1% / 94.5–95.2%）；Codex 做真实点球外推、覆盖审计、双线整合、Asai 100 Hz 三球复演、DFL 11 段筛选；C
↪  的论文初稿同步 P1 |
| **11-08 中午（额度耗尽时）** | Codex 最后一段**未提交**的改动还留在本地工作区：通用化 `physics.py` 接口 + P1–P5/AsAI 实验脚本和运行结果 |

## 二、我这次" 恢复工作" 具体做了什么

1. **抢救断线前的未提交成果**：把 Codex 留在 integration worktree 里的 47 个文件（含 P1–P5、AsAI 脚本、p1_calibration/p2–p5 结果）提交、
↪  与最新远端 rebase、解决冲突、跑过 14 项单测，合并进 `main`（提交 `dbb2ded`）——**不抢救就丢了**。
```

2. **补上官方硬性项：AI 使用披露**：自动从本机日志提取 **OpenAI ChatGPT/Codex（2 个会话，62+2 条提问）**与 **DeepSeek Harness（7 个会话，30 条提问）**，共 **94 条原始提问 + 202 段完整输出**，生成 58 页报告（中文逐字照录；账号名、团队仓库链接、微信 ID、邮箱、校名等已脱敏并注明），作为论文最后一部分。
3. **生成提交版论文**：`155B.pdf`，共 **73 页**（英文正文 15 页 + AI 报告 58 页）。已验证：Summary 212 词、每页页眉 Team 155、正文无姓名/学校/个人链接、无缺字、编译无错误、14 项测试通过。
4. **工具化 + 入库**：`tools/build_ai_report.ps1` 一键重建（导日志→提取→生成→XeLaTeX→pdfLaTeX→`155B.pdf`）；`ai-report-team.tex` 供队员补记录。已提交并推送：仓库最新 `64185d0`。

三、还剩什么（按优先级）

1. ⚠ **唯一硬性缺口**：`论文模板/ai-report-team.tex` 目前是占位段落，需要 A/C 同学提供**其他生成式 AI 工具**的记录（系统 + 原始提问原文 + 完整输出）；若确实没有，改成一句 "No other generative-AI tools were used by the team."。**不补不能提交**。
2. 提交前重跑 `tools/build_ai_report.ps1`，把之后（包括这轮）与 AI 的交互刷新进报告——当前 PDF 的快照截至生成时，最后这条回答还没进 AI 报告。
3. 人工过一眼 `155B.pdf` 的图表与正文表述（结构性问题我已查过）。
4. ** 邮件提交 **：[email redacted]，主题和正文都写队号，附件 `155B.pdf`，截止 ** 北京时间 11-09 09:00**（现在 11-08 12:20，约 20.5 小时）。

四、需要你确认

1. ** 队友用过哪些其他 AI 工具 **（Gemini/Kimi/Claude 等）？把他们的原始提问和完整输出发我，我补进 Section C。
2. 要不要我接着做：① 通读校对正文；② 等记录补齐后重跑最终版；③ 其他任何检查？

文件：本地 [155B.pdf](UPC155/论文模板/155B.pdf) • [写作状态/待办](UPC155/论文模板/写作状态.md) • GitHub [仓库 `64185d0`]([team repository]) • [AI 报告纯文本](UPC155/ai_logs/UPC155_AI_usage_log.md)。

Query 8 (exact wording).

根据新数据做的进化做完了？或者你可以整理现有成果，我找一台有额度的电脑继续跑

Query 9 (exact wording).

This is an automatically generated checkpoint condensing an earlier span of the conversation to free up context. Treat the captured context as established background and build on it without restating it. Continue the task directly from the messages that follow, without acknowledging this checkpoint.

<compacted-summary>
Primary Request and Intent
- Original: **"与GPT沟通，获取upc相关她的全部成果，并将其中需要与组员共享的代码之类上传仓库：[team repository] — read GPT/Codex's UPC outputs and upload shareable code/results to GitHub repo.
- Follow-ups: read A's handoff zip and **"读取codex的最新工作成果，并结合队友的回复推进"**; then A's third-round decisions were relayed verbatim and must be implemented; then **"查看gpt的最新工作"**; then **"codex又没有额度了qwq，看看她和你一起工作到哪了？恢复工作吧"** — Codex quota exhausted; DSH takes over, reports joint progress, and resumes work.
- A's verbatim decisions (Nov 7): agree §3 direction fix using `unit(ω̂×v)` + zero-cross handling; retract "original residual proves C_D(v) required"; paper wording for drag-prior sensitivity = "在本次模型和两组先验下，后验均值移动约 2 cm，三次重复的区域面积差异小于种子间波动" (do not write 1.7–2.6 cm as interval, no generalization); ISSIA vertical-force results only mean "model extension worth considering", *cannot* be used as C_D(v) evidence (correlation≈0/condition number don't prove unique identification; vertical force may absorb tracking error); literature trajectories by original figure/time-axis/axes/points, 3–5 cases, no 95% coverage; tell C: √5 (√6 = all three positions noisy, state assumption), Z=1.920 m, Ĉ_D=0.3784 at ρ=1.20.

Key Technical Concepts
- UPC 2026 Problem B: predict penalty goal-plane crossing (Y,Z), 50%/95% joint regions, goal probability from r(0)=(0,0,0.11), r(0.05), r(0.10); goal plane x=11 m, Y∈±3.66, Z∈[0,2.44].
- Canonical simulator: `student_b/physics.py` batch RK4 (dt 0.002), gravity + quadratic drag (C_D~U[0.15,0.30] per-trajectory, ρ=1.20) + transverse Magnus `CL=min(1.4S,0.30)`, `S=Rω⊥/U`; zero-cross → lift 0; goal/ground events.
- Bayesian importance sampling (`student_b/inference.py`, 4 adaptive stages, p/q correction, ESS); full-covariance MDN (K=3); P0 5-arm ablation; P1 final model: 11 physics features, 3×128, GELU, LayerNorm, K=3 full covariance, 37,650 params, calibrated regions.
- P1 final results (paper main): blind test 6,000 trajectories / 5,036 airborne; 5 mm median error **0.290 m**, calibrated 50%/95% coverage **47.6–49.1% / 94.5–95.2%**, NLL −0.219; case mode (2.62, 2.15) m, areas 0.177/0.775 m², in-goal prob 97.3% (Bayes 96.3%).
- Real-data evidence: 2 DFL penalties, 4 measured flights (spin), 11 screened DFL segments, Asai 100 Hz 3-kick replay (~50–60 cm 11 m virtual-section error); DFL/Aasi = exploratory case-level only.
- Repo coordination: GitHub PR/branch workflow; Codex created worktree `F:\ChatGPT\upc\integration` sharing git dir of DSH repo `F:\Program Files\upc\UPC155\.git`; teammate pushes via main.
- Git over proxy: direct GitHub flaky; use `git -c http.proxy=http://127.0.0.1:7897` (Clash Verge mixed port 7897; token via GCM, user [team member], repo public, push permission).
- Deadline: contest start Nov 6 18:00 MST = Nov 7 09:00 Beijing; **48 h → Nov 9 09:00 Beijing**; current time **2026-11-08 12:01** (~21 h left).

Files and Code
- `F:\Program Files\upc\UPC155` — DSH main worktree (branch `main` at local `1e5daf8`, ahead 1 / behind 25–30 vs `origin/main`); stray local commit `1e5daf8 "docs: add agent progress and next steps"` = obsolete agent_readme draft.

- `F:\ChatGPT\upc\integration` — Codex worktree (shared git dir, branch `codex/integrate-flight-data`; was `6122085`, behind origin; now local commit `8f742a4 "wip(resume): preserve post-6122085 work..."` after rebase start, conflicts unresolved).
- `origin/main` = `2839884 "feat(asai): replay three measured kicks with frozen P1"` (authors: [team member]/[team member] for integration commits, [team member] for P0/P1, [team] for data PRs); recent commits include `33a7d02` (P1–P5 results), `00ae82f` (P1 + paper sync), `ebdb13e` (student-c P0), `1a36725` (desktop verification), `6122085`, `8a0225c`, `e81f9ce3`, `e9e3c79`.
- Remote `agent_readme.md`: status board — P1 final chosen, paper synced, **AI disclosure still TODO**, Asai replay added, dual-line evidence integrated; PDF in repo stale.
- `论文模板/main.tex` (remote, 355 lines/41.7 KB): title "Two Points to the Goal: A Noise-Conditioned Mixture Density Network for Probabilistic Penalty Kick Prediction", team 155/B; `ai-report.tex` still TODO template; `写作状态.md` says only AI report + final checks remain.
- `student-c/P1/` — P1 final config, checkpoints, calibration, figures, `results.md`; `student-c/P0/` — P0 report.
- `student_b/runs/` — literature50k, fresh_validation, case_cd_prior, issia_A, real_penalties, coverage_audit, real_spin*, spin_prior, p1_calibration…p5_transfer_spin_prior, asai_factorial, asai_replay, dfl_screened_spin.
- `integration` uncommitted→committed in `8f742a4` (47 files, +29515): generalized `student_b/physics.py` API (`observation_times`, `initial_z`, `goal_x`; local hash `6c1ffe4` vs remote `a084c0a`), scripts `p1_calibrate_arm_c.py`, `p2_train_spin_symmetry.py`, `p3_variable_window.py`, `p5_transfer_spin_prior.py`, `asai_factorial.py`, `asai_transfer.py`, `compare_real_spin_priors.py`, `diagnose_spin_prior.py`, plus run artifacts; `.gitignore` added `student_b/runs/**/*.pt`.
- `F:\ChatGPT\upc\deliverables/` — `UPC155_双线成果整合.md`, `asai_official/paper/` (42 KB main.tex, PDF 866 KB), `asai_ablation/`, `asai_transfer/` (Codex→DSH bridge tasks, `dsh_result.json`); reference line implementation in `F:\ChatGPT\upc\src`, `outputs`, `.venv`.
- `F:\Program Files\upc\_work\` — DSH scratch: `P0_report_2026-11-07.md`, conversation dumps, `handoff_v2/extracted/...`, commit msgs.
- `F:\Program Files\upc\AI对话记录_ChatGPT_UPC_2026-11-07.md` — full Codex UPC conversation export (local only, candidate raw material for AI disclosure).
- Conflict files in rebase: `.gitignore`, `agent_readme.md`, `student_b/experiments/ablation.py` (3 hunks), `student_b/experiments/common.py` (1 hunk), `student_b/validate_real_spin.py` (whole-file: remote newer rework already includes `aero_draws`), plus ~20 add/add duplicates of `runs/*` artifacts and `asai_replay` PNG/summary (prefer remote/ours).

Errors and Fixes
- Earlier `git push` direct failed (`RPC failed; curl 55`, `Empty reply from server`) → fixed by `git -c http.proxy=http://127.0.0.1:7897 push origin main`; remote had teammate commits → rebase then push (`bf482cf…c596458…46c2f00…aaecc2f`).
- Rebase conflicts on README/inventory with teammate wechat-archive commit `d92bd6c` → resolved by merging both sections (K 微信留档 + L 第三轮), tests re-run OK.
- `test_zero_cross_product_gives_no_lift` initially failed because near-parallel ω gives tiny nonzero cross normalized to full lift → fixed in `physics.py` with relative threshold `valid = norm > 1e-9 * |ω||v|` and `np.where(valid, cross/norm, 0)`, `S` zeroed.
- A's self-test §3 lift direction error found: `ω̂×v{ω̂•v}` is ~89.6° off `unit(ω×v)`; physical direction + constant (C_D=0.3784, C_L=0.2105) reproduces given points to 1.4 mm/2.6 mm (A's formula gives 19.8/77.4 mm) → A confirmed correction and retraction of C_D(v) claim.
- `case_cd_prior.py` first run failed JSON serialization of numpy arrays → patched to pop/listify `y,z,thresholds,density`.
- Powershell heredoc/quoting failures with inline python → use `write` tool or `edit` tool instead of inline `python -c`.
- Integration worktree had huge uncommitted work after Codex quota loss → committed as `8f742a4` before rebasing (preservation step).

Pending Jobs
- Resolve in-progress rebase conflicts in `F:\ChatGPT\upc\integration` (branch `codex/integrate-flight-data` on top of `origin/main`=`2839884`), then push branch and fast-forward/push `main`.
- Sync DSH main worktree (`1e5daf8` obsolete → reset to origin/main), run 14-test suite, verify merged scripts run.
- Build final paper PDF from latest `论文模板/main.tex` (TeX at `C:\texlive\2026\bin\windows\pdflatex.exe`/`xelatex.exe`), check summary ≤300 words, anonymity/team number.
- **AI disclosure** (`论文模板/ai-report.tex`, hard submission blocker): gather ChatGPT/Codex thread + DSH session logs (+ possibly Gemini/reference-line logs) — exact queries + complete outputs; Chinese logs need XeLaTeX/xeCJK.
- Final submission artifacts: `155B.pdf` naming, PDF metadata empty, team number on every page, no identifying info; confirm systems used with user.
- Optionally commit reference-line deliverables into repo and clean large binary growth.

Current Work
- Executing rescue/sync phase after Codex quota exhaustion: preserved `integration` uncommitted work in commit `8f742a4`, started `git rebase origin/main`; conflicts currently unresolved; inspecting hunks to merge:
  - `ablation.py`: HEAD (remote) has P1 params (`input_kind,k,depth,activation,correlation,cosine,dynamic_noise`), local adds (`spec,warm_start,mirror,select_validation`) — must merge both; local `p2_train_spin_symmetry.py` calls `train_one(..., spec=spec, warm_start=warm, mirror=..., select_validation=True)`; `p1_calibrate_arm_c.py` calls `p0.train_one('C', seed, parts)`.
  - `common.py`: HEAD `phys_reduced` indices `[0,1,2,3,4,5,9,10,11,14,15]` (11-dim P1) vs local `[0,1,2,3,4,5,9,10,11,12,13,14,15]` (13-dim) — prefer HEAD (11-dim) unless `p2` breaks.
  - `validate_real_spin.py`: remote HEAD rework already includes `sample_prefix(..., aero_draws=...)`; local scripts (`p5`, `replay_asai_3kicks.py`, `compare_real_spin_priors.py`, `asai_transfer.py`) import it — take HEAD entirely.
  - `.gitignore`: keep HEAD block (student-c/P1 *.pt, 论文模板 aux/log/out/toc) + local `student_b/runs/**/*.pt`.
  - `agent_readme.md`: take HEAD; duplicate add/add `runs/*` + `asai_replay` artifacts: prefer HEAD (`git checkout --ours`), then `git add`, `git rebase --continue`.

Next Step
- Finish the rebase: `git checkout --ours` for duplicate/`agent_readme.md`/`validate_real_spin.py`, merge `.gitignore`/`ablation.py`/`common.py` hunks, `git add -A`, `GIT_EDITOR=true git rebase --continue`, verify with `python -m unittest discover -s student_b` and `py_compile` on merged scripts, push branch via proxy, then reset DSH main to origin/main, merge and push.

Critical Context

```
- Two worktrees share one `.git` (`F:\Program Files\upc\UPC155\.git`; integration `.git` file points to `.git/worktrees/integration`) —
↪  **never write both simultaneously**; main branch is checked out in DSH worktree.
- Local stray commit `1e5daf8` is a superseded agent_readme draft → discard on sync (`git reset --hard origin/main`).
- Codex quota exhausted; DSH now owns continuation; user expects tangible resumed progress, not just a report.
- Known paper/repo state: P1 final numbers are canonical; P0 4,187 = dev set, P1 5,036 = main table; reference-line results go to
↪  sensitivity appendix; DFL/Asai/ISSIA = case-level only; 50% coverage miscalibration acknowledged; zero-spin & <18 m/s samples absent
↪  (coverage gap); callout "97.3% = conditional on airborne crossing".
- Repo contains large binaries (wechat archive, DFL zip 3.3 MB, big CSVs) — clone size growing; `.npz/.npy/*.pt` mostly ignored.
- AI rules (raw/official/contestrules.md): paper must be English, team number on every page, no names/institution; AI use must disclose
↪  system + exact query + complete output; first page only team number/problem/title/summary (≤300 words).
- Teammates: A=[team]/[team member]? Actually data PRs by [team]; C=[team member] (codex verification, student-c, paper); user=[team
↪  member]/[team member] (repo owner collaborator); reference-line other AI work integrated via `deliverables/UPC155_双线成果整合.md`.
- Open questions for user: which AI systems to disclose (ChatGPT/Codex, DSH, Gemini?, other teammates' tools), whether to include full raw
↪  transcripts in AI appendix, and whether team wants DSH to prepare `155B.pdf` for submission.
</compacted-summary>
```

Query 10 (exact wording).

```
<system-reminder>
The available skill catalog changed. This complete catalog replaces every earlier available-skills list in this session:

<available_skills>
- `ainiee-translate`: Use when the user wants to translate a novel/epub end-to-end on the coding agent itself (Claude Code or Codex; no
↪  AiNiee app), AiNiee-style — parse, build a locked glossary, translate chapter by chapter following rules (names preserved, title
↪  3-way, term consistency), write back and export. Triggers on "用 agent 翻译这本书", "agent 版 aniee 翻译", "把这本 epub 翻译了" and
↪  similar.
- `brainstorm`: Divergent-then-convergent idea exploration skill. Use when the user has a vague idea, an open problem, a stuck project, or
↪  asks to "头脑风暴 / 帮我发散 / 想几个方案 / 换个思路" and does NOT yet want a decision or an implementation. Turns a fuzzy prompt into
↪  a spread of genuinely different directions, then stress-tests them and lands on one concrete next action. Handles naming, positioning,
↪  project directions, feature ideas, research angles, event themes, and "我该做什么" 类选择困难。
- `business-data-analyst-skill`: Business data analysis and operating diagnosis skill. Use when the user needs to translate a business
↪  question into an analysis plan, define metric logic, validate data quality, break down changes in growth, conversion, retention,
↪  revenue, or efficiency, identify root causes, quantify business impact, and produce actionable recommendations or experiment ideas.
↪  Suitable for operating reviews, growth analysis, user behavior analysis, channel performance analysis, funnel analysis, sales
↪  conversi...
- `campus-event-planning`: 校园与社团活动策划 skill。当用户要策划、审批、执行或复盘一场校内活动时使用——比赛/竞赛、讲座/分享会、迎新/招新、
↪  晚会、展览、志愿服务、社团开放日等。覆盖立项与审批、场地与设备、经费与报销、宣传节奏、人员分工、当天执行脚本、志愿者管理、
↪  应急预案与活动复盘总结。输出可直接交给指导老师、团委或学生会审阅的策划书。
- `durable-tech-buy`: Research and compare expensive, long-lived computer hardware and digital products before purchase. Use for NAS, PCs,
↪  laptops, phones, cameras, networking gear, storage, displays, and similar products when the user wants exact-model cross-platform
↪  pricing, review synthesis, same-price alternatives, price-cycle judgment, reliability/performance analysis, or lifecycle total cost.
↪  Optimized for JD, Taobao/Tmall, Pinduoduo, and Douyin; not for placing orders, adding to carts, or monitoring prices ...
- `research-paper-review`: Academic paper comprehension and adversarial review skill for unpublished drafts. Use when the user needs an
↪  unpublished paper explained in plain language, wants reviewer-grade constructive criticism, needs an advisor-facing feedback memo, or
↪  wants submission-readiness checks (venue compliance, ablation completeness, baseline strength, statistical reporting,
↪  reproducibility). Covers ML/RL/optimization/transportation/energy-systems papers, including MARL and EV-charging scheduling work.
↪  Handle...
</available_skills>

Use only names in this replacement catalog. If the user names a listed skill, or the task clearly matches its description, call the
↪  `skill` tool with the exact name before acting.
A user may also invoke a skill directly; its <skill_content> block then appears in this conversation. Follow it, and do not call the
↪  `skill` tool again for that skill.
</system-reminder>
```

Query 11 (exact wording).

```
Current runtime context. This snapshot supersedes earlier runtime-context snapshots.

Current DSH file policy: danger-full-access. The DSH file sandbox does not restrict file modifications by available operations.

Approval prompts are disabled in this session: actions that require approval are rejected automatically — do not request sandbox
↪  escalation (do not set `sandbox_permissions`).
```

Complete output 11.1.

```
两件事都做了：** 新数据的三块分析全部跑完 **（包括 Codex 额度耗尽时卡住没做完的那块），** 换机交接包也整理好了 **。
```

Team 155

```
## 一、" 根据新数据做的进化": 做完了

三份 xlsx（Fig3 / Sample05 / Sample12, Asai 2020 实测三球）一共做了三块:

| 分析 | 状态 | 关键结果 |
|---|---|---|
| 冻结 P1 三球复演 | □ 之前已完成 | P1 高度平移后 11 m 虚拟截面误差 54.49 / 49.87 / 59.57 cm; canonical 物理后验 55.17 / 52.36 / 61.92 cm;
↪  全段回拟合 RMSE 0.20 / 1.12 / 0.65 cm |
| 2×3×2 因子对照（MAP vs MAP） | □ 之前已完成 | 无先验 26.00 → 仅幅值先验 22.30 → **手册方向先验 10.63** → 留一 22.45 cm; 方向约束是主因,
↪  但先验中心是人工常数, **不能当泛化提升**: Sample12 改善但另两球变差 |
| ** 方向先验外推 + MAP/后验匹配 ** | □ ** 这次补完 **（Codex 断在这里） | 见下 |

**补跑这块时发现 Codex 停机不全是环境问题, 有一个真实数值 bug**: `endpoint_draws` 在"这一步没触地"时仍算了负的地面分数,
↪  导致上升段过截面被误判为触地而丢弃 → 后验截面质量统计失真。另两个自检错误（对齐期望轨道、RMSE 括号）是检查逻辑问题。修复后 **6 项自检 +
↪  归档复现检查 + 12 项契约测试全部通过**。

结果（从仓库根目录 `student_b/runs/asai_transfer/README.md` 可看完整表）:

- **方向先验不能外推**: 2 场 DFL 点球 + 2 段 ISSIA 的留出帧 RMSE——无先验 **30.09 cm**, 手册方向先验 46.53, pooled 43.50。11 段补充 DFL
↪  上平均略好但逐例混杂。→ Asai 上 10.63 cm 属"对这三球的样本内正则化"。
- **旧差距很大一部分是估计量定义**: 同一模型/同一先验/同一基下, MAP 8.55–13.32 cm, 但**后验均值 51–54 cm**、KDE 众数 5.9–19.8 cm。→
↪  这正好回答你之前问的"手册 11.39 vs canonical 50–60": 主要是 MAP vs 后验均值 + 先验方向, 不是新数据让模型变准。

**正式 P1、训练集、论文主表都没动**; 这些是 exploratory/appendix-level 证据。论文正文我没改——是否把因子/迁移结果写进 Appendix 由 C 定
↪  （可作为可选 P1, 见交接包§5）。

## 二、换机交接包: 已整理好（仓库 `main` 最新 `b02edd5`）

- **交接文档**: [handoff/继续跑_交接包_2026-11-08.md](UPC155/handoff/继续跑_交接包_2026-11-08.md) ——现状总览、必须带走的东西、环境、
↪  常用命令、剩余待办、给下一个 AI 的启动 prompt、口径与坑。
- **三份工作簿**已入仓: [handoff/asai_workbooks_2026-11-08/](UPC155/handoff/asai_workbooks_2026-11-08/README.md)（Asai 2020, CC BY 4.0,
↪  sha256 与桌面原件一致）。
- **实验实现/测试/运行脚本**: [deliverables/asai_transfer/](UPC155/deliverables/asai_transfer/README.md)（`README` +
↪  `test_asai_transfer.py` + `run.ps1`）, 结果和自动生成报告在 `student_b/runs/asai_transfer/`。
- **换机器最省事的方式**: `git clone` 仓库 → 装 Python（numpy/scipy/torch/openpyxl/pandas）+ TeX Live → 跑 `python -m unittest discover -s
↪  student_b` 和 asai 的三条命令即可; 若要在新机器刷新 AI 披露, 把本机 `~/.codex/thread_history_1.sqlite` 和 `~/.dsh/sessions/` 一起拷过去,
↪  或保留现有 AI 报告只补 Section C。

## 三、交接/提交前只剩这些

1. ⚠ **补 `论文模板/ai-report-team.tex`**（唯一硬缺口）: A/C 同学用过的其他 AI 工具, 按"系统 + 原始提问原文 + 完整输出"补; 没有就写一句声明。
2. 提交前重跑 `tools/build_ai_report.ps1`（我已把 AI 报告刷新到 98 条提问/203 段输出, **155B.pdf 现在是 77 页 = 正文 15 + AI 报告 62**,
↪  无身份信息、每页 Team 155）。
3. 人工过一遍图表 → 邮件提交 `[email redacted]`, 截止 ** 北京时间 11-09 09:00**（现在约 19 小时）。

**问一句**: 你说的"根据新数据做的进化"如果指的是"**用这三条实测轨迹去升级/重训模型**", 那没有做、也不建议在截止前做（n=3 且三条都已看过, 会破坏
↪  P1 独立性）; 如果你希望我把 Asai 因子/迁移结果补进论文 Appendix（作为诊断证据）, 我可以现在起草一页给 C 审。
```

Query 12 (exact wording).

```
gemini给的建议, 参考一下。我的想法是: 现在还有相对充裕的时间, 能不能根据asai教授的数据重新生成更好的仿真数据集, 然后丢给台式机去训练?
↪  能不能把理论误差极限的分析加入论文也作为我们的亮点? 对照之前给你的往年获奖作品, 我们离获大奖还差些什么?
```

C. Additional generative-AI tools used by other team members

[To be completed by the other team members: system name and how it was used; exact query; complete output. Duplicate this block for each tool.]