

**NAME**

dedupe - delete files from a cull tree that duplicate an actual tree

**SYNOPSIS**

**dedupe** --database *DB* [--delete] [--allow-mixed] *ACTUAL CULL*

**DESCRIPTION**

**dedupe** dismantles a redundant copy of a directory tree. *ACTUAL* is the copy being kept -- it is never modified, ever. *CULL* is the redundant copy: every file in it whose digest duplicates a file in the *corresponding* directory of *ACTUAL* is deleted, regardless of name, and directories emptied by this are removed on the way back up. If cull holds three files matching one actual-side witness, all three are deleted. What survives in cull is therefore always a signpost -- something unique, unknown, or suspicious -- and the cull root itself always survives, even empty, as a placeholder and a receipt.

**dedupe** deletes files. It is an experimental companion to **sumtag**(1) and works from a sumtag SQLite database that already knows both trees; it never computes a checksum. A bare run is a full preview (**would delete, would sweep, would rmdir**, with the database opened read-only); actual deletion requires the explicit **--delete** option.

**THE SYNCHRONIZED WALK**

Both trees are walked depth-first at the same time, locked in step by relative path: while visiting *ACTUAL/foob* the walk is in *CULL/foob*, and it never descends into a subdirectory name that does not exist as a real directory on both sides. Comparison and deletion are therefore flat, one directory pair at a time: a cull file dies exactly when a same-digest file sits in the corresponding actual directory -- same name not required, same relative directory required. Reorganised duplicates are out of scope by design, in exchange for a comparison that can be verified by looking at one directory pair at a time.

The one exception is the empty-directory carve-out: a cull-side subdirectory with no real files anywhere beneath it (only ignorable junk files such as **.DS\_Store**, qualifying symbolic links, and empty directories) is swept even without an actual-side counterpart -- deleting it destroys nothing.

**WHAT IS DELETED, AND WHAT NEVER IS**

Only plain files positively identified as duplicates are deleted, plus the exit junk below, and only ever on the cull side.

- ☯ Files the database does not know (never stamped or mirrored) are invisible: never matched, never deleted, left in place even if that leaves their directory standing.
- ☯ Ignorable junk files (**.DS\_Store**) never block a directory's removal, and are swept exactly when

they are the last thing standing before the directory is removed -- never earlier.

- ✦ Symbolic links are never followed and never digest-matched. A link is swept at directory exit only if it is relative and points inside the cull tree -- where it points is what matters, not whether the target still exists, since the deletion phase has usually just emptied it. An absolute link is never deleted, wherever it points, and neither is any link escaping the cull tree: such a link blocks its directory like any other survivor.
- ✦ A cull directory containing an **@sumtag-ignore** marker (see **sumtag(1)**) is fenced off: not descended, nothing inside it deleted, swept, or removed; it blocks its parent like any survivor. A marker on the cull root itself is honoured with a warning, and the run does nothing.

## TRUST MODEL

Stored digests are trusted; neither side is re-hashed. That is defensible because deleting a true duplicate is reversible -- the actual tree keeps the bytes -- but it only holds if the stored digests describe the current bytes, so three vetoes gate every candidate, none of which read file contents:

- ✦ the database digest must equal the digest in the file's own extended attribute, on both sides;
- ✦ the file's live mtime must equal the mtime recorded in its extended attribute, on both sides;
- ✦ the cull file's live size must equal its witness's. **XXH3-64** is a 64-bit non-cryptographic hash, and the size check is free collision insurance: a digest match with differing sizes is reported loudly as a mismatch, the file is kept, and the run exits 2.

A cull-side file failing a veto is kept, with a warning; an actual-side file failing a veto simply witnesses nothing.

## SAFETY CHECKS

All of the following are verified before anything is at risk:

- ✦ Both roots must exist and be disjoint under **realpath(3)** -- not equal, and neither nested inside the other, so symbolic links cannot disguise an overlap.
- ✦ The database must already exist and must know both roots: each root's live mount point must be recorded and file rows must be present beneath it. An unmounted drive is an error, never a silent no-match.
- ✦ If the two roots' rows carry more than one digest algorithm, the run is refused unless **--allow-mixed** is given, because cross-algorithm duplicates would silently survive.

- ☛ At the moment of deletion, if the cull file and its witness resolve to the same path under **realpath**(3), they are one directory entry reached through links; the deletion is refused loudly (exit status 2), since deleting "the copy" would delete the only name. The same inode behind different real paths is a genuine hard link -- safe to delete, and noted.

Pass the roots spelled as sumtag scanned them: row lookups use the absolute path as given, exactly as sumtag records paths, so a differently-spelled root (for example through a symlinked path component) fails the must-know-both-roots check with a clear error rather than matching nothing.

## OPTIONS

### **--database** *DB*

Path to the sumtag SQLite database that knows both trees. Required.

### **--delete**

Actually delete. Without it, the run is a complete preview and the database is opened read-only. Deleted files' database rows are removed in the same run, committed per directory, so an interrupted run stays consistent.

### **--allow-mixed**

Proceed even when the roots carry more than one digest algorithm. Cross-algorithm duplicates silently survive; see **SAFETY CHECKS** above.

## RUN SUMMARY

Every run ends with a summary block: files deleted (or would-delete) and their cumulative size, items swept, directories removed, files kept (broken down as unique, unknown, or stale), directories fenced by **@sumtag-ignore** markers, errors, and the database and roots in use. Interrupting a run with Ctrl-C prints the same summary, prefixed by an **interrupted** line; the counters cover only completed work, and commits are per directory, so the database matches what actually happened.

## EXIT STATUS

- 0** nothing redundant was found.
- 1** duplicates were found (deleted, or would-delete under preview).
- 2** errors or a safety refusal prevented a complete, clean run.
- 130** the run was interrupted by Ctrl-C (128 + SIGINT, the shell convention).

## EXAMPLES

Preview what dismantling a redundant backup copy would delete:

```
dedupe --database /var/lib/sumtag.sqlite /data/proj /backup/proj-old
```

Actually delete:

```
dedupe --database /var/lib/sumtag.sqlite --delete /data/proj /backup/proj-old
```

## NOTES

**dedupe** is experimental -- and it is the dangerous companion: always preview first. Both trees should be freshly stamped (**sumtag --sum --database ...**) before a run, so the trust-model vetoes have current metadata to check against; stale stamps cause files to be kept, never wrongly deleted.

## SEE ALSO

**sumtag(1)**, **grouper(1)**

## AUTHOR

The sumtag authors.