
NAME

RDKitStandardizeMolecules.py - Standardize molecules

SYNOPSIS

```
RDKitStandardizeMolecules.py [--infileParams <Name,Value,...>] [--methodologyParams  
<Name,Value,...>] [--mode <standardize or count>] [--mp <yes or no>] [--mpParams <Name,Value,...>]  
[--outfileParams <Name,Value,...>] [--overwrite] [--standardizeParams <Name,Value,...>] [--quiet  
<yes or no>] [-w <dir>] [-o <outfile>] -i <infile>
```

RDKitStandardizeMolecules.py -h | --help | -e | --examples

DESCRIPTION

Standardize molecules and write them out to an output file or simply count the number of molecules to be standardized. The standardization methodology consists of the following 4 steps executed in a sequential manner:

1. Cleanup molecules
2. Keep largest fragment
3. Neutralize molecules
4. Select canonical tautomer

The molecules are cleaned up by performing the following actions:

1. Remove hydrogens
2. Disconnect metal atoms - Disconnect metal atoms covalently bonded to non-metals
3. Normalize - Normalize functional groups and recombine charges
4. Reionize - Ionize strongest acid groups first in partially ionized molecules
5. Assign stereochemistry

You may optionally skip any cleanup action during standardization.

The supported input file formats are: SD (.sdf, .sd), SMILES (.smi., csv, .tsv, .txt)

The supported output file formats are: SD (.sdf, .sd), SMILES (.smi)

OPTIONS

-e, --examples

Print examples.

-h, --help

Print this help message.

-i, --infile <infile>

Input file name.

--infileParams <Name,Value,...> [default: auto]

A comma delimited list of parameter name and value pairs for reading molecules from files. The supported parameter names for different file formats, along with their default values, are shown below:

```
SD, MOL: removeHydrogens,no,sanitize,yes,strictParsing,yes  
SMILES: smilesColumn,1,smilesNameColumn,2,smilesDelimiter,space,  
smilesTitleLine,auto,sanitize,yes
```

Possible values for smilesDelimiter: space, comma or tab.

-m, --mode <standardize or count> [default: standardize]

Specify whether to standardize molecules and write them out or simply count the number of molecules being standardized.

--methodologyParams <Name,Value,...> [default: auto]

A comma delimited list of parameter name and value pairs to control the execution of different steps in the standardization methodology. The supported parameter names along with their default values are shown below:

```
cleanup,yes,removeFragments,yes,neutralize,yes,
```

canonicalizeTautomer, yes

The standardization methodology consists of the following 4 steps executed in a sequential manner starting from step 1:

1. cleanup
2. removeFragments
3. neutralize
4. canonicalizeTautomer

You may optionally skip the execution of any standardization step.

The step1, cleanup, performs the following actions:

1. Remove hydrogens
2. Disconnect metal atoms - Disconnect metal atoms covalently bonded to non-metals
3. Normalize - Normalize functional groups and recombine charges
4. Reionize - Ionize strongest acid groups first in partially ionized molecules
5. Assign stereochemistry

You may optionally skip any cleanup action using '-s, --standardize' option.

The step2, removeFragments, employs `rdMolStandardize.FragmentParent()` function to keep the largest fragment.

The step3, neutralize, uses `rdMolStandardize.Uncharger().uncharge()` function to neutralize molecules by adding/removing hydrogens.

The step4, canonicalizeTautomer, relies on `Canonicalize()` function available via `rdMolStandardize.TautomerEnumerator()` to select a canonical tautomer.

--mp <yes or no> [default: no]

Use multiprocessing.

By default, input data is retrieved in a lazy manner via `mp.Pool.imap()` function employing lazy RDKit data iterable. This allows processing of arbitrary large data sets without any additional requirements memory.

All input data may be optionally loaded into memory by `mp.Pool.map()` before starting worker processes in a process pool by setting the value of 'inputDataMode' to 'InMemory' in '--mpParams' option.

A word to the wise: The default 'chunkSize' value of 1 during 'Lazy' input data mode may adversely impact the performance. The '--mpParams' section provides additional information to tune the value of 'chunkSize'.

--mpParams <Name,Value,...> [default: auto]

A comma delimited list of parameter name and value pairs to configure multiprocessing.

The supported parameter names along with their default and possible values are shown below:

```
chunkSize, auto
inputDataMode, Lazy [ Possible values: InMemory or Lazy ]
numProcesses, auto [ Default: mp.cpu_count() ]
```

These parameters are used by the following functions to configure and control the behavior of multiprocessing: `mp.Pool()`, `mp.Pool.map()`, and `mp.Pool.imap()`.

The chunkSize determines chunks of input data passed to each worker process in a process pool by `mp.Pool.map()` and `mp.Pool.imap()` functions. The default value of chunkSize is dependent on the value of 'inputDataMode'.

The `mp.Pool.map()` function, invoked during 'InMemory' input data mode, automatically converts RDKit data iterable into a list, loads all data into memory, and calculates the default chunkSize using the following method as shown in its code:

```
chunkSize, extra = divmod(len(dataIterable), len(numProcesses) * 4)
if extra: chunkSize += 1
```

For example, the default chunkSize will be 7 for a pool of 4 worker processes and 100 data items.

The `mp.Pool.imap()` function, invoked during 'Lazy' input data mode, employs 'lazy' RDKit data iterable to retrieve data as needed, without loading all the data into memory. Consequently, the size of input data is not known a priori. It's not possible to estimate an optimal value for the chunkSize. The default chunkSize is set to 1.

The default value for the chunkSize during 'Lazy' data mode may adversely impact the performance due to the overhead associated with exchanging small chunks of data. It is generally a good idea to explicitly set chunkSize to a larger value during 'Lazy' input data mode, based on the size of your input data and number of processes in the process pool.

The mp.Pool.map() function waits for all worker processes to process all the data and return the results. The mp.Pool.imap() function, however, returns the the results obtained from worker processes as soon as the results become available for specified chunks of data.

The order of data in the results returned by both mp.Pool.map() and mp.Pool.imap() functions always corresponds to the input data.

-o, --outfile <outfile>

Output file name.

--outfileParams <Name,Value,...> [default: auto]

A comma delimited list of parameter name and value pairs for writing molecules to files. The supported parameter names for different file formats, along with their default values, are shown below:

SD: compute2DCoords,auto,kekulize,yes,forceV3000,no
 SMILES: smilesKekulize,no,smilesDelimiter,space, smilesIsomeric,yes,
 smilesTitleLine,yes,smilesMolName,yes,smilesMolProps,no

Default value for compute2DCoords: yes for SMILES input file; no for all other file types.

--overwrite

Overwrite existing files.

-q, --quiet <yes or no> [default: no]

Use quiet mode. The warning and information messages will not be printed.

-s, --standardizeParams <Name,Value,...> [default: auto]

A comma delimited list of parameter name and value pairs for standardizing molecules. The supported parameter names along with their default values are shown below:

acidbaseFile,none,fragmentFile,none,normalizationsFile,none,
 tautomerTransformsFile,none,
 cleanupRemoveHydrogens,yes,cleanupDisconnectMetals,yes,
 cleanupNormalize,yes,cleanupNormalizeMaxRestarts,200,
 cleanupReionize,yes,cleanupAssignStereo,yes,
 cleanupAssignStereoCleanIt,yes,cleanupAssignStereoForce,yes
 largestFragmentChooserUseAtomCount,yes,
 largestFragmentChooserCountHeavyAtomsOnly,no,preferOrganic,no,
 doCanonical,yes,
 maxTautomers,1000,maxTransforms,1000,
 tautomerRemoveBondStereo,yes,tautomerRemoveIsotopichs,yes
 tautomerRemoveSp3Stereo,yes,tautomerReassignStereo,yes

A brief description of the standardization parameters, taken from RDKit documentation, is as follows:

acidbaseFile - File containing acid and base definitions
 fragmentFile - File containing fragment definitions
 normalizationsFile - File containing normalization transformations
 tautomerTransformsFile - File containing tautomer transformations

cleanupRemoveHydrogens - Remove hydrogens during cleanup
 cleanupDisconnectMetals - Disconnect metal atoms covalently bonded
 to non-metals during cleanup
 cleanupNormalize - Normalize functional groups and recombine
 charges during cleanup
 cleanupNormalizeMaxRestarts - Maximum number of restarts during
 normalization step of cleanup
 cleanupReionize - Ionize strongest acid groups first in partially
 ionized molecules during cleanup
 cleanupAssignStereo - Assign stereochemistry during cleanup
 cleanupAssignStereoCleanIt - Clean property _CIPCode during
 assign stereochemistry
 cleanupAssignStereoForce - Always perform stereochemistry
 calculation during assign stereochemistry

largestFragmentChooserUseAtomCount - Use atom count as main

criterion before molecular weight to determine largest fragment
 in LargestFragmentChooser
 largestFragmentChooserCountHeavyAtomsOnly - Count only heavy
 atoms to determine largest fragment in LargestFragmentChooser
 preferOrganic - Prefer organic fragments over inorganic ones when
 choosing fragments

doCanonical - Apply atom-order dependent normalizations in a
 canonical order during uncharging

maxTautomers - Maximum number of tautomers to generate
 maxTransforms - Maximum number of transforms to apply during
 tautomer enumeration
 tautomerRemoveBondStereo - Remove stereochemistry from double bonds
 involved in tautomerism
 tautomerRemoveIsotopicHs - Remove isotopic Hs from centers involved in tautomerism
 tautomerRemoveSp3Stereo - Remove stereochemistry from sp3 centers
 involved in tautomerism
 tautomerReassignStereo - AssignStereochemistry on all generated tautomers

The default value is set to none for the following file name parameters: acidbaseFile, fragmentFile, normalizationsFile, and tautomerTransformsFile. The script relies on RDKit to automatically load appropriate acid base and fragment definitions along with normalization and tautomer transformations from a set of internal catalogs.

Note: The fragmentFile doesn't appear to be used by the RDKit method
 rdMolStandardize.FragmentParent() to find largest fragment.

The contents of various standardization definitions and transformations files are described below:

acidbaseFile - File containing acid and base definitions

// Name	Acid	Base
-OS03H	OS(=O)(=O)[OH]	OS(=O)(=O)[O-]
-S03H	[!O]S(=O)(=O)[OH]	[!O]S(=O)(=O)[O-]
-OS02H	O[SD3](=O)[OH]	O[SD3](=O)[O-]
... ..		

fragmentFile - File containing fragment definitions

// Name	SMARTS
hydrogen	[H]
fluorine	[F]
chlorine	[Cl]
... ..	

normalizationsFile - File containing normalization transformations

// Name	SMIRKS
Sulfone to S(=O)(=O)	[S+2:1]([O-:2])([O-:3])>> [S+0:1](=[O-0:2])(=[O-0:3])
Pyridine oxide to n+0-	[n:1]=[O:2]>>[n+1][O-:2]
... ..	

tautomerTransformsFile - File containing tautomer transformations

// Name	SMARTS	Bonds	Charges
1,3 (thio)keto/enol f	[CX4!H0]-[C]=[O,S,Se,Te;X1]		
1,3 (thio)keto/enol r	[O,S,Se,Te;X2!H0]-[C]=[C]		
1,5 (thio)keto/enol f	[CX4,NX3;!H0]-[C]=[C][CH0]=[O,S,Se,Te;X1]		
... ..			

-w, --workingdir <dir>

Location of working directory which defaults to the current directory.

EXAMPLES

To standardize molecules in a SMILES file by executing all standardization steps and write out a SMILES file, type:

```
% RDKitStandardizeMolecules.py -i Sample.smi -o SampleOut.smi
```

To standardize molecules in a SD file by executing all standardization steps, performing standardization in multiprocessing mode on all available CPUs without loading all data into memory, and write out and write out a SD file, type:

```
% RDKitStandardizeMolecules.py --mp yes -i Sample.sdf -o SampleOut.sdf
```

To standardize molecules in a SMILES file by executing all standardization steps, performing standardization in multiprocessing mode on all available CPUs by loading all data into memory, and write out and write out a SMILES file, type:

```
% RDKitStandardizeMolecules.py --mp yes --mpParams "inputDataMode,
InMemory" -i Sample.smi -o SampleOut.smi
```

To standardize molecules in a SMILES file by executing all standardization steps, performing standardization in multiprocessing mode on specific number of CPUs and chunk size without loading all data into memory, and write out a a SMILES file, type:

```
% RDKitStandardizeMolecules.py --mp yes --mpParams "inputDataMode, Lazy,
numProcesses,4,chunkSize,8" -i Sample.smi -o SampleOut.smi
```

To count number of molecules to be standardized without generating any output file, type:

```
% RDKitStandardizeMolecules.py -m count -i Sample.sdf
```

To standardize molecules in a SD file by executing specific standardization steps along with explicit values for various parameters to control the standardization behavior, and write out a SD file, type:

```
% RDKitStandardizeMolecules.py --methodologyParams "cleanup,yes,
removeFragments,yes,neutralize,yes,canonicalizeTautomer,yes"
--standardizeParams "cleanupRemoveHydrogens,yes,
cleanupDisconnectMetals,yes,cleanupNormalize,yes,
cleanupNormalizeMaxRestarts,200,cleanupReionize,yes,
cleanupAssignStereo,yes,largestFragmentChooserUseAtomCount,yes,
doCanonical,yes,maxTautomers,1000"
-i Sample.sdf -o SampleOut.sdf
```

To standardize molecules in a CSV SMILES file, SMILES strings in column 1, name in column 2, and generate output SD file, type:

```
% RDKitStandardizeMolecules.py --infileParams
"smilesDelimiter,comma,smilesTitleLine,yes,smilesColumn,1,
smilesNameColumn,2" --outfileParams "compute2DCoords,yes"
-i SampleSMILES.csv -o SampleOut.sdf
```

AUTHOR

Manish Sud(msud@san.rr.com)

SEE ALSO

RDKitConvertFileFormat.py, RDKitEnumerateTautomers.py, RDKitRemoveDuplicateMolecules.py, RDKitRemoveInvalidMolecules.py, RDKitRemoveSalts.py, RDKitSearchFunctionalGroups.py, RDKitSearchSMARTS.py

COPYRIGHT

Copyright (C) 2026 Manish Sud. All rights reserved.

The functionality available in this script is implemented using RDKit, an open source toolkit for cheminformatics developed by Greg Landrum.

This file is part of MayaChemTools.

MayaChemTools is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.