

FinOpsBench: A Benchmark for Evaluating Agentic LLMs on Financial Analysis Tasks with Tool Use

Anonymous ACL submission

Abstract

We introduce FinOpsBench, a comprehensive benchmark for evaluating the capabilities of large language models (LLMs) in agentic financial analysis tasks that require tool use. The benchmark is released in two versions: (1) FinOpsBench-v1, a synthetic set of 5,979 natural-language financial analysis tasks that an agent must solve by issuing structured queries to a tool-callable data environment, with quality control by a panel of LLM judges, and (2) FinOpsBench-v2, a set of 1,108 multi-hop reasoning tasks grounded in real financial documents and embedded in custom tool environments. Both subsets require models to retrieve information exclusively through tool calls rather than relying on in-context information, testing genuine agentic tool use and reasoning capabilities. We evaluate a range of frontier and open-source models, finding that even the strongest model achieves only 68.9% on FinOpsBench-v1 and 69.6% on FinOpsBench-v2, while open-source baselines fall as low as 21.9% and 16.3% respectively, demonstrating significant room for improvement in agentic financial reasoning. We release the full benchmark, evaluation code, and model traces to facilitate future research.

1 Introduction

Large language models (LLMs) are increasingly deployed as autonomous agents capable of using tools to accomplish complex tasks (Schick et al., 2023; Qin et al., 2024b). In the financial domain, such agents can assist with financial analysis, compliance checking, and decision support by issuing tool calls against structured business data and synthesizing the retrieved evidence into actionable answers. However, evaluating the agentic capabilities of LLMs presents significant challenges. Existing financial QA benchmarks like FinQA (Chen et al., 2021) and TAT-QA (Zhu et al., 2021) primarily test reading comprehension and numerical




Figure 1: Accuracy on FinOpsBench grows log-linearly with the (estimated) parameter count of the agent’s base model. Closed-source sizes are taken from the IKP estimates (Li, 2026)

reasoning over provided contexts, rather than genuine tool-use and multi-step reasoning. We introduce FinOpsBench, a benchmark specifically designed to evaluate agentic LLMs on financial analysis tasks requiring tool use. We argue an agentic financial benchmark should at once provide diagnostic control over a large pool of executable tasks (so that failures can be traced to a specific planning or tool-use mistake rather than to evaluator noise) and realism on human-authored financial questions (so that accuracies remain comparable with the financial-QA literature). These two goals pull in opposite directions, so FinOpsBench is released as two complementary parts - each targeting one of these goals and both evaluated under the same agent environment:

- **FinOpsBench-v1:** 5,979 examples; each pairs a natural-language financial question with a small, freshly generated database that the agent must query through a single structured-data tool to reach the answer. Examples are quality-controlled by a panel of LLM judges.
- **FinOpsBench-v2:** This benchmark is pro-

duced by building agentic environments around questions and tables taken from FinQA, and consists of 1,108 samples. Each sample bundles a financial question, a tool environment with diverse custom Python tools, distractor tools and rows, and a gold answer. The agent must perform multi-hop reasoning across several tool calls.

Both benchmarks share the same design principles. First, answers cannot be extracted from the prompt alone, so agents must use tools to retrieve information. Second, examples require multi-step reasoning with intermediate tool calls. Third, distractor information is present to test the agent’s ability to filter relevant from irrelevant data. A related concern with benchmarks is data contamination, where test examples may have been seen during model training. Where part of our benchmark builds on a prior dataset, each item is re-instantiated inside a bespoke tool environment with a redacted system prompt and a multi-step tool-call plan the model has not seen during training, so familiarity with the underlying source items does not translate into a direct answer pathway.

Our main contributions are:

- A novel benchmark for evaluating agentic LLMs on financial tasks requiring genuine tool use.
- A rigorous benchmark construction pipeline with quality control by a panel of LLM judges
- Comprehensive evaluation of a range of frontier and open-source LLMs used as the *base models* inside the agents, revealing significant gaps in agentic financial reasoning capabilities.
- An open-source release¹ of the complete benchmark together with the evaluation framework and all model traces. We treat this release as a contribution in its own right, supporting reproducible research and direct reuse of our infrastructure for new agentic financial tasks.

As Figure 1 shows that the performance of different models on FinOpsBench grows log-linearly with the parameter count of the agent’s base model. This is an expected sanity check that the benchmark’s difficulty tracks model capability rather than a task-design artifact, and that performance gaps therefore reflect real differences in agentic competence. Parameter counts for closed-source models

are taken from the IKP calibration of Li (2026).

2 Related Work

FinOpsBench is situated at the intersection of three research areas: context-bound financial Question Answering (QA), general agentic tool-use evaluation, and domain-specific semantic parsing.

Context-Bound Financial QA. Foundational financial benchmarks like FinQA (Chen et al., 2021), ConvFinQA (Chen et al., 2022), TAT-QA (Zhu et al., 2021), and FinanceBench (Islam et al., 2023) measure numerical reasoning, tabular-textual integration, and reasoning over SEC filings within static, explicitly provided contexts. These established datasets are inherently non-agentic as they do not require dynamic interaction or external system calls; all necessary information is supplied in the prompt, testing reading comprehension rather than tool use or dynamic information retrieval. Our FinOpsBench-v2 component transitions this evaluation to a dynamic environment where information must be actively retrieved through multi-hop tool calls, isolating and testing the core planning and execution logic.

Agentic and Tool-Use Benchmarks. General agent benchmarks, such as ToolBench (Qin et al., 2024a,b), MCP-Verse (Lei et al., 2025), AgentBench (Liu et al., 2024), and SWE-bench (Jimenez et al., 2024), establish the methodological standard for evaluating LLMs’ planning abilities against a large breadth of tools and domains (web browsing, code execution, APIs at scale). While essential for assessing general tool augmentation, these benchmarks prioritize scale over domain depth, and none concentrate on financial analysis with structured-data tools. Financial analysis critically demands precision and specialized interpretation. By specializing the tool environment for finance, FinOpsBench tests the *depth* of financial logic, revealing significant gaps where general planning skills fail to confer the necessary domain competence (16–70% accuracy on grounded financial reasoning tasks). Recent real-world financial benchmarks like FinGAIA (Zeng et al., 2025), the Finance Agent Benchmark (Bigéard et al., 2025), and FinAgentBench (Choi et al., 2025) prioritize realism by using live web data (SEC EDGAR) or SEC-filing retrieval, while FinOpsBench is engineered for *diagnostic fidelity* using controlled, synthetic environments to attribute failures unequivocally to flawed planning logic, rather than external noise or

¹Code: <https://anonymous.4open.science/r/FinOpsBench>

API variability. We further compare FinOpsBench against FinAgentBench and the Finance Agent Benchmark numerically along the size–accuracy axis in Appendix A.

Tool Use over Structured Business Data A related line of work studies semantic parsing over structured data: cross-domain datasets such as Spider (Yu et al., 2018) and BIRD (Li et al., 2023) score a model on the fidelity of a single generated query string against a fixed schema. FinOpsBench is deliberately *not* a semantic-parsing benchmark: the agent is never scored on a query string. Instead, FinOpsBench-v1 evaluates the full agentic loop (tool selection, multi-turn interaction with the data tool, evidence aggregation across calls, and natural-language answer synthesis) over financially specialized environments. Two consequences follow that make the task qualitatively different from text-to-query parsing. First, success requires planning under partial observability: the schema and contents must be probed via tool calls rather than read from context. Second, financial domain semantics such as accounts-payable aging, variance attribution, and revenue recognition become first-class evaluation targets rather than incidental surface features. The structured-data tool is the means, not the end being measured.

Our approach leverages synthetic data generation and a rigorous quality control process, utilizing a panel of three LLM judges, to mitigate data contamination risks and ensure high integrity at scale, validating that observed low accuracy reflects genuine performance limitations.

Data Generation. Synthetic data generation has proven valuable for creating evaluation benchmarks at scale (Wang et al., 2023). Recent work has explored using LLMs to generate and verify synthetic datasets with quality control mechanisms (Prabhakar et al., 2026). Our approach utilizes these methods and adapts them to creating financial agentic datasets.

3 Benchmark Description

3.1 Overview

Following the rationale laid out in the introduction, FinOpsBench comprises two complementary parts (Table 1): FinOpsBench-v1 materialises the diagnostic-control side of the split (a large, fully synthetic pool with executable ground truth), while FinOpsBench-v2 materialises the realism side, anchored in human-authored questions over real fi-

Property	FinOpsBench-v1	FinOpsBench-v2
# Examples	5,979	1,108
Tool type	Single structured-data tool	Many custom Python tools
Multi-hop	≥ 1 hop	≥ 2 hops
Distractor data	Yes	Yes
Quality control	Panel	Execution-based

Table 1: Overview of the two FinOpsBench versions.

nancial documents.

3.2 FinOpsBench-v1

FinOpsBench-v1 consists of financial analysis tasks that an agent must solve by issuing structured-data queries through a single tool. Each example is backed by an isolated SQLite store generated specifically for that example; the agent is never required to produce or score a query string, and only the final answer is evaluated. Each example contains *User role* (the persona making the query, e.g., CFO, auditor, financial analyst), *Query* (a natural language question about financial data), *Backing data schema* (a plausible company-data schema generated for this example), *Backing data* (realistic financial records including distractor rows), *Expected answer* (the ground-truth answer), and *Agent trace* (a reference solution demonstrating correct tool use).

FinOpsBench-v1 spans diverse financial analysis categories including Accounts Payable (AP) analysis, Revenue recognition, Variance analysis, Data integrity and reconciliation, and Financial reporting. Representative queries spanning user roles and task categories are listed in Appendix D, and the empirical category mix of the full FinOpsBench-v1 stream is reported in Appendix G.

3.3 FinOpsBench-v2

FinOpsBench-v2 transforms FinQA samples into complete agentic environments. Each example includes *System prompt* (scenario description and available tools without table data), *Synthetic backing store* (an SQLite (Owens and Allen, 2010) table set reconstructed from the original FinQA tables), *Core tools* (functions required to derive the answer), *Distractor tools* (irrelevant tools to test filtering ability), and *Correct plan* (reference multi-hop solution). Critically, the agent receives only the scenario description and tool definitions, not the underlying data table. This ensures agents must use tools to retrieve information rather than extracting

answers from context. Representative questions, together with a worked example showing the query, available tools, and a reference tool-call sequence, are given in Appendix E and Table 5.

4 Benchmark Construction

4.1 FinOpsBench-v1 pipeline

FinOpsBench-v1 is created through a 9-stage pipeline. Figure 2 (top) gives an end-to-end overview of the FinOpsBench-v1 construction process; the individual stages are described in detail below.

Stage 1: Query Generation. We start with a few seed queries spanning financial analysis categories (in our experiment, we took 12 seed queries). These seeds are then expanded using an LLM, varying user roles and specific details. We utilize a prompt that takes one seed and generates 20 queries to increase diversity and run it multiple times to generate a large number of queries. We also use embedding-based similarity filtering (cosine threshold 0.9) to remove near-duplicates.

Stage 2: Schema Generation. For each query, an LLM generates a plausible data schema that is: (1) sufficient to answer the query, (2) realistic for a company’s records, and (3) appropriately complex.

Stage 3: Data Generation. The LLM is then tasked with generating realistic data for each query and schema, including: (1) data necessary to answer the query, and (2) distractor rows to increase difficulty. The LLM is also required to provide the correct answer to the query consistent with the generated data.

Stage 4: Execution-Based Validation. All generated schema and data definitions are validated by execution against SQLite. Errors are iteratively fixed using LLM assistance (up to 5 attempts). We found that LLMs struggle with fixing small errors in (relatively) long generated programs, so we split the program into individual statements and fix them one by one.

Stage 5: Agent Trace Generation. An agent runs on each query. It is supplied with access to the example’s backing data through the structured-data tool, with up to 6 rounds of interaction allowed. The full conversation trace is recorded.

At this point, we have a benchmark subset that contains a query, a data schema, backing data (records necessary to answer the query and distractor rows), intended answer to the query, and an agent trace demonstrating the solution to the query.

However, there may be hallucinations, unnatural data, wrong tool calls, or wrong answers in the agent trace that need to be identified and fixed.

Stage 6: Panel Judgement. A panel of three LLM judges evaluates each example’s data and agent trace on five criteria: (1) *Data naturalness*: Is the generated data realistic? (2) *Trace reasonableness*: Does the agent examine appropriate data? (3) *Trace soundness*: Is the reasoning logical? (4) *Grounding*: Is reasoning based only on tool outputs? (5) *Answer correctness*: Does the answer address the query?

An example passes only if it receives majority approval (2/3 judges) on *all* criteria. In that case, it proceeds to the next stage. Otherwise, it goes to the improvement loop (Stages 7 and 8). Note that the loop only runs once for each example; if the improved example fails the judgement again, it is rejected completely.

Stage 7: Feedback Reconciliation. The judges’ criticisms are given to an LLM which is asked to aggregate them into actionable feedback. The LLM at this stage has access to most of the example’s data, including the query, the data schema, the backing data, and the agent trace.

Stage 8: Feedback Application. The agent runs again with a prompt containing the query, the data schema, the previous agent trace, and the feedback produced in Stage 7. It still has access to the structured-data tool, and the conversation is limited to 6 rounds. The full conversation trace is recorded.

Stage 9: Second Judgement. The improved examples are then re-judged by the panel. If an example passes, it proceeds to the next stage. Otherwise, it is dropped from the benchmark.

Final Filtering. The final benchmark includes only examples that passed panel judgement. We run two filtering passes to ensure quality and complexity of the benchmark. The first pass uses an LLM to compare the final answer produced in the agent trace with the intended answer created in Stage 3. Additionally, we filter out examples where the agent did not actually invoke the structured-data tool (removing examples answerable from context alone).

4.2 FinOpsBench-v2 pipeline

The FinOpsBench-v2 pipeline transforms FinQA samples through 9 stages (Figure 2, bottom):

Stage 1: Initial Solution. An LLM creates a direct Python solution using the original table data, establishing the computational logic.




Figure 2: Construction pipelines for the two FinOpsBench versions. **Top:** FinOpsBench-v1(9 stages with a panel-judgement gate and an improvement loop). **Bottom:** FinOpsBench-v2(9 strictly linear stages, each validated by execution).

Stage 2: Backing Data Store Generation. An SQLite-backed table set is generated to model the scenario, containing the records needed to answer the question.

Stage 3: Basic Tools. Tool functions are created as abstractions over the backing store, designed to enable multi-hop reasoning.

Stage 4: Correct Plan (Basic). A reference solution is written using the basic tools.

Stage 5: Augmented Backing Store. The backing store is expanded with additional tables, split data, and distractor rows to increase difficulty.

Stage 6: Augmented Tools. Extended tools are created including core tools for the correct solution, partial information tools requiring chaining, and distractor tools providing irrelevant data.

Stage 7: Correct Plan (Augmented). A reference solution using the augmented tools demonstrates the multi-hop solution path.

Stage 8: System Prompt. A system prompt is

generated containing the scenario description and tool definitions, explicitly excluding table data and answer hints.

Stage 9: Agent Code. A runnable agent using the `smolagents` (Roucher et al., 2025) library is generated for evaluation.

Each stage is required to output a file (Python code in all stages except Stage 8 which outputs a system prompt with the task formulation). For each stage, the LLM receives in the context: (1) A long description of the whole process with all the stages described; (2) An indication of what stage is currently running; (3) All previous files' content from the previous stages, and (4) In Stage 9, an example agent code showing coding practices for achieving more stable results. After completing, each stage undergoes an execution-based validation. If the execution fails, the stage is rerun with a prompt that includes the error message and asks to fix the errors (up to 10 attempts).




Figure 3: FinOpsBench-v1 construction funnel: number of examples surviving each stage of the 9-stage pipeline plus the final filtering pass.

Stage	Number of Examples
Seed queries	12
1. Query expansion	10,000
2. Schema generation	10,000
3. Data generation	10,000
4. Execution-based validation	10,000
5. Agent trace generation	9,557
6. Panel judgement	
– passed	5,401
– to be improved	4,156
7. Feedback reconciliation	4,156
8. Feedback application	3,967
9. Panel judgement	2,832
Total passed so far	8,233
Filtering (post-pipeline)	5,979

Table 2: Number of examples in FinOpsBench-v1 after each stage.

5 Experiments

5.1 Setup

We evaluate a diverse set of LLMs as the agent’s base model. The frontier set is GPT-4.1, GPT-4.1-mini, GPT-5, GPT-5-mini, and o4-mini (Achiam et al., 2023) (OpenAI). The open-source set is Qwen3-8B and Qwen3-30B-A3B (Yang et al., 2025) (Alibaba), and Llama-3.1-8B-Instruct (Dubey et al., 2024) (Meta). Frontier models are accessed through OpenAI’s API; the three open-source models are served locally on a single NVIDIA H100 GPU. Our primary metric is *accuracy*. For FinOpsBench-v1, an LLM judge compares the agent’s final answer against the expected output and outputs a yes/no verdict; we evaluate on a randomly selected test set of 729 examples for cost reasons. For FinOpsBench-v2, the numerical answers are compared against the correct plan output with a tolerance of one least significant digit, and we evaluate on the full set.

5.2 Construction statistics

We first describe how many examples survived each pipeline stage for the two versions.

FinOpsBench-v1. We constructed FinOpsBench-v1(5,979 examples) by starting with 12 seed queries and generating 10,000 diverse queries, then proceeding with all the remaining stages of the pipeline. The default LLM used in all stages is GPT-4.1-mini with the following exceptions: Stages 4 (execution-based validation), 7 (feedback reconciliation), and 8 (feedback application) are run with o4-mini; Stage 6 (panel judgement) is run with three different models: Claude Sonnet 4 (Anthropic, 2025), o4-mini, and o3-mini, one per judge. See Table 2 for the number of examples after each stage.

Figure 3 visualises the same attrition: the pipeline holds steady through Stages 1–4 (deterministic generation against a fixed schema), then loses 4% of examples at the agent-trace stage, a further 14% at panel judgement, and 27% at the final filtering pass.

FinOpsBench-v2. We ran the data-example creation routine using the protocol described above for 1,247 examples drawn uniformly at random from the FinQA training split, resulting in 1,108 examples (the rest failed in at least one of the stages). Appendix F lists the per-example file layout.

5.3 Results

The final evaluation results for both versions of the benchmark are presented in Table 3.

Model	Acc. v1 (%)	Acc. v2 (%)
<i>Frontier models</i>		
GPT-5	68.9	69.6
GPT-5-mini	65.8	67.5
o4-mini	67.1	67.3
GPT-4.1	62.4	60.6
GPT-4.1-mini	61.5	56.9
<i>Open-source models</i>		
Qwen3-30B-A3B	50.5	53.0
Qwen3-8B	47.6	44.1
Llama-3.1-8B-Instruct	21.9	16.3

Table 3: Per-model accuracy on FinOpsBench-v1(v1) and FinOpsBench-v2(v2). Bold values mark the best score within each tier.

Findings. Having run experiments on both versions, we observe a consistent picture: overall model capability tracks benchmark accuracy, but the strongest models still leave substantial headroom. The log-linear dependence of accuracy




Figure 4: Per-model accuracy on FinOpsBench-v1 and FinOpsBench-v2. Frontier models occupy the left half, open-source the right.

on the agent’s base-model parameter count is already visible in Figure 1, and Table 3 provides the per-model numbers. On FinOpsBench-v1, even the best model (GPT-5) reaches only 68.9%, indicating substantial room for improvement; modern and larger models such as GPT-5 outperform smaller, older ones such as Llama-3.1-8B; and the frontier/open-source gap is wide, with even Qwen3-30B-A3B scoring 11 pp below the worst frontier model (GPT-4.1-mini). Figure 5 further shows that this ranking is stable across the four query categories carried by the seed set: every model’s per-category polygon is approximately concentric, so the gap is not driven by any single financial sub-domain.

On FinOpsBench-v2 we observe essentially the same ranking. GPT-5 and o4-mini lead at ~67–70%, the GPT-4.1 variants follow, and the open-source models trail. Llama-3.1-8B again severely underperforms its size-matched newer sibling Qwen3-8B, suggesting that tool-use capability is sensitive to the training paradigm and not only to parameter count. Per-model accuracies track each other across the two versions (mean absolute difference 2.6 pp); the side-by-side bar chart in Figure 4 and the $y = x$ scatter in Appendix B (Figure 9) make this agreement explicit, with the only material outliers being Qwen3-30B-A3B and Qwen3-8B, which both score noticeably lower on the FinQA-grounded version, where the multi-hop, multi-tool environment exposes more of the weaker models’ failure modes.

Native tool calling vs. ReAct. While analyzing the traces of smaller models, we found it hard to understand what they were struggling with when calling tools, because there was no record of the rea-




Figure 5: Per-category accuracy on FinOpsBench-v1 for the eight evaluated models. Axes are the five categories described in Section 3.2; each query in the 729-example test set is assigned to one of these five categories. The category mix of the full FinOpsBench-v1 stream is reported in Appendix G.

soning behind the tool and argument choices. We therefore added a second experiment using the ReAct tool-calling protocol (Yao et al., 2023), which requires the model to output its reasoning before calling a tool. This experiment was performed on FinOpsBench-v1; Table 4 presents the results.

Model	Accuracy (%)	
	Native	ReAct
<i>Non-thinking Models</i>		
GPT-4.1	62.4	<u>63.8</u>
GPT-4.1-mini	61.5	<u>63.5</u>
Llama-3.1-8B-Instruct	21.9	<u>28.3</u>
<i>Thinking Models</i>		
GPT-5	68.9	64.6
o4-mini	<u>67.1</u>	64.3
Qwen3-30B-A3B	<u>50.5</u>	46.2
Qwen3-8B	<u>47.6</u>	44.3

Table 4: Evaluation results on tool calling protocol. Underlined values are the best result for each model.

The split is clean and visible in Figure 6: every *non-thinking* model gains from switching to ReAct (a strict green delta on the right of the plot), while every *thinking* model loses (a strict red delta on the left). The gains shrink as the non-thinking model gets stronger, from +6.4 pp for Llama-3.1-8B-Instruct down to +1.4 pp for GPT-4.1, suggesting that ReAct’s explicit reasoning scaffold matters most when the model lacks an internal chain-of-thought process and matters less, or even hurts, once the model already reasons before acting.




Figure 6: Native tool calling vs. ReAct on FinOpsBench-v1. Numbers above each pair give the ReAct minus Native delta in percentage points.

6 Discussion

Benchmarking Agentic Capabilities. Our results demonstrate that FinOpsBench effectively discriminates between models’ agentic capabilities. The significant gap from ceiling performance (around 69%) suggests current models have substantial room for improvement in financial tool use.

Open-Source Gap. The large gap between frontier and open-source models (up to 50+ percentage points) highlights an important direction for open-source development. Financial agentic tasks may require specialized training on tool-use trajectories. Concretely, closing this gap likely requires trajectory-level fine-tuning or reinforcement learning over realistic tool-use sequences (including tool selection, argument formation, and intermediate-result handling) rather than additional next-token pre-training on financial text alone.

Native Tool Calling vs. ReAct. ReAct allows the model to reason before choosing a tool to call. This has a large impact on performance for models that do not reason in their default setting, highlighting the improvement that test-time scaling can bring. For models that are already thinking, ReAct decreases performance. This may reflect that modern thinking models are well-optimized for structured function calling, while ReAct’s verbose format introduces additional opportunities for error.

Quality Control. Our panel-based quality control ensures high-quality examples but introduces potential biases. The judges themselves are LLMs, which may share systematic blind spots with the evaluated models.

7 Conclusion

We introduced FinOpsBench, a benchmark for evaluating agentic LLMs on financial analysis tasks requiring tool use. The benchmark is released in two versions: FinOpsBench-v1 (5,979 synthetically generated examples) and FinOpsBench-v2 (1,108 FinQA-grounded examples). Evaluation of frontier and open-source LLMs used as the base models inside the agents reveals significant room for improvement, with best accuracies of 69%.

Our work provides a foundation for developing and evaluating financial AI agents. Future work may extend the benchmark to additional financial domains, incorporate real corporate data sources (with appropriate anonymization), and develop training approaches to improve agentic financial reasoning.

Ethics Statement

We plan to release FinOpsBench under the MIT License for research and educational use, in line with our goal of supporting external contributors and downstream reproducibility. FinOpsBench-v2 is built on top of FinQA (Chen et al., 2021), which is itself distributed under the MIT License; our use of FinQA (building derivative tool environments around its public questions and tables) is consistent with its intended use as a public research benchmark, and we redistribute only derivative artifacts (synthetic backing stores, tool environments, reference plans, and agent traces) rather than the original FinQA tables verbatim.

FinOpsBench contains no personal or otherwise identifying data. FinQA is built on aggregated public corporate-finance disclosures from S&P 500 companies and contains no individual-person information; FinOpsBench-v1 is generated end-to-end, and therefore contains no records traceable to real people or companies. No additional anonymisation step was required, and the benchmark and its accompanying artifacts are provided in English language.

During the preparation of our work, AI assistants were used for auxiliary tasks. A detailed description of this process is given in Appendix I.

Limitations

FinOpsBench is scoped accordingly. Both versions currently instrument structured-data and Python-tool environments; other modalities such as live web search, document retrieval, and multimodal

financial reports lie outside this scope. These are deliberate scope choices for an initial release rather than fundamental limitations, and the construction methodology can in principle accommodate such extensions.

References

- Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, and 1 others. 2023. GPT-4 technical report. *arXiv preprint arXiv:2303.08774*.
- Anthropic. 2024. The claude 3 model family: Opus, sonnet, haiku. Technical report, Anthropic.
- Anthropic. 2025. System card: Claude Opus 4 and Claude Sonnet 4. Technical report, Anthropic.
- Antoine Bigeard, Langston Nashold, Rayan Krishnan, and Shirley Wu. 2025. Finance Agent Benchmark: Benchmarking LLMs on real-world financial research tasks. *arXiv preprint arXiv:2508.00828*.
- Zhiyu Chen, Wenhui Chen, Charese Smiley, Sameena Shah, Iana Borova, Dylan Langdon, Reema Moussa, Matt Beane, Ting-Hao Huang, Bryan Routledge, and William Yang Wang. 2021. FinQA: A dataset of numerical reasoning over financial data. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 3697–3711. Association for Computational Linguistics.
- Zhiyu Chen, Shiyang Li, Charese Smiley, Zhiqiang Ma, Sameena Shah, and William Yang Wang. 2022. ConvFinQA: Exploring the chain of numerical reasoning in conversational finance question answering. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 6279–6292. Association for Computational Linguistics.
- Chanyeol Choi, Jihoon Kwon, Alejandro Lopez-Lira, Chaewoon Kim, Minjae Kim, Juneha Hwang, Jaeseon Ha, Hojun Choi, Suyeol Yun, Yongjin Kim, and 1 others. 2025. FinAgentBench: A benchmark dataset for agentic retrieval in financial question answering. In *Proceedings of the 6th ACM International Conference on AI in Finance (ICAIF)*, pages 632–637. Association for Computing Machinery.
- Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, and 1 others. 2024. The Llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.
- Pranab Islam, Anand Kannappan, Douwe Kiela, Rebecca Qian, Nino Scherrer, and Bertie Vidgen. 2023. FinanceBench: A new benchmark for financial question answering. *arXiv preprint arXiv:2311.14194*.
- Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik R. Narasimhan. 2024. SWE-bench: Can language models resolve real-world GitHub issues? In *Proceedings of the 12th International Conference on Learning Representations (ICLR)*.
- Fei Lei, Yibo Yang, Wenxiu Sun, and Dahua Lin. 2025. MCPVerse: An expansive, real-world benchmark for agentic tool use. *arXiv preprint arXiv:2508.16260*.
- Bojie Li. 2026. Incompressible knowledge probes: Estimating black-box LLM parameter counts via factual capacity. *arXiv preprint arXiv:2604.24827*.
- Jinyang Li, Binyuan Hui, Ge Qu, Jiaxi Yang, Binhua Li, Bowen Li, Bailin Wang, Bowen Qin, Ruiying Geng, Nan Huo, Xuanhe Zhou, Chenhao Ma, Guoliang Li, Kevin C.-C. Chang, Fei Huang, Reynold Cheng, and Yongbin Li. 2023. Can LLM already serve as a database interface? a big bench for large-scale database grounded text-to-SQLs. In *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*, volume 36.
- Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, Shudan Zhang, Xiang Deng, Aohan Zeng, Zhengxiao Du, Chenhui Zhang, Sheng Shen, Tianjun Zhang, Yu Su, Huan Sun, and 3 others. 2024. AgentBench: Evaluating LLMs as agents. In *Proceedings of the 12th International Conference on Learning Representations (ICLR)*.
- Leland McInnes, John Healy, Nathaniel Saul, and Lukas Großberger. 2018. UMAP: Uniform manifold approximation and projection. *Journal of Open Source Software*, 3(29):861.
- Mike Owens and Grant Allen. 2010. *SQLite*. Apress LP New York.
- Akshara Prabhakar, Zuxin Liu, Ming Zhu, Jianguo Zhang, Tulika Manoj Awalganekar, Shiyu Wang, Zhiwei Liu, Haolin Chen, Thai Hoang, Juan Carlos Niebles, and 1 others. 2026. Apigen-mt: Agentic pipeline for multi-turn data generation via simulated agent-human interplay. *Advances in Neural Information Processing Systems*, 38.
- Yujia Qin, Shengding Hu, Yankai Lin, Weize Chen, Ning Ding, Ganqu Cui, Zheni Zeng, Xuanhe Zhou, Yufei Huang, Chaojun Xiao, and 1 others. 2024a. Tool learning with foundation models. *ACM Computing Surveys*, 57(4):1–40.
- Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, Sihan Zhao, Runchu Tian, Ruobing Xie, Jie Zhou, Mark Gerstein, Dahai Li, Zhiyuan Liu, and Maosong Sun. 2024b. ToolLLM: Facilitating large language models to master 16000+ real-world APIs. In *Proceedings of the 12th International Conference on Learning Representations (ICLR)*.

Aymeric Roucher, A Villanova del Moral, Thomas Wolf, Leandro von Werra, and Erik Kaunismäki. 2025. smolagents: A smol library to build great agentic systems. *Hugging Face*.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. 2023. Toolformer: Language models can teach themselves to use tools. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 36.

Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A. Smith, Daniel Khashabi, and Hannaneh Hajishirzi. 2023. Self-Instruct: Aligning language models with self-generated instructions. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 13484–13508. Association for Computational Linguistics.

An Yang, Baosong Anil, and 1 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. ReAct: Synergizing reasoning and acting in language models. In *Proceedings of the 11th International Conference on Learning Representations (ICLR)*.

Tao Yu, Rui Zhang, Kai Yang, Michihiro Yasunaga, Dongxu Wang, Zifan Li, James Ma, Irene Li, Qingning Yao, Shanelle Roman, Zilin Zhang, and Dragomir Radev. 2018. Spider: A large-scale human-labeled dataset for complex and cross-domain semantic parsing and text-to-SQL task. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing (EMNLP)*. Association for Computational Linguistics.

Lingfeng Zeng, Fangqi Lou, Zixuan Wang, Jiajie Xu, Jinyi Niu, Mengping Li, Yifan Dong, Qi Qi, Wei Zhang, Ziwei Yang, Jun Han, Ruilun Feng, Ruiqi Hu, Lejie Zhang, Zhengbo Feng, Yicheng Ren, Xin Guo, Zhaowei Liu, Dongpo Cheng, and 2 others. 2025. FinGAIA: A chinese benchmark for AI agents in real-world financial domain. *arXiv preprint arXiv:2507.17186*.

Fengbin Zhu, Wenqiang Lei, Youcheng Huang, Chao Wang, Shuo Zhang, Jiancheng Lv, Fuli Feng, and Tat-Seng Chua. 2021. TAT-QA: A question answering benchmark on a hybrid of tabular and textual content in finance. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (ACL-IJCNLP)*, pages 3277–3287. Association for Computational Linguistics.

A Cross-Benchmark Comparison of Size–Accuracy Trends

Beyond the within-benchmark sanity checks shown in Figure 1, where accuracy on FinOpsBench grows

log-linearly with the agent’s base-model size, we cross-check the size–accuracy relationship on two other recent financial-agent benchmarks. Parameter counts for closed-source models throughout this appendix come from the IKP calibration of Li (2026); we use the direct estimates from that paper’s main table where available and invert the published log-linear calibration on the extended-table IKP scores otherwise.

FinAgentBench (Choi et al., 2025). On the document- and chunk-ranking tasks of FinAgentBench (Figure 7), the trend is the opposite of the one we observe on FinOpsBench: across the three evaluated proprietary models (Claude-Sonnet-4 at $\approx 237\text{B}$, Claude-Opus-4 at $\approx 1.4\text{T}$, and GPT-o3 at $\approx 3\text{T}$), the *smallest* model wins or ties on every metric (nDCG@5, MAP@5, MRR@5) in both ranking tables. A monotonically negative slope on accuracy versus parameter count is a strong negative signal for benchmark validity. It suggests either that the task probes a narrow stylistic regime that the larger models are over-trained out of, or that smaller models in the same family have been exposed to closely related retrieval data during training. In short, performance on this benchmark appears to be governed more by model-family biases or potential data leakage than by raw model capability.

Finance Agent Benchmark (Bigeard et al., 2025). On the 22-model Finance Agent Benchmark leaderboard (Figure 8), accuracy does increase with parameter count, fitting a roughly +15.5 pp-per-decade log-linear trend. However, the residual variance around this trend is large enough that the fit is not, on its own, a reliable validity signal. First, at comparable sizes models differ by 20–40 pp; for example, Claude 3.7 Sonnet ($\approx 676\text{B}$) reaches 44% while GPT-4o ($\approx 720\text{B}$) reaches only 20%. Second, several large models sit far below the trend line: o1 at $\approx 3.5\text{T}$ scores only 21.4%, and LLaMA 4 Maverick at $\approx 400\text{B}$ scores only 3.1%, which the source paper attributes to tool-interface misuse. Third, and most strikingly, the same model run in two different reasoning modes can differ by 13 pp at fixed parameter count (Grok 3 Mini at 30.9% high-reasoning vs. 17.6% low-reasoning). The positive slope therefore conflates parametric capacity with reasoning paradigm and tool-use training; it does not isolate size as the dominant driver, in contrast to the cleaner relationship observed on FinOpsBench.




Figure 7: Size-accuracy on FinAgentBench (Choi et al., 2025), Tables 1 and 2. The smallest model wins or ties on every metric, an inverse trend that is inconsistent with what we observe on FinOpsBench.




Figure 8: Size-accuracy on the Finance Agent Benchmark (Bigeard et al., 2025), Table 2. The positive log-linear slope (≈ 15.5 pp/decade) is consistent with the FinOpsBench picture, but the wide intra-size scatter (20–40 pp) and the same-model reasoning-mode variation indicate that size is not the dominant driver.

B Per-model accuracies across the two FinOpsBench versions

This appendix complements the side-by-side bar chart in Figure 4 with a per-model agreement view: Figure 9 plots the same data as a scatter against a $y = x$ reference line, separating models that score equally on the two versions from those that score lower on FinOpsBench-v2.

C Benchmark Statistics

This appendix collects descriptive statistics for both benchmark versions, organised by version below. Together the plots give a per-axis (text, schema, agent activity, tool surface) snapshot of how the two versions compare at the example level.

C.1 FinOpsBench-v1 Statistics

The figures below summarise FinOpsBench-v1 along three axes. Figures 10 and 11 cover the text side of the corpus (query length and the semantic spread of the queries in UMAP (McInnes




Figure 9: Per-model agreement between FinOpsBench-v1 and FinOpsBench-v2 accuracies. Models on the $y = x$ line score identically on both benchmarks; models below the line are weaker on FinOpsBench-v2.

et al., 2018) space). Figures 12 and 13 describe the size of the per-example backing stores in terms of table count and total row count. Figures 14 and 15 report the interaction depth of the reference agent traces (assistant turns and tool invocations per example), indicating how much agent activity each task induces.




Figure 10: FinOpsBench-v1: Query length distribution.

The figures below summarise FinOpsBench-v2. Figures 16–18 cover the answer-length distribution, the system-prompt-length distribution, and the per-example tool count. Figures 19 and 20 project the system prompts and the tool-name vocabularies into UMAP space to visualise topical and lexical coverage.




Figure 11: FinOpsBench-v1: UMAP of query embeddings.




Figure 13: FinOpsBench-v1: Number of total data rows per example.




Figure 12: FinOpsBench-v1: Number of data tables per example.




Figure 14: FinOpsBench-v1: Number of assistant turns per example.

D Example Queries from FinOpsBench-v1

The following queries are drawn at random from the filtered FinOpsBench-v1 test set. Each query is paired with the persona the LLM was instructed to assume when it generated the question; together they illustrate the breadth of user roles and the diversity of analysis categories covered by FinOpsBench-v1.

- *Internal Auditor*: Can you provide a list of transactions that were processed without obtaining necessary managerial approvals in the last quarter?
- *Tax Advisor*: Identify any vendor invoices that may impact VAT input tax claims for the current tax period.
- *Chief Financial Officer*: How do we ensure the reported accounts payable aging genuinely

reflects outstanding vendor obligations without distortion?

- *Financial Controller*: What is the total outstanding balance on all overdue invoices by supplier category?
- *Procurement Officer*: Which suppliers have outstanding invoices that have not been approved for payment yet?
- *Finance Director*: What percentage of supplier invoices in the last financial year were paid late, grouped by supplier?
- *Risk Manager*: List suppliers with overdue invoices over 90 days that have credit limit warnings.
- *Internal Controls Manager*: Detect any payments made with override flags but missing authorization memos.




Figure 15: FinOpsBench-v1: Number of tool calls per example.




Figure 16: FinOpsBench-v2: Answer length distribution.

Across the full 5,979-example set we observe more than 60 distinct user roles (e.g. CFO, internal/external auditor, controller, procurement officer, treasury manager, tax advisor, compliance officer, risk manager), and queries span the accounts-payable, reconciliation, variance-analysis, revenue-recognition, and financial-reporting categories described in Section 3.2.

E Example Questions from FinOpsBench-v2

The following questions are drawn at random from the filtered FinOpsBench-v2set. Each is a multi-hop numerical-reasoning question taken from a FinQA item; the agent must reach the answer by calling the example’s bespoke Python tools rather than by reading the original FinQA table directly.

- What is the percent change in receivables from or (payables to) the Money Pool from 2001 to 2002?
- In 2018, what was the ratio of the qualified defined benefit pension plans’ estimated pay-




Figure 17: FinOpsBench-v2: System prompt length distribution.




Figure 18: FinOpsBench-v2: Number of tools per example.

ments for the period starting after 2024 compared with the amount for 2019?

- What percentage were North American consumer packaging net sales of consumer packaging sales in 2014?
- As of December 31, 2016, what was the percent of the total future minimum lease commitments for operating leases that was due in 2017?
- What was the change in percentage of the company’s consolidated net sales from 2006 to 2008?
- For the year ended December 31, 2007, what was the ratio of the shares granted to the shares vested?
- If you held 1,000 shares on May 30, 2014, how much would you receive in dividends?
- What is the total, in millions, of current assets acquired?

Across the full 1,108-example set, every question is taken from FinQA and the surrounding tool environment is generated automatically (see Section 3.3). The questions span ratio computations, year-over-year changes, percentage shares of totals, and aggregate sums, mirroring the financial-reasoning surface of the original FinQA dataset and




Figure 19: FinOpsBench-v2: UMAP of system prompt embeddings.




Figure 20: FinOpsBench-v2: UMAP of tool name embeddings.

reinstantiating it as an agentic task.

Table 5 shows a fully worked example: the question text, the bespoke Python tools the agent has access to, and the reference tool-call sequence that solves the task.

F Per-example file layout for FinOpsBench-v2

Each example in FinOpsBench-v2 is shipped as a small directory of source files, listed below.

`initial_solution.txt`

Correct answer to the question.

`synthetic_db_generator_augmented.py`

Python code that creates the SQLite database.

`tools_augmented.py`

Tools required for the multi-step processing, plus distractor tools.

`tool_proxy.py`

Same tools, adapted for use with small agents.

Query (part of system prompt)

What is the percent change in receivables from or (payables to) the Money Pool from 2001 to 2002?

Available tools

```
list_available_years()
get_quarterly_money_pool_amount(year, q)
get_total_money_pool_amount_for_year(year)
compute_percent_change(old, new)
get_cash_flow_transactions(start, end, limit)
sum_cash_flow_for_year(year)
```

Correct tool-call sequence

```
def annual(y):
    return sum(
        get_quarterly_money_pool_amount(y, q)
        for q in range(1, 5))
a01 = annual(2001)
a02 = annual(2002)
pct = compute_percent_change(a01, a02)
answer = f"{round(pct)}%"
```

Table 5: A worked FinOpsBench-v2 example (excerpt): question, available tools, and reference tool-call sequence.

`correct_plan_augmented.py`

Intended sequence of tool calls that solves the task.

`agent_system_prompt.txt`

LLM prompt with context, tool descriptions, and the question.

`agent.py`

Agent code that runs a specified LLM with the system prompt and tools.

In addition, each example directory carries auxiliary intermediate files kept from the build process for reproducibility.

G Category distribution of FinOpsBench-v1

Table 6 reports the share of FinOpsBench-v1 examples assigned to each of the five categories from Section 3.2. Categorisation is done automatically by nearest-anchor TF-IDF similarity over a short description sentence per category, applied to the full FinOpsBench-v1 stream. The mix is dominated by accounts-payable queries (over half of the corpus), reflecting the seed-query composition; the remaining four categories are balanced between 7 and 15%.

H Prompts and Examples

Figure 22 shows the prompt template used for the panel LLM judge in FinOpsBench-v1.

Figure 21 shows an annotated example from FinOpsBench-v1 illustrating the schema and data format.

Category	% of FinOpsBench-v1
Accounts Payable (AP) analysis	56.5
Variance analysis	14.8
Data integrity & reconciliation	13.5
Revenue recognition	8.2
Financial reporting	7.1

Table 6: Category share of the full FinOpsBench-v1stream (percentages, computed by nearest-anchor TF-IDF assignment). Rounded to one decimal; totals to 100.1% due to rounding.

I Use of AI Assistants

In the spirit of transparent reporting of AI-assisted authoring, we summarise how AI tools were used in the preparation of this paper. All core benchmark code, prompts, and configuration were written manually by the authors and reviewed end-to-end; the main body of the paper was likewise written manually. We used Claude ([Anthropic, 2024](#)) during the final preparation pass for two narrowly scoped tasks: (i) editorial revisions of phrasing and tightening of existing prose, and (ii) auxiliary code for collecting statistics about the benchmark and rendering some of the analysis figures. Every artifact produced by Claude was iteratively reviewed and accepted by the authors; no Claude output was incorporated without manual inspection.

Query: Could duplicated invoice payments be causing discrepancies in our aged payables report?

Schema:

```
CREATE TABLE Suppliers (
    supplier_id INTEGER PRIMARY KEY,
    supplier_name TEXT NOT NULL
);
CREATE TABLE Invoices (
    invoice_id INTEGER PRIMARY KEY,
    supplier_id INTEGER NOT NULL,
    invoice_date DATE NOT NULL,
    due_date DATE NOT NULL,
    invoice_amount NUMERIC NOT NULL,
    FOREIGN KEY (supplier_id)
    REFERENCES Suppliers(supplier_id)
);
CREATE TABLE Payments (
    payment_id INTEGER PRIMARY KEY,
    invoice_id INTEGER NOT NULL,
    payment_date DATE NOT NULL,
    payment_amount NUMERIC NOT NULL,
    FOREIGN KEY (invoice_id)
    REFERENCES Invoices(invoice_id)
);
```

Data:

```
INSERT INTO Payments VALUES
(5001, 1002, '2025-07-05', 500.00),
(5002, 1002, '2025-07-10', 500.00),
(5003, 1002, '2025-07-12', 500.00);
```

Figure 21: FinOpsBench-v1: Annotated example item showing query, schema, and data (excerpt).

```
# Task
You are a senior QA engineer working
on AI agents for finance. You have to
judge the test case provided and check
the following rules:

- The test case's data should be
  natural: it should be similar to what
  data could a real company have, and
  how it would be stored in a database.
- The agent's trace should be
  reasonable: the agent should look at
  the data needed to answer the query.
- The agent's trace should be sound:
  the reasoning steps should be logical,
  should follow from the previous steps
  and lead to the final answer.
- The agent's reasoning and final answer
  should be grounded: the only data the
  agent has access to is what was
  returned from its tool calls. The
  reasoning should not be based on any
  other data, including the data in the
  database that was not queried with
  the tools.
- The agent's final answer should
  answer the user's query.
```

In case one of these requirements are not met, you should provide a concise actionable feedback so the author can improve the test case.

```
# Test case:

## Query
{{ item.query }}

## SQL schema
{{ item.schema_sql }}

## Data
{{ item.data_sql }}

## Agent trace
{{ item.agent_dialog | tojson(2) }}

# Output format
Reply with JSON object like this:
{
  "data_is_natural": 1 | 0,
  "trace_is_reasonable": 1 | 0,
  "trace_is_sound": 1 | 0,
  "reasoning_is_grounding": 1 | 0,
  "answer_is_sound": 1 | 0,
  "feedback": "..."
}
```

Figure 22: FinOpsBench-v1: Prompt template for a panel member judge.