

[Documentos](#)[API de la nube de WhatsApp](#)[Webhooks](#)[Anulaciones de Webhooks](#)

En esta página

Se actualizó este documento.

La traducción en español no está disponible todavía.

Actualización del documento en inglés: 29 de oct.

Actualización del documento en español: 16 de ene.

[Volver al documento en español](#)

# Webhook Overrides

*Cloud API only.*

[Messages](#) webhooks are sent to the callback URL set on your app, but you can override this for your own app by designating an alternate callback URL for the WhatsApp Business Account (WABA) or business phone number.

When a messages webhook is triggered, we will first check if your app has designated an alternate callback URL for the business phone number associated with the message. If set, we will send the webhook to your alternate callback URL. If the phone number has no alternate, we will check if the WABA associated with the number has an alternate callback URL, and if set, send it there. If the WABA also has no alternate, we will then fallback to your app's callback URL.

## Requirements

Before setting an alternate callback URL, make sure your app is [subscribed to webhooks for the WABA](#) and verify that your alternate callback endpoint can receive and process messages webhooks correctly.

## Set WABA Alternate Callback

Use the [POST /<WABA\\_ID>/subscribed\\_apps](#) endpoint to set an alternate callback URL on a WABA.

Request Syntax

```
POST /<WABA_ID>/subscribed_apps
```

Post Body

```
{
  "override_callback_uri":"<WABA_ALT_CALLBACK_URL>",
  "verify_token":"<WABA_ALT_CALLBACK_URL_TOKEN>"
}
```

Body Parameters

Placeholder	Description	Example Value
<WABA_ALT_CALLBACK_URL>	<p><b>Required.</b></p> <p>Alternate callback URL where messages webhooks should be sent.</p> <p>Maximum 200 characters.</p>	<p><a href="https://my-waba-alternate-callback.com/webhook">https://my-waba-alternate-callback.com/webhook</a></p>
<WABA_ALT_CALLBACK_URL_TOKEN>	<p><b>Required.</b></p> <p>Alternate callback URL verification token.</p> <p>No maximum.</p>	<p><a href="#">myvoiceismypassport?</a></p>

Response

Upon success:

```
{
  "success": true
}
```

## Example Request

```
curl -X POST \
'https://graph.facebook.com/v24.0/102290129340398/subscribed_apps' \
-H 'Authorization: Bearer EAAJi...' \
-H 'Content-Type: application/json' \
-d '{
  "override_callback_uri":"https://my-waba-alternate-callback.com/webhook",
  "verify_token":"myvoiceismypassport?"
}'
```

## Example Response

```
{
  "success": true
}
```

## Get WABA Alternate Callback

Use the **GET /<WABA\_ID>/subscribed\_apps** endpoint to get a list of all apps subscribed to webhooks on the WABA. The response should include an **override\_callback\_uri** property and value.

## Example Response

```
{
  "data" : [
    {
      "whatsapp_business_api_data" : {
        "id" : "670843887433847",
        "link" : "https://www.facebook.com/games/?app_id=67084...",
        "name" : "Lucky Shrub"
      },
      "override_callback_uri" : "https://my-waba-alternate-callback.com/webhook"
    }
  ]
}
```

```
}  
]  
}
```

## Delete WABA Alternate Callback

Use the **POST /<WABA\_ID>/subscribed\_apps** endpoint to subscribe your app to webhooks on the WABA as you normally would (i.e. without any post body parameters). This will remove the alternate endpoint's callback URL from the WABA, and messages webhooks for the WABA will once again be sent to the callback URL set in the App Dashboard.

## Set Phone Number Alternate Callback

Use the **POST /<BUSINESS\_PHONE\_NUMBER\_ID>** endpoint to set an alternate callback URL on the business phone number.

### Request Syntax

```
POST /<BUSINESS_PHONE_NUMBER_ID>
```

### Post Body

```
{  
  "webhook_configuration": {  
    "override_callback_uri": "<PHONE_ALT_CALLBACK_URL>",  
    "verify_token": "<PHONE_ALT_CALLBACK_URL_TOKEN>"  
  }  
}
```

### Body Parameters

Placeholder	Description	Example Value
<PHONE_ALT_CALLBACK_URL>	Required.	<a href="https://my-phone-alternate-">https://my-phone-alternate-</a>

Placeholder	Description	Example Value
<PHONE_ALT_CALLBACK_URL_TOKEN>	Alternate callback URL where messages webhooks should be sent.	callback.com/webhook
	Maximum 200 characters.	
	<b>Required.</b>	myvoiceismypassport?
	Alternate callback URL verification token.	
	No maximum.	

## Response

Upon success:

```
{
  "success": true
}
```

## Example Request

```
curl 'https://graph.facebook.com/v24.0/106540352242922' \
-H 'Content-Type: application/json' \
-H 'Authorization: Bearer EAAJB...' \
-d '{
  "webhook_configuration": {
    "override_callback_uri": "https://my-phone-alternate-callback.com/webhook",
    "verify_token": "myvoiceismypassport?"
  }
}'
```

## Example Response

```
{  
  "success": true  
}
```

## Get Phone Number Alternate Callback

Use the **GET /<BUSINESS\_PHONE\_NUMBER\_ID>** endpoint and request the **webhook\_configuration** field to verify that the business phone number has an alternate callback URL.

### Request Syntax

```
GET /<BUSINESS_PHONE_NUMBER_ID>  
?fields=webhook_configuration
```

### Response

Upon success:

```
{  
  "webhook_configuration": {  
    "phone_number": "<PHONE_ALT_CALLBACK_URL>",  
    "whatsapp_business_account": "<WABA_ALT_CALLBACK_URL>",  
    "application": "<APP_CALLBACK_URL>"  
  },  
  "id": "106540352242922"  
}
```

Note that **whatsapp\_business\_account** is only included if the WABA associated with the business phone number also has an alternate callback URL set.

### Example Request

```
curl 'https://graph.facebook.com/v17.0/106540352242922?fields=webhook_configuration'  
-H 'Authorization: Bearer EAAJB...'
```

## Example Response

```
{
  "webhook_configuration": {
    "phone_number": "https://my-phone-alternate-callback.com/webhook",
    "whatsapp_business_account": "https://my-waba-alternate-callback.com/webhook",
    "application": "https://my-production-callback.com/webhook"
  },
  "id": "106540352242922"
}
```

## Delete Phone Number Alternate Callback

To delete a business phone number's alternate callback URL, use the **POST** **/<BUSINESS\_PHONE\_NUMBER\_ID>** endpoint with the **override\_callback\_uri** property set to an empty string:

```
{
  "webhook_configuration": {
    "override_callback_uri": "",
  }
}
```

### API de la nube de WhatsApp

#### Información general

#### Empezar

#### Mensajes

#### Plantillas

#### Webhooks

##### Test webhook app

##### Ejemplos de cargas útiles

##### Anulaciones de Webhooks

#### Calling

#### Grupos

#### Bloqueo de usuarios

**Números de teléfono**

**Vender productos y servicios**

**Payments API - India**

**Payments API - Brazil**

**Referencia de la API**

**Webhooks reference**

**Asistencia**