Namespace BOOSEapp

Classes

AppCanvas

Custom canvas implementation used by the BOOSE interpreter. Responsible for drawing shapes and managing the drawing cursor.

AppCommandFactory

Custom command factory used to create BOOSE commands. It extends the default command factory and returns application-specific command implementations.

Form1

Main user interface for the BOOSE interpreter. Allows the user to input BOOSE programs, execute them, and display graphical output on the canvas.

Class AppCanvas

Namespace: BOOSEapp

Assembly: BOOSEapp.dll

Custom canvas implementation used by the BOOSE interpreter. Responsible for drawing shapes and managing the drawing cursor.

```
public class AppCanvas : ICanvas
```

Inheritance

object ← AppCanvas

Implements

ICanvas

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

AppCanvas(int, int)

Initializes a new drawing canvas with the specified size.

```
public AppCanvas(int xsize, int ysize)
```

Parameters

`xsize` int

Width of the canvas.

`ysize` int

Height of the canvas.

Properties

PenColour

Gets or sets the current pen colour.

```
public object PenColour { get; set; }
```

Property Value

object

Xpos

Gets or sets the current X position of the drawing cursor.

```
public int Xpos { get; set; }
```

Property Value

int

Ypos

Gets or sets the current Y position of the drawing cursor.

```
public int Ypos { get; set; }
```

Property Value

int

Methods

Circle(int, bool)

Draws a circle from the current cursor position.

```
public void Circle(int radius, bool filled)
```

Parameters

`radius` int

Radius of the circle.

`filled` bool

Determines whether the circle is filled.

Clear()

Clears the canvas to white.

```
public void Clear()
```

DrawTo(int, int)

Draws a line from the current cursor position to the given coordinates.

```
public void DrawTo(int x, int y)
```

Parameters

`x` int

Target X coordinate.

`y` int

Target Y coordinate.

MoveTo(int, int)

Moves the cursor to a new position without drawing.

```
public void MoveTo(int x, int y)
```

Parameters

`x` int

New X coordinate.

`y` int

New Y coordinate.

Rect(int, int, bool)

Draws a rectangle from the current cursor position.

```
public void Rect(int width, int height, bool filled)
```

Parameters

`width` int

Width of the rectangle.

`height` int

Height of the rectangle.

`filled` bool

Determines whether the rectangle is filled.

Reset()

Resets the cursor to default position.

```
public void Reset()
```

Set(int, int)

Resizes the canvas.

```
public void Set(int width, int height)
```

Parameters

`width` int

New width.

`height` int

New height.

SetColour(int, int, int)

Sets the drawing colour using RGB values.

```
public void SetColour(int red, int green, int blue)
```

Parameters

`red` int

Red component.

`green` int

Green component.

`blue` int

Blue component.

Tri(int, int)

Draws a triangle .

```
public void Tri(int width, int height)
```

Parameters

`width` int

`height` int

WriteText(string)

Writes text to the canvas.

```
public void WriteText(string text)
```

Parameters

`text` string

getBitmap()

Returns the bitmap representing the canvas.

```
public object getBitmap()
```

Returns

object

Bitmap object.

Class AppCommandFactory

Namespace: BOOSEapp

Assembly: BOOSEapp.dll

Custom command factory used to create BOOSE commands. It extends the default command factory and returns application-specific command implementations.

```
public class AppCommandFactory : CommandFactory, ICommandFactory
```

Inheritance

object ← CommandFactory ← AppCommandFactory

Implements

ICommandFactory

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

AppCommandFactory(ICanvas)

Initializes a new instance of the AppCommandFactory class.

```
public AppCommandFactory(ICanvas canvas)
```

Parameters

`canvas` ICanvas

Canvas used by commands created by the factory.

Methods

MakeCommand(string)

Creates a command object based on the command name.

```
public override ICommand MakeCommand(string commandType)
```

Parameters

`commandType` string

The name of the BOOSE command.

Returns

ICommand

An BOOSE.ICommand implementation for the requested command.

Class Form1

Namespace: BOOSEapp

Assembly: BOOSEapp.dll

Main user interface for the BOOSE interpreter. Allows the user to input BOOSE programs, execute them, and display graphical output on the canvas.

```
public class Form1 : Form, IDropTarget, ISynchronizeInvoke, IWin32Window,
IBindableComponent, IComponent, IDisposable, IContainerControl
```

Inheritance

object ← MarshalByRefObject ← Component ← Control ← ScrollableControl ← ContainerControl ← Form ← Form1

Implements

IDropTarget, ISynchronizeInvoke, IWin32Window, IBindableComponent, IComponent, IDisposable, IContainerControl

Inherited Members

Form.SetVisibleCore(bool) , Form.OnFormCornerPreferenceChanged(EventArgs) , Form.OnFormBorderColorChanged(EventArgs) , Form.OnFormCaptionBackColorChanged(EventArgs) , Form.OnFormCaptionTextColorChanged(EventArgs) , Form.Activate() , Form.ActivateMdiChild(Form) , Form.AddOwnedForm(Form) , Form.AdjustFormScrollbars(bool) , Form.Close() , Form.CreateAccessibilityInstance() , Form.CreateControlsInstance() , Form.CreateHandle() , Form.DefWndProc(ref Message) , Form.ProcessMnemonic(char) , Form.CenterToParent() , Form.CenterToScreen() , Form.LayoutMdi(MdiLayout) , Form.OnActivated(EventArgs) , Form.OnBackgroundImageChanged(EventArgs) , Form.OnBackgroundImageLayoutChanged(EventArgs) , Form.OnClosing(CancelEventArgs) , Form.OnClosed(EventArgs) , Form.OnFormClosing(FormClosingEventArgs) , Form.OnFormClosed(FormClosedEventArgs) , Form.OnCreateControl() , Form.OnDeactivate(EventArgs) , Form.OnEnabledChanged(EventArgs) , Form.OnEnter(EventArgs) , Form.OnFontChanged(EventArgs) , Form.OnGotFocus(EventArgs) , Form.OnHandleCreated(EventArgs) , Form.OnHandleDestroyed(EventArgs) , Form.OnHelpButtonClicked(CancelEventArgs) , Form.OnLayout(LayoutEventArgs) , Form.OnLoad(EventArgs) , Form.OnMaximizedBoundsChanged(EventArgs) , Form.OnMaximumSizeChanged(EventArgs) , Form.OnMinimumSizeChanged(EventArgs) , Form.OnInputLanguageChanged(InputLanguageChangedEventArgs) , Form.OnInputLanguageChanging(InputLanguageChangingEventArgs) ,

Form.OnVisibleChanged(EventArgs) , Form.OnMdiChildActivate(EventArgs) ,
Form.OnMenuStart(EventArgs) , Form.OnMenuComplete(EventArgs) ,
Form.OnPaint(PaintEventArgs) , Form.OnResize(EventArgs) ,
Form.OnDpiChanged(DpiChangedEventArgs) , Form.OnGetDpiScaledSize(int, int, ref Size) ,
Form.OnRightToLeftLayoutChanged(EventArgs) , Form.OnShown(EventArgs) ,
Form.OnTextChanged(EventArgs) , Form.ProcessCmdKey(ref Message, Keys) ,
Form.ProcessDialogKey(Keys) , Form.ProcessDialogChar(char) ,
Form.ProcessKeyPreview(ref Message) , Form.ProcessTabKey(bool) ,
Form.RemoveOwnedForm(Form) , Form.Select(bool, bool) ,
Form.ScaleMinMaxSize(float, float, bool) ,
Form.GetScaledBounds(Rectangle, SizeF, BoundsSpecified) ,
Form.ScaleControl(SizeF, BoundsSpecified) , Form.SetBoundsCore(int, int, int, int, BoundsSpecified) ,
Form.SetClientSizeCore(int, int) , Form.SetDesktopBounds(int, int, int, int) ,
Form.SetDesktopLocation(int, int) , Form.Show(IWin32Window) ,
Form.ShowAsync(IWin32Window) , Form.ShowDialog() , Form.ShowDialog(IWin32Window) ,
Form.ShowDialogAsync() , Form.ShowDialogAsync(IWin32Window) , Form.ToString() ,
Form.UpdateDefaultButton() , Form.OnResizeBegin(EventArgs) , Form.OnResizeEnd(EventArgs) ,
Form.OnStyleChanged(EventArgs) , Form.ValidateChildren() ,
Form.ValidateChildren(ValidationConstraints) , Form.WndProc(ref Message) , Form.AcceptButton ,
Form.ActiveForm , Form.ActiveMdiChild , Form.AllowTransparency , Form.AutoScroll ,
Form.AutoSize , Form.AutoSizeMode , Form.AutoValidate , Form.BackColor ,
Form.FormBorderStyle , Form.CancelButton , Form.ClientSize , Form.ControlBox ,
Form.CreateParams , Form.DefaultImeMode , Form.DefaultSize , Form.DesktopBounds ,
Form.DesktopLocation , Form.DialogResult , Form.HelpButton , Form.Icon , Form.IsMdiChild ,
Form.IsMdiContainer , Form.IsRestrictedWindow , Form.KeyPreview , Form.Location ,
Form.MaximizedBounds , Form.MaximumSize , Form.MainMenuStrip , Form.MinimumSize ,
Form.MaximizeBox , Form.MdiChildren , Form.MdiChildrenMinimizedAnchorBottom ,
Form.MdiParent , Form.MinimizeBox , Form.Modal , Form.Opacity , Form.OwnedForms ,
Form.Owner , Form.RestoreBounds , Form.RightToLeftLayout , Form.ShowInTaskbar ,
Form.ShowIcon , Form.ShowWithoutActivation , Form.Size , Form.SizeGripStyle ,
Form.StartPosition , Form.Text , Form.TopLevel , Form.TopMost , Form.TransparencyKey ,
Form.FormCornerPreference , Form.FormBorderColor , Form.FormCaptionBackColor ,
Form.FormCaptionTextColor , Form.WindowState , Form.AutoSizeChanged ,
Form.AutoValidateChanged , Form.HelpButtonClicked , Form.MaximizedBoundsChanged ,
Form.MaximumSizeChanged , Form.MinimumSizeChanged , Form.Activated , Form.Deactivate ,
Form.FormClosing , Form.FormBorderColorChanged , Form.FormCaptionBackColorChanged ,
Form.FormCaptionTextColorChanged , Form.FormCornerPreferenceChanged , Form.FormClosed ,
Form.Load , Form.MdiChildActivate , Form.MenuComplete , Form.MenuStart ,
Form.InputLanguageChanged , Form.InputLanguageChanging , Form.RightToLeftLayoutChanged ,
Form.Shown , Form.DpiChanged , Form.ResizeBegin , Form.ResizeEnd ,

ContainerControl.OnAutoValidateChanged(EventArgs) , ContainerControl.OnMove(EventArgs) ,
ContainerControl.OnParentChanged(EventArgs) , ContainerControl.PerformAutoScale() ,
ContainerControl.RescaleConstantsForDpi(int, int) , ContainerControl.Validate() ,
ContainerControl.Validate(bool) , ContainerControl.AutoScaleDimensions ,
ContainerControl.AutoScaleFactor , ContainerControl.AutoScaleMode ,
ContainerControl.BindingContext , ContainerControl.CanEnableIme ,
ContainerControl.ActiveControl , ContainerControl.CurrentAutoScaleDimensions ,
ContainerControl.ParentForm , ScrollableControl.ScrollStateAutoScrolling ,
ScrollableControl.ScrollStateHScrollVisible , ScrollableControl.ScrollStateVScrollVisible ,
ScrollableControl.ScrollStateUserHasScrolled , ScrollableControl.ScrollStateFullDrag ,
ScrollableControl.GetScrollState(int) , ScrollableControl.OnMouseWheel(MouseEventArgs) ,
ScrollableControl.OnRightToLeftChanged(EventArgs) ,
ScrollableControl.OnPaintBackground(PaintEventArgs) ,
ScrollableControl.OnPaddingChanged(EventArgs) , ScrollableControl.SetDisplayRectLocation(int, int) ,
ScrollableControl.ScrollControlIntoView(Control) , ScrollableControl.ScrollToControl(Control) ,
ScrollableControl.OnScroll(ScrollEventArgs) , ScrollableControl.SetAutoScrollMargin(int, int) ,
ScrollableControl.SetScrollState(int, bool) , ScrollableControl.AutoScrollMargin ,
ScrollableControl.AutoScrollPosition , ScrollableControl.AutoScrollMinSize ,
ScrollableControl.DisplayRectangle , ScrollableControl.HScroll , ScrollableControl.HorizontalScroll ,
ScrollableControl.VScroll , ScrollableControl.VerticalScroll , ScrollableControl.Scroll ,
Control.GetAccessibilityObjectById(int) , Control.SetAutoSizeMode(AutoSizeMode) ,
Control.GetAutoSizeMode() , Control.GetPreferredSize(Size) ,
Control.AccessibilityNotifyClients(AccessibleEvents, int) ,
Control.AccessibilityNotifyClients(AccessibleEvents, int, int) , Control.BeginInvoke(Delegate) ,
Control.BeginInvoke(Action) , Control.BeginInvoke(Delegate, params object[]) ,
Control.BringToFront() , Control.Contains(Control) , Control.CreateGraphics() ,
Control.CreateControl() , Control.DestroyHandle() , Control.DoDragDrop(object, DragDropEffects) ,
Control.DoDragDrop(object, DragDropEffects, Bitmap, Point, bool) ,
Control.DrawToBitmap(Bitmap, Rectangle) , Control.EndInvoke(IAsyncResult) , Control.FindForm() ,
Control.GetTopLevel() , Control.RaiseKeyEvent(object, KeyEventArgs) ,
Control.RaiseMouseEvent(object, MouseEventArgs) , Control.Focus() ,
Control.FromChildHandle(nint) , Control.FromHandle(nint) ,
Control.GetChildAtPoint(Point, GetChildAtPointSkip) , Control.GetChildAtPoint(Point) ,
Control.GetContainerControl() , Control.GetNextControl(Control, bool) ,
Control.GetStyle(ControlStyles) , Control.Hide() , Control.InitLayout() , Control.Invalidate(Region) ,
Control.Invalidate(Region, bool) , Control.Invalidate() , Control.Invalidate(bool) ,
Control.Invalidate(Rectangle) , Control.Invalidate(Rectangle, bool) , Control.Invoke(Action) ,
Control.Invoke(Delegate) , Control.Invoke(Delegate, params object[]) ,
Control.Invoke<T>(Func<T>) , Control.InvokePaint(Control, PaintEventArgs) ,
Control.InvokePaintBackground(Control, PaintEventArgs) , Control.IsKeyLocked(Keys) ,

Control.IsInputChar(char) , Control.IsInputKey(Keys) , Control.IsMnemonic(char, string) ,
Control.LogicalToDeviceUnits(int) , Control.LogicalToDeviceUnits(Size) ,
Control.ScaleBitmapLogicalToDevice(ref Bitmap) , Control.NotifyInvalidate(Rectangle) ,
Control.InvokeOnClick(Control, EventArgs) , Control.OnAutoSizeChanged(EventArgs) ,
Control.OnBackColorChanged(EventArgs) , Control.OnBindingContextChanged(EventArgs) ,
Control.OnCausesValidationChanged(EventArgs) , Control.OnContextMenuStripChanged(EventArgs) ,
Control.OnCursorChanged(EventArgs) , Control.OnDataContextChanged(EventArgs) ,
Control.OnDockChanged(EventArgs) , Control.OnForeColorChanged(EventArgs) ,
Control.OnNotifyMessage(Message) , Control.OnParentBackColorChanged(EventArgs) ,
Control.OnParentBackgroundImageChanged(EventArgs) ,
Control.OnParentBindingContextChanged(EventArgs) , Control.OnParentCursorChanged(EventArgs) ,
Control.OnParentDataContextChanged(EventArgs) , Control.OnParentEnabledChanged(EventArgs) ,
Control.OnParentFontChanged(EventArgs) , Control.OnParentForeColorChanged(EventArgs) ,
Control.OnParentRightToLeftChanged(EventArgs) , Control.OnParentVisibleChanged(EventArgs) ,
Control.OnPrint(PaintEventArgs) , Control.OnTabIndexChanged(EventArgs) ,
Control.OnTabStopChanged(EventArgs) , Control.OnClick(EventArgs) ,
Control.OnClientSizeChanged(EventArgs) , Control.OnControlAdded(ControlEventArgs) ,
Control.OnControlRemoved(ControlEventArgs) , Control.OnLocationChanged(EventArgs) ,
Control.OnDoubleClick(EventArgs) , Control.OnDragEnter(DragEventArgs) ,
Control.OnDragOver(DragEventArgs) , Control.OnDragLeave(EventArgs) ,
Control.OnDragDrop(DragEventArgs) , Control.OnGiveFeedback(GiveFeedbackEventArgs) ,
Control.InvokeGotFocus(Control, EventArgs) , Control.OnHelpRequested(HelpEventArgs) ,
Control.OnInvalidated(InvalidateEventArgs) , Control.OnKeyDown(KeyEventArgs) ,
Control.OnKeyPress(KeyPressEventArgs) , Control.OnKeyUp(KeyEventArgs) ,
Control.OnLeave(EventArgs) , Control.InvokeLostFocus(Control, EventArgs) ,
Control.OnLostFocus(EventArgs) , Control.OnMarginChanged(EventArgs) ,
Control.OnMouseDoubleClick(MouseEventArgs) , Control.OnMouseClick(MouseEventArgs) ,
Control.OnMouseCaptureChanged(EventArgs) , Control.OnMouseDown(MouseEventArgs) ,
Control.OnMouseEnter(EventArgs) , Control.OnMouseLeave(EventArgs) ,
Control.OnDpiChangedBeforeParent(EventArgs) , Control.OnDpiChangedAfterParent(EventArgs) ,
Control.OnMouseHover(EventArgs) , Control.OnMouseMove(MouseEventArgs) ,
Control.OnMouseUp(MouseEventArgs) ,
Control.OnQueryContinueDrag(QueryContinueDragEventArgs) ,
Control.OnRegionChanged(EventArgs) , Control.OnPreviewKeyDown(PreviewKeyDownEventArgs) ,
Control.OnSizeChanged(EventArgs) , Control.OnChangeUICues(UICuesEventArgs) ,
Control.OnSystemColorsChanged(EventArgs) , Control.OnValidating(CancelEventArgs) ,
Control.OnValidated(EventArgs) , Control.PerformLayout() , Control.PerformLayout(Control, string) ,
Control.PointToClient(Point) , Control.PointToScreen(Point) ,
Control.PreProcessMessage(ref Message) , Control.PreProcessControlMessage(ref Message) ,
Control.ProcessKeyEventArgs(ref Message) , Control.ProcessKeyMessage(ref Message) ,

Control.RaiseDragEvent(object, DragEventArgs) , Control.RaisePaintEvent(object, PaintEventArgs) ,
Control.RecreateHandle() , Control.RectangleToClient(Rectangle) ,
Control.RectangleToScreen(Rectangle) , Control.ReflectMessage(nint, ref Message) ,
Control.Refresh() , Control.ResetMouseEventArgs() , Control.ResetText() , Control.ResumeLayout() ,
Control.ResumeLayout(bool) , Control.Scale(SizeF) , Control.Select() ,
Control.SelectNextControl(Control, bool, bool, bool, bool) , Control.SendToBack() ,
Control.SetBounds(int, int, int, int) , Control.SetBounds(int, int, int, int, BoundsSpecified) ,
Control.SizeFromClientSize(Size) , Control.SetStyle(ControlStyles, bool) , Control.SetTopLevel(bool) ,
Control.RtlTranslateAlignment(HorizontalAlignment) ,
Control.RtlTranslateAlignment(LeftRightAlignment) ,
Control.RtlTranslateAlignment(ContentAlignment) ,
Control.RtlTranslateHorizontal(HorizontalAlignment) ,
Control.RtlTranslateLeftRight(LeftRightAlignment) , Control.RtlTranslateContent(ContentAlignment) ,
Control.Show() , Control.SuspendLayout() , Control.Update() , Control.UpdateBounds() ,
Control.UpdateBounds(int, int, int, int) , Control.UpdateBounds(int, int, int, int, int, int) ,
Control.UpdateZOrder() , Control.UpdateStyles() , Control.OnImeModeChanged(EventArgs) ,
Control.InvokeAsync(Action, CancellationToken) ,
Control.InvokeAsync<T>(Func<T>, CancellationToken) ,
Control.InvokeAsync(Func<CancellationToken, ValueTask>, CancellationToken) ,
Control.InvokeAsync<T>(Func<CancellationToken, ValueTask<T>>, CancellationToken) ,
Control.AccessibilityObject , Control.AccessibleDefaultActionDescription ,
Control.AccessibleDescription , Control.AccessibleName , Control.AccessibleRole ,
Control.AllowDrop , Control.Anchor , Control.AutoScrollOffset , Control.LayoutEngine ,
Control.DataContext , Control.BackgroundImage , Control.BackgroundImageLayout ,
Control.Bottom , Control.Bounds , Control.CanFocus , Control.CanRaiseEvents ,
Control.CanSelect , Control.Capture , Control.CausesValidation ,
Control.CheckForIllegalCrossThreadCalls , Control.ClientRectangle , Control.CompanyName ,
Control.ContainsFocus , Control.ContextMenuStrip , Control.Controls , Control.Created ,
Control.Cursor , Control.DataBindings , Control.DefaultBackColor , Control.DefaultCursor ,
Control.DefaultFont , Control.DefaultForeColor , Control.DefaultMargin ,
Control.DefaultMaximumSize , Control.DefaultMinimumSize , Control.DefaultPadding ,
Control.DeviceDpi , Control.IsDisposed , Control.Disposing , Control.Dock ,
Control.DoubleBuffered , Control.Enabled , Control.Focused , Control.Font ,
Control.FontHeight , Control.ForeColor , Control.Handle , Control.HasChildren , Control.Height ,
Control.IsHandleCreated , Control.InvokeRequired , Control.IsAccessible ,
Control.IsAncestorSiteInDesignMode , Control.IsMirrored , Control.Left , Control.Margin ,
Control.ModifierKeys , Control.MouseButtons , Control.MousePosition , Control.Name ,
Control.Parent , Control.ProductName , Control.ProductVersion , Control.RecreatingHandle ,
Control.Region , Control.RenderRightToLeft , Control.ResizeRedraw , Control.Right ,
Control.RightToLeft , Control.ScaleChildren , Control.Site , Control.TabIndex , Control.TabStop ,

Control.Tag , Control.Top , Control.TopLevelControl , Control.ShowKeyboardCues , Control.ShowFocusCues , Control.UseWaitCursor , Control.Visible , Control.Width , Control.PreferredSize , Control.Padding , Control.ImeMode , Control.ImeModeBase , Control.PropagatingImeMode , Control.BackColorChanged , Control.BackgroundImageChanged , Control.BackgroundImageLayoutChanged , Control.BindingContextChanged , Control.CausesValidationChanged , Control.ClientSizeChanged , Control.ContextMenuStripChanged , Control.CursorChanged , Control.DockChanged , Control.EnabledChanged , Control.FontChanged , Control.ForeColorChanged , Control.LocationChanged , Control.MarginChanged , Control.RegionChanged , Control.RightToLeftChanged , Control.SizeChanged , Control.TabIndexChanged , Control.TabStopChanged , Control.TextChanged , Control.VisibleChanged , Control.Click , Control.ControlAdded , Control.ControlRemoved , Control.DataContextChanged , Control.DragDrop , Control.DragEnter , Control.DragOver , Control.DragLeave , Control.GiveFeedback , Control.HandleCreated , Control.HandleDestroyed , Control.HelpRequested , Control.Invalidated , Control.PaddingChanged , Control.Paint , Control.QueryContinueDrag , Control.QueryAccessibilityHelp , Control.DoubleClick , Control.Enter , Control.GotFocus , Control.KeyDown , Control.KeyPress , Control.KeyUp , Control.Layout , Control.Leave , Control.LostFocus , Control.MouseClick , Control.MouseDoubleClick , Control.MouseCaptureChanged , Control.MouseDown , Control.MouseEnter , Control.MouseLeave , Control.DpiChangedBeforeParent , Control.DpiChangedAfterParent , Control.MouseHover , Control.MouseMove , Control.MouseUp , Control.MouseWheel , Control.Move , Control.PreviewKeyDown , Control.Resize , Control.ChangeUICues , Control.StyleChanged , Control.SystemColorsChanged , Control.Validating , Control.Validated , Control.ParentChanged , Control.ImeModeChanged , Component.Dispose() , Component.GetService(Type) , Component.Container , Component.DesignMode , Component.Events , Component.Disposed , MarshalByRefObject.GetLifetimeService() , MarshalByRefObject.InitializeLifetimeService() , MarshalByRefObject.MemberwiseClone(bool) , object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object)

Constructors

Form1()

Initializes the main form and sets up BOOSE components.

```
public Form1()
```

Properties

UserInput

Gets or sets the BOOSE program entered by the user.

```
[Browsable(false)]
public string UserInput { get; set; }
```

Property Value

string

Methods

Dispose(bool)

Clean up any resources being used.

```
protected override void Dispose(bool disposing)
```

Parameters

`disposing` bool

true if managed resources should be disposed; otherwise, false.

button1_Click(object, EventArgs)

```
public void button1_Click(object sender, EventArgs e)
```

Parameters

`sender` object

`e` EventArgs