

# STATS 205: Final Project Write-Up

*Brian Liu*

*6/14/2019*

## 1. Background of the data and why it is interesting or important

The data we are using is the data from WHO suicide statistics from Kaggle. This gives population-based statistics on suicide rate...

## 2. Explanation of the method studied and its properties

## 3. Data analysis or simulation study

We will use the crude rate of suicide per 100,000 people.

This analysis provides information on age-standardized rates...

```
who_suicide_statistics_df <- read.csv("who_suicide_statistics.csv")
nrow(who_suicide_statistics_df)
```

```
## [1] 43776
```

```
colnames(who_suicide_statistics_df)
```

```
## [1] "country"      "year"          "sex"           "age"           "suicides_no"
## [6] "population"
```

Filter and save countries with missing suicide rate.

```
library(tidyverse)
```

```
## Registered S3 methods overwritten by 'ggplot2':
```

```
##   method      from
##   [.quosures   rlang
##   c.quosures   rlang
##   print.quosures rlang
```

```
## -- Attaching packages ----- tidyverse 1.2.1 --
```

```
## v ggplot2 3.1.1    v purrr  0.3.2
## v tibble  2.1.1    v dplyr  0.8.1
## v tidyr   0.8.3    v stringr 1.4.0
## v readr   1.3.1    v forcats 0.4.0
```

```
## -- Conflicts ----- tidyverse_conflicts() --
```

```
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()    masks stats::lag()
```

```
filtered_suicide_df <- drop_na(who_suicide_statistics_df, "suicides_no")
nrow(filtered_suicide_df)
```

```
## [1] 41520
```

After filtering countries with missing suicide rate, take a random

#### 4. Interpretation of the results or discussion