



Security Audit

Report for Astherus

Contracts

Date: February 10, 2025 **Version:** 1.0

Contact: contact@blocksec.com

Contents

Chapter 1 Introduction	1
1.1 About Target Contracts	1
1.2 Disclaimer	1
1.3 Procedure of Auditing	2
1.3.1 Software Security	2
1.3.2 DeFi Security	2
1.3.3 NFT Security	3
1.3.4 Additional Recommendation	3
1.4 Security Model	3
Chapter 2 Findings	5
2.1 DeFi Security	6
2.1.1 Lack of invoking function <code>reDelegateTokens()</code> after <code>mpcWallet</code> update	6
2.1.2 Lack of refunding mechanism for excessive cross-chain fees	7
2.1.3 Potential reward loss due to COMPOUNDER role change	8
2.1.4 Precision loss in reward distribution results in permanently locked dust tokens	10
2.2 Additional Recommendation	11
2.2.1 Lack of non-zero check for key parameters	11
2.2.2 Lack of range check in function <code>updateMaxRewardPercent()</code>	12
2.2.3 Inconsistent validation of <code>revenueSharingPools</code> variable	12
2.2.4 Add non-zero checks in <code>add1InchRouterWhitelist()</code> and <code>addSwapSrcTokenWhitelist()</code> functions	14
2.2.5 Redundant event definitions in <code>IWithdrawVault</code> contract	15
2.2.6 Grant the BOT role in function <code>initialize()</code> of <code>Buyback</code> contract	16
2.2.7 Incorrect comment in function <code>_smartMint()</code>	17
2.3 Notes	18
2.3.1 Potential centralization risk	18
2.3.2 Timely distributing rewards before updating <code>rewardsSender</code> in function <code>setRewardsSender()</code>	18
2.3.3 Timely invocation of the function <code>settleActivity()</code>	18
2.3.4 Potential DoS due to expired lock in <code>VeCake</code> contract	19

Report Manifest

Item	Description
Client	Astherus
Target	Astherus Contracts

Version History

Version	Date	Description
1.0	February 10, 2025	First release

Signature

About BlockSec BlockSec focuses on the security of the blockchain ecosystem and collaborates with leading DeFi projects to secure their products. BlockSec is founded by top-notch security researchers and experienced experts from both academia and industry. They have published multiple blockchain security papers in prestigious conferences, reported several zero-day attacks of DeFi applications, and successfully protected digital assets that are worth more than 14 million dollars by blocking multiple attacks. They can be reached at [Email](#), [Twitter](#) and [Medium](#).

Chapter 1 Introduction

1.1 About Target Contracts

Information	Description
Type	Smart Contract
Language	Solidity
Approach	Semi-automatic and manual verification

The target of this audit is the code repository of [ass-bnb-earn-contract](#)¹, [asBTC](#)², [ass-cake-earn-contract](#)³, [asUSDFEarn](#)⁴, [asUSDF](#)⁵ of Astherus. Note that, we did **NOT** audit all the modules in the repository. Specifically, the files covered in this audit include:

- [ass-bnb-earn-contract/src/*](#)
- [ass-cake-earn-contract/src/*](#)
- [astherus-earn-contract/contracts/oft/asBTC.sol](#)
- [asUSDF.sol](#)
- [asUSDFEarn.sol](#)

The auditing process is iterative. Specifically, we would audit the commits that fix the discovered issues. If there are new issues, we will continue this process. The commit SHA values during the audit are shown in the following table. Our audit report is responsible for the code in the initial version ([Version 1](#)), as well as new code (in the following versions) to fix issues in the audit report.

Project	Version	Commit Hash
ass-bnb-earn-contract	Version 1	61fc9f5610914cf94dddc3ab83e21ca22d388e92
	Version 2	9bddf07c4a2792e8567b2863c48a62e079d07273
astherus-earn-contract	Version 1	b3bd39d38dac0e1671514c8e600dfee7d0fdf148
ass-cake-earn-contract	Version 1	5eb634c4ca7e1597e943c8c46e91683d76ac3ba9
	Version 2	ebb5af69a25cb1d5363731edf6ad662f021dec85

1.2 Disclaimer

This audit report does not constitute investment advice or a personal recommendation. It does not consider, and should not be interpreted as considering or having any bearing on, the potential economics of a token, token sale or any other product, service or other asset. Any entity should not rely on this report in any way, including for the purpose of making any decisions to buy or sell any token, product, service or other asset.

¹<https://github.com/astherus-contract/ass-bnb-earn-contract>

²<https://github.com/astherus-contract/astherus-earn-contract/blob/audit/contracts/oft/asBTC.sol>

³<https://github.com/astherus-contract/ass-cake-earn-contract>

⁴<https://bscscan.com/address/0xdB57a53C428a9faFcbFefFB6dd80d0f427543695>

⁵<https://bscscan.com/address/0x917AF46B3C3c6e1Bb7286B9F59637Fb7C65851Fb>

This audit report is not an endorsement of any particular project or team, and the report does not guarantee the security of any particular project. This audit does not give any warranties on discovering all security issues of the smart contracts, i.e., the evaluation result does not guarantee the nonexistence of any further findings of security issues. As one audit cannot be considered comprehensive, we always recommend proceeding with independent audits and a public bug bounty program to ensure the security of smart contracts.

The scope of this audit is limited to the code mentioned in Section 1.1. Unless explicitly specified, the security of the language itself (e.g., the solidity language), the underlying compiling toolchain and the computing infrastructure are out of the scope.

1.3 Procedure of Auditing

We perform the audit according to the following procedure.

- **Vulnerability Detection** We first scan smart contracts with automatic code analyzers, and then manually verify (reject or confirm) the issues reported by them.
- **Semantic Analysis** We study the business logic of smart contracts and conduct further investigation on the possible vulnerabilities using an automatic fuzzing tool (developed by our research team). We also manually analyze possible attack scenarios with independent auditors to cross-check the result.
- **Recommendation** We provide some useful advice to developers from the perspective of good programming practice, including gas optimization, code style, and etc.

We show the main concrete checkpoints in the following.

1.3.1 Software Security

- * Reentrancy
- * DoS
- * Access control
- * Data handling and data flow
- * Exception handling
- * Untrusted external call and control flow
- * Initialization consistency
- * Events operation
- * Error-prone randomness
- * Improper use of the proxy system

1.3.2 DeFi Security

- * Semantic consistency
- * Functionality consistency
- * Permission management
- * Business logic
- * Token operation
- * Emergency mechanism

- * Oracle security
- * Whitelist and blacklist
- * Economic impact
- * Batch transfer

1.3.3 NFT Security

- * Duplicated item
- * Verification of the token receiver
- * Off-chain metadata security

1.3.4 Additional Recommendation

- * Gas optimization
- * Code quality and style



Note The previous checkpoints are the main ones. We may use more checkpoints during the auditing process according to the functionality of the project.

1.4 Security Model

To evaluate the risk, we follow the standards or suggestions that are widely adopted by both industry and academy, including OWASP Risk Rating Methodology ⁶ and Common Weakness Enumeration ⁷. The overall *severity* of the risk is determined by *likelihood* and *impact*. Specifically, likelihood is used to estimate how likely a particular vulnerability can be uncovered and exploited by an attacker, while impact is used to measure the consequences of a successful exploit.

In this report, both likelihood and impact are categorized into two ratings, i.e., *high* and *low* respectively, and their combinations are shown in Table 1.1.

Table 1.1: Vulnerability Severity Classification

Impact	High	High	Medium
	Low	Medium	Low
		High	Low
		Likelihood	

Accordingly, the severity measured in this report are classified into three categories: **High**,

⁶https://owasp.org/www-community/OWASP_Risk_Rating_Methodology

⁷<https://cwe.mitre.org/>

Medium, Low. For the sake of completeness, **Undetermined** is also used to cover circumstances when the risk cannot be well determined.

Furthermore, the status of a discovered item will fall into one of the following four categories:

- **Undetermined** No response yet.
- **Acknowledged** The item has been received by the client, but not confirmed yet.
- **Confirmed** The item has been recognized by the client, but not fixed yet.
- **Fixed** The item has been confirmed and fixed by the client.

Chapter 2 Findings

In total, we found **four** potential security issues. Besides, we have **seven** recommendations and **four** notes.

- Low Risk: 4
- Recommendation: 7
- Note: 4

ID	Severity	Description	Category	Status
1	Low	Lack of invoking function <code>reDelegateTokens()</code> after <code>mpcWallet</code> update	DeFi Security	Fixed
2	Low	Lack of refunding mechanism for excessive cross-chain fees	DeFi Security	Fixed
3	Low	Potential reward loss due to COMPOUNDER role change	DeFi Security	Confirmed
4	Low	Precision loss in reward distribution results in permanently locked dust tokens	DeFi Security	Fixed
5	-	Lack of non-zero check for key parameters	Recommendation	Fixed
6	-	Lack of range check in function <code>updateMaxRewardPercent()</code>	Recommendation	Fixed
7	-	Inconsistent validation of <code>revenueSharingPools</code> variable	Recommendation	Fixed
8	-	Add non-zero checks in <code>add1InchRouterWhitelist()</code> and <code>addSwapSrcTokenWhitelist()</code> functions	Recommendation	Fixed
9	-	Redundant event definitions in <code>IWithdrawVault</code> contract	Recommendation	Confirmed
10	-	Grant the BOT role in function <code>initialize()</code> of Buyback contract	Recommendation	Fixed
11	-	Incorrect comment in function <code>_smartMint()</code>	Recommendation	Fixed
12	-	Potential centralization risk	Note	-
13	-	Timely distributing rewards before updating <code>rewardsSender</code> in function <code>setRewardsSender()</code>	Note	-
14	-	Timely invocation of the function <code>settleActivity()</code>	Note	-
15	-	Potential DoS due to expired lock in Ve-Cake contract	Note	-

The details are provided in the following sections.

2.1 DeFi Security

2.1.1 Lack of invoking function `reDelegateTokens()` after `mpcWallet` update

Severity Low

Status Fixed in [Version 2](#)

Introduced by [Version 1](#)

Description The `YieldProxy` contract is designed to deposit received `slisBNB` into the `SlisBNBProvider` and delegates the minted `clisBNB` to the `mpcWallet` to earn rewards. Note that the `SlisBNBProvider` supports delegation to only one target at a time. Therefore, whenever the `MANAGER` role updates the `mpcWallet` using the `setMPCWallet()` function, it is crucial to immediately invoke the `reDelegateTokens()` function. Failure to do so will cause the delegation to persist with the previous `mpcWallet`, leading to a denial of service (DoS) and preventing users from minting `asBNB`.

```
338 function setMPCWallet(address _mpcWallet) external onlyRole(MANAGER) {
339     require(_mpcWallet != address(0) && _mpcWallet != mpcWallet, "Invalid MPC wallet address");
340     address oldMpcWallet = mpcWallet;
341     mpcWallet = _mpcWallet;
342     emit MPCWalletSet(oldMpcWallet, _mpcWallet);
343 }
```

Listing 2.1: YieldProxy.sol

```
304 function reDelegateTokens() external onlyRole(MANAGER) whenNotPaused {
305     require(slisBNBProvider != address(0), "slisBNBProvider not set");
306     require(mpcWallet != address(0), "mpcWallet not set");
307     ISlisBNBProvider(slisBNBProvider).delegateAllTo(mpcWallet);
308 }
```

Listing 2.2: YieldProxy.sol

```
80 function provide(uint256 _amount, address _delegateTo)
81     external
82     virtual
83     whenNotPaused
84     nonReentrant
85     returns (uint256)
86 {
87     require(_amount > 0, "zero deposit amount");
88     require(_delegateTo != address(0), "delegateTo cannot be zero address");
89     require(_delegateTo != msg.sender, "delegateTo cannot be self");
90     require(
91         delegation[msg.sender].delegateTo == _delegateTo ||
92         delegation[msg.sender].amount == 0, // first time, clear old delegattee
93         "delegateTo is differ from the current one"
94     );
95
96
97     IERC20(token).safeTransferFrom(msg.sender, address(this), _amount);
```

```
98      // do sync before balance modified
99      _syncLp(msg.sender);
100     uint256 userPartLp = _provideCollateral(msg.sender, _delegateTo, _amount);
101
102
103     Delegation storage userDelegation = delegation[msg.sender];
104     userDelegation.delegateTo = _delegateTo;
105     userDelegation.amount += userPartLp;
106
107
108     emit Deposit(msg.sender, _amount, userPartLp);
109     return userPartLp;
110 }
```

Listing 2.3: SlisBNBProvider.sol

Impact Users are unable to deposit assets into the protocol.

Suggestion Merge `setMPCWallet()` and `reDelegateTokens()` into a single function to ensure timely redelegation to the new address after update.

2.1.2 Lack of refunding mechanism for excessive cross-chain fees

Severity Low

Status Fixed in [Version 2](#)

Introduced by [Version 1](#)

Description The `mintAsBnbToChain()` function allows users to pay a certain amount of native tokens as cross-chain fees to mint a corresponding amount of `asBNB` by staking `slisBNB`. The minted `asBNB` will then be transferred to the target chain for users. However, if the attached cross-chain fees exceed the required amount, the excess fee will not be refunded to the user, which is incorrect.

```
243     function mintAsBnbToChain(
244         uint256 amountIn,
245         SendParam memory sendParam
246     ) external payable override whenNotPaused depositEnabled nonReentrant returns (uint256) {
247         // get cross chain fee and validate the existence of OFTAdapter
248         MessagingFee memory fee = getCrossChainFee(sendParam);
249         require(msg.value >= fee.nativeFee, "Invalid fee");
250         // transfer token from user to this contract
251         token.safeTransferFrom(msg.sender, address(this), amountIn);
252
253
254         return _mintToChain(amountIn, sendParam, fee);
255     }
```

Listing 2.4: AsBnbMinter.sol

Impact Excess fees paid by the user will not be refunded.

Suggestion Add a refund mechanism for excess cross-chain fees or enforce that the attached `msg.value` exactly matches the calculated fee.

2.1.3 Potential reward loss due to COMPOUNDER role change

Severity Low

Status Confirmed

Introduced by Version 1

Description In the `ass-cake-earn` protocol, the `RewardDistributionScheduler` contract, acting as the `COMPOUNDER` role for the `Minter` contract, is responsible for redistributing the received `CAKE` tokens according to the pre-set schedules back to the `Minter` contract for further use. However, only contracts with the `COMPOUNDER` role can invoke the function `compoundRewards()`. Therefore, before changing the `COMPOUNDER` role in the `Minter` contract, it is crucial to ensure that all pending reward distributions are executed, as `CAKE` tokens that haven't been executed cannot be compounded after the role change.

```

136 function executeRewardSchedules() external override onlyRole(BOT) nonReentrant whenNotPaused {
137     // flooring the current timestamp to 1 day
138     uint256 currentTimestamp = (block.timestamp / 1 days) * 1 days;
139     // get num. of reward types
140     uint max = (uint)(type(IMinter.RewardsType).max);
141     // rewards type array
142     IMinter.RewardsType[] memory rewardsTypes = new IMinter.RewardsType[](max);
143     // total rewards per type array
144     uint256[] memory totalRewards = new uint256[](max);
145
146
147     // from the day of last distribution
148     // process the rewards day by day
149     while (lastDistributeRewardsTimestamp <= currentTimestamp) {
150         // sum up rewards for each type
151         for (uint i; i < max; ++i) {
152             rewardsTypes[i] = IMinter.RewardsType(i);
153             // if there are rewards to distribute for that type on that day
154             if (epochs[lastDistributeRewardsTimestamp][rewardsTypes[i]] != 0) {
155                 // add up rewards for that type and increase allowance
156                 totalRewards[i] += epochs[lastDistributeRewardsTimestamp][rewardsTypes[i]];
157                 IERC20(token).safeIncreaseAllowance(minter, epochs[lastDistributeRewardsTimestamp][
                    rewardsTypes[i]]);
158                 // remove it from the epoch
159                 delete epochs[lastDistributeRewardsTimestamp][IMinter.RewardsType(i)];
160             }
161         }
162         // process the next day
163         lastDistributeRewardsTimestamp += 1 days;
164     }
165     // compound all types of rewards at once
166     IMinter(minter).compoundRewards(rewardsTypes, totalRewards);
167 }

```

Listing 2.5: `RewardDistributionScheduler.sol`

```

237 function compoundRewards(
238     IMinter.RewardsType[] memory _rewardsTypes,

```

```
239     uint256[] memory _rewards
240 ) external override onlyRole(COMPOUNDER) whenNotPaused nonReentrant {
241     require(_rewardsTypes.length > 0 && _rewardsTypes.length == _rewards.length, "Invalid
        rewards length");
242
243
244     // separate compoundAmount and fee
245     uint256 compoundAmount = 0;
246     uint256 fee = 0;
247     // compound the rewards
248     for (uint i; i < _rewardsTypes.length; ++i) {
249         IMinter.RewardsType rewardsType = _rewardsTypes[i];
250         uint256 amountInPerType = _rewards[i];
251         // process only if amount is not 0
252         if (amountInPerType != 0) {
253             uint256 feePerType = 0;
254             // collect fee per type
255             if (rewardsType == RewardsType.VeTokenRewards) {
256                 feePerType = (amountInPerType * veTokenRewardsFeeRate) / DENOMINATOR;
257             } else if (rewardsType == RewardsType.VoteRewards) {
258                 feePerType = (amountInPerType * voteRewardsFeeRate) / DENOMINATOR;
259             } else if (rewardsType == RewardsType.Donate) {
260                 feePerType = (amountInPerType * donateRewardsFeeRate) / DENOMINATOR;
261             } else {
262                 revert("Invalid rewardsType");
263             }
264             // add up fee
265             fee += feePerType;
266             // add up amt. of compound after fee is deducted
267             compoundAmount += amountInPerType - feePerType;
268             // accumulate rewards per type
269             totalRewards[rewardsType] += amountInPerType - feePerType;
270         }
271     } // transfer token from compounder
272     require(compoundAmount + fee > 0, "Invalid compound amount");
273     IERC20(token).safeTransferFrom(msg.sender, address(this), compoundAmount + fee);
274
275
276     // reset vesting amount
277     _updateVestingAmount(compoundAmount);
278
279
280     // update total fee and actual total tokens
281     totalFee += fee;
282     _totalTokens += compoundAmount;
283
284
285     // compound rewards
286     IERC20(token).safeIncreaseAllowance(universalProxy, compoundAmount);
287     IUniversalProxy(universalProxy).lock(compoundAmount);
288
289
290     emit RewardsCompounded(msg.sender, compoundAmount, fee);
```

291 }

Listing 2.6: Minter.sol

Impact The received [CAKE](#) will remain locked in the [RewardDistributionScheduler](#) contract.

Suggestion Ensure all pending reward distributions are executed before changing the [COMPOUNDER](#) role to prevent locking [CAKE](#) tokens.

Feedback from the project The team will ensure all rewards will be fully distributed if there is any upcoming change of the [COMPOUNDER](#) role.

2.1.4 Precision loss in reward distribution results in permanently locked dust tokens

Severity Low

Status Fixed in [Version 2](#)

Introduced by [Version 1](#)

Description In the [RewardDistributionScheduler](#) contract of the [ass-cake-earn](#) protocol, the privileged role [MANAGER](#) is authorized to deposit rewards into the contract via the function [addRewardsSchedule\(\)](#), which evenly distributes the rewards across each [epoch](#). However, due to integer division, this process results in leftover token dust. The contract lacks a mechanism to handle or distribute this dust, and it also cannot be withdrawn. Consequently, these leftover rewards are permanently locked within the contract.

```

94  function addRewardsSchedule(
95      IMinter.RewardsType _rewardsType,
96      uint256 _amount,
97      uint256 _epochs,
98      uint256 _startTime
99  ) external override onlyRole(MANAGER) nonReentrant whenNotPaused {
100      require(_amount > 0, "Invalid amount");
101      require(_epochs > 0, "Invalid epochs");
102      require(_startTime > 0, "Invalid startTime");
103      //valid rewardsType
104      require(
105          IMinter.RewardsType.VeTokenRewards == _rewardsType ||
106          IMinter.RewardsType.VoteRewards == _rewardsType ||
107          IMinter.RewardsType.Donate == _rewardsType,
108          "Invalid rewardsType"
109      );
110
111
112      uint256 startTime = (_startTime / 1 days) * 1 days;
113
114
115      // The rewards have been distributed,
116      // and additional reward plans added later.
117      // if the start time is less than the emitted time. Need to reset the release time
118      if (startTime < lastDistributeRewardsTimestamp) {
119          lastDistributeRewardsTimestamp = startTime;

```

```
120     }
121
122
123     // transfer funds to this contract
124     token.safeTransferFrom(msg.sender, address(this), _amount);
125     // average daily reward amount
126     uint256 amountPerDay = _amount / _epochs;
127     // spread rewards every day
128     for (uint256 i; i < _epochs; i++) {
129         // accumulation of different reward types
130         epochs[startTime + i * 1 days][_rewardsType] += amountPerDay;
131     }
132     // emit event
133     emit RewardsScheduleAdded(msg.sender, _rewardsType, _amount, _epochs, startTime);
134 }
```

Listing 2.7: RewardDistributionScheduler.sol

Impact Part of the rewards will be permanently locked in the contract and cannot be withdrawn.

Suggestion Revise the calculation logic to ensure that the rewards are fully distributed.

2.2 Additional Recommendation

2.2.1 Lack of non-zero check for key parameters

Status Fixed in [Version 2](#)

Introduced by [Version 1](#)

Description In the [AsBnbOFT](#) contract, the function `initialize()` is used to configure important global variables, including roles and essential settings for the contract. However, it does not check if any of the provided addresses are zero when granting roles, which is inappropriate.

```
35 function initialize(
36     address _admin,
37     address _manager,
38     address _pauser,
39     string memory _name,
40     string memory _symbol,
41     address _delegate
42 ) external initializer {
43     __OFT_init(_name, _symbol, _delegate);
44     __Ownable_init(_delegate);
45     __AccessControl_init();
46     __Pausable_init();
47     __ERC20Permit_init(_name);
48     __UUPSUpgradeable_init();
49
50
51     _grantRole(DEFAULT_ADMIN_ROLE, _admin);
52     _grantRole(MANAGER, _manager);
```

```
53     _grantRole(PAUSER, _pauser);
54 }
```

Listing 2.8: AsBnbOFT.sol

Suggestion Add a check to ensure that the provided addresses are not zero addresses.

2.2.2 Lack of range check in function `updateMaxRewardPercent()`

Status Fixed in [Version 2](#)

Introduced by [Version 1](#)

Description In the `asUSDFEarn` contract, the `maxRewardPercent` parameter controls the maximum percentage of rewards distributed, which should be a value between 0 and 1e18. However, the `updateMaxRewardPercent()` function does not perform a range check. If the parameter is set to 0, rewards will always be 0. If set above 1e18, it could cause a single distribution to exceed the total distributable amount, leading to incorrect behavior.

```
106 function updateMaxRewardPercent(uint newValue) external onlyRole(ADMIN_ROLE) {
107     uint oldValue = maxRewardPercent;
108     require(oldValue != newValue, "already set");
109     maxRewardPercent = newValue;
110     emit UpdateMaxRewardPercent(oldValue, newValue);
111 }
```

Listing 2.9: asUSDFEarn.sol

```
185 function dispatchReward(uint amount) external nonReentrant onlyRole(REWARD_ROLE) {
186     //
187     if (getUnvestedAmount() > 0) {
188         return;
189     }
190     require(amount <= USDF.totalSupply() * maxRewardPercent / EXCHANGE_PRICE_DECIMALS, "too
        much");
191     lastDispatchTime = block.timestamp;
192     USDF.safeTransferFrom(msg.sender, address(this), amount);
193     lastReward = amount;
194     emit RewardDispatched(amount, block.timestamp, VESTING_PERIOD);
195 }
```

Listing 2.10: asUSDFEarn.sol

Suggestion Implement a range check to ensure that `maxRewardPercent` is within a valid range.

2.2.3 Inconsistent validation of `revenueSharingPools` variable

Status Fixed in [Version 2](#)

Introduced by [Version 1](#)

Description In the `UniversalProxy` contract of the `ass-cake-earn` protocol, the `initialize()` function requires the `revenueSharingPools` array to be non-zero. However, in the `setRevenuePoolIds()` function, it allows the `revenueSharingPools` array to be empty, which is inconsistent with the validation logic.

```
91  function initialize(
92      address _admin,
93      address _pauser,
94      address _minter,
95      address _bot,
96      address _manager,
97      address _token,
98      address _veToken,
99      address _gaugeVoting,
100     address _ifo,
101     address _rewardDistributionScheduler,
102     address[] memory _revenueSharingPools,
103     address _revenueSharingPoolGateway,
104     address _cakePlatform
105 ) external initializer {
106     require(_admin != address(0), "Invalid admin address");
107     require(_token != address(0), "Invalid token address");
108     require(_veToken != address(0), "Invalid veToken address");
109     require(_gaugeVoting != address(0), "Invalid gaugeVoting address");
110     require(_ifo != address(0), "Invalid ifo address");
111     require(_revenueSharingPoolGateway != address(0), "Invalid revenueSharingPoolGateway
112         address");
113     require(_cakePlatform != address(0), "Invalid cakePlatform address");
114     require(_rewardDistributionScheduler != address(0), "Invalid rewardDistributionScheduler
115         address");
116     require(_revenueSharingPools.length > 0, "revenueSharingPools must have at least one
117         address");
118
119     __AccessControl_init();
120     __Pausable_init();
121     __ReentrancyGuard_init();
122     __UUPSUpgradeable_init();
123     _grantRole(DEFAULT_ADMIN_ROLE, _admin);
124     _grantRole(PAUSER, _pauser);
125     _grantRole(MINTER, _minter);
126     _grantRole(BOT, _bot);
127     _grantRole(MANAGER, _manager);
128
129     lockCreated = false;
130     token = IERC20(_token);
131     veToken = IVeCake(_veToken);
132     gaugeVoting = IGaugeVoting(_gaugeVoting);
133     ifo = IIFOV8(_ifo);
134     revenueSharingPools = _revenueSharingPools;
135     revenueSharingPoolGateway = IRevenueSharingPoolGateway(_revenueSharingPoolGateway);
136     rewardsDistributionScheduler = IRewardDistributionScheduler(_rewardDistributionScheduler);
137     cakePlatform = ICakePlatform(_cakePlatform);
138 }
```

Listing 2.11: UniversalProxy.sol


```
347 function setRevenuePoolIds(address[] memory poolIds) external onlyRole(MANAGER) {
348     revenueSharingPools = poolIds;
349     emit RevenuePoolIdsSet(poolIds);
350 }
```

Listing 2.12: UniversalProxy.sol

Suggestion Revise the logic to ensure the validation is consistent.

2.2.4 Add non-zero checks in `add1InchRouterWhitelist()` and `addSwapSrcTokenWhitelist()` functions

Status Fixed in [Version 2](#)

Introduced by [Version 1](#)

Description In the [Buyback](#) contract, the `add1InchRouterWhitelist()` function lacks a check for the `oneInchRouter` parameter, and the `addSwapSrcTokenWhitelist()` function does not check the `srcToken` parameter. It is recommended to add a non-zero address check to ensure that these parameters are valid addresses.

```
91 function initialize(
92     address _admin,
93     address _pauser,
94     address _minter,
95     address _bot,
96     address _manager,
97     address _token,
98     address _veToken,
99     address _gaugeVoting,
100    address _ifo,
101    address _rewardDistributionScheduler,
102    address[] memory _revenueSharingPools,
103    address _revenueSharingPoolGateway,
104    address _cakePlatform
105 ) external initializer {
106     require(_admin != address(0), "Invalid admin address");
107     require(_token != address(0), "Invalid token address");
108     require(_veToken != address(0), "Invalid veToken address");
109     require(_gaugeVoting != address(0), "Invalid gaugeVoting address");
110     require(_ifo != address(0), "Invalid ifo address");
111     require(_revenueSharingPoolGateway != address(0), "Invalid revenueSharingPoolGateway
112         address");
113     require(_cakePlatform != address(0), "Invalid cakePlatform address");
114     require(_rewardDistributionScheduler != address(0), "Invalid rewardDistributionScheduler
115         address");
116     require(_revenueSharingPools.length > 0, "revenueSharingPools must have at least one
117         address");
118     __AccessControl_init();
119     __Pausable_init();
120     __ReentrancyGuard_init();
```

```
120     __UUPSUpgradeable_init();
121     _grantRole(DEFAULT_ADMIN_ROLE, _admin);
122     _grantRole(PAUSER, _pauser);
123     _grantRole(MINTER, _minter);
124     _grantRole(BOT, _bot);
125     _grantRole(MANAGER, _manager);
126
127
128     lockCreated = false;
129     token = IERC20(_token);
130     veToken = IVeCake(_veToken);
131     gaugeVoting = IGaugeVoting(_gaugeVoting);
132     ifo = IIFOV8(_ifo);
133     revenueSharingPools = _revenueSharingPools;
134     revenueSharingPoolGateway = IRevenueSharingPoolGateway(_revenueSharingPoolGateway);
135     rewardsDistributionScheduler = IRewardDistributionScheduler(_rewardDistributionScheduler);
136     cakePlatform = ICakePlatform(_cakePlatform);
137 }
```

Listing 2.13: UniversalProxy.sol

```
243 function addSwapSrcTokenWhitelist(address srcToken) external onlyRole(MANAGER) {
244     require(!swapSrcTokenWhitelist[srcToken], "srcToken already whitelisted");
245     // add srcToken to swapSrcTokenWhitelist
246     swapSrcTokenWhitelist[srcToken] = true;
247     emit SwapSrcTokenChanged(srcToken, true);
248 }
```

Listing 2.14: Buyback.sol

Suggestion Add a non-zero addresses check for the `oneInchRouter` and `srcToken` parameters to prevent invalid zero addresses from being added to the whitelist.

2.2.5 Redundant event definitions in IWithdrawVault contract

Status Confirmed

Introduced by [Version 1](#)

Description In the `IWithdrawVault` contract, several events are defined but never emitted, making them redundant.

```
8 interface IWithdrawVault {
9
10
11     event ReceiveETH(address indexed from, address indexed to, uint256 amount);
12     event TransferNative(address receipt, uint256 amount);
13     event Transfer(address receipt, IERC20 token, uint256 amount);
14
15
16     function transfer(address receipt, IERC20 token, uint256 amount) external;
17     function transferNative(address receipt, uint256 amount) external;
18
19 }
```

Listing 2.15: IWithdrawVault.sol

Suggestion Remove the redundant event definitions from the contract, as they are not being emitted.

Feedback from the project Currently, we not support `NativeToken` so not use it, just for future functionality.

2.2.6 Grant the BOT role in function `initialize()` of Buyback contract

Status Fixed in [Version 2](#)

Introduced by [Version 1](#)

Description In the `Buyback` contract, the `buyback()` function uses the `onlyRole(BOT)` modifier to restrict access to the `BOT` role. However, the role is not granted during the contract initialization. This means that the `ADMIN` must manually invoke the `grantRole()` function after the contract is initialized. To simplify the process and enhance contract functionality, it is recommended to grant the `BOT` role directly in the `initialize()` function.

```

79  function initialize(
80      address _admin,
81      address _manager,
82      address _pauser,
83      address _swapDstToken,
84      address _receiver,
85      address _oneInchRouter,
86      address _swapNativeAddress
87  ) external override initializer {
88      require(_admin != address(0), "Invalid admin address");
89      require(_manager != address(0), "Invalid _manager address");
90      require(_pauser != address(0), "Invalid _pauser address");
91      require(_swapDstToken != address(0), "Invalid swapDstToken address");
92      require(_receiver != address(0), "Invalid receiver address");
93      require(_oneInchRouter != address(0), "Invalid oneInchRouter address");
94      require(_swapNativeAddress != address(0), "Invalid swapNativeAddress address");
95
96      __AccessControl_init();
97      __Pausable_init();
98      __ReentrancyGuard_init();
99      __UUPSUpgradeable_init();
100
101
102
103      _grantRole(DEFAULT_ADMIN_ROLE, _admin);
104      _grantRole(MANAGER, _manager);
105      _grantRole(PAUSER, _pauser);
106
107
108      swapDstToken = _swapDstToken;
109      receiver = _receiver;
110      swapNativeAddress = _swapNativeAddress;

```

```
111     oneInchRouterWhitelist[_oneInchRouter] = true;
112 }
```

Listing 2.16: Buyback.sol

Suggestion Grant the `BOT` role directly in the `initialize()` function to avoid manual assignment after contract deployment.

2.2.7 Incorrect comment in function `_smartMint()`

Status Fixed in [Version 2](#)

Introduced by [Version 1](#)

Description The `_smartMint()` function in the `Minter` contract contains a misleading comment. The comment “swap to asCAKE by `pancakeSwap`” inaccurately describes the implementation, as the section of the code is responsible for minting tokens, not for performing a token swap.

```
475 function _smartMint(uint256 _amountIn, uint256 _mintRatio, uint256 _minOut) private returns (
    uint256) {
476     // valid amount
477     require(_amountIn > 0, "Invalid amount");
478     // valid mintRatio
479     require(_mintRatio <= DENOMINATOR, "Incorrect Ratio");
480     // transfer funds to this contract
481     token.safeTransferFrom(msg.sender, address(this), _amountIn);
482     //convert CAKE amount by this contract
483     uint256 mintAmount = (_amountIn * _mintRatio) / DENOMINATOR;
484     // swap CAKE amount by pancakeSwap
485     uint256 buybackAmount = _amountIn - mintAmount;
486     // asCAKE amount
487     uint256 amountRec = 0;
488
489
490     if (mintAmount > 0) {
491         // swap to asCAKE by pancakeSwap
492         amountRec += _mint(mintAmount);
493         // increase total CAKE
494         _totalTokens += mintAmount;
495     }
496
497
498     if (buybackAmount > 0) {
499         // make sure minOut is not 0
500         require(_minOut > amountRec, "MinOut not match");
501         //swap CAKE by pancakeSwap
502         amountRec += _buyback(buybackAmount, _minOut - amountRec);
503     }
504     // the received amount is greater than equal to the estimated amount
505     require(amountRec >= _minOut, "MinOut not match");
506
507 }
```

```
508     // transfer asCAKE to sender
509     IERC20(assToken).safeTransfer(msg.sender, amountRec);
510
511
512     // emit event
513     emit SmartMinted(msg.sender, _amountIn, amountRec);
514
515
516     return amountRec;
517 }
```

Listing 2.17: Minter.sol

Suggestion Update the comment to accurately reflect the functionality.

2.3 Notes

2.3.1 Potential centralization risk

Introduced by [Version 1](#)

Description In the current implementation, several privileged roles are set to govern and regulate the system-wide operation (e.g., parameter setting, pause/unpause and grant roles). Additionally, the [owner](#) also has the ability to upgrade contracts. If the private keys of them are lost or maliciously exploited, it could potentially lead to losses for users.

Feedback from the project We will use a time-lock contract with [minDelay 6](#) hours to perform any contract upgrade. Also, all proposers and executors are multi-sig wallet.

2.3.2 Timely distributing rewards before updating rewardsSender in function `setRewardsSender()`

Introduced by [Version 1](#)

Description In the [YieldProxy](#) contract, when native tokens are received, the contract checks if the `msg.sender` matches the designated `rewardsSender` to determine whether the tokens are user rewards. If they are identified as user rewards, the amount is added to the global variable `rewardedAmount`, which is later converted into `sliisbnb` for distribution to users. However, the `rewardsSender` can be changed through the privileged function `setRewardsSender()`. If rewards are not distributed promptly before `rewardsSender` is updated, it could result in issues with reward distribution, potentially causing user losses.

2.3.3 Timely invocation of the function `settleActivity()`

Introduced by [Version 1](#)

Description The protocol aggregates users' `sliisBNB`, deposits them into [Lista](#) to receive `clisBNB`, and mints `asBNB` for the users. When rewards reach a certain threshold, they are processed via the `settleActivity()` function, adjusting the exchange rate between `asBNB` and `sliisBNB`. As a result, when users burn `asBNB` to redeem `sliisBNB`, they will receive more than

their initial deposit. However, the function `settleActivity()` is actively invoked by the `BOT` role once rewards are distributed. It is crucial that the `BOT` triggers the function promptly. Otherwise, users may miss out on their rewards.

Feedback from the project The `Astherus` team will ensure the high availability of the off-chain service.

2.3.4 Potential DoS due to expired lock in VeCake contract

Introduced by `Version 1`

Description In the `ass-cake-earn`'s `UniversalProxy` contract, the `BOT` role must timely invoke the privileged function `extendLock()` to extend the lock duration in the `VeCake` contract, ensuring that it does not expire. If the lock expires, the global variable `lockCreated` in the contract cannot revert from `true` to `false`, preventing the contract from creating a new lock in the `VeCake` contract. In such a case, any attempt by the contract to lock new `CAKE` into `VeCake` by invoking the function `increaseLockAmount()` will result in a DoS.

