**LEARN MORE** 

HIDE AD • AD VIA BUYSELLADS



# **Q-Learning in Python**

Last Updated: 19-04-2020

Pre-Requisite: Reinforcement Learning

**Reinforcement Learning** briefly is a paradigm of Learning Process in which a learning agent learns, overtime, to behave optimally in a certain environment by interacting continuously in the environment. The agent during its course of learning experience various different situations in the environment it is in. These are called *states*. The agent while being in that state may choose from a

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy Policy</u>

**LEARN MORE** 

HIDE AD • AD VIA BUYSELLADS

- i. **u-values or Action-values:** u-values are defined for states and actions.  $\mathcal{Q}(\mathcal{O},\mathcal{A})$  is an estimation of how good is it to take the action A at the state S. This estimation of Q(S,A) will be iteratively computed using the **TD- Update rule** which we will see in the upcoming sections.
- 2. **Rewards and Episodes:** An agent over the course of its lifetime starts from a start state, makes a number of transitions from its current state to a next state based on its choice of action and also the environment the agent is interacting in. At every step of transition, the agent from a state takes an action, observes a reward from the environment, and then transits to another state. If at any point of time the agent ends up in one of the terminating states that means there are no further transition possible. This is said to be the completion of an episode.
- 3. Temporal Difference or TD-Update:

The Temporal Difference or TD-Update rule can be represented as follows:

$$Q(S,A) \leftarrow Q(S,A) + \alpha (R + \gamma Q(S',A') - Q(S,A))$$

This update rule to estimate the value of Q is applied at every time step of the agents interaction with the environment. The terms used are explained below. :

- ullet S : Current State of the agent.
- ullet : Current Action Picked according to some policy.

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy Policy</u>

LEARN MORE

HIDE AD • AD VIA BUYSELLADS

- $\gamma$  (>0 and <=1): Discounting Factor for Future Rewards. Future rewars are less valuable than current rewards so they must be discounted. Since Q-value is an estimation of expected rewards from a state, discounting rule applies here as well.
- $\alpha$ : Step length taken to update the estimation of Q(S, A).

### 4. Choosing the Action to take using $\epsilon$ -greedy policy:

 $\epsilon$ -greedy policy of is a very simple policy of choosing actions using the current Q-value estimations. It goes as follows :

- With probability  $(1-\epsilon)$  choose the action which has the highest Q-value.
- ullet With probability  $(\epsilon)$  choose any action at random.

Now with all the theory required in hand let us take an example. We will use OpenAl's gym environment to train our Q-Learning model.

Command to Install gym -

```
pip install gym
```

Before starting with example, you will need some helper code in order to visualize the working of the algorithms. There will be two helper files which need to be downloaded in the working directory. One can find the files here.

**Step # 1 :** Import required libraries.

```
import gym
import itertools
import matplotlib
import matplotlib.style
import numpy as np
import pandas as pd
import sys

from collections import defaultdict
from windy_gridworld import WindyGridworldEnv
import plotting

matplotlib.style.use('ggplot')
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our Cookie Policy & Privacy Policy

**LEARN MORE** 

HIDE AD • AD VIA BUYSELLADS

```
env = WindyGridworldEnv()
Step #3: Make the \epsilon-greedy policy.
def createEpsilonGreedyPolicy(Q, epsilon, num_actions):
    Creates an epsilon-greedy policy based
    on a given Q-function and epsilon.
    Returns a function that takes the state
    as an input and returns the probabilities
    for each action in the form of a numpy array
    of length of the action space(set of possible actions).
    def policyFunction(state):
         Action_probabilities = np.ones(num_actions,
                 dtype = float) * epsilon / num_actions
         best_action = np.argmax(Q[state])
         Action_probabilities[best_action] += (1.0 - epsilon)
         return Action_probabilities
    return policyFunction
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy Policy</u>

LEARN MORE

HIDE AD • AD VIA BUYSELLADS

```
def qLearning(env, num_episodes, discount_factor = 1.0,
                            alpha = 0.6, epsilon = 0.1):
    Q-Learning algorithm: Off-policy TD control.
    Finds the optimal greedy policy while improving
    following an epsilon-greedy policy"""
    # Action value function
    # A nested dictionary that maps
    # state -> (action -> action-value).
    Q = defaultdict(lambda: np.zeros(env.action space.n))
    # Keeps track of useful statistics
    stats = plotting.EpisodeStats(
        episode lengths = np.zeros(num episodes),
        episode rewards = np.zeros(num episodes))
    # Create an epsilon greedy policy function
    # appropriately for environment action space
    policy = createEpsilonGreedyPolicy(Q, epsilon, env.action_space.n)
    # For every episode
    for ith_episode in range(num_episodes):
        # Reset the environment and pick the first action
        state = env.reset()
        for t in itertools.count():
            # get probabilities of all actions from current state
            action probabilities = policy(state)
            # choose action according to
            # the probability distribution
            action = np.random.choice(np.arange(
                      len(action_probabilities)),
                       p = action_probabilities)
            # take action and get reward, transit to next state
            next_state, reward, done, _ = env.step(action)
            # Update statistics
            stats.episode rewards[ith episode] += reward
            stats.episode_lengths[ith_episode] = t
            # TD Update
            hast next action = nn argmax/O[next state])
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our Cookie Policy & Privacy Policy

**LEARN MORE** 

HIDE AD • AD VIA BUYSELLADS

state = next\_state


return Q, stats

Step #5: Train the model.

Q, stats = qLearning(env, 1000)

Step #6: Plot important statistics.


plotting.plot\_episode\_stats(stats)




We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy Policy</u>

LEARN MORE







#### **Conclusion:**

We see that in the Episode Reward over time plot that the episode rewards *progressively increase* over time and ultimately *levels out* at a high reward per episode value which indicates that the agent has learnt to maximize its total reward earned in an episode by behaving optimally at every state.

Attention geek! Strengthen your foundations with the Python Programming Foundation Course

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy Policy</u>

**LEARN MORE** 

HIDE AD • AD VIA BUYSELLADS

#### **Recommended Posts:**

Important differences between Python 2.x and Python 3.x with examples

Python | Set 4 (Dictionary, Keywords in Python)

Python | Sort Python Dictionaries by Key or Value

Python | Merge Python key values to list

Reading Python File-Like Objects from C | Python

Python | Add Logging to a Python Script

Python | Add Logging to Python Libraries

JavaScript vs Python : Can Python Overtop JavaScript by 2020?

Python | Visualizing O(n) using Python

Python | Index of Non-Zero elements in Python list

Python | Convert list to Python array

MySQL-Connector-Python module in Python

Python - Read blob object in python using wand library

Python | PRAW - Python Reddit API Wrapper

twitter-text-python (ttp) module - Python

Reusable piece of python functionality for wrapping arbitrary blocks of code: Python Context

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our Cookie Policy & Privacy Policy

**LEARN MORE** 

HIDE AD • AD VIA BUYSELLADS





#### Kaustav kumar Chanda

Check out this Author's contributed articles.

If you like GeeksforGeeks and would like to contribute, you can also write an article using contribute.geeksforgeeks.org or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please Improve this article if you find anything incorrect by clicking on the "Improve Article" button below.

Improved By: VishvajeetRamanuj

Article Tags: Advanced Computer Subject Machine Learning Python

**Practice Tags:** Machine Learning

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy Policy</u>

**LEARN MORE** 

HIDE AD • AD VIA BUYSELLADS

	4
To-do Done	Based on 1 vote(s)
(Improve Article)	
Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.	
Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.	
Load Comments	
ADVERTISEMENT	"The biggest threat to organizations today is not knowing about the assets that they've got."  GET ALISSA'S PERSPECTIVE



• 5th Floor, A-118, Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

Company Learn

About Us Algorithms

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy Policy</u>

**LEARN MORE** 

HIDE AD • AD VIA BUYSELLADS

## Practice Contribute

Courses Write an Article

Company-wise Write Interview Experience

Topic-wise Internships

How to begin? Videos

@geeksforgeeks, Some rights reserved