

kavach.

LIVING WHITE PAPER / VERSION 0.1

Your account. Your rules. Beyond one key.

Programmable accounts for Cardano.

What exists. How it is protected. What comes next.

09 SEPTEMBER 2026 / DEVELOPMENT EDITION

Source baseline f2b9420

Not independently audited or production qualified.

About this edition

Living white paper and technical specification · Version 0.1

Document control	Value
Status	Development draft; not an audited or production-qualified protocol
Last reviewed	9 September 2026
Implementation baseline	Kavach repository commit f2b9420
Intended readers	Account owners, wallet developers, protocol engineers and security reviewers
Maintained source	This Markdown document; diagrams are editable Mermaid source
Scope	Existing implementation, its qualification boundaries, and proposed next work

The goal: keep an account independent of any one device or signing key. Change who can authorize it, apply spending rules, and retain a separately controlled recovery path. The present: a working local Yaci DevKit development stack with contracts, Java SDK, dashboard, wallet signing and an iPhone companion. Transfers and policy workflows have ledger evidence. Recovery has implementation and partial evidence, but its full qualification remains open. Use test assets only.

Version **0.1 is this document's version**. It does not rename the on-chain schema, module ABI, signing schemes or deployed scripts.

Reading routes

- **New to Kavach:** read sections 1–5, then the examples in section 7.
- **Building an integration:** read sections 6–10 and the source specifications in section 15.
- **Reviewing security:** start with sections 11–14 and follow the evidence links.

Contents

1. Purpose and vocabulary
2. System overview
3. What exists today
4. The account model
5. Signing and funding
6. Creation and account changes
7. Spending rules and budgets
8. Lifecycle and recovery
9. Technical profile
10. Storage and restoration
11. Security model
12. Privacy and device boundaries
13. Economics and areas to improve
14. Roadmap and release gates
15. Specifications, evidence and maintenance

1. Purpose and vocabulary

A conventional wallet often treats a payment key as the account. Kavach separates the account from the credentials that authorize it. Assets sit at a script-controlled Cardano address; the account's current rules decide which approvals permit an operation.


This enables policies such as: "My phone can approve a small ADA payment; larger payments also need my wallet key." A different policy can control changes to those rules. A lost or replaced device need not imply a new account address when the change fits the existing immutable core.

Kavach is a **protocol and integration framework**. Its longer-term role can be an account foundation for applications, with replaceable providers handling transaction execution and fees behind a familiar approval experience (section 5.3). The dashboard is its reference management interface. Yano Wallet is its initial wallet integration, and Yano Companion supplies an independent iPhone signing key. Neither wallet brand is part of the on-chain authorization rule.

Term	Plain meaning
Account	A script-controlled asset address, authenticated state and associated rules
UTxO	An unspent transaction output: a particular piece of ledger value that can be consumed once
State NFT	A unique asset identifying the account's canonical state; it is not a user's transferable membership token
Credential / key	A registered public key whose corresponding private key can approve certain operations
Intent	The exact, typed instruction being authorized, including its account and transaction constraints
Policy	Which registered keys must approve an operation, and the required threshold
Authorization module	On-chain code that checks the configured credentials and approval rules
Fee payer / sponsor	A wallet providing transaction funding and collateral where required
Locator	Public account-discovery information, useful for restoration; not a signing secret
Qualification	Evidence that a particular implementation/profile passed specified tests; not an independent audit

A visible balance is not a universal spendability guarantee. Supported asset shapes, account mode, available approvals, transaction limits and funding all matter.

2. System overview



Account state • Assets • Authorization rules

Private spending keys stay with the signers.

Figure 1 — The current development stack. The backend builds transactions but does not hold account spending keys. Signing still requires a wallet or phone. The current phone exchange is local/offline; no remote relay is implemented.

There are four distinct responsibilities:

Layer	Responsibility
Immutable core	State identity and custody, allowed lifecycle changes, replay binding, transaction shape and value accounting
Authorization module	Determine whether the correct registered authorities approved the exact operation
SDK and backend	Resolve ledger data, prepare canonical requests, verify returned evidence, build/evaluate/submit transactions
Signer and interface	Present the requested action, obtain consent and produce signatures for supported profiles

This separation helps prevent an authorization upgrade from silently replacing the rules that protect asset custody. It does not eliminate bugs in those rules or compromise of a signing device.

3. What exists today

Here, **implemented** means present in the development stack. **Live evidence** means specified transactions were accepted by the local DevKit ledger. Neither term means production readiness or comprehensive wallet compatibility.


Capability	Existing behavior	Evidence / boundary
Account creation	Authenticated state NFT, registered credentials, six authority policies	Live creation; current per-key flow has ten transactions
ADA transfers	Exact-input, signed recipient allocations and bounded account fee contribution	Compiled and live SDK/browser flows
Native assets	Bounded ordinary transfers; dedicated whole-UTxO path preserves the complete native-asset map	Live reference profiles; phone signing remains narrower
Consolidation	Combine supported account inputs into valid account change	Bounded builder/profile behavior; not arbitrary transaction composition
Per-key signing	COSE and transaction-witness methods in a mixed configuration	Compiled and live mixed/all-COSE flows
Dynamic creation signers	Add/remove controls, 3–8 keys in the dashboard	Eight-key creation tested; larger protocol registry is not a UI support claim
Amount tiers	Small ADA payments use one policy; larger/other transfers use the strong policy	Compiled and live tier selection
Optional periodic budget	Fixed daily or weekly ADA debit cap; enable/change/disable	Compiled boundary and live lifecycle/contention evidence
Credential and module changes	Existing administrators approve; destination/candidate proofs are checked	Live replacements and subsequent transfers
Freeze and unfreeze	Separate authorities and lifecycle checks	Compiled and short live flows; full race/recovery qualification open
Delayed recovery	Start, cancel and complete transition logic with target commitments and immutable timing	Compiled cases and short initiation/cancellation evidence; full real-delay completion qualification remains open
Workspace restoration	Multiple saved locators, switch/forget, authenticated state restoration	Browser and SDK tests; backend/provider trust remains
Approval wizard	Per-key progress, purpose grouping, device routing, separate funding phase	Browser checks and owner-observed DevKit use
iPhone approval	Device key, pairing, request review, response QR/file/JSON	Swift tests, builds and owner-observed signing; limited operations

Capability	Existing behavior	Evidence / boundary
Independent fee payer	Wallet outside the authority registry can fund an all-COSE request	Live synthetic-signer 15/35 ADA test
Positive reward accounting	Core/SDK receipt rules and historical positive-refund ledger tests	Current dashboard restricts itself to zero-reward checkpoints

See the [policy ledger](#), [browser ledger](#), and [Phase 2 progress](#). Earlier ledger entries describe earlier snapshots; later increments add evidence without retrospectively qualifying old artifacts.

Not currently delivered: production deployment, a public sponsorship service, remote phone relay, generic dApp execution, arbitrary authentication algorithms, passkeys/YubiKey authorization, Google/Apple login authorization, CIP-113 programmable-token support, or fully qualified end-to-end recovery.

4. The account model



Change a supported key or module. Keep the account address.

Changing the immutable core is a separate migration question.

Figure 2 — Identity is tied to authenticated state, not to whichever key is currently active. Ordinary asset spends reference state; state-changing operations consume and recreate it.

The canonical state contains account/deployment identity, immutable core bindings, current module and configuration, state version, lifecycle mode, and recovery parameters/state. Finding a datum with the right-looking account ID is insufficient: validators and SDK restoration check the **complete NFT identity, quantity, custody address, schema and immutable bindings**.

Ordinary spending normally leaves the state UTxO unconsumed, allowing different asset inputs to be spent concurrently. State changes consume that state and increment its version, making requests against the former version state.

Change	Address consequence
Replace keys within a supported configuration	Account asset address remains unchanged
Change supported per-key signing methods under current administration	Same address; requires an on-chain configuration update
Replace a compatible authorization module	Same immutable account custody identity; current admin and candidate checks still apply
Add budget enforcement to an account created with the budget-capable core	Can be enabled using the supported module/configuration flow
Add budget capability to an ordinary core without it	Requires a new asset-validator profile/address and separately designed migration
Change immutable core code, parameters or compiler output	May change script hashes and addresses; never an automatic upgrade

The current mutable-state implementation does not make archived sealed Phase 1 accounts upgradeable. Their historical state/reference deposits remain subject to their original scripts.

5. Signing and funding

5.1 Methods are configured, not guessed

The signing method belongs to each registered credential in a mixed account configuration. Evidence cannot choose a different method. A key is counted once per proof, regardless of how many addresses or devices expose it.

Scheme	Meaning	Typical use
0	Raw Ed25519 signature over the canonical intent digest	Original SDK/reference profile
1	Cardano transaction witnesses for named payment-key signers	Legacy/advanced browser transaction authorization
2	Bounded CIP-8-style COSE evidence over the exact digest	Wallet signData and supported Companion approvals
3	Mixed per-key methods with amount-tiered approval	Current dashboard's final per-key creation module

Scheme	Meaning	Typical use
4	Mixed policy inside the optional periodic-budget configuration	Budget-capable account with periodic enforcement

CIP-30 is the browser-wallet interface. In the dashboard, “transaction witness” means approving the final Cardano transaction via that interface. COSE is a signed-message format; wallets can provide it through `signData`. These are not two different kinds of account asset address chosen by a signature alone.

New dashboard keys default to **COSE intent approval**. Transaction-witness authorization remains an advanced choice. Existing accounts keep their on-chain methods until an authorized update confirms.

5.2 Approve, fund, confirm




Figure 3 — Recommended all-COSE workflow. A transaction-witness authority profile additionally requires its authority witnesses on the final body.

A COSE approval authorizes a request; it does not itself submit a transaction or pay fees. In an all-COSE account, the funding signature cannot replace any required COSE approval, even when the same wallet owns both keys.

A sponsor need not be an account authority. Sponsorship still needs a funded wallet, compatible transaction construction and explicit signing. A hosted sponsor service has not been built. Changing the sponsor in the current dashboard requires preparing a new request.

Keys derived at different HD address indexes can be distinct credentials. Yano's tested integration can discover matching address-index keys within a bounded search. Discovery belongs to the wallet, not the contract, and distinct keys under one seed do **not** provide independent protection against compromise of that seed.

5.3 Accounts as infrastructure: sponsored intent execution

Proposed direction. Kavach can become the account layer behind everyday applications: users choose an action and approve it with a familiar device, while an execution provider handles the blockchain mechanics. That provider could be an application-funded sponsor, an independently chosen operator, or a participant in a decentralized intent network.

The simple experience is “**Review** → **Approve** → **Done.**” A user might approve “Send 15 ADA to this recipient; network fee paid by the application” on their phone. They need not maintain a separate fee balance, select collateral or sign a second fee-wallet prompt. The provider still pays and signs the required funding transaction. Account policies still determine how many authority approvals are needed.




Figure 4 — Proposed sponsored execution. Users authorize the action; providers supply execution and funding. The current local fee-payer primitive exists, but a decentralized execution network does not.

This could make Kavach a reusable account foundation across applications. **The account is the durable authority layer; the execution network is replaceable infrastructure.** A network operator should not become a privileged key, control recovery, or dictate where the account can be used.

What the network would do

Responsibility	Proposed provider behavior	What stays with the account/user
Discovery and quotes	Find eligible requests and offer funding/service terms	Select providers and consent to every account-paid charge
Preparation	Resolve state and construct a request within the supported profile	Review the exact action before signing
Execution	Assemble, evaluate and submit a valid transaction	Enforce configured approval, value, replay and budget rules
Funding	Supply provider-owned fees, collateral and agreed top-ups	Retain spending keys and account authority
Availability	Retry safely or hand off to another compatible provider	Keep a direct/user-selected funding path

A message relay alone is not an intent execution network: it need not build transactions, provide ADA, price risk or settle provider compensation. Several operators behind one mandatory gateway also do not establish decentralization. Operator choice, independent operation and tested failover are part of that claim.

Abstraction without hidden authority or hidden charges

The user can avoid blockchain mechanics while still seeing the action, destination, amount, total account debit, fee responsibility and confirmation status. A subsidy should be labeled “paid by the application,” not presented as if execution had no cost. The intended experience needs an **all-COSE authority policy**; a transaction-witness authority still has to sign the Cardano transaction. Sponsorship does not make an unsupported phone operation or authentication algorithm supported.

Possible funding arrangements include an application subsidy, an external subscription, or an explicitly approved account-paid charge. These are design options, not delivered billing systems. Network fees, service charges, deposits/top-ups and collateral exposure are different costs and need separate terms.

Existing V1 has **no implicit relayer tip**. Its signed account-fee ceiling cannot be repurposed as an arbitrary service fee. An account-paid service charge must be an explicit signed recipient allocation within the supported profile; it affects approval tiers and budget debit as applicable. Token reimbursement, exchange-rate conversion and new settlement rules require additional qualification. The current single-recipient iPhone flow cannot silently add a second recipient for a provider fee.

What the current exact-intent model permits

Kavach currently signs constrained, exact transactions: account inputs, recipient output indices/addresses/values, state, operation and validity are bound. It does not yet accept a generic “find any route to achieve this outcome” solver order. Providers cannot reorder signed outputs or change recipients, amounts or expiry. If signed fields change, the user must authorize the new request.

Quotes and preparation should therefore settle the user-visible terms before approval. Cross-provider reuse of a COSE proof is safe only when all signed semantics remain unchanged and state, inputs and validity are still usable; that handoff is not currently qualified. The dashboard today prepares a fresh request for a different sponsor.

As a conceptual reference, [ERC-7683](#) separates order dissemination, solver execution and settlement. It is an Ethereum ecosystem standard, not evidence of Cardano or Kavach compatibility. Kavach needs its own qualified interfaces around its exact intent and UTxO constraints.

Security and delivery gates

A provider cannot spend beyond a valid account authorization, but it can refuse service, delay submission or observe requests. Public intent feeds can expose payment plans before confirmation; encryption does not automatically hide metadata. A sponsor must protect its own funding inputs, collateral and return address by checking the entire transaction.

Start with a specified external-sponsor API and one qualified operator, then add multiple independent providers and failure handling before claiming a decentralized network. Test malicious quotes, excess charges, stale state/counters, duplicate delivery, concurrent attempts, provider disappearance, collateral loss and rollback. Freeze, cancellation and recovery need a replaceable funding path too: if no provider will fund them, correct authorization alone cannot make them execute.

See [ADR-010](#) for the proposed boundary. This is a product and architecture direction, not a deployed network or a change to existing contracts.

6. Creation and account changes

6.1 Guided creation




Figure 5 — Three user-facing phases currently contain ten ledger transactions. Grouping the interface does not turn those transactions into one transaction.

The final mixed authorization module is too large to include the full genesis flow in the qualified publication shape. Creation therefore uses a restricted setup module. That module accepts initialization and only the authorized activation of its **precommitted final module with unchanged configuration**; spending is blocked until activation.

All registered keys prove possession in their selected method. The activation step separately needs current administration approval and candidate possession. This explains why the same key can appear twice in the wizard: one proof says “I authorize this update,” and another says “I control this key in the resulting policy.” The proofs have different domains and cannot substitute for one another.

The dashboard can prepare the next request after confirmation, but it never automatically obtains the next wallet signature. Setup after confirmed genesis can resume from the locator and verified deployment records. Pre-genesis progress remains more fragile because pending request state is in memory.

6.2 Six authorities

Role	Controls	Important separation
Spend	Transfers, with small/strong tier rules when configured	Does not implicitly grant administration or recovery powers
Admin	Replace configuration or compatible module	Must remain stronger than unilateral everyday spending
Freeze	Stop future spending after confirmation	Cannot undo an already confirmed payment
Unfreeze	Return a frozen account to normal operation	Independent from the strong spend and recovery sets
Recovery	Initiate a committed replacement configuration	Cannot bypass the immutable delay
Cancel	Cancel a pending recovery into Frozen mode	Independent from spend and recovery authorities

The reference rules reject unsafe role overlaps. Recovery keys are disjoint from cancellation and unfreeze keys; defensive cancellation/unfreeze keys are disjoint from spend keys. Cancellation and unfreeze may share keys. Threshold and overlap checks remain authoritative even if the UI makes a selection easy.

7. Spending rules and budgets

7.1 Approval tier versus spending cap

These are separate controls:

Setting	Question it answers	Current semantics
Small-payment threshold	How many approvals does this payment need?	Inclusive ADA threshold; stronger policy above it
Strong policy	Who approves larger or non-small transfers?	Configured key subset and threshold
Optional daily/weekly budget	How much ADA may leave across a fixed period?	Hard cumulative debit limit while enabled
Independent hard per-transaction cap	Must even a fully approved payment be rejected above this amount?	Not a separate delivered user setting

Small approval is available only for ordinary ADA-only allocations where:

$\text{recipient ADA total} + \text{signed maximum account-paid fee} \leq \text{small-payment threshold}$


Native-token recipients and whole-UTxO transfers always use strong approval. A larger payment is not rejected merely for exceeding the small threshold; it needs stronger authorization.

Example: the tested three-key arrangement

- Small payments up to 30 ADA: Key 0, the iPhone.
- Strong approval: both Key 0 and Key 1, a wallet key.
- Administration: both Key 0 and Key 2, another wallet key.
- Freeze/recovery: Key 1. Unfreeze/cancel: Key 2.
- All three keys use COSE; the fee wallet signs separately.

With zero account-paid fee, 15 ADA needs the phone; 35 ADA needs the phone and Key 1. If a positive maximum account fee is signed, that maximum also counts toward tier selection. A small-policy membership must be a subset of the strong policy, and every sufficient strong subset must satisfy the small policy too.

7.2 Optional fixed-period budget



Competing enabled spends share one counter; a stale request must be rebuilt.

Figure 6 — The optional cap trades concurrency for one globally consistent budget per account. It is not a server-maintained usage balance.

The counter holds a unique NFT and an authenticated datum. Every enabled spend must consume that counter and recreate its exact custody/value with the next usage. The debit is:

$\text{actual account-input ADA} - \text{valid account-change ADA}$

This includes actual account-paid fees. Sponsor change and counter deposits cannot masquerade as account change. Tokens have no price-oracle conversion: only their accompanying ADA debit counts toward this ADA budget.

Daily means a fixed UTC calendar day. **Weekly** means a fixed UTC week anchored on Monday. These are not rolling windows or Cardano epochs. Contracts use ledger validity intervals in POSIX time. The DevKit adapter converts slots using its verified one-second slot configuration; other networks require correct era-history conversion.


Usage resets on the next accepted spend in a new period—no cron job or backend reset is needed. The complete transaction validity interval must fit within one period.

Administrative change	Effect
Raise/lower limit only	Retains the existing recorded usage
Set limit to zero	Disables enforcement; retains counter identity and period
Re-enable same period	Retains recorded usage in that window; disabled spending is not counted retrospectively

Administrative change	Effect
Change daily to weekly, or vice versa	Explicitly authorizes a new period counter interpretation on the next spend
Replace with ordinary module	Removes the budget under old-admin authorization; counter deposit stays locked

Two concurrent spends cannot consume the same counter UTxO. One can confirm; the other must be rebuilt. More approvals do not override an enabled cap. Administrators can change/disable the policy, so the cap is not a restriction against a sufficiently authorized administrator.

8. Lifecycle and recovery



Full recovery qualification remains open.

Figure 7 — Intended and implemented lifecycle transitions. Compiled transition checks and short ledger flows do not establish complete recovery qualification.

Normal asset spending is restricted to Normal mode. Starting recovery commits the complete replacement configuration and a sequence-bound proposal. Completion must use that exact target after the stored deadline; it cannot install a relayer's substitute target or require the lost old spending key.

The ordinary candidate permits creation-time recovery delays from one to ninety days and cooldowns from one hour to thirty days. Its wire profile has no timing-update action: successors preserve those timing parameters. Delay/cooldown arithmetic is bounded; state version and recovery sequence cannot overflow.

Cancellation leaves the account Frozen. Unfreeze cannot bypass a pending recovery. Cooldown deadlines are monotonic, limiting repeated recovery attempts from erasing the waiting period.

Ordering matters: a freeze does not front-run a competing spend by definition. If a spend confirms first, freeze cannot reverse it. A confirmed state mutation invalidates stale referenced state for subsequent transactions, subject to ledger ordering and rollback behavior.

The acceptance ledger still records open real-delay completion, positive-reward mutation, adversarial/race and final-review gates. This paper does not infer completion just because a recorded deadline is in the past. See [Phase 2 acceptance](#).

9. Technical profile

9.1 Canonical requests and module boundaries

The signing object is a typed intent, not an arbitrary backend-supplied hash. Its domain binds the account, network/deployment parameters and immutable core. The envelope also binds current state version/reference, operation, validity interval and operation-specific fields such as inputs, recipient allocations and fee ceiling.

Canonical bytes follow Cardano `serialiseData`, not a generic “canonical JSON” or generic deterministic-CBOR convention. Unknown versions/tags, wrong arity, malformed types, duplicate IDs, invalid ordering and out-of-range values reject. Genesis, configuration/candidate possession and recovery target proofs have distinct digest domains.

The core requires the installed module under the exact Rewarding-purpose invocation and checks the same envelope and receipts. Merely including a reference script, executing a certificate path, or supplying an unrelated module withdrawal cannot authorize an operation. The module independently authenticates the account state and derives its digest.

The bounded COSE adapter accepts reviewed Ed25519 COSE shapes, including the qualified address-valued `kid` variant. It validates algorithm/key metadata, exact payload, protected bytes and signing address against the registered payment key and network. It is not unrestricted CIP-8 or arbitrary COSE support.

9.2 Principal bounds

These are intersections of count, byte and execution bounds—not a promise that every combination fits a ledger transaction.

Ordinary candidate constraint	Bound / distinction
Total inputs / references / outputs	16 / 4 / 16
Account inputs / recipient allocations	8 / 8
Ordinary distinct assets	12 including ADA, plus aggregate native-entry limits
Registered keys / members per role / signatures per proof	16 / 8 / 8
Dashboard creation	3–8 keys; phone transport and activation limit the exposed flow
Configuration / intent bytes	1,024 / 1,536 serialized Data bytes

Ordinary candidate constraint	Bound / distinction
Intent validity width	At most 300,000 ms
Signed account fee ceiling	At most 5 ADA, also bounded by actual fee
Whole-UTxO profile	One exact input; full Value digest; no account-funded fee; separately bounded Value size

Some UI wording still mentions sixteen ordinary inputs; that does not override the stricter eight-account-input SDK/contract limit. Aligning those messages is an integration improvement, not grounds to enlarge the supported profile.

Whole-UTxO transfer is a specific escape route for token-heavy supported deposits. It preserves every native token and at least the input's ADA at a plain key recipient, with sponsor-funded fees/top-ups. It is not arbitrary script execution, and the iPhone does not currently sign that profile.

9.3 Implementation and portability

The reference stack uses JuLC targeting Plutus V3, Java 25, Gradle 9.2.0, CCL 0.8.0-pre5, and the pinned JuLC snapshot 0.1.0-pre17-6754861-SNAPSHOT. Binary-hash checks and qualification records matter: this is not an unqualified floating compiler dependency.

Future implementations must satisfy the language-neutral schema, invariants and conformance vectors. Equivalent behavior in Aiken or another language does not imply identical script bytes, hashes or addresses. See [toolchain provenance](#).

10. Storage and restoration

Location	What lives there	What it does not establish
Cardano ledger	Assets, canonical account state, configured rules, budget counter and confirmed transactions	Private signing keys
Browser local storage	Workspace locators, names/device hints, selection and local request references	Authority to spend or a complete backend backup
Backend local files	Verified public deployment/profile records; persistent Companion request-signing identity	Account spending keys; the authoritative budget usage
Backend memory	Prepared plans and collected pending approval progress	Restart-safe pending requests
Browser wallet	Its own wallet keys and wallet-specific account discovery	Automatic authority for all keys in a Kavach account
iPhone Keychain	Device signing key, pinned peers and approval history	An on-chain account backup or automatic recovery

The locator identifies the account NFT, deployment domain and immutable bindings. Restoration queries the ledger and validates the returned state and script hashes. It does not require the original spending key, but a locator alone cannot authorize a transaction. Surviving authorities and funding are still needed.

The backend/provider is trusted for current ledger information; these checks do not supply independent inclusion or freshness proofs. The phone currently does not independently query and authenticate live account state. The browser relies on the backend's canonical request rendering.

Forgetting an account removes a browser entry only. It does not close the on-chain account, destroy funds, revoke a key or disable policy. Clearing browser storage can lose convenient discovery. Losing deployment records or the pairing identity has different consequences and requires explicit restoration/re-pairing.

The dashboard backend currently runs locally; Kavach does not require a hosted service just to use the local workflow. Remote coordination would need a separately designed transport and availability model.

11. Security model

Kavach's security case is built from **specific invariants and tested boundaries**, not from the label “smart account.” The following protections depend on correct deployed code and ledger validation.

Threat	Intended enforcement	Residual boundary
Fake account state	Full state NFT identity/quantity, exact custody, supported schema and immutable binding checks	Provider freshness and deployment trust still matter
Reuse or redirect an approval	Canonical account/domain/action binding, exact input references, state version, distinct proof domains	Compromised signer/display can still approve a malicious request
Reuse a spend twice	Signed inputs are consumed once; state mutations invalidate old state references	Expiry alone is not replay protection; rollback/finality must be handled
Lower threshold through evidence	Methods fixed in signed config; sorted unique IDs; threshold and membership checks	Compromise of enough legitimately authorized keys satisfies the policy
Unauthorized upgrade	Old administration approves the exact replacement; candidate proofs are separate	Administrators intentionally have power to change supported rules
Steal incidental tokens or change	Account for every asset and exact recipient allocations; validate account change and fee bound	Unsupported deposits/transaction shapes must be surfaced clearly
Count one output twice	Recipient, change, successor and reward-receipt allocations are constrained/disjoint	Complete transaction composition must be tested, not only helpers
Bypass budget	Authenticate counter NFT/custody, actual debit and unique successor atomically	Enabled counter serializes spends; admin can change the policy
Accelerate or substitute recovery	Ledger intervals, conservative deadline calculation, exact stored target and monotonic sequence/cooldown	Full recovery qualification and reliable defensive monitoring remain open
Abuse module invocation	Correct script, purpose, same state/envelope and supported operation checks	A bad new module can weaken authorization within the permitted core boundary
Divert script rewards	Separate immutable sinks and distinct receipt outputs; no mixing with account conservation	Dashboard positive-reward routing remains unsupported
Malformed/oversized input	Bounded parsing, canonical encoding, integer/size checks and fail-closed operation support	Parser/compiler defects still require independent review

11.1 Independence matters more than the number of keys

Three HD keys from one wallet seed are three cryptographic credentials but one seed-compromise domain. For meaningful multi-party or multi-device protection, distribute authorities across independently secured credentials. A phone plus a wallet key is useful only to the extent their storage and approval paths are independently protected.

A sufficiently authorized user can approve a harmful policy or payment. Kavach cannot infer intent beyond the signed instruction, guarantee that a device display is honest, or repair loss of every required credential.

11.2 Verification layers

1. **Schema and golden vectors:** independent encodings, digests and signatures.
2. **JVM/SDK tests:** parsing, rendering, construction and rejection behavior.
3. **Compiled Plutus tests:** emitted UPLC validation, adversarial cases and execution budgets.
4. **Live ledger tests:** final balanced/signed transaction acceptance, value movement and contention.
5. **Real-device checks:** wallet/phone consent, camera transport, Keychain and user-facing behavior.
6. **Independent audit and production qualification:** still required.

Passing one layer does not establish another. Fabricated time contexts are not an elapsed-day/week/recovery-delay test. Synthetic wallet responses are not a compatibility certificate for every wallet/version. Historical script qualification does not automatically qualify changed hashes.

12. Privacy and device boundaries

The account is not private by default. Ledger addresses, values, transaction structure and published account configuration can reveal relationships between credentials and activity. COSE evidence included in transactions is not a zero-knowledge proof. The reviewed profiles do not intentionally publish private keys, wallet seed phrases, a phone passcode or biometric templates.

The iPhone uses a device-only Keychain item with passcode/user-presence controls. User presence may be satisfied by passcode rather than Face ID. **Ed25519 signing occurs in application memory, not inside the Secure Enclave.** A compromised phone remains a material threat. Simulator keys lack the physical-device protection and are unsuitable for funded accounts.

Pairing pins the desktop's request-signing public key after fingerprint comparison. It authenticates the requesting desktop, not the safety of every request that desktop may send. The phone independently parses the supported request bytes and requires affirmative review before signing; it does not yet independently verify current ledger state.

QR/file messages are authenticated **but not encrypted**. Anyone who obtains one can see its contents. Response scanning adds evidence; it does not itself submit a transaction. Unpairing a desktop does not revoke an already issued signature or remove a credential from the on-chain account.

Current Companion support includes bounded ADA Spend, genesis and supported configuration/module policy proofs. Native assets, whole transfers, recovery and ordinary wallet transaction signing need separate phone profiles and qualification. No passkey, secure-hardware Ed25519, anonymous relay or automatic device-loss recovery claim is made.

13. Economics and areas to improve

13.1 Separate fees, deposits and locked value

Cost category	Current development behavior
Network fee	Paid per transaction; includes transaction bytes, execution and reference-script charges
Reference publications	Current per-key setup publishes six outputs, each at the ledger minimum for its own script size: about 220 ADA permanently locked for the five core references in this development reference arrangement, plus the sixth mixed-setup module
Account state	Current setup creates a 12 ADA state output, retained by state-custody rules
Stake registration	Additional ledger deposits; not included in the reference-deposit figure
Optional budget counter	3 ADA retained by the counter script, still locked after disabling/removing the budget
Sponsor collateral/top-ups	Separate funding requirements; not the same thing as the quoted transaction fee

These values describe the local builder/profile, not a production price quote or an economic minimum. A setup transaction count of ten means ten transactions requiring fees, even if the UI groups them into three phases.

Historical fee measurements help locate costs but must not be mixed as if they measured the same current profile:

Recorded profile	Paid fee	Interpretation
Optimized pre-Phase-2 ordinary ADA transfer	1.024019 ADA	Historical scripts; approximately 15.3% below the recorded 1.208773 ADA baseline
Phase 2 ordinary ADA transfer	1.122225 ADA	Later core and lifecycle implementation; separate qualification snapshot
Phase 2 eight-input/eight-recipient transfer	2.059199 ADA	Larger transaction shape; not a single-payment estimate
Browser custom-policy samples	Approximately 1.18–1.23 ADA	Token/multi-input/whole samples; not directly comparable with plain ADA

Sources: [fee measurements](#), [Phase 2 progress](#), and [browser qualification](#). In the historical 1.024019 ADA sample, reference scripts accounted for 0.489120 ADA—an important optimization target, not a forecast for current mixed/budget requests.

13.2 Improvement priorities

Area	Proposed work	Acceptance condition
Script size and execution	Reduce duplicated work and emitted bytes within invariant-preserving boundaries	Same adversarial rejects, full combined budgets, final ledger acceptance and reproducible hashes
Onboarding cost	Investigate reusable reference infrastructure, publication planning and safe batching	Creator binding and setup activation cannot be bypassed; deposits/fees measured separately
Locked deposits	Design explicit reclaimable lifecycle where compatible, rather than assuming current deposits are refundable	New semantics, reviewed custody authorization and migration consequences
Witness/fee estimation	Count actual required witnesses, protect exact recipient allocations during balancing	Final fee decomposition reconciles and signed output meaning stays unchanged
Approval UX	Fewer redundant interactions, clear next signer, compact requests and accessible review	No automatic signing, no merged proof domains, no hidden policy changes
Pending plans	Durable, integrity-checked resumable plans and better stale/expiry handling	Restart/replay/rebuild tests; no private spending-key persistence
Input and QR limits	Align UI limits with SDK/contracts; improve larger request transport	Explicit size/budget and real-device tests before raising limits
Periodic concurrency	Keep global cap optional; investigate other explicitly defined budget models	New models must not masquerade as the same globally serialized cap
Restoration	Independent provider checks, artifact availability and phone state verification	Fresh-device tests with realistic failures and surviving authority requirements
Benchmark reporting	Maintain current per-profile fees, bytes, CPU/memory and collateral/deposit breakdown	Record network parameters, source/script hashes and actual confirmed transactions

Fee savings must not come from removing state authentication, value checks, target binding or authorization independence. A new core layout can change addresses; “optimization” is not an exemption from migration design.

14. Roadmap and release gates

These are **proposed workstreams, not dated commitments or implemented capabilities**.

Priority	Workstream	Required result before claiming support
P0	Complete recovery qualification	Real immutable delay, recovered-key transfer, positive-reward transitions, race/adversarial cases and clean-device restoration
P0	Independent security review	Review immutable core, modules, SDK composition, canonical parsers and device consent; resolve findings
P0	Production deployment discipline	Reproducible artifacts, supported network manifests, rollback/failure guidance and operational ownership
P1	Lower fees and creation friction	Current-profile benchmark suite and measured safe improvements; preserve proof/custody boundaries
P1	Persistent workflow recovery	Resume after browser/backend interruption; clear stale-request rebuilding and setup status
P1	Better companion transport	Evaluate authenticated encrypted relay coordination without granting relay spending authority
P1	Broader device qualification	Physical iPhone security/failure matrix, wallet/version captures and supported operation expansion
P1	Optional explicit per-transaction cap	Specify a hard cap separately from approval tiers, including admin and fee semantics
P1	Sponsored execution interface	Exact-intent request/quote API, explicit costs, provider consent, funding failure and safe retry tests
P2	Decentralized intent execution	Multiple independent funding/execution providers, qualified settlement and failover, privacy/censorship evidence and no privileged account operator
P2	Additional authentication modules	Demonstrate supported on-chain cryptography, exact intent binding and safe upgrade/candidate rules
P2	CIP-113 programmable tokens	Separate custody/authority prototype and qualification; ordinary V1 explicitly defers this support
P2	Other platforms and language implementations	Cross-implementation conformance and platform-specific key/consent evidence

Nostr and CIP-45/WebRTC coordination are research candidates for transport, not installed Kavach features. Encryption can protect message content but does not automatically hide relay metadata, guarantee delivery or make a malicious request safe. No relay design has been selected here.

Google/Apple login would not make their login assertion directly accepted by the existing contracts. A service that verifies login and signs Kavach intents with its own registered key introduces that service as an authority. Such a design needs a separate trust model and should not silently replace independently held keys. Passkeys and NFC security keys likewise require a qualified cryptographic/profile path; the present Ed25519 modules cannot verify arbitrary hardware assertions.

CIP-113 was explicitly deferred under the Phase 0 decision. The project makes no promise that future interoperability can be added without new custody addresses or migration. See [ADR-002](#) and the [Phase 0 decision record](#).

15. Specifications, evidence and maintenance

15.1 Authority and source map

This document is a readable, maintained synthesis. It does not supersede the detailed wire schemas or promote a proposed ADR into an audited specification. When this overview and detailed evidence disagree, use the narrower supported claim and resolve the discrepancy explicitly.

Topic	Authoritative detail / implementation guide
Architecture and invariants	ADR-001
Ordinary wire semantics and bounds	Ordinary specification , CDDL , module ABI
Browser signature formats	Bounded browser profile , ADR-005
Mixed policy and budgets	Policy specification , schema , vectors
Budget architecture	ADR-007 , ADR-008
Creation and approval workflow	ADR-009 , dashboard guide
Restoration	Locator specification
iPhone implementation	Companion guide , device security , ADR-006
Sponsored execution proposal	ADR-010 ; network execution is future work
Current qualification	Policy , browser , Phase 2

Topic	Authoritative detail / implementation guide
Historical qualification	Phase 0, Phase 1, fee review

15.2 Reproducing relevant checks

From the repository root, with the pinned dependencies installed:

```
./gradlew check dashboardWebBuild
./gradlew :dashboard-app:backend:dashboardIntegrationTest
```

The second command uses disposable accounts on a running local DevKit. check alone does not run those live flows. Frontend and phone core tests run from their respective directories:

```
cd dashboard-app/web
npm test

cd companion-apps/ios
swift test
```

Real-delay recovery and positive-reward tests are separate long-running gates. Preserve their workers and evidence; never reset DevKit or shorten time parameters to claim completion.

15.3 Update policy

Keep this file at a stable path. Update the version, date and source baseline when changing material claims. For every newly supported feature, add:

1. Its exact scope and on-chain/off-chain ownership.
2. Wire/profile and address-compatibility consequences.
3. Security assumptions, failure behavior and privacy implications.
4. Compiled, ledger and device evidence appropriate to the claim.
5. Fees, deposits, limits and unresolved qualification work.

Maintain diagrams in this source so they change with the design. Markdown is the canonical edition because Git can review every wording and diagram change. Every PDF export must show the same version/date/source baseline and remain a derived snapshot, not a separately edited specification.

Version	Date	Change
0.1	2026-09-09	First consolidated white paper: current development features, architecture, signing/funding, policies, security boundaries, economics, sponsored intent-network direction and roadmap