

Name : Rajkumar B L  
Reg.No : 2047120  
Course : MCS NoSQL (LAB 10)

Redis:

String:

```
> set mem1 Raj
OK

> set mem2 hareesma
OK

> set mem3 Rohin
OK

> set cars kia,alto,beat,innova,qualis
OK

> get mem1
"Raj"

> get mem2
"hareesma"
```

```
> get cars
"kia,alto,beat,innova,qualis"
```

List:

```
> lpush employee chui
```

```
(integer) 1
```

```
> lpush employee chan
```

```
(integer) 2
```

```
> lpush employee hari
```

```
(integer) 3
```

```
> rpush employee lingam
```

```
(integer) 4
```

```
> lrange employee 0 10
```

```
1) "hari"
```

```
2) "chan"
```

```
3) "chui"
```

```
4) "lingam"
```

```
> lrange employee 0 1
```

```
1) "hari"
```

```
2) "chan"
```

```
> lrange employee 0 10
```

```
1) "chan"
```

```
2) "chui"
```

**Set:**

```
> sadd rentalLoc OrionMall
```

```
(integer) 1
```

```
> sadd rentalLoc funMall
```

```
(integer) 1
```

```
> sadd rentalLoc2 VaughanMall
```

```
(integer) 1
```

```
> sadd rentalLoc2 DowntownMall
```

```
(integer) 1
```

```
> sunionstore allRentalLocs rentalLoc rentalLoc2
```

```
4
```

```
> smembers allRentalLocs
```

```
1) "VaughanMall"
```

```
2) "OrionMall"
```

```
3) "DowntownMall"
```

```
4) "funMall"
```

```
> sismember allRentalLocs Forum
(integer) 0

> sismember allRentalLocs OrionMall
(integer) 1

> srem rentalLoc OrionMall
1

> smembers rentalLoc
1) "funMall"
```

## Hash:

```
> hset id:1000 name Raj ocp student
2

> hset id:1001 name Hareesma ocp Doctor
2

> hset id:1002 name Rohin ocp Engineer
2

> hset id:1003 name Lingam ocp TA
2
```

```
> hgetall id:1003
```

- 1) "name"
- 2) "Lingam"
- 3) "ocp"
- 4) "TA"

```
> hget id:1002 name
```

```
"Rohin"
```

```
> hdget id:1001 ocp
```

```
> hget id:1001 ocp
```

```
"Doctor"
```

```
> hdel id:1001 name
```

```
(integer) 1
```

```
> hgetall id:1001
```

- 1) "ocp"
- 2) "Doctor"

```
> hdel id:1001 ocp
```

```
(integer) 1
```

```
> hgetall id:1001
```

```
(empty list or set)
```

## Sorted Set:

```
> zadd locid 1001 OrionMall  
  
(integer) 1  
  
> zadd locid 1002 ForumMall  
  
(integer) 1  
  
> zadd locid 1003 VaughanMall  
  
(integer) 1  
  
> zadd locid 1004 DowntownMall  
  
(integer) 1  
  
> zrange locid 0 10  
  
1) "OrionMall"  
2) "ForumMall"  
3) "VaughanMall"  
4) "DowntownMall"
```