A Simple Protocol for the Inference of RNA Global Pairwise Alignments

Felix Karg

15. Januar 2019

University of Freiburg



Content

Recap Sankoff

Tree-Based LocARNA


Content


Recap

Tree-Based

Sankoff

LocARNA





SPS - introduction

Sum of Pairs Score

SPS - introduction

Sum of Pairs Score

Used to measure the alignment of two RNA sequences

SPS - introduction

Sum of Pairs Score

Used to measure the similarity of two RNA sequences

A: AAGGCTT

B: AAGGC

C: AAGGCAT

Similiarity:

A: AAGGCTT

B: AAGGC

C: AAGGCAT

Similiarity:

A: AAGGCTT

B: AAGGC

C: AAGGCAT

Similarity: 60% = 1 - (2 / 5)

A: AAGGCTT

B: AAGGC

C: AAGGCAT

Similiarity:

A: AAGGCTT

B: AAGGC

C: AAGGCAT

Similarity: 60% = 1 - (2 / 5)

A: AAGGCTT

B: AAGGC

C: AAGGCAT


Similiarity:

A: AAGGCTT

B: AAGGC

C: AAGGCAT

Similarity: 86% = 1 - (1 / 7)



A: AAGGCTT

B: AAGGC

C: AAGGCAT

Identity:

A: AAGGCTT

B: AAGGC

C: AAGGCAT

Identity:

A: AAGGCTT

B: AAGGC

C: AAGGCAT

Identity: 100%

A: AAGGCTT

B: AAGGC

C: AAGGCAT

Identity:

A: AAGGCTT

B: AAGGC

C: AAGGCAT

Identity: 100%

A: AAGGCTT

B: AAGGC

C: AAGGCAT

Identity:


A: AAGGCTT

B: AAGGC


C: AAGGCAT

Identity: 85% = 6 / 7

needle



Needleman-Wunsch-Algorithm



Content


Recap

Tree-Based

Sankoff

Locarna

Tree-based



Content

Recap

Tree-Based

Sankoff

LocARNA

• Dynamic Programming

- Dynamic Programming
- Runtime $O(n^6)$

- Dynamic Programming
- Runtime $O(n^6)$
- Space needed: $O(n^4)$

- Dynamic Programming
- Runtime $O(n^6)$
- Space needed: $O(n^4)$

What does it do ... ?

Global free energy minimisation.

• Base match

- Base match
- Base insertion

- Base match
- Base insertion
- Base deletion

- Base match
- Base insertion
- Base deletion
- Base **pair** match

Content

Recap

Tree-Based

Sankoff

LocARNA

LocARNA - Introduction

intro